


## KC-7786V

### 50M IR High Res. Day & Night Vari-Focal CCD Camera

| ITEM                   | DESCRIPTION   |
|------------------------|---|
| Sensor Chip            | 1/3" SONY SUPER HAD / SONY HQ1 DSP  |
| Picture Element        | NTSC: 768 (H) × 494 (V)<br>PAL: 752 (H) × 582 (V)   |
| Scanning Frequency     | NTSC: 15734Hz (H), 60Hz (V)<br>PAL: 15625Hz (H), 50Hz (V)   |
| H. Resolution          | 540 TV Lines  |
| Illumination           | Color mode automatically switches to B/W mode under 5 Lux<br>0.1 Lux without IR light ; 0 Lux with IR light |
| IR Led                 | 60 pcs (IR Wavelength : 850nm)  |
| IR Distance            | 50 Meters (IR 30) - STANDARD<br>70 Meters (IR 20) - OPTIONAL<br>100 Meters (IR 10) - OPTIONAL               |
| Synchronizing          | Internal Sync., 2:1 Interlace   |
| Mirror                 | ON/OFF Switchable   |
| Flickerless            | ON/OFF Switchable   |
| Backlight Compensation | ON/OFF Switchable   |
| Auto Gain Control      | ON/OFF Switchable   |
| Auto White Balance     | ON/OFF Switchable ; Color Rolling Reduce Switchable   |
| S/N Ratio              | More than 52dB (AGC OFF)  |
| Gamma Correction       | 0.45  |

**YAKDHANE***Votre sécurité C'est notre affaire.*

|                       |   |
|-----------------------|---|
| Electronic Shutter    | Auto 【1/60(50)~1/100,000】   |
| Video Output          | 1.0Vp-p75Ω  |
| Lens Mount            | Japan Computar:3~9mm(F1.2) Auto Iris Lens 9~22mm (F1.4)                                   |
| Heater Function       | Optional - ON -> 0 °C ; OFF -> 5 °C   |
| Blower Function       | AUTO - ON -> 40 °C ; OFF -> 25 °C   |
| Power                 | DC 12V/ 1A For IR ON (DC12V/AC24V Dual Power Option) ; AC90~240V Switching Power Optional |
| Dimension/Weight      | 135 (W) x 105 (H) x 265(D) mm ; 1.2 kgs   |
| Operating Temperature | －10°C～＋50°C   |