

**YAKDHANE***Votre sécurité C'est notre affaire*

## MPEG-4 IP SPEED


DOME CAMERA



### IPS-900POD-1

Hi-END Outdoor 36 times Day&Night Mpeg-4 IP Speed Dome Camera

- Integrate VIDEO SERVER into high speed dome camera for all-in-one solution, able to perform omnidirectional network surveillance.
- MPEG-4 Advanced Simple Profile is able to deliver DVD resolution video at lower data rates and smaller file sizes.
- Offer MPEG-4 D1 resolution 720x480, providing sharper image.
- The intelligent network system on a Chip(SoC) solution delivering high performance and QoS (802.1pQ) for ensuring a stable and high quality video streaming(IP multicast, IGMP supported).
- DDNS supported.
- Simultaneously analog and digital outputs.
- MPEG-4 Living Streaming
- QoS Function setting – Priority service scheduling.
- Authorization setting – The system supervisor can set authorization to prevent unauthorized user.
- Offer max. 10 user password management.
- Offer multilingual operation interface.
- Pan scan angle: 360° , Tilt scan angle: 90°.
- Pan scan speed : 1~380°/SEC.
- Tilt scan speed : 1~150°/SEC.
- Preset points up to 128 points.
- 1/4" Hi-Resolution SONY Ex-view CCD
- NTSC 811H\*508V; PAL 795H\*596V, Camera Lens: 3.4mm~122.4mm, 36x optical Lens (512x digital zoom), with Original SONY Camera Module Resolution 530TVL, 0.7Lux/F1.5 (Day), 0.01Lux/F1.5 (Night), S/N: 50dB.
- WDR function
- IP66

**YAKDHANE***Votre sécurité C'est notre affaire***Specification:**

Model	IPS-800		IPS-830	IPS-900
Compression	MPEG-4 ASP hardware compression			
Resolution	QCIF(160x112/NTSC;176x144/PAL) / CIF(352x240/NTSC;352x288/PAL) / D1(720x480/NTSC;720x576/PAL)			
Image FPS	30FPS at full D1 resolution(NTSC) / 25FPS at full D1 resolution(PAL)			
Network	RJ-45x1, LAN port			
Video output	BNC connector x 1, Composite: 1.0 Vp-p, 75Ohms			
Ethernet system	10/100base-T x1 for LAN			
Protocol supported	TCP/IP,UDP,HTTP,ARP,PPPoE,DDNS,IGMP			
CCD Sensor	COLOR 1/4" SONY Ex-VIEW CCD			
Picture Pixels	NTSC: 811 x 508 / PAL: 795 x 596			
Lens	18x optical zoom, f=4.1 mm (wide) to 73.8 mm (tele), F1.4 to F3.0	26x optical zoom, f=3.5 mm (wide) to 91.0 mm (tele), F1.6 to F3.8	36x optical zoom, f=3.4 mm (wide) to 122.4 mm (tele), F1.6 to F4.5	
Digital zoom	12x (216x with Digital zoom)	12x (312x with Digital zoom)	12x (432x with Digital zoom)	
Focus system	Auto / Manual			
Iris system	Auto / Manual			
WDR function	No			Yes
H-Resolution	480TV Lines at NTSC / PAL			530TV Lines at NTSC / PAL
Min illumination	0.7 lux(Day mode), 0.01 lux (Night mode, 1/4sec)	1.0 lux(Day mode), 0.01 lux (Night mode, 1/4sec)	1.4 lux(Day mode), 0.01 lux (Night mode, 1/4sec)	
S/N Ratio	More than 50 dB			
Pan movement	0° ~ 360° continuous endless			
Tilt movement	0° ~ 90°			
Pan manual speed	1°/SEC to 60°/SEC vari-speed			
Tilt manual speed	1°/SEC to 30°/SEC vari-speed			
PRESET speed	380°/SEC			
Preset	128 preset point			
Preset Accuracy	±0.1°			
Outdoor protected	IP66			
Power Supply	AC110V/AC220V			

