

IP Camera

H.264 IP Camera



H.264 IP Box Camera

KCC-IP230

Function

- H.264 Compression Algorithm
- PoE Support (Optional)
- 1/3" Super HAD Color CCD With 410K Pixels
- High Resolution of 540TV Line
- True Day & Night
- C/CS lens available
- Motion Detecton
- Bulitin OSD (ON Screen Display)
- DNR (Digital Noise Reduction) Chip
- Upto128X SENSE-UP
- BLC (Back Light Compensation)
- Privacy Image Masking with Free Position : 4 Zones
- Min. Illumination of 0.3 LUX @ F1.2 (Normal Color Mode) 0.002 LUX @ F1.2(Sens-up)
- Option -Dual Power (DC12V & AC24)
- Lens with format 1/3" (a third of inch)
- Lens with automatic iris of the kindDC
- Lens with standard varifocal; lens with focal distance of 5 to 40mm
- Adaptor Power Over Ethernet Fast Ethernet(10/100BaseT)

Specifications

Model no		KCC-IP230
Network	Network Interface	Ethernet 10/100Base-T (RJ-45)
	Network Protocol	TCP/IP, UDP, Multicast, DHCP, SMTP, HTTP, SNMP, RTP, RTSP
Camera	Image Sensor	1/3" Sony Super HAD CCD, 410,000pixels
	Max. aperture Ratio	1:1.3~2.0
	Lens	C/CS Selective
	Back Light Compensation	On/Off/Auto
	Gain Control	AGC-L, AGC-H, OFF selectable
	White Balance	W-ATW/S-AWC/AWC/Manual
	Output	1 Composite (1 Vpp 75 Ohm, BNC)
	White Balance	MD 1 / MD 2 / Off
	Electric Shutter Speed	1/60 ~ 1/200,000 sec
	Min. Illumination	0.002Lux (Intensifier), 0.3Lux (F1.3)
	S/N Ratio	50dB (AGC Off)
	Motion Detection	MD1 / MD2 / OFF
Video	Standards	H.264 compression algorithm
	Data Rate	32kbps ~ 4Mbps
	Resolution	NTSC : 720x480, 720x240, 352x480, 352x240 PAL : 720x576, 720x288, 352x576, 352x288 540 TV Line
	Max Frame Rate	NTSC : Max 30fps / PAL : Max 25fps
	Frame Rate Range	NTSC : 0.2 ~ 30fps / PAL : 0.2 ~ 25fps
Audio	Standards	G.711
	Sample Rate	8Khz
	Data Rate	64kbps
	Input	1 Line-in (Mini-stereo)
	Output	1 Line-in (Mini-stereo)
Serial	Port	RS-422/485
	Data Rate	2,400bps ~ 115,200bps
Alarm / Sensor	Sensor Input	1
	Alarm Output	1
User Interface	System Status	LED, OSD
Software	CMS, Web Viewer	Live Monitoring, Recording, Search & Playback, Backup & Web Viewer
Physical	Dimension	114(W) X 64(D) X 56(H)mm
	Weight	340g (Without Lens)
	Power Source	DC 12V/5A, PoE(Power over Ethernet): 802.3af
	Power Consumption	Max 5W
Warranty		36 months

Picture View



Dimensions

