



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services

✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website



ACCEL-A2203

22" Medical AI All-in-One PC with 14th Gen Core i CPU and MXM Graphics



FEATURE

- NVIDIA RTX A1000/A2000/A4500 MXM Graphics
- Intel® 14th generation Core® i9/ i7/ i5 / i3 Processor
- Support Dual Channel DDR5 5600Mhz SODIMM up to 96GB
- 22" Full HD High Contrast LCD w/ Capacitive Multi-Touch Screen
- 2.5 Gigabit LAN x 1, Gigabit LAN x 1
- High Speed USB 3.2 Gen2 Ports
- 8MP Camera with Mic (optional)
- Imprivata RFID Reader (optional)

DESCRIPTION

ACCEL-A2203 is a 22" all-in-one medical AI panel PC combining clinical-grade touchscreen functionality with embedded AI edge computing. It is built to power real-time inference, imaging, and diagnostics directly at the point of care.

- 21.5" Full HD touchscreen with medical-grade housing (IP65 front)
- Integrated NVIDIA® Jetson AGX Orin® for AI workloads
- Intel® Tiger Lake-UP3 i7/i5/i3 processor for system-level performance
- EN 60601-1 certified for clinical safety
- Fanless, hygienic design ideal for OR, ICU, and nurse stations
- Rich I/O: USB 3.2, HDMI, LAN, COM, GPIO
- Optional: camera, RFID, smart card reader, barcode scanner
- Wall-mount and cart-compatible for flexible deployment

APPLICATION

- AI Diagnostic Stations: Embedded inference engine for imaging or pathology screening
- Smart Nursing Stations: Data visualization, vitals analysis, and patient insights
- OR Workstations: Real-time surgical imaging enhancement and overlay
- Clinical Monitoring: Local AI processing for anomaly detection and alerting
- Medical Cart Integration: Combines display, computing, and AI in one compact unit
- Telemedicine Hubs: Supports HD video, edge analytics, and remote diagnostics

SPECIFICATION

Main Specifications

Processor	Intel® 14th Gen Core i9-14900/ i7-14700/ i5-14500 (TDP 65W)
System Memory	Support Dual Channel DDR5 5600Mhz SODIMM up to 96GB
Expansion	M.2 2280 M-key(PCIe[x4]) slot x1
OS Support	Windows® 10 Windows® 11 Linux®
MXM Graphics	802.11 a/b/g/n /AC/AX + BT5.2 (Optional)
Storage Disk Driver	M.2 2242 M Key NVMe x 1
Wireless Communication	802.11 ax (optional) Bluetooth 5.3 (optional)
Function Key	Power on/off, LCD up/down Touch enable/disable Reading Light enable/disable
Speaker	2W x 2
Security	Trusted Platform Module 2.0 Imprivata RFID Reader (optional)
Power Requirement	Medical Adapter 330W 12V

Display

Size	22" LCD
Resolution	1920 x 1080
View Angle	178° (H)/178° (V)
Contrast Ratio	1000:1
Luminance (cd/m2)	250
Back Light Life Time	50,000 Hours

Touch Screen Capacitive Multi-Touch

I/O

USB	USB 3.0 (Type-A) x1 USB 3.0 (Type-C with External Display) x1
Ethernet	2.5 Gigabit LAN x 1 Gigabit LAN x 1
Video Out	HDMI 2.0b x 2 Display Port 1.4a x 1
Audio	Mic-in Line-out

SPECIFICATION

Mechanical and Environmental

Operating Temperature 0°C ~ 35°C(32°F ~ 95°F)

Storage Temperature -20°C ~ 60°C(-4°F ~ 140°F)

Mounting VESA 100 mm

Degree of Protection IP65 in the front ; IPX1 in the back

Dimension 542 x 355 x 69 mm (approx.)

Package Size 711 x 195 x 503 mm

Gross Weight 11.5 kg

Net Weight 8.5 kg

Certifications CE: EN 60601-1-2:2015(V4.1)
FCC: Part 18 Class B
UL: ANSI/AAMI ES60601-1:2012 (V3.2)
cUL: CAN/CSA-C22.2 No. 60601-1:2014 (V3.2)