



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services

✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website

ACCEL-JS1100

NVIDIA Jetson AGX Orin platform with 5" front touch screen for Medical AI imaging application



FEATURE

- NVIDIA Jetson AGX Orin platform with 64GB LPDDR5 or 32GB LPDDR5
- Powerful AI computing performance with up to 275 TOPS
- Support Front Screen
- Support DP 1.4 or HDMI 2.0 video output
- Compact size suitable for space limited area
- Support HDMI 2.0 and 12G SDI video input
- Medical certified with CE/FCC/UL
- Support optional PCIe [x8] x1 for possible customization
- Support built in speaker x 2

DESCRIPTION

ACCEL-JS1100 is an ultra-compact medical AI edge computer, powered by NVIDIA® Jetson Orin™ NX, designed to bring intelligent processing to embedded clinical applications. It delivers high-efficiency performance for AI inference at the point of care.

- Powered by NVIDIA® Jetson Orin™ NX module (up to 275 TOPS AI performance)
- Fanless, space-saving design ideal for integration in medical devices
- Medical-grade safety compliant (EN 60601-1) for clinical use
- Rich I/O: HDMI, LAN, USB 3.2, CAN bus, RS-232
- Supports popular AI frameworks: CUDA, TensorRT, DeepStream
- Optimized for low-power, high-performance inference workloads

APPLICATION

- Smart Diagnostic Devices: Enables AI-powered analysis in compact imaging and test devices
- Edge AI in Patient Monitoring: Detect anomalies locally with low-latency performance
- Mobile & Handheld Medical Devices: Embedded AI for portable medical tools
- Clinical Automation: Supports robotics, motion control, and sensor fusion
- Point-of-Care AI: Deploy intelligent decision support directly where care is delivered

SPECIFICATION

Main Specifications

AI Engine	NVIDAI Jetson AGX Orin
CPU	8-core Arm®Cortex®-A78AE v8.2 64-bit CPU 2MB L2+4MB L3 12-core Arm®Cortex®-A78AE v8.2 64-bit CPU 3MB L2 +6MB L3
System Memory	32GB or 64GB 256-bit LPDDR5 204.8 GB/s
Graphics	1792-core NVIDIA Ampere GPU with 56 Tensor Cores 2048-core NVIDIA Ampere GPU with 64 Tensor Cores
Storage	oboard 64GB eMMC 5.1, M.2 NVMe SSD (Optional)
OS support	Ubuntu with Jetpack
Security	TPM 2.0
Speaker	2W x Speaker x 2
Front Screen	5" LED Panel with P-Cap Touch Resolution :800 x 480 Brightness :800 nits

I/O

USB	USB 3.2 Type A x 2, USB 3.2 Type C x 1
Ethernet	GigaLAN x 1, 10G LAN x 1
Video Out	HDMI 2.0 x 1 and Display Port 1.4 (without front screen) HDMI 2.0 x 1 or Display Port 1.4 (with front screen)
Video input (Optional)	3G SDI or HDMI (FHD), 12G SDI or HDM 2.0 3G SDI(Max resolution up to 1920x1080p@60fps) 12G SDI(Max resolution up to 4096x2160@60fps) HDMI (FHD)(Max resolution up to 1920x1080p@60fps)
Audio	Mic-in x 1 , Line out x 1
Serial Port	RS232 x 1
Function Port	Reset Button x 1 ,Recovery Button x 1,Grounding pin x 1
DC-in	12V DC Jack
Front I/O	Power Button with Power LED indicator x 1
Wireless Communication	802.11a/b/g/n/ac/ax.w/BT5.2 (Optional)
Expansion I/O	PCIe [x8] x 1(Optional)

Environment and Mechanical

Power	Medical adapter 12V 120W
Operating temperature	0°C ~ 35°C(32°F ~ 95°F)
Storage temperature	-20°C ~ 60°C(-4°F ~ 140°F)
Dimension	220 x 217.7 x 111.1 mm
Package Size	TBC
Gross Weight	TBC
Net Weight	TBC
Certifications	CE: EN 60601-1-2:2015(V4.0), EN 60601-1:2006/A1:2013/A12:2014 (V3.1) FCC: Part 18 Class B UL: ANSI/AAMI ES60601-1:2012 (V3.1) cUL: CAN/CSA-C22.2 No. 60601-1:2014 (V3.1)

SPECIFICATION

Environment and Mechanical

Operating Temperature 0°C ~ 35°C(32°F ~ 95°F)

Storage Temperature -20°C ~ 60°C(-4°F ~ 140°F)

Mounting VESA 100 mm

Degree of Protection IP65 in the front ; IPX1 in the back

Dimension 542 x 355 x 69 mm (approx.)

Mechanical and Environmental

Package Size 711 x 195 x 503 mm

Gross Weight 11.5 kg

Net Weight 8.5 kg

Certifications CE: EN 60601-1-2:2015(V4.1)
FCC: Part 18 Class B
UL: ANSI/AAMI ES60601-1:2012 (V3.2)
cUL: CAN/CSA-C22.2 No. 60601-1:2014 (V3.2)