



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services

✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website



ACCEL-VM1000

Dual GPU card Medical AI Box PC with Intel 13/12th Gen Core i9 CPU



FEATURE

- Intel® 13/12 Gen Core i9 Processor
- Support 4 x DDR4 3200 288 pin Long-DIMM up to 128GB
- Optional 7" Front Screen with P-Cap Touch
- Support front dual USB 3.0
- Support GPIO and Remote Power Switch design for embedded use
- Support Dual Nvidia RTX 6000 Ada cards and additional capture card installation
- Support 4 x PCIe Gen4 Slots for high end graphic card and capture card integration
- Support Medical Grade 1500W PSU for Dual GPU Card and 700W PSU for Single GPU card

DESCRIPTION

ACCEL-VM1000 is a high-performance medical AI video processing system, designed for real-time multi-channel imaging and intelligent analytics in surgical and diagnostic environments. Built with NVIDIA RTX™ GPU, it enables ultra-fast video inference and 4K streaming.

- Powered by Intel® 12th Gen Core™ CPU and NVIDIA RTX™ A2000 GPU
- Supports 4-channel HDMI video input and up to 2-channel HDMI output
- AI acceleration for real-time image recognition, segmentation, and enhancement
- Medical-grade certified (EN 60601-1) for clinical deployment
- High-speed I/O: USB 3.2, LAN, HDMI, CAN, and optional DICOM/PACS support
- Compact and fan-cooled design optimized for OR, endoscopy, and mobile carts
- Compatible with major AI SDKs: TensorRT, CUDA, DeepStream, OpenVINO™

APPLICATION

- AI Surgical Imaging: Real-time object detection, tracking, and overlay during surgery
- Endoscopy Video Processing: AI-assisted lesion detection and automatic annotation
- Multi-Channel Video Recorder: Seamless integration with PACS/ DICOM workflow
- Telehealth & Remote Surgery: Low-latency 4K video streaming with embedded inference
- Diagnostic AI Workstation: GPU-powered platform for AI model deployment and training

SPECIFICATION

Main Specifications

Processor	Intel® 13/12th generation Core I Processor
Chipset	Intel W680
System Memory	DDR4 3200 DIMM x 4 up to 128GB
Front Scree(Optional)	7" LED Panel with P-Cap Touch
Storage Disk	2.5" SATA SSD x 2
Drive	M.2 2280 NVMe SSD x 1
TPM	2.0
Security	TPM 2.0
Speaker (Optional)	5W x 2
OS Support	Windows® 10 and 11 Linux (optional)

I/O

USB	USB 3.2 Gen 2 Type A x 5 USB Gen 2 20G Type C x 1
Ethernet	2.5G Gigabit LAN x 3
Video Out	Line-in x 1 Mic-in x 1 Line-out x 1
Series Ports	RS232 x 2
Function I/O	Remote power switch x 1 (Optional) Grounding pin x 1
Power	AC input
Expansion I/O	2 x PCIe Gen4 Slots (PCIe1/PCIe3:single at x16(PCIe1) dual at x8 (PCIe1) / x8 (PCIe3)) with x16 connector PCIe [x 4] x 2 M.2 2230 E Key x 1 M.2 2280 M Key [PCIe x 4] x 1

SPECIFICATION

Mechanical and Environmental

Power 100V to 240V AC Input

Consumption 700W or 1500W

Operating Temperature 0°C ~ 35°C(32°F ~ 95°F)

Storage Temperature

-20°C ~ 60°C(-4°F ~ 140°F)

Dimension

420 x 169 x 409 mm

Package Size 630 x 310 x 565 mm

Gross Weight 12kg

Net Weight 11kg

Certifications CE: EN 60601-1-2: 2015 + A1: 2021 (V4.1)
EN 60601-1: 2007 + A1:2013 +A2:2021 (V3.2)
EN 55032:2015/A1:2020
EN 55035:2017/A11:2020 (ITE)
IEC 62368-1:2020+A11:2020 (ITE)
FCC: Part 15B/ Part 18
UL: ANSI AAMI ES60601-1:2005/A1:2012/
A2:2021(V3.2)
cUL: CAN/CSA-C22.2 No. 60601-1:14 (IEC 60601-1:
2005+A1:2012+A2:2020,MOD) (V3.2)