



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services

✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website



AI REAL-TIME BREATHING MONITORING SYSTEM

Visualizing Breath, Safeguarding Health



FEATURE

- Real-time monitoring & alerts
- Multi-level sedation assessment
- Airway obstruction detection
- Enhanced Patient Safety

DESCRIPTION



Provides continuous respiratory sound monitoring, transforming breathing sounds into visual spectrograms. Enhanced by AI deep learning for abnormal sound detection and real-time alerts, improving patient safety.



DISPOSABLE SENSORS

2-year shelf-life sensor with dual electrical safety protection against shock and current leakage.

3M PATENTED SURGICAL TAPE

Small size with thin profile and skin-friendly adhesive ideal for patients with smaller necks or sensitive skin.

APPLICATION

- Compliant with North American Society of Anesthesiologists guidelines for oral moderate sedation monitoring
- Sedation Monitoring: Detects light/moderate/deep sedation levels, alerts breathing changes
- Surgery & Dental: Real-time airway obstruction detection (e.g., saliva)
- Respiratory Tracking: Monitors asthma conditions

SPECIFICATION

Electrical Specification

AC Power Input 100 - 240V ~ 0.6 - 0.3A, 50 - 60Hz

Electrical Safety Class II Equipment

Applied Part Type B Applied Part
Classification

Applied Part Disposable Sensor

Controller Hub

Dimension 99.0x71.0x16.6 mm (3.9x2.8x0.65 inches)

Enclosure ABS
Material

LED Indicator Power Indicator
Channel Indicator

Connection Port Power Input
Audio Output
4 USB-C Port (for patient cables)

Control Button Volume Adjustment
Next Channel
Mute

Service Life 2 years

Patient Cable

Length 1450mm $\pm$ 20 mm

Hi-Pot AC 200V, 1.5 mA

Sustainability

Insulation DC 200V/20M Ohm
Resistance

Contact 3 Ohm
Resistance

Disposable Sensor

Disposable Sensor 19.0x34.0x8.0 mm (0.75x1.3x0.32 inches)