



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services

✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website



HAND DIAGNOSIS RADIOGRAPHY IMAGING SYSTEM

Safe, sharp, and precise: Excellence in every image



FEATURE

- Advanced radiation safety with 80% reduced exposure, ensuring optimal protection for both patients and operators.
- Highly portable design with comprehensive shielding protection, enabling secure imaging anywhere at any time.
- Equipped with current clinical applications for precise Bone Age assessment and accurate fracture detection.
- Future-ready technology featuring advanced bone density measurement and gout diagnosis capabilities.
- All-in-one mobile imaging solution combining safety, portability, and versatile diagnostic applications.



DESCRIPTION




Hand Diagnosis Radiography Imaging System design integrates our patented transmission X-ray technology for application in hand diagnostic radiography. Fully compliant with ISO, QMS, and FDA certification for bone age assessment.

BENCHTOP SIZE

W62 x L65 x H70cm Weight: 80kg

RADIATION SHIELDING

< 5.0 μ Sv/hr at 5cm from surface





FLAT PANEL DETECTOR

14 X 17 DIGITAL X-RAY DETECTOR

CSI Scintillator

150 μ m Pixel Pitch

MODULE

Tube Voltage: 40 to 70 kVp

Tube Current: 0.10 to 0.50 mA

Spot size: 0.2 mm

APPLICATION

- Orthopedic Clinics: Diagnosis of fractures, dislocations, and bone-related conditions
- Rheumatology Clinics: Assessment of arthritis, gout, and joint inflammation
- Emergency Rooms: Rapid trauma diagnosis for acute hand injuries
- Hand Surgery Departments: Pre-operative planning and post-surgical monitoring
- Rehabilitation Centers: Tracking bone and joint healing progress
- Pediatric Clinics: Evaluation of bone development and growth plates in children
- Sports Medicine Centers: Diagnosis of sports-related hand and wrist injuries
- Imaging Centers: Specialized hand radiography services
- Occupational Health Clinics: Assessment of work-related hand conditions
- Plastic Surgery Clinics: Pre and post-operative evaluation for hand reconstruction

SPECIFICATION

SpeciesTube Voltage	40 to 70 kV
Tube Current	0.10 to 0.50 mA
Spot size	0.20 mm
Dimensions	620 x 640 x 700 mm
Weight	about 80kg
Beam Angle	40° at 45cm SID
Radiation Field	10" x 12"
Radiation Shield	Less than 5 pSv/h at 5 cm from the surface of the chassis as per FDA 21 CFR 1020.40