



FIRST IN SMART CARE, ALWAYS THERE TO CONNECT

🌐 healthmit.services


✉ support@healthmit.services

📞 786-743-7936 🖨 786-955-2211

👤 801 Brickell Avenue, Suite 800 Miami, Florida 33131



Website



VENUS 224

21.5" Dual Hot Swappable Battery Medical Cart Computer



FEATURE

- Intel 11th gen Tigerlake, fan less implementation
- Windows 11 and IGEL Compliant
- Dual Hot Swappable Batteries
- Easy cleanable and anti-bacterial
- Internal Imprivata compliant RFID reader (optional)
- WiFi 6 (optional)
- Compliant with all Venus batteries
- Remotely Manageable by central iT departments

DESCRIPTION

Venus-224 is a slim, fanless 21.5" medical-grade cart computer designed for high-efficiency workflows in modern hospitals. Engineered for mobility, infection control, and all-day performance.



- 21.5" Full HD P-CAP touch display with wide viewing angle
- Powered by Intel® 12th Gen Core® i7/i5/i3 (Alder Lake-U) processors
- Fanless design with IP65-rated front panel for easy disinfection
- Hot-swappable dual battery system for 24/7 non-stop operation
- Medical-grade certified: EN 60601-1, CE, FCC Class B
- Flexible mounting options: compatible with carts, arms, or wall-mounts
- Optional: camera, RFID, smart card reader, and expansion ports
- Rich I/O support for peripherals and hospital system integration

APPLICATION

- Mobile Medical Carts: Lightweight and battery-powered for seamless bedside care
- Nurse Workstations: Quiet, fanless design ideal for shift-based environments
- Telehealth Carts: Optional webcam and mic enable virtual rounds and consults
- Medication Verification: RFID and smart card reader options ensure secure access
- Surgical Assistance: Reliable imaging and touch interface in sterile zones
- Outpatient Clinics: Sleek and compact for exam rooms or consultation spaces

SPECIFICATION

Main Specifications

Processor	Intel® 11th generation Core i7 1165G7 / i5 1135G7
System Memory	DDR4 up to 64GB
OS Support	Microsoft® Windows 11 Microsoft® Windows 10 (64bit) Ubuntu 20.04 LTS IGEL (thin client solution)
Storage	m.2 SSD up to 1TB
Wireless	802.11 a/b/g/n/ac/ax (optional)
Communication	WiFi 6E + Bluetooth 5.3 (optional)
Touch	PCT (optional)
Speaker	3W x 2
Trusted Platform Module	TPM 2.0
Speaker	2W x 2
Trusted Platform Module	TPM 2.0
Security	Smart Card Reader (optional) Imprivata RFID reader (optional) Barcode reader (optional)

Waterproof Front IP65 ; rear IPX1

Display

Display Size	21.5"
Resolution	FHD 1920 x 1080
Max. Colors	16.7 M
Contrast Ratio	1000:1
Luminance (cd/m2)	250

I/O

USB	Rear I/O :USB 3.0 x2, USB 2.0 x2 Front button I/O : USB 3.0 x2
Video Out	HDMI 1.4 x1
COM	COM port x2
Audio	Combo audio port x1
Ethernet	1.5kv isolated Gigabit LAN x2
DC-in	19V DC-in x1

Mechanical and Environmental

VESA 75/100 mm VESA mount

Operating Temperature 0°C ~ 40°C(32°F ~ 104°F)

Storage Temperature -20°C ~ 60°C(-4°F ~ 140°F)

Storage Humidity 10% ~ 95%@35°C
non-condensing

Dimension 510(L) x 78.4(W) x 346(H) mm

Package Size 645(L) x 210(W) x 513(H) mm

Net Weight 6kg

Certifications CE: EN 60601-1-2: 2015 + A1: 2021 (V4.1), EN 60601-1: 2007 + A1:2013 +A2:2021 (V3.2)
EN 55032:2015/A1:2020
EN55035:2017/A11:2020(ITE)
IEC62368-1:2020+A11:2020 (ITE)
FCC : Part 15B/ Part 18
UL: ANSI AAMI ES60601-1:2005/A1:2012/A2:2021(V3.2)
cUL: CAN/CSA-C22.2 No. 60601-1:14 (IEC 60601-1: 2005+A1:2012+A2:2020,MOD) (V3.2)
TELEC :JAPAN TELEC