NovaTech Solutions — API Technical Documentation

Fictional developer reference for RAG practice

Purpose: This fictional document is designed for experimenting with document loading, text chunking, embeddings, metadata, and semantic search.

1. Base URL

The sample API base URL is https://api.novatech.example/v1. All examples in this document are illustrative and do not connect to a real service.

2. Authentication

The API uses bearer-token authentication. Clients send an Authorization header with the value Bearer followed by the access token. Tokens must be stored securely and must not be committed to source control. A missing or invalid token returns HTTP 401 Unauthorized.

3. List Workflows

GET /workflows returns workflows visible to the authenticated account. Optional query parameters include limit and cursor. The default limit is 20 records and the maximum limit is 100. The response includes an items array and a next_cursor field; next_cursor is null when there are no more results.

4. Create a Workflow

POST /workflows creates a workflow. The request body must include a non-empty name and a trigger object. A successful request returns HTTP 201 Created and the new workflow object. If required fields are missing, the API returns HTTP 400 Bad Request with a structured error message.

5. Rate Limits

The sample API allows 60 requests per minute per workspace. When a client exceeds the limit, the API returns HTTP 429 Too Many Requests and includes a Retry-After header indicating how many seconds to wait before retrying. Clients should use bounded retries and exponential backoff.

6. Error Codes

HTTP 400 indicates an invalid request. HTTP 401 indicates missing or invalid authentication. HTTP 403 indicates the authenticated client lacks permission. HTTP 404 indicates that the requested resource was not found or is not visible to the client. HTTP 429 indicates a rate limit was exceeded. HTTP 500 indicates an unexpected server error.

7. Pagination Example

A client can request GET /workflows?limit=20. If the response contains next_cursor equal to abc123, the next request can use GET /workflows?limit=20&cursor=abc123. Clients should treat cursor values as opaque strings and should not construct or modify them.

Training sample only. NovaTech Solutions and the example policies, products, prices, and API are fictional.