

Challenges in Milk Yield Forecasting and Feed Optimization: A Comparative Study of AI-based and Quantum-enhanced Dairy Systems

Renu Chaudhary

Department of Computer Science and Engineering
M.M. Engineering College
Maharishi Markandeshwar (Deemed to be University)
Ambala, Haryana, India
mail.renuchaudhary@gmail.com

Rajeev Gupta

Department of Computer Science and Engineering,
M.M. Engineering College
Maharishi Markandeshwar (Deemed to be University)
Ambala, Haryana, India
rajeev.gupta@mmumullana.org

Abstract—The global dairy industry is under increasing pressure to enhance milk production forecasting and milk feed optimization in the face of increasing operational costs and sustainability demands. Lots of classical AI-based mechanisms have been suggested by researchers, but still, there is no systematic comparison of classical AI and quantum-enhanced methods of handling such issues. The purpose of the study is to compare classical AI and quantum-enhanced methods for milk production forecasting and milk feed optimization, with comparative advantages, weaknesses, and implementation. With concern of methodology used, a multi-dimensional comparative analysis of the classical machine learning and quantum computing methods was performed with the examination of the following dimensions of their computational efficiency, accuracy of predictions, scaling, optimization capacity, and feasibility of practical implementation in dairy farming situations. The major findings of this study are that classical machine learning algorithms obtain prediction rates of 80-85% and are operationally mature solutions; they are poor at processing high-dimensional data and performing multi-objective optimization in real-time. The feed costs, which are 60-70% of the total operational costs, are controlled using the fixed optimization measures that are not dynamic. Quantum computing solutions are based on superposition and entanglement to provide theoretically superior performance in optimization, but the performance gains obtained by benchmarking are not proven to be effective in the dairy environment, and significant challenges in hardware availability, system integration, and deployment preparedness mean that it cannot be adopted in agriculture in the near future. With concern of interpretations and implications, it can be seen that there is a striking contrast between the classical AI systems, which can be deployed and scaled on the current infrastructure, and quantum-enhanced systems, which can be applied in complex optimization problems through transformational response but must be confined to experimental settings until hardware maturity. The recommendation to stakeholders in the dairy industry is to use classical AI solutions in the short run and strategically observe the quantum advancements in the future to incorporate it. This structure promotes accurate livestock management and provides a guide towards sustainable production systems of dairy with the capacity to fulfill the projected global food security requirements.

Keywords—Milk Yield Prediction, Feed Optimization, Quantum Machine Learning, Precision Dairy Farming, Agricultural Decision Support, Computational Optimization

I. INTRODUCTION

Dairy farming represents a fundamental component of global agricultural systems, directly contributing to food

security for populations projected to reach 9.73 billion by the year 2050 [1]. The contemporary dairy sector is subjected to multidimensional constraints that necessitate concomitant optimization of a variety of conflicting goals such as productivity improvement, cost minimization, environmental sustainability, and animal welfare preservation [1]. The most important performance measure is milk production, which is affected by a great number of interdependent factors, including genetic predisposition, nutritional consumption, management, environmental factors, and the health condition of animals [2]. Modern dairy enterprises produce heterogeneous data flows as a result of automated milking systems, environmental sensors, and precision feeding devices, and bring opportunities and analytical problems to the farm management decision-making [3].

A. Problem Background and Motivation

Feed optimization represents approximately 60–70% of total dairy farm operational costs [4], [21]. Optimal nutrition is achieved through strict balancing of sources of energy, protein, minerals, and vitamins, depending on specific animal factors such as lactation stage, body weight, and health status [5]. Technologies of precision feeding that include sensors and artificial intelligence are a better improvement compared to conventional ones, because they allow tracking intake in real-time and adjusting diets automatically [3]. The biological complexity of the processes of milk production makes optimization problems that cannot be addressed by traditional computational methods [4]. The dairy management systems are now dominated by classical artificial intelligence methods, more especially the machine learning algorithms, which exhibit fair accuracy in milk yield prediction and optimization of operations [8]. According to a study by Zhang et al., neural networks that include environmental factors, feeding information, and physiological measurements are able to predict with accuracies of 80-85% [9]. Liseune et al. established that deep learning models that are trained on thirty days of historical data can produce correlation coefficients of 0.77 in lactation curve prediction [10]. In spite of these successes, classical approaches are faced with computational problems when handling high-dimensional data, nonlinear biological interactions, and real-time multi-objective optimization [11].

B. Research Gap and Problem Statement

The computational challenge manifests across multiple dimensions in contemporary dairy farming systems [12]. The high-dimensional feature spaces with many interacting variables require large processing resources that are a burden on the classical computing architecture [13]. Multifaceted

biological cross-functionalities between the input parameters and production outputs are not easy to model accurately using conventional algorithm methods [14]. Temporal dependencies further complicate the problem, and most classical approaches cannot model them with enough accuracy [14]. The nature of real-time optimization needs requires dynamism in adapting to changing environmental conditions, behaviors of animals and variable resource availability, which are beyond the responsiveness of the classical models, which are static [15].

Quantum computing has been a potentially revolutionary paradigm that takes advantage of the concepts of superposition and entanglement to search a large solution space by using parallel processing techniques [16]. Recent quantum machine learning research shows promising signs, with quantum models getting a 97.01% accuracy in comparison to 96.5% of classical approaches in neuroinformatics applications [17]. Peral-Garcia et al. have noted that Quantum Neural Networks can retain 75% of accuracy even when the system noise is 40% of the system, whereas Quantum-Cognitive Neural Networks can train at a rate of fifty times more than classical counterparts [18]. Quantum algorithms such as the Quantum Approximate Optimization Algorithm and the Variational Quantum Eigensolvers provide new ways of solving combinatorial optimization problems, which are hard to solve using classical algorithms [19].

Although both computational paradigms have improved over time, there still exist a lot of knowledge gaps in comparative knowledge about implementation issues [20]. Classical artificial intelligence literature focuses on capabilities and gives limited consideration to the computational constraints and scalability limits [21]. The study of quantum computing is largely theoretical and without a critical examination of barriers to practice and complexities of system integration [19]. Such a lack of knowledge makes it uncertain to the stakeholders who are involved in making technology adoption decisions in agricultural situations [6].

C. Research Objectives

This study performs a systematic comparative study of the issues in predicting milk output and feed support in classical artificial intelligence-based and quantum-enhanced dairy production models. The targeted objectives are:

- Determining and classifying the problems of computational challenges in both paradigms using a systematic literature review.
- Comparison of comparative performance potentialities such as accuracy, processing efficiency, and scalability characteristics.
- Evaluating the ability to implement based on hardware needs, the maturity of the software, and the complexity of implementation.
- Delivering evidence-based suggestions to the stakeholders in selecting technologies in precision livestock management settings.

The research study belongs to the expanding body of knowledge on precision agriculture since it offers systematized knowledge on relative merits, limitations, and implementation problems in both forms of calculation [7].

D. Key Terminology

Precision Dairy Farming is a management philosophy that involves the use of information technology and thorough data analysis to optimize the productivity, economic efficiency, environmental sustainability, and animal welfare in dairy operations [6]. The quantum Superposition is a quantum mechanical phenomenon in which quantum bits are present in many states at once until they are measured, which allows them to explore multiple solution spaces in parallel [16]. Quantum Entanglement is a quantum correlation of the particles where the state of one particle instantly affects another despite the spatial distance, and it can perform complex computation tasks that classical computers are not able to perform [18]. Variational Quantum Circuits are parameterized quantum algorithms, which are optimized via hybrid training algorithms that combine classical and quantum training methods in machine learning tasks [19].

II. REVIEW OF LITERATURE

This part is a review of existing literature on optimization of dairy farming and computational methods, which summarizes the results of the classical AI and quantum computing literature to provide the theoretical framework of the comparative analysis made in this paper.

A. Dairy Farming Optimization Requirements

Modern dairy farming optimization encompasses multidimensional objectives requiring sophisticated analytical methodologies for effective integration [3]. Halachmi et al. highlighted that the purpose of production optimization is to reach the maximum possible milk production without considering the quality, through proper genetic selection, proper nutrition control, and a regulated environment [3]. Resource management is related to feed formulation, water consumption, and energy consumption with the aim of reducing the cost and satisfying the physiological requirements of individual animals [4]. According to Gonzalez-Rivas et al., these features of environmental sustainability are the reduction of greenhouse gas emissions, waste management efficiency, and land use optimization [7]. The animal welfare parameters include regular health examinations, stress relievers, and behavioral control systems [6]. These objectives are usually mutually exclusive, and multi-objective optimization systems are required, which cannot be done by traditional single-objective operational paradigms [5].

The dairy farming systems are complex in nature due to the dynamic interactions of the management practices, the environmental factors, and the biological processes [7]. The genetically determined basic production capacity and disease-resistant traits are genetically determined [2]. The nutritional inputs directly influence the quantity of milk and the quality of composition through complex metabolism [4]. Quality of housing, ambient temperatures, and the level of humidity are some of the environmental factors that have a massive impact on the results of comfort and productivity of animals [7]. The overall performance of the operations is affected by the management practices, such as milking schedule, health interventions, and breeding choices [21]. These features imply nonlinear interactions that create optimization landscapes that are inaccessible to conventional analysis plans [26].

B. Classical AI Applications in Dairy Management

Classical artificial intelligence applications in dairy farming employ diverse methodologies for prediction and optimization tasks [8]. Dongre and Gandhi showed that neural networks are one of the key tools of milk yield prediction, where multi-layer perceptrons and recurrent architectures are used to model time-dependent relationships [8]. Support vector machines are used in classification, such as disease detection and breeding selection [20]. Autoregressive Integrated Moving Average models and exponential smoothing methods are time series analysis techniques that deal with the seasonal patterns of production [13]. Random forests and decision trees offer interpretable management decision support features [8].

Milk yield prediction performance using machine learning varies substantially based on methodological approach and dataset characteristics [9]. According to Zhang et al., neural network techniques that use environmental factors, feeding information, and physiological indicators as inputs yield accuracies of between 80-85% [9]. Correlation coefficients of up to 0.77 were reported by Liseune et al. for the prediction of lactation curves using deep learning in controlled experimental studies, and these are quoted here merely as evidence from previous literature, and not as results of the current study. [10]. Murphy et al. discovered that simpler statistical models can be more effective than complex machine learning algorithms when the quality or quantity of data is inadequate, which implies that the methodology should be matched to the data properties [13]. These performance levels are realized when the computational limits are imposed to limit the real-time processing capabilities and scalability to large-scale operations [12].

In classical feed optimization techniques, linear programming models are mostly used, which assume that nutritional needs are fixed and ingredient prices are fixed [4]. Recently, Usigbe et al. offered numerous ideas of many-objective optimization frameworks of dairy cattle feed development that address a variety of conflicting objectives at the same time, which is a step forward compared to the conventional single-objective models [5]. Akintan et al. have highlighted the need to establish a direct relationship between feed formulation and milk quantity, quality, and animal health by using data-driven decision-making processes [4]. These methods do not have mechanisms of dynamic adaptation to the changing circumstances, and reinforcement learning applications are still not widespread in livestock settings [22].

C. Critical Analysis of Existing Studies

The existing literature on milk production forecasting mainly focuses on accuracy in predictions through traditional machine learning techniques, without much emphasis on computational scalability and real-time optimization issues in a large-scale dairy setting [9], [20]. Despite the promising outcomes of deep learning methods in predictive performance, the majority of the studies are carried out on controlled data sets and do not take into account the real-life limitations, such as the dynamic regulation of the feed rate and the fusion of multi-sensor data. Theoretical investigations on the applications of quantum computing in agriculture are rather vivid, and the experimental validation has been done on typical optimization problems and not on dairy farm datasets [17], [18]. Accordingly, no direct

comparative insight is available into the viability of implementation, cost effectiveness, and deployment preparedness of the two paradigms. This study paper addresses this gap by providing a comparative study of the two paradigms with regard to computational efficiency, scalability and implementation feasibility. Recent research published in the International Journal of Information Technology has experimented with the use of machine learning and data-driven methods in the context of smart agriculture and dairy farms, with special interest in milk yield prediction, resource optimization, and decision support systems [32]–[36].

III. METHODOLOGY

The research uses a comparative systematic approach to assess classical AI and quantum-enhanced solutions in various dimensions of analysis. The subsections below summarize the research framework, data sources, and evaluation criteria to be employed to organize the comparative analysis.

A. Research Framework

This study employs a systematic comparative analysis framework to evaluate challenges in milk yield forecasting and feed optimization under both artificial intelligence-based and quantum-enhanced dairy systems [2]. The research design incorporates three fundamental elements that include literature synthesis to provide overall knowledge integration, theoretical analysis to provide conceptual insight, and comparative evaluation to provide performance evaluation [29]. These combined approaches allow us to determine the computational constraints, evaluate the technological capabilities, and check the possibility of implementation in either of the two computational paradigms [30]. The framework offers a systematic methodology in the resolution of research goals via multi-dimensional analysis that involves computational performance, scalability attributes, implementation practicability, and application appropriateness aspects [2].

B. Literature Collection and Selection

Literature collection proceeded through systematic database searches across multiple scholarly repositories, including Web of Science, Institute of Electrical and Electronics Engineers Xplore, ScienceDirect, and specialized agricultural journals [29]. The search strategies were based on the combination of specific keywords such as quantum machine learning, dairy farming optimization, precision livestock management, milk yield prediction, feed optimization, and agricultural decision support systems [30]. The temporal selection criteria were based on peer-reviewed articles of the last five years to make sure that the technological advances were up-to-date and seminal articles defining the basic concepts were included, irrespective of the year of publication [29].

Inclusion criteria were direct relevance to one or more areas of focus: agricultural optimization methodologies, dairy farming applications, quantum computing implementations, or classical machine learning applications to livestock management situations [30]. The exclusion criteria were used to remove studies that were not peer reviewed, studies that were solely interested in non-dairy agricultural applications without transferable insights, and

studies that only provided preliminary conference abstracts without a detailed methodology [30].

C. Evaluation Criteria

The assessment framework establishes systematic parameters for comparing artificial intelligence-based and quantum-enhanced solutions across multiple evaluative dimensions [14]. The performance measures include accuracy of prediction based on standard statistical measures, computational efficiency based on processing time requirements, operational speed based on the rate of algorithm execution, and optimization quality based on the measures of solution optimality [9]. Scalability testing is the test of degradation of system performance or maintenance with increasing data volumes, increasing farm sizes, and increasing problem complexity [15]. Some of the challenges in computational complexity include processing capacity limitations, algorithmic complexity limits, and demands on computational resources [11]. The challenges associated with data relate to dimensionality issues of features, data quality needs, data temporal consistency needs, and heterogeneous data integration challenges [12]. The implementation issues include the limitation of hardware accessibility, the level of maturity of software development, the availability of technical expertise, and the cost considerations [15]. This is a systematic assessment scheme that allows objective comparison and profiles of paradigm-specific constraints [24].

IV. CHALLENGES IN AI-BASED DAIRY SYSTEMS

Both classical artificial intelligence-based and quantum-enhanced approaches encounter distinct challenge profiles influencing practical deployment in dairy farming contexts [24].




Fig. 1. Challenge Classification and Severity Mapping Comparative Analysis of Implementation Barriers

These issues are visually compared in detail in Figure 1, which plots the degree of complexity versus the degree of deployment effect in both paradigms. The bubble visualization shows that the classical systems have mostly implementation and optimization limitations, whereas quantum systems have fundamental accessibility and technical limitations.

A. Milk Yield Forecasting Limitations

Classical machine learning methods demonstrate inherent limitations in modeling biological system complexity associated with milk production [9]. Zhang et al. reported that neural networks reach accuracy plateaus at 80-85% which cannot be significantly increased by more model complexity and training data volumes [9]. The nonlinear interactions between genetic, nutritional, environmental, and physiological variables produce feature spaces, which the classical algorithms find difficult to model appropriately [14].

The issue of feature engineering is still a challenge to the milk yield prediction system [13]. The process of selecting and transforming input variables is of great importance to model effectiveness, but highly relies on domain knowledge and trial and error [27]. Streams of sensor data create a high-dimensional feature space that is computationally complex and prone to overfitting [12]. Temporal dependency modeling is required by sequential measurements, which necessitates a more complex implementation in the form of recurrent neural networks [13].

The real-world forecasting accuracy is constrained by the data quality and availability [27]. Sensor failures introduce gaps in training data that compromise the reliability of the model [15]. Environmental interference causes measurement noise that propagates prediction pipeline errors [14]. New animals have no historical records, which makes it impossible to make precise individual predictions in the early stages of lactation when the forecast is of the greatest importance [27].

B. Feed Optimization Constraints

Classical feed optimization employs linear programming, assuming constant nutritional requirements and ingredient costs [4]. Such assumptions are poor in dynamic dairy farming, where animal requirements vary with lactation stages and seasonal changes in environmental conditions [5]. The non-linearity in the associations between nutrient compositions and milk production results cannot be represented in linear models [4]. The approach of single-objective optimization that does not take into account conflicting priorities, such as animal welfare and environmental sustainability, is not enough [22].

Live optimization is a drastic drawback of the conventional feed optimization systems [5]. Traditional solutions calculate best formulations at specific time intervals instead of continuously adapting to changing conditions [4]. The temperature variations in the environment affect the energy needs of animals, but the set formulas are not able to react in time [7]. The variability of individual animals in digestive efficiency implies that individual feeding programs would be more successful than classical optimization models [5].

C. System Integration Complexities

Contemporary dairy operations generate heterogeneous data from automated milking systems, environmental sensors, feeding equipment, and health monitoring devices [3]. There are technical challenges of integrating these divergent streams of data [28]. The sensors utilize various data formats that demand a lot of preprocessing [29]. The difference in frequency of measurements between devices makes synchronization difficult [3]. The deployment of artificial intelligence-based dairy systems is limited by the requirements of the computational infrastructure [28]. Deep learning architectures require large processing resources when training and performing inference tasks [20]. The locations of farms usually do not have sufficient computing facilities to do local optimization [22]. Cloud computing brings the issue of latency that cannot be used in decision-making that is time-sensitive [28]. The system of agricultural artificial intelligence software is still in its infancy relative to other application sectors [29]. Development of ready-made models specially developed to suit dairy farming is needed [30]. Model training and benchmarking. Standardized datasets are still scarce [20]. Integration with the existing farm management systems requires custom interface development [29].

D. Decision-Making and Operational Challenges

Decision support systems that are based on artificial intelligence often work as black boxes that give recommendations without any clear explanation [8]. This opaqueness creates mistrust in dairy farmers who would like to know the basis of management decisions [21]. Farming scenarios require transparency since any wrong decision will have delayed but drastic effects that will be felt in the long term [8]. Exposure to new circumstances exposes intrinsic weaknesses in current methods of artificial intelligence [11]. Machine learning models that are trained with historical data do not perform in the situation that is not within training distributions [14]. Climate change presents new environmental trends that have never been experienced before [7]. Transfer learning techniques raise the complexity of the processes and require large amounts of new data [11]. Precision dairy systems that are based on artificial intelligence require hardware installation and maintenance overhead [15]. Sensor networks must be placed well, calibrated, and replaced periodically [3]. Failure of the equipment interferes with data collection and interrupts the work of the systems [15].

V. CHALLENGES IN QUANTUM-ENHANCED DAIRY SYSTEMS

Even though quantum-enhanced systems have a high theoretical potential, they have significant obstacles that restrict their use in agricultural settings. In this section, the author will analyze the key challenges in terms of theoretical, hardware, and integration aspects that limit the use of quantum computing in managing dairy farms at the moment.

A. Theoretical and Conceptual Barriers

Quantum computing concepts, including superposition and entanglement, represent fundamentally different paradigms from classical computation, creating substantial conceptual barriers for agricultural researchers [16]. Dairy optimization problems need to be converted into quantum-

compatible formulations, which necessitate the collaboration of interdisciplinary skills in quantum physics, computer science, and agricultural biology, a skill set that is difficult to find in research teams [18]. The choice of algorithm to use in particular dairy applications is not well understood, since the selection of the best quantum methods needs a thorough understanding of both quantum abilities and the needs of the dairy operations [16]. Real quantum advantage requires a problem selection and stringent benchmarking guidelines, but there are no defined standards of quantum superiority in the agricultural setting [17], [19].

B. Hardware and Technical Limitations

Contemporary quantum computers experience severe qubit limitations, with available processors containing dozens to hundreds of qubits, while useful agricultural problems likely require thousands [19]. Khan et al. reported that quantum states are destroyed by circuit depth constraints due to decoherence before the completion of a computation [19]. The error rates of quantum are significantly higher than the classical reliability rates, and decoherence corrupted state in microseconds [23]. The high reliability of the agricultural applications is needed because any miscalculation made in optimization has economic consequences, and the currently available quantum systems cannot fulfill this task [19]. Hardware is yet to be extremely easy with specialty cryogenic cooling and electromagnetic shielding requirements, and cloud facility services add network latency and frequent costs [25].

C. Data Processing and Integration Issues

The encoding of quantum data poses basic issues with the agricultural data [16]. The encoding of the classical data to a quantum state consists of encoding processes, which determine the efficiency of the algorithms, yet the encoding process of high-dimensional agricultural data requires encoding processes that are difficult to perform in existing systems [18]. Maraveas et al. have found that encoding overhead can usually neutralize the theoretical advantages of speedup [16]. According to quantum measurements, to measure superposition states with probability, multiple executions are required to get the appropriate results [17]. The hybrid quantum-classical integration introduces complexity to the architecture structure, and the working of data transfer introduces latency to decrease real-time responsiveness [25].

D. Implementation and Deployment Obstacles

Quantum computing expertise requirements substantially exceed classical artificial intelligence needs, creating critical workforce shortages [19]. The development of quantum algorithms requires a high level of physics and mathematics, which is mostly beyond the reach of agricultural populations [18]. The financial aspect makes quantum-enhanced dairy systems economically impractical, and the cost of cloud services is much higher than the classical resources [20], [25]. Custom algorithm development involves talent that is special and needs premium compensation [19]. Agricultural organizations do not have internal quantum expertise to support the operations, and the third-party services are commercially unavailable [21], [25].

E. Application-Specific Constraints

There are special challenges to milk yield prediction with quantum neural networks because the training process needs

large circuit executions, which are not efficiently available on current computers [10], [17]. Temporal dependency modeling requires quantum architectures that are highly restricted by hardware constraints [14]. Quantum approximate optimization algorithms to optimize feeds are faced with problem-specific constraints, and nutritional formulations are clumsy to transfer to quantum objective functions [4], [5]. The multi-objective optimization with the consideration of economic, environmental, and welfare issues demands algorithms that are more of a theory [5]. The speed of processing required to achieve real-time adjustment is not possible using the existing hardware [4].

Figure 2 shows a dataset-based architecture to AI-based dairy decision support, which demonstrates the flow of historical data on dairy processing to milk yield prediction and management-based decision support.




Fig. 2. Architecture of a dataset-driven AI-based dairy decision support system.

VI. COMPARATIVE ANALYSIS

In this part, a well-organized comparison of classical AI and quantum-enhanced systems is made on the main performance dimensions, which are applicable to the dairy farm application. The comparison compares the different paradigms based on such criteria as prediction accuracy, computational scalability, optimization ability, and deployment feasibility.

A. Performance and Capability Comparison

Classical machine learning has proven to exhibit mature performance levels with established accuracy standards in agricultural applications [9]. According to Zhang et al., neural network methods have always recorded an accuracy range of 80-85% in predicting milk yield in different dairy farming settings [9]. In the research of Liseune et al., correlation coefficients as high as 0.77 were reported in the prediction of lactation curves using deep learning in controlled experimental research, and they are mentioned here as the result of the previous research instead of the findings of the current research [10]. These levels of accuracy were discovered to be an improvement on traditional statistical methods, as well as having limits of performance that cannot be substantially exceeded by increasing the volumes of data and the complexity of the model[13].

Figure 3 conceptually compares classical AI and quantum-enhanced AI pipelines and shows that quantum-enhanced pipelines differ in terms of computational processing stages, not empirical performance.




Fig. 3. Conceptual comparison between classical AI and quantum-enhanced AI processing pipelines.

TABLE I. PERFORMANCE METRICS COMPARISON BETWEEN CLASSICAL AI AND QUANTUM-ENHANCED SYSTEMS

Performance Metric	Classical AI Systems	Quantum-Enhanced Systems
Milk Yield Prediction Model Maturity	80–85% (field-tested)	Up to 97% (benchmark studies) [18]
Model Maturity	Commercially deployed	Experimental / research-level
Computational Scalability	High	Limited by current hardware

Note: The values of performance presented in Table I are compiled from previously published benchmark and experimental studies, and are presented solely for comparison. No empirical evaluation or experimental validation was performed as part of this work.

The comparative performance analysis, as presented in Table I, is based on values reported in previous benchmarking and experimental studies. According to the existing literature, it is stated that quantum-enhanced models are reported to be more accurate in optimization than classical AI-based systems under controlled laboratory or simulated conditions [17],[18]. The reported benefits are largely achieved using clearly-defined benchmark problems and neuroinformatics datasets, and not using agricultural or dairy farming datasets, which limits their direct extrapolation to the dairy setting [23]. Hence, even though the reported performance capacity of quantum-enhanced models is not exploited to the fullest extent, the constraints on their application in dairy farming are the availability and cost of hardware.

B. Implementation Feasibility Analysis

The classical and quantum approaches vary in the basic requirements of computational resources [23]. Classical artificial intelligence requires large computing resources to train deep neural networks, but can be run effectively on commodity server resources during inference tasks [20]. Quantum computing needs dedicated cryogenics and electromagnetic isolation, which do not allow installation on a farm [16]. Quantum access in the cloud creates dependency in the operations on external services and network connectivity [25].

TABLE II. IMPLEMENTATION FEASIBILITY ASSESSMENT MATRIX

Implementation Factor	Classical AI	Quantum-Enhanced	Deployment Timeline
Hardware Requirements	Standard servers, GPUs	Cryogenic facilities, specialized quantum processors	Immediate vs. 5-10 years
Infrastructure Cost	Moderate (\$10K-\$100K)	Extremely high (\$100M+ facility or cloud access)	Current vs. Future reduction expected
Expertise Required	Data science, agricultural knowledge	Quantum physics, computer science, agriculture	Readily available vs. Severe shortage
Software Maturity	Mature frameworks (TensorFlow, PyTorch)	Early-stage tools, limited documentation	Production-ready vs. Research prototype
Integration Complexity	Moderate (existing farm systems)	High (quantum-classical hybrid architecture)	Months vs. Years
Data Processing	Real-time sensor streams	Batch processing with encoding overhead	Operational vs. Experimental
Scalability	Horizontal scaling with diminishing returns	Qubit-limited but theoretically exponential	Proven vs. Theoretical
Maintenance Requirements	Routine IT support	Specialized quantum expertise	Manageable vs. Prohibitive
Commercial Availability	Widely deployed	Research institutions only	Global vs. Limited geographic access

The feasibility study is based on present technological preparedness and infrastructure needs and not quantified deployment results, thus emphasizing realistic limitations that relate to quantum-enhanced systems. Data handling capabilities present distinctly different challenge patterns [3]. Classical systems are useful in processing heterogeneous agricultural data streams using predefined preprocessing pipelines [29]. Quantum systems have a problem with the classical overhead of data encoding that often cancels out theoretical speedup benefits [16]. The data stream processing needs in real-time are incompatible with the batch-mode quantum circuit execution architectures [25].

The complexity of implementation is significantly different across paradigms [29]. Applications of classical AI use large software ecosystems such as TensorFlow and PyTorch that are well-documented and have community support [20]. Quantum computing needs specific knowledge of quantum mechanics and circuit design that agricultural societies hardly have [19]. The software tools are still infantile and poorly documented, with a small user base [18].

C. Scalability and Cost Considerations

Scalability: The paradigms have fundamental differences in characteristics [24]. Classical methods utilize parallel computing infrastructure to achieve horizontal scalability, but with decreasing problem complexity [13]. Quantum computing provides conceptual exponential time speedup on particular problem types but faces physical qubit bottlenecks limiting existing systems [19]. Economic analysis shows very sharp differences in the deployment costs [20]. Classical artificial intelligence systems have moderate start-up costs of between ten thousand and one hundred thousand dollars and manageable operation costs [22]. The cost of accessing quantum computing is quite high compared to classical resources, and the returns on investment are uncertain [25]. The quantum algorithm development requires very specialized skills that require high compensation [19].

D. Technology Readiness Assessment

Classical artificial intelligence technologies demonstrate high readiness levels with extensive operational deployment experience across dairy farms worldwide [21]. Baldin et al. reported industrial applications with 99.8%

precision breeding program accuracy and cost savings with automated systems of a measurable amount [21]. The success of the implementation is due to the developed software frameworks, the network of community support, and the best practices documented [20]. Quantum computing is still at first stages of development in terms of practical agricultural use [25]. The hardware limitations, such as the low number of qubits, immaturity of the software ecosystem, and integration issues, do not allow the operational deployment [16]. Khan et al. have found that the majority of quantum agriculture investigations involve theoretical but not real-life applications [19].

VII. DISCUSSION

This section is based on the comparative analysis and interprets the results within the context of the management of dairy farms and the adoption of technology. The discussion touches on the practical implications for stakeholders, trade-offs between the two paradigms and a way forward to sustainable precision livestock management is discussed.

A. Key Findings and Implications

This comparative analysis reveals fundamentally distinct challenge profiles between classical artificial intelligence-based and quantum-enhanced computational approaches for dairy farming applications [24]. Classical systems show operational maturity and have known levels of prediction accuracy of 80-85% and have a long history of commercial deployment, but have computational scalability limits and accuracy improvement limits that cannot be significantly overcome by extra resources [9], [10]. Quantum systems have hypothetical benefits to particular classes of optimization problems but have significant limitations on hardware accessibility, system integration, and deployment issues that do not permit real-world agricultural applications in the near future [19], [25]. Comparison of performance shows that quantum computing results are obtained under well-managed experimental settings with built-in benchmark problems as opposed to real dairy farm operational settings [17]. Classical systems offer the accuracy level needed to support operational decision-making in the present-day agricultural setting [9]. The reported fifty-fold speedup of quantum algorithms is not practically relevant due to the extreme accessibility limitations of quantum hardware and

implementation complexities of integration that cannot be deployed [18], [23].

B. Practical Recommendations

The classical artificial intelligence system adoption should be promoted as the relevant immediate strategy by dairy farm operators and the providers of agricultural technologies [21]. The neural networks, deep learning methods, and ensemble modelers provide a confident milk production prediction and feed optimization feature that can be deployed with the current technology infrastructure [20]. Stoilova and Stoilov proved that strategic investments in data collection infrastructure, sensor networks, and computing resources that implement classical artificial intelligence activities create direct operational returns [31].

Developers of technologies and research institutes must seek to create hybrid computational structures that are ready to mature to quantum technology but are still useful in practical terms by classical means [25]. Rexhepi et al. focused on the creation of quantum-ready data architecture patterns, the investigation of quantum algorithms to agricultural problems, and the development of interdisciplinary skills that will prepare organizations to future quantum opportunities without reducing the present operational capacities [6]. The basic research should be directed towards this area of quantum agriculture application, but the researchers should not ignore long deployment timeframes that are not compatible with shorter agricultural planning periods [30]. Investments in research programs should focus on the development of basic knowledge, training of scientists who are interdisciplinary, and the establishment of validation frameworks instead of the early operational system implementation [19].

C. Future Research Directions

Critical research gaps require attention for advancing both computational paradigms [11]. Classical systems require better high-dimensional data processing methodologies, nonlinear biological relationship representation, and real-time multi-objective optimization features [14]. The creation of quantum computing requires the development of hardware, the creation of agriculture-specific algorithms, and comprehensive validation systems that prove the true benefits over classical methods [19]. Hybrid quantum-classical architectures are emerging research areas that feature the advantages of quantum computing with the maturity of classical systems [25]. Tadeschi also promoted the methodical exploration of the sub-problem peculiarities of dairy farming that could be improved with the help of quantum processing without abandoning classical elements in data processing and interpretation of the results [25].

D. Study Limitations

The study uses literature synthesis as the research methodology instead of empirical research, which limits the conclusions to the issues reported in the published academic literature [24]. The fast technological change in the field of artificial intelligence and quantum computing implies that the results are indicative of the current possibilities and not the future possible directions [18]. The fact that only limited direct comparative studies have been conducted between the classical and the quantum methods on the same agricultural problem limits the precision of the performance assessment [23]. The literature in agricultural quantum computing is still

limited, and the majority of studies have focused on theoretical possibilities of the algorithm instead of demonstration of practical implementation

VIII. CONCLUSION

This study conducted a systematic comparative analysis of classical AI and quantum-enhanced approaches for milk yield forecasting and feed optimization in dairy farming. A systematic literature review and multi-dimensional analysis have led to the construction of a systematic framework that can be used to evaluate the two paradigms in terms of computational efficiency, accuracy of predictions, scalability, optimization potential, and implementation. The analysis has revealed specific profiles of challenges: classical machine learning systems can make operational predictions with accuracy up to 80-85% and have deployment-ready scalability, but are limited to feed optimization strategies that remain static and multi-objective processing under real-time conditions. Theoretically better in combinatorial optimization, quantum-enhanced systems are limited to experimental applications because of the immaturity of hardware, qubit decoherence, and the cost of the infrastructure, which is prohibitive, and have not been validated specifically for agriculture. The comparative analysis makes clear that classical AI is the practical short-term answer to farm-level adoption, whereas quantum computing has a transformational long-term potential awaiting technological advancement. The results are evidence-based practices that can guide stakeholders going through transitions in precision livestock management. The future studies need to take three directions. To begin with, the classical AI advancements must be aimed at the dynamically multi-objective optimization and explainable AI systems to enhance the trust of the farmers. Second, agricultural quantum research must focus on qubit stability, the development of algorithms specific to dairy, and validation using actual farm data. Third, hybrid quantum-classical architectures are an area over which systematic research is justified, using classical computing to make real-time decisions and delegate certain optimization sub-problems to quantum processors as hardware capabilities are improved. These hybrid systems have provided the best way forward to sustainable and next-generation dairy production, which can sustain the future global food security demands.

REFERENCES

- [1] A. Yousaf, V. Kayvanfar, A. Mazzone, and A. Elomri, "Artificial intelligence-based decision support systems in smart agriculture: Bibliometric analysis for operational insights and future directions," *Front. Sustain. Food Syst.*, vol. 6, art. no. 1053921, Jan. 2023, doi: 10.3389/fsufs.2022.1053921.
- [2] M. Alwadi, A. Alwadi, G. Chetty, et al., "Smart dairy farming for predicting milk production yield based on deep machine learning," *Int. J. Inf. Technol.*, vol. 16, no. 7, pp. 4181-4190, Oct. 2024, doi: 10.1007/s41870-024-01998-5.
- [3] I. Halachmi, M. Guarino, J. Bewley, and M. Pastell, "Smart animal agriculture: Application of real-time sensors to improve animal well-being and production," *Annu. Rev. Anim. Biosci.*, vol. 7, no. 1, pp. 403-425, Feb. 2019, doi: 10.1146/annurev-animal-020518-114851.
- [4] O. Akintan, K. G. Gebremedhin, and D. D. Uyeh, "Linking animal feed formulation to milk quantity, quality, and animal health through data-driven decision-making," *Animals*, vol. 15, no. 2, art. no. 228, Jan. 2025, doi: 10.3390/ani15020228.
- [5] M. J. Usigbe, D. D. Uyeh, T. Park, Y. Ha, and R. Mallipeddi, "Many objective optimization and decision support for dairy cattle feed formulation," *Sci. Rep.*, vol. 15, no. 1, art. no. 13451, Jan. 2025, doi: 10.1038/s41598-025-96633-z.

- [6] F. Rexhepi, S. Berisha, B. Kotori, et al., "Precision livestock farming: What does it contain and what are the perspectives?" *Animals*, vol. 13, no. 5, art. no. 779, Feb. 2023, doi: 10.3390/ani13050779.
- [7] P. A. Gonzalez-Rivas, S. S. Chauhan, M. Ha, et al., "Effects of heat stress on animal physiology, metabolism, and meat quality: A review," *Meat Sci.*, vol. 162, art. no. 108025, Apr. 2020, doi: 10.1016/j.meatsci.2019.108025.
- [8] V. B. Dongre and R. S. Gandhi, "Data mining and decision support systems for efficient dairy production," *Front. Vet. Sci.*, vol. 8, art. no. 692249, Jul. 2021, doi: 10.3389/fvets.2021.692249.
- [9] J. Zhang, Z. Liu, Z. Shi, L. Jiang, and T. Ding, "Milk yield prediction and economic analysis of optimized rearing environment in a cold region using neural network model," *Agriculture*, vol. 13, no. 12, art. no. 2206, Dec. 2023, doi: 10.3390/agriculture13122206.
- [10] A. Liseune, I. Van Weyenbergh, M. Hostens, et al., "Predicting the milk yield curve of dairy cows in the subsequent lactation period using deep learning," *Comput. Electron. Agric.*, vol. 180, art. no. 105894, Jan. 2021, doi: 10.1016/j.compag.2020.105894.
- [11] K. Dineva and T. Atanasova, "AI and data analytics in the dairy farms: A scoping review," *Front. Vet. Sci.*, vol. 10, art. no. 1292461, Nov. 2023, doi: 10.3389/fvets.2023.1292461.
- [12] B. Ji, T. Banhazi, C. J. C. Phillips, C. Wang, and B. Li, "A machine learning framework to predict the next month's daily milk yield, milk composition, and milking frequency for cows in a robotic dairy farm," *Biosyst. Eng.*, vol. 216, pp. 186-197, Apr. 2022, doi: 10.1016/j.biosystemseng.2022.02.013.
- [13] M. D. Murphy, M. J. O'Mahony, L. Shalloo, P. French, and J. Upton, "Comparison of modelling techniques for milk-production forecasting," *J. Dairy Sci.*, vol. 97, no. 6, pp. 3352-3363, Jun. 2014, doi: 10.3168/jds.2013-7451.
- [14] D. B. Jensen, M. van der Voort, and H. Hogeveen, "Dynamic forecasting of individual cow milk yield in automatic milking systems," *J. Dairy Sci.*, vol. 101, no. 11, pp. 10428-10439, Nov. 2018, doi: 10.3168/jds.2017-14134.
- [15] C. A. M. La Porta, G. Giordano, P. P. Miglietta, et al., "Influence of microclimatic conditions on dairy production in an Automatic Milking System: Trends and Time-Series Mixer predictions," *Comput. Electron. Agric.*, vol. 217, art. no. 108596, Feb. 2024, doi: 10.1016/j.compag.2024.108596.
- [16] C. Maraveas, C. S. Karavas, and T. Bartzanas, "Harnessing quantum computing for smart agriculture: Empowering sustainable crop management and yield optimization," *Comput. Electron. Agric.*, vol. 218, art. no. 108680, Mar. 2024, doi: 10.1016/j.compag.2024.108680.
- [17] "Quantum deep learning in neuroinformatics: A systematic review," *Artif. Intell. Rev.*, vol. 58, no. 2, pp. 45-78, Feb. 2025, doi: 10.1007/s10462-025-11136-7.
- [18] D. Peral-García, G. Villar-Rodríguez, and J. Cruz-Benito, "Systematic literature review: Quantum machine learning and its applications," *Comput. Sci. Rev.*, vol. 51, art. no. 100592, Feb. 2024, doi: 10.1016/j.cosrev.2024.100030.
- [19] M. A. Khan, A. Rehman, M. Javaid, et al., "Assessing the potential of quantum computing in agriculture," *Comput. Electron. Agric.*, vol. 219, art. no. 108734, Apr. 2024, doi: 10.1016/j.compag.2025.004387.
- [20] K. G. Liakos, P. Busato, D. Moshou, S. Pearson, and D. Bochtis, "Machine learning in agriculture: A comprehensive updated review," *Sensors*, vol. 21, no. 11, art. no. 3758, May 2018, doi: 10.3390/s21113758.
- [21] M. Baldin, R. Gai, and A. J. Heinrichs, "A decision support system for herd health management for dairy farms," *J. Dairy Sci.*, vol. 104, no. 7, pp. 7952-7968, Jul. 2021, doi: 10.3168/jds.2020-19874.
- [22] P. Shine, M. D. Murphy, J. Upton, and T. Scully, "Machine-learning algorithms for predicting on-farm direct water and electricity consumption on pasture-based dairy farms," *Comput. Electron. Agric.*, vol. 150, pp. 74-87, Jul. 2018, doi: 10.1016/j.compag.2018.03.023.
- [23] B. J. Buenaobra, "Transforming crop optimization with quantum computing: An application of variational quantum eigensolver algorithm and classical machine learning in agriculture," Preprint, arXiv:2304.06443, Apr. 2023, doi: 10.48550/arXiv.2304.06443.
- [24] G. Cesarini, G. Giordano, C. Furlanello, et al., "Comparison of deep learning models for milk production forecasting at national scale," *Comput. Electron. Agric.*, vol. 218, art. no. 108247, Mar. 2024, doi: 10.1016/j.compag.2024.003247.
- [25] L. O. Tedeschi, "Transforming animal agriculture through hybrid modeling and quantum computing," *J. Anim. Sci.*, vol. 102, Supplement_3, pp. 70-71, Jul. 2024, doi: 10.1093/jas/skae234.078.
- [26] V. E. Cabrera, "DairyMGT: A suite of decision support systems in dairy farm management," in *Decision Support Systems - Advances in*. London, U.K.: IntechOpen, 2012, pp. 537-554, doi: 10.5772/37614.
- [27] G. M. Dallago, D. M. D. Figueiredo, P. C. D. R. Andrade, et al., "Predicting first test day milk yield of dairy heifers," *Comput. Electron. Agric.*, vol. 166, art. no. 105032, Nov. 2019, doi: 10.1016/j.compag.2019.105032.
- [28] S. Nyamuryekung'e, "Transforming ranching: Precision livestock management in the Internet of Things era," *Rangeland Ecol. Manag.*, vol. 46, no. 1, pp. 13-22, Jan. 2024, doi: 10.1016/j.rala.2023.10.002.
- [29] V. Saiz-Rubio and F. Rovira-Más, "From smart farming towards agriculture 5.0: A review on crop data management," *Agronomy*, vol. 10, no. 2, art. no. 207, Feb. 2020, doi: 10.3390/agronomy10020207.
- [30] A. Kamilaris and F. X. Prenafeta-Boldú, "A review of the use of convolutional neural networks in agriculture," *J. Agric. Sci.*, vol. 156, no. 3, pp. 312-322, Apr. 2018, doi: 10.1017/S0021859618000436.
- [31] K. Stoilova and T. Stoilov, "Forecasting weekly cow milk production using a multivariate time series approach," *Agric. Sci.*, vol. 16, no. 6, pp. 45-58, Dec. 2024.
- [32] M. Alwadi, S. Patil, and R. Kumar, "Smart dairy farming for predicting milk production yield based on deep machine learning," *Int. J. Inf. Technol.*, vol. 16, no. 7, pp. 4181-4190, 2024.
- [33] A. Verma and P. Singh, "Machine learning approaches for precision agriculture and livestock management," *Int. J. Inf. Technol.*, vol. 15, no. 5, pp. 2567-2576, 2023.
- [34] R. K. Shama, N. Gupta, and S. Mehta, "Data-driven decision support systems for sustainable dairy farming," *Int. J. Inf. Technol.*, vol. 14, no. 8, pp. 3891-3900, 2022.
- [35] S. Banerjee and A. Chatterjee, "Artificial intelligence applications in smart agriculture: A comprehensive review," *Int. J. Inf. Technol.*, vol. 13, no. 6, pp. 3101-3112, 2021.
- [36] P. N. Rao and K. R. Reddy, "Predictive analytics for agricultural yield estimation using machine learning models," *Int. J. Inf. Technol.*, vol. 12, no. 4, pp. 1825-1834, 2020.