

connector - with screw terminals one piece housing




Product description		
BALS-Prd.-Nr		303
EAN		4024941349703
Product category		Connector INNOLINQ
Current		16A
Number of poles		5p
Arrangement of phases		3p+N+PE
Position of earth contact		6 h
Voltage		200/346 - 240/415V~
Frequency		50/60Hz

Product description	
Protection degree	IP54
Colour code	red RAL 3000
Colour of appliance	Hinged lid dark grey RAL 7012, Collar red RAL 3000, Cable gland dark grey RAL 7012, Housing cover dark grey RAL 7012
Connection design	with screw terminal
Maximum conductor size	2,5 qmm
Cable entry	Cable gland
Height	171mm
Width	71mm
Depth	94mm
Material of enclosure	Polyamide
Contacts	The contacts are brass, The contact carrier is made of high temperature resistant material

Additional technical information	
	Multi-Grip cable gland with gasket and integrated strain relief, Screwless housing connection with snap fastening, For cable diameter from 10 up to max. 21 mm

Logistics data	
Weight/pcs	0.237 kg / Piece
Packaging	Carton
Content amount	10 ST
EAN	4024941349710

Logistics data	
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.503 kg
Volume	8,787,032.9 mmq



Ampere Polzahl	16 3	16 5	32 3	32 4	32 5
ø a	55,0	68,0	69,0	69,0	76,0
x	157,0	171,0	205,0	205,0	205,0
y	59,0	71,0	80,0	80,0	80,0
z	80,0	94,0	99,0	99,0	105,0
ø e	18,0	21,0	29,0	29,0	29,0
Cond. mm² min	1	1	2,5	2,5	2,5
Cond. mm² max	2,5	2,5	6,0	6,0	6,0