


# POLYCAB SOLAR AS NZS 5000 XLPO – TWIST ANTI TERMITE

## Photovoltaic Power Cable, Halogen Free, Flame Retardant



Images not to scale. Follow table for dimensions

### APPLICATION

POLYCAB low smoke, halogen free, two single cores twisted cable with electron beam cross linked insulation and sheath is designed to use for Photovoltaic installation at the Direct current side. These cables are suitable for permanent outdoor use under variable climatic condition.

### CHARACTERISTICS

#### Voltage Rating

Nominal Voltage: 1500 V DC between conductors as well as conductor and earth. Max permitted voltage: 1800 V

#### Operation Temperature

Fixed: -40°C to +120°C

Maximum conductor temperature: +120°C

#### Bending Radius

For fixed installation - > 15D

For occasional moved - > 25D

### CONSTRUCTION

- Conductor: Aluminium conductor as per IEC 60228, class 2 / AS-NZS 5000.1
- Insulation: E-Beam cross linked halogen free and flame-retardant compound (XLPO), Colour: Black
- Anti Termite Jacket: Polyamide (Nylon), Colour: Black
- Sheath: E-Beam cross linked halogen free and flame-retardant compound (XLPO).

#### Core Identification

Black & Black with red Strip

#### Test Voltage

6.5kv AC 50Hz

### OUTSTANDING FEATURES

- Halogen free
- Electron Beam Cross-linked
- Flame retardant
- High life
- UV, Ozone resistant
- Hydrolysis resistant
- High temperature resistant
- Termite Resistant

### STANDARD FOLLOWS

IEC 60228  
AS/NZS 5000.1  
AS/NZS 3808  
EN 50618  
IEC 60332-1-2  
UL 4703  
IEC 62930

### COMPLIANCE

Fire Performance	- EN 60332-1
Smoke Emission	- IEC 61034/ EN 50268-2
Halogen free material	- EN 50267-2-1 / IEC 60754-2
Toxicity	- EN 50305
Resistance to ozone	- EN 50396
Weathering / UV	- HD 605/A1 or DIN 53667
Life Expectancy	- IEC 60216

### OUR ACCREDITATIONS



# POLYCAB SOLAR AS NZS 5000 XLPO – TWIST ANTI TERMITE

## Photovoltaic Power Cable, Halogen Free, Flame Retardant

### DIMENSIONS AND WEIGHTS:

No. of Cores	Core Cross sectional Area	Nominal insulation thickness	Min. Nylon Jacket thickness	Nominal Sheath thickness	Approx. Overall Diameter	Weight (Approx.)
No.	mm <sup>2</sup>	mm	mm	mm	mm	Kg/Km
2	120	1.2	0.2	1.5	20.3 x 40.6	1160
2	150	1.4	0.2	1.6	22.4 x 44.8	1420
2	185	1.6	0.2	1.6	24.4 x 48.8	1700
2	240	1.7	0.2	1.7	27.3 x 54.6	2160
2	300	1.8	0.2	1.8	29.9 x 59.8	2620
2	400	2.0	0.2	1.9	33.7 x 67.4	3380
2	500	2.2	0.2	2.0	37.2 x 74.4	4160
2	630	2.4	0.2	2.2	42.3 x 84.6	5440

### ELECTRICAL CHARACTERISTICS:

No. of Cores	Core Cross sectional Area	Max. DC Resistance at 20°C	Max. AC Resistance at 90°C	Approx. Cable Capacitance	Approx. Cable Reactance	Impedance of Cable at 90°C	Current Rating capacity		
							Two cables touching in air unenclosed spaced from surface	Two cable touching in air on surface	Two cable touching in enclosure Underground
No.	mm <sup>2</sup>	Ω/km	Ω/km	mfd/km	Ohm/km	Ohm/km	Amp.	Amp.	Amp.
2	120	0.253	0.325	0.81	0.0982	0.339	305	253	252
2	150	0.206	0.265	0.77	0.0965	0.282	350	291	283
2	185	0.164	0.212	0.75	0.0945	0.231	406	340	329
2	240	0.125	0.162	0.81	0.0918	0.186	485	408	388
2	300	0.100	0.130	0.85	0.089	0.158	562	473	440
2	400	0.0778	0.103	0.87	0.089	0.135	660	559	516
2	500	0.0605	0.0813	0.9	0.0869	0.118	772	656	590
2	630	0.0469	0.0649	0.92	0.0853	0.107	904	772	695

# POLYCAB SOLAR AS NZS 5000 XLPO – TWIST ANTI TERMITE



## Photovoltaic Power Cable, Halogen Free, Flame Retardant

### De-rating factor

Current Ratings are based on AS/NZS 3008 std, Max. Conductor Temperature at 90°C, Ambient temperature at 40°C in Air, Ambient temperature at 25°C in Ground, Soil thermal resistivity 1.2 k.m/W, Depth of Laying 0.5m.

Current rating de-rating factors for other than 40°C ambient air temperature.

Temperature	15	20	25	30	35	45	50	55	60	65	70	75	80	85
Factor	1.26	1.20	1.15	1.10	1.05	0.94	0.88	0.81	0.73	0.65	0.57	0.47	0.34	0.19

Current rating de-rating factors for other than 25°C ground temperature.

Temperature	10	15	20	30	35	40
Factor	1.11	1.07	1.03	0.97	0.93	0.89