


POLYCAB HFFR-01ZZ-K / 03XZZ-K flat Industrial Cords, 1100 V AC



Images not to scale. Follow table for dimensions

APPLICATION

POLYCAB HFFR-01ZZ-K/03XZZ-K flat, insulated and sheathed with halogen free flame retardant (HFFR) thermoplastic or cross-linked halogen free thermosetting compound confirming to IS 17048 is suitable to use in electric power and lighting for indoor use in AC single phase systems with rated voltage up to and including 1100 V. This cable is also suitable for DC systems with rated voltage up to and including 1500 V to earth

CHARACTERISTICS

Voltage Rating
1100 V

Operation Temperature
Fixed: -15°C to 70°C

CONSTRUCTION

- Bare or tinned bunched copper conductor as per IS 8130, class 5
- Insulated with halogen free flame retardant compound type HFI TP 70 or cross linked halogen free flame retardant compound (HFFR) type HFI-XL 70 to IS 17048
- Sheathed with halogen free flame retardant compound type HFS TP 70 or cross linked halogen free flame retardant compound (HFFR) type HFS-XL 70 to IS 17048

Core Identification

Two core Red and Black

Bending Radius

Fixed installation 6 x Overall diameter
Occasional 4 x Overall diameter

Test Voltage

3000V AC at room temperature

OUTSTANDING FEATURES

- Low Smoke
- Halogen Free
- Flame Retardant
- Highly Flexible

STANDARD FOLLOWS

IS 8130:2013
IS 17048:2018
IEC 60332-1-2

COMPLIANCE

Conductor resistance - IS 8130
Insulation resistance - IS 17048:2018
Oxygen Index > 31% As per ASTM D2863
Smoke emission test < 6% As Per ASTM D2843
Acid gas Generation - <0.0 As per IEC 60754-1
Under fire condition - Resist as per EN 60332

OUR ACCREDITATIONS



APPROVAL



NOTES

Sheathing with cross linked halogen free flame retardant HFS-XL 70 available on demand.

POLYCAB HFFR-01ZZ-K / 03XZZ-K flat Industrial Cords, 1100 V AC

Weight & Dimension Data

Product Code	Conductor size	Nominal insulation thickness	Overall dimension (Approx.)	Weight (Approx.)
	n x mm ²	mm	mm	kg/km
LDIS09CLUALS002C0.5S	2 x 0.5	0.6	6 x 3.9	46
LDIS09CLUALS002C.75S	2 x 0.75	0.6	6.4 x 4.1	54
LDIS09CLUALS002C001S	2 x 1	0.6	6.8 x 4.3	61
LDIS09CLUALS002C1.5S	2 x 1.5	0.6	7.3 x 4.6	74
LDIS09CLUALS002C2.5S	2 x 2.5	0.7	8.8 x 5.4	109
LDIS09CLUALS002C004S	2 x 4	0.8	10.1 x 6.1	144

Electrical characteristics

Current carrying capacity and maximum DC conductor resistance.

Nominal cross sectional area	Current rating	Maximum DC conductor resistance at 20°C
mm ²	Amp.	Ω/km
0.5	4	39
0.75	7	26
1	11	19.5
1.5	14	13.3
2.5	19	7.98
4	26	4.95

Air Ambient temperature: 40°C,

Conductor operating temperature: 70°C

The above table is in accordance with IS:3961(Part 5)

De-Rating Factor

De-rating factor for 70°C thermoplastic or thermosetting insulated cable

Ambient Temperature	35°C	40°C	45°C	50°C	55°C	60°C	65°C
De-Rating Factor	1.08	1	0.91	0.82	0.7	0.57	0.4