



Images not to scale. Follow table for dimensions

## APPLICATION

POLYCAB FR-LSH wire is eco-friendly & suitable for use where high flexibility is of prime importance. This is also suitable for indoor installation in industries, household appliances and building electrification.

## OUTSTANDING FEATURES

- Optimised current carrying capacity
- Fire retardant and safe for protection
- Low emission of toxic gases
- Low carbon emission
- Low volatile organic content – less contamination
- High conductivity electrolytic copper conductor

## CHARACTERISTICS

**Voltage Rating**  
1100 V

**Operation Temperature**  
Fixed: -15°C to 70°C

**Bending Radii**  
Fixed installation 6 x Overall Diameter  
Occasional 4 x Overall Diameter

## CONSTRUCTION

- Annealed stranded or bunched copper conductor as per IS 8130, class 2 or class 5
- Insulated by PVC Type D with FR-LSH to IS 5831

### Core Identification

Red/Yellow/Blue/Black/Green/any customise colour

### Electrical Property

- High insulation resistance
- Higher current carrying capacity
- Electrical energy saving

### Mechanical & Physical Properties

- High Flexibility
- Free from hazardous substances
- Resistant to Termite & Rodent
- Resistant to moisture for use in wet area
- High abrasion resistance
- Resistant to Acid & Alkali

**Test Voltage**  
3000 V AC at (20±5) °C

## STANDARD FOLLOWS

IS 8130:2013  
IS 5831:1984  
IS 694:2010

## COMPLIANCE

Conductor resistance test IS 8130  
Flammability IEC 60332-1  
Oxygen index ASTM D 2863  
Temperature index IEC 60332-1  
Halogen acid gas generation IEC 60754-1  
Smoke density ASTM D 2843-19

## OUR ACCREDITATIONS



## APPROVAL



## NOTES

**WEIGHT AND DIMENSION:**

Product code	Nominal cross-sectional area mm <sup>2</sup>	Class of conductor	No. of wire/wire dia. No./mm	Nominal insulation thickness mm	Overall dia. (Approx.) mm
LDIS09CYUAYL001C.75S	0.75	5	24/0.2	0.6	2.3
LDIS09CYUAYL001C001S	1	2	14/0.3	0.6	2.5
LDIS09CYUAYL001C001S	1	5	32/0.2	0.6	2.5
LDIS09CYUAYL001C1.5S	1.5	2	22/0.30	0.7	3.0
LDIS09CYUAYL001C1.5S	1.5	5	30/0.25	0.6	2.8
LDIS09CYUAYL001C2.5S	2.5	2	36/0.30	0.8	3.4
LDIS09CYUAYL001C2.5S	2.5	5	50/0.25	0.7	3.6
LDIS09CYUAYL001C004S	4	5	56/0.3	0.8	4.2
LDIS09CYUAYL001C006S	6	5	84/0.3	0.8	4.7
LDIS09CYUAYL001C010S	10	5	80/0.4	1	6.1
LDIS09CYUAYL001C016S	16	5	126/0.4	1	7.1

**Electrical characteristics**

Current carrying capacity and Max. DC conductor resistance.

Nominal cross-sectional area mm <sup>2</sup>	Class of conductor	Reference Method B (enclosed in conduit on a wall or in trunking etc.) Amp.	Reference Method C (clipped direct) Amp.	Maximum DC conductor resistance at 20°C Ω/km
0.75	5	7	7.5	26
1	2	11.6	12.6	18.1
1	5	11	12	19.5
1.5	2	14.7	16.8	12.1
1.5	5	14	16	13.3
2.5	2	20	23.1	7.41
2.5	5	19	22	7.98
4	5	26	29	4.95
6	5	31	37	3.3
10	5	42	51	1.91
16	5	57	68	1.21

The ambient temperature is 40°C.

Conductor operating temperature 70°C.

**De-Rating Factor**

**De-rating factor for various ambient temperature.**

Ambient Temperature	35°C	40°C	45°C	50°C	55°C	60°C	65°C
De-Rating Factor	1.08	1	0.91	0.82	0.7	0.57	0.4

POLYCAB