



Images not to scale. Follow table for dimensions

## APPLICATION

POLYCAB MV 19/33 KV XLPE insulated with Aluminium conductor single core cable is suitable to use for power supply to wide networks i.e. Commercial, Industrial and Urban / Residential.

## CHARACTERISTICS

### Voltage Rating

Nominal Voltage: 19/33 (36) kV

### Operation Temperature

Min. installation temperature: 0°C

Operating temperature: -25°C to +90°C

Emergency operating temperature: 105°C  
(max. operation of 36hrs, at 3 periods for 12 consecutive months use)

Max. Short Circuit Temperature: 250°C

### Bending Radius:

Fixed Installation: 20D

During Installation: 30D

D is diameter over nylon

## CONSTRUCTION

- Conductor: Stranded Compacted Circular aluminium conductor as per AS/NZS 1125
- Conductor Screen: Extruded Semi-conductive compound
- Insulation: XLPE
- Insulation Screen: Extruded strippable Semi-conductive compound
- Longitudinal Water blocking : Water blocking tape above and below copper screen (Optional)
- Metallic Insulation Screen: Copper Wire Screen + helically applied copper tape (E/F current capacity – Based on requirement)

### Composite sheath

- Inner layer : Extruded Polyvinyl Chloride, Colour: Orange
- Termite Protection: Polyamide (Nylon -12)
- Outer layer: HDPE (Black)

## OUTSTANDING FEATURES

- Long life
- UV resistant
- Resistant to chemical exposure
- Resistant to weather exposure
- Resistant to water (AD7/AD8)
- Termite resistant

## STANDARD FOLLOWS

AS/NZS 1429.1

AS/NZS 1125

AS/NZS 3808

## COMPLIANCE

- Conductor resistance AS/NZS 1125
- Insulation resistance AS/NZS 1429.1
- Voltage test AS/NZS 1429.1

## OUR ACCREDITATIONS



## APPROVAL



## NOTES

High Voltage Test (kV AC)	Partial discharge test (kV AC)		Impulse test Voltage (kV peak)
	200% to rated voltage	150% to rated voltage	
63	38	29	200

# POLYCAB SC ANTI-TERMITE MV AS/NZS 1429.1 19/33 (36) KV

## MV Cable AL Conductor, XLPE Insulation, CU Screen and UA

### DIMENSIONAL CHARACTERISTICS:

Product Code	No. of Cores	Core Cross sectional Area	Nominal Diameter		
	No.	mm <sup>2</sup>	Under metallic screen mm	Over metallic screen mm	Overall mm
MVNZ54AXUAPH001C050SAXXXX	1	50	27.2	29.1	36.0
MVNZ54AXUAPH001C070SAXXXX	1	70	28.8	30.7	37.0
MVNZ54AXUAPH001C095SAXXXX	1	95	30.4	32.3	39.0
MVNZ54AXUAPH001C120SAXXXX	1	120	32	33.9	41.0
MVNZ54AXUAPH001C150SAXXXX	1	150	33.3	35.2	42.0
MVNZ54AXUAPH001C185SAXXXX	1	185	35	36.9	44.0
MVNZ54AXUAPH001C240SAXXXX	1	240	37.3	39.2	46.0
MVNZ54AXUAPH001C300SAXXXX	1	300	39.5	41.4	49.0
MVNZ54AXUAPH001C400SAXXXX	1	400	42.2	44.1	52.0
MVNZ54AXUAPH001C500SAXXXX	1	500	45.6	47.5	55.0
MVNZ54AXUAPH001C630SAXXXX	1	630	48.8	50.7	59.0
MVNZ54AXUAPH001C800SAXXXX	1	800	52.7	54.6	63.0
MVNZ54AXUAPH001C01KSAXXXX	1	1000	57.2	59.1	68.0

• Above mentioned parameters are based on 3kA/sec earth fault current capacity of copper screen

### ELECTRICAL CHARACTERISTICS:

No. of Cores	Core Cross sectional Area	Max. DC Resistance at 20°C	Max. AC Resistance at 90°C	Approx. Capacitance	Approx. Inductance	Approx. Reactance	Continuous Current Rating					
							In ground at 20°C		In Ducts		In air at 30°C	
							Flat	Trefoil	Flat	Trefoil	Flat	Trefoil
No.	mm <sup>2</sup>	Ω/km	Ω/km	μF/km	mH/km	Ω/km	Amps					
1	50	0.641	0.822	0.14	0.500	0.157	157	152	146	142	189	184
1	70	0.443	0.568	0.15	0.464	0.146	192	186	178	176	236	230
1	95	0.32	0.411	0.17	0.443	0.139	229	221	213	210	287	280
1	120	0.253	0.325	0.18	0.422	0.132	260	252	242	240	332	324
1	150	0.206	0.265	0.19	0.409	0.128	288	281	271	267	376	368
1	185	0.164	0.211	0.21	0.394	0.124	324	317	307	303	432	424
1	240	0.125	0.161	0.23	0.377	0.118	373	367	356	351	511	502
1	300	0.1	0.129	0.25	0.363	0.114	419	414	402	397	586	577
1	400	0.0778	0.101	0.27	0.350	0.110	466	470	457	451	676	673
1	500	0.0605	0.080	0.3	0.337	0.106	525	530	510	505	760	750
1	630	0.0469	0.063	0.33	0.326	0.102	580	585	560	555	860	850

Document No.: 00370.Rev No.: 00 Date: 04-01-2024 / We reserve the rights to make technical changes.

POLYCAB SC ANTI-TERMITE MV AS/NZS 1429.1 19/33

(36) KV

MV Cable AL Conductor, XLPE Insulation, CU Screen and UA

POLYCAB

IDEAS. CONNECTED.

No. of Cores	Core Cross sectional Area	Max. DC Resistance at 20°C	Max. AC Resistance at 90°C	Approx. Capacitance	Approx. Inductance	Approx. Reactance	Continuous Current Rating					
							In ground at 20°C		In Ducts		In air at 30°C	
							Flat	Trefoil	Flat	Trefoil	Flat	Trefoil
No.	mm <sup>2</sup>	Ω/km	Ω/km	μF/km	mH/km	Ω/km	Amps					
1	800	0.0367	0.051	0.36	0.315	0.099	650	655	620	615	960	950
1	1000	0.0291	0.042	0.4	0.306	0.096	715	705	670	665	1060	1050

\*: Current Ratings are based on IEC 60502-2 & IEC 60287, Max. Conductor Temperature at 90°C, Ambient temperature at 30°C in Air / at 20°C in Ground, Thermal resistivity of Soil 1.5 k.m/W & for earthenware ducts 1.2k.m/W and Depth of Laying 0.8m.

Current rating de-rating factors for other than 30°C ambient air temperature.

20	25	35	40	45	50	55	60
1.08	1.04	0.96	0.91	0.87	0.82	0.76	0.71

Current rating de-rating factors for other than 20°C ground temperature.

10	15	25	30	35	40	45	50
1.07	1.04	0.96	0.93	0.89	0.85	0.80	0.76