

wall mounting socket outlet, switched, interlocked and fused - housing dimensions 460x180, with mounting rail



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 17541 |
| EAN | 4024941175418 |
| Product group | GT wall mounting socket outlet switched interlocked, fused |
| Current | 63A |
| Number of poles | 5p |
| Arrangement of the phases | 3P+N+PE |
| Earth 'clock' position | 6 h |
| Voltage | 200/346 up to 240/415V |

| Product description | |
|------------------------|--|
| Frequency | 50 and 60Hz |
| Protection degree | IP67 |
| Colour code | red |
| Colour of appliance | Operating window smoky topaz, Hinged lid red, Bayonet ring grey, Housing screws grey, Housing bottom grey, Housing top grey, Control knob grey |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 25,0 qmm |
| Cable entry | top entry M40 bottom entry M40/M32 |
| Height | 503mm |
| Width | 180mm |
| Depth | 192mm |
| Dimension of enclosure | 460x180 mm (HxW) |
| Material of enclosure | Polycarbonate |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | The cable entry is one at top and two at bottom open |
| | In 0-position lockable for 4 padlocks with bow diameter up to 7 mm |
| | With mounting rail, With mounting rail for 8 modules, vertical |

| Logistics data | |
|----------------|---------------|
| Weight/pcs | 3.41 |
| Packaging | Cart |
| Content amount | 1 ST |
| EAN | 4024941175418 |
| Length | 560 mm |
| Width | 215 mm |
| Height | 260 mm |
| Weight | 3.877 kg |
| Volume | 26,400 ccm |

