



POLYCAB BMS 300 MC-C4

BMS Cable PVC Insulated Overall Braided 300V.



Images not to scale. Follow table for dimensions

APPLICATION

POLYCAB BMS 300 MC-C4, Flexible copper conductor, PVC insulated, laid up with tinned copper braided and FRLS sheathed cable conforming to BS EN 50288-7 are designed for transmission of analogue and digital signals in Building management system. POLYCAB BMS 300 MC-C4 cables are used for diverse applications for control & monitoring of service provided within the building.

CHARACTERISTICS

Voltage Rating
300 V

Operation Temperature
Max.: PVC 70°C

Bending Radius
12 x Overall diameter

CONSTRUCTION

- Flexible (Class 5) Copper conductor as per EN 60228
- Insulated with PVC Type A as per EN 50288-7
- Tinned copper wire braided.
- Sheathed with Extruded PVC FRLS as per EN 50290-2-22

Core Identification

White/Grey core with number printing.

Outer sheath colour: Blue

OUTSTANDING FEATURES

High life
Flame Retardant
Low Smoke
Flexible

STANDARD FOLLOWS

EN 50288-7
EN 50288-1
EN 60228
EN 50290-2-22
EN 60332-1-2

COMPLIANCE

Conductor resistance - EN 60228
Insulation resistance - EN 50288-7
L/R Ratio - EN 50288-7
Mutual capacitance - EN 50288-7

OUR ACCREDITATIONS



APPROVAL



NOTES

Note: As per the application/identification requirement, other colour also available on request.

POLYCAB BMS 300 MC-C4

BMS Cable PVC Insulated Overall Braided 300V.

Weight & Dimension Data :

300 VOLTS, MULTI CORE, FLEX.COPPER, PVC TYPE A INSULATED, OVERALL TINNED COPPER WIRE BRAIDED BMS CABLES AS PER EN 50288-7

Area of conductor	No.of core	Min. thickness of insulation	Nominal thickness of outer sheath	Nominal overall Diameter	Approx. weight
sqmm		mm	mm	mm	kg/km
0.5	2	0.26	0.83	4.84	37
0.5	3	0.26	0.84	5.09	45
0.5	4	0.26	0.86	5.49	53
0.5	5	0.26	0.87	5.93	63
0.5	6	0.26	0.89	6.39	72
0.5	7	0.26	0.89	6.39	78
0.5	8	0.26	0.92	7.09	90
0.5	10	0.26	0.95	7.94	108
0.5	12	0.26	0.96	8.18	122
0.5	16	0.26	0.99	9.02	153
0.5	18	0.26	1.01	9.48	169
0.5	19	0.26	1.01	9.48	175
0.5	20	0.26	1.03	9.99	186
0.5	24	0.26	1.06	11.03	219
0.75	2	0.26	0.85	5.29	45
0.75	3	0.26	0.86	5.57	56
0.75	4	0.26	0.88	6.03	68
0.75	5	0.26	0.90	6.52	80
0.75	6	0.26	0.92	7.05	93
0.75	7	0.26	0.92	7.05	101
0.75	8	0.26	0.95	7.85	116
0.75	10	0.26	0.98	8.82	141
0.75	12	0.26	0.99	9.11	161
0.75	16	0.26	1.03	10.06	203
0.75	18	0.26	1.05	10.59	225
0.75	19	0.26	1.05	10.59	233

POLYCAB BMS 300 MC-C4
BMS Cable PVC Insulated Overall Braided 300V.

Area of conductor	No.of core	Min. thickness of insulation	Nominal thickness of outer sheath	Nominal overall Diameter	Approx. weight
sqmm		mm	mm	mm	kg/km
0.75	20	0.26	1.07	11.17	247
0.75	24	0.26	1.11	12.36	293
1	2	0.26	0.86	5.66	53
1	3	0.26	0.88	5.97	66
1	4	0.26	0.90	6.48	81
1	5	0.26	0.92	7.03	96
1	6	0.26	0.94	7.61	112
1	7	0.26	0.94	7.61	123
1	8	0.26	0.97	8.49	141
1	10	0.26	1.01	9.57	173
1	12	0.26	1.02	9.88	197
1	16	0.26	1.06	10.94	251
1	18	0.26	1.08	11.52	278
1	19	0.26	1.08	11.52	289
1	20	0.26	1.11	12.17	307
1	24	0.26	1.15	13.48	364
1.5	2	0.35	0.90	6.63	71
1.5	3	0.35	0.92	7.03	91
1.5	4	0.35	0.94	7.66	112
1.5	5	0.35	0.96	8.34	134
1.5	6	0.35	0.99	9.08	157
1.5	7	0.35	0.99	9.08	173
1.5	8	0.35	1.03	10.18	200
1.5	10	0.35	1.08	11.52	245
1.5	12	0.35	1.10	11.91	282
1.5	16	0.35	1.15	13.23	360
1.5	18	0.35	1.17	13.96	401
1.5	19	0.35	1.17	13.96	417

POLYCAB BMS 300 MC-C4

BMS Cable PVC Insulated Overall Braided 300V.

Area of conductor	No.of core	Min. thickness of insulation	Nominal thickness of outer sheath	Nominal overall Diameter	Approx. weight
sqmm		mm	mm	mm	kg/km
1.5	20	0.35	1.20	14.77	442
1.5	24	0.35	1.26	16.40	526

For Cables of sizes or cores not listed above the product data is available on request
Dimensions & Weights are representative figures and may vary

Electrical Parameter

Area of Conductor	Max. DC resistance of conductor at 20°C Plain wires	Insulation resistance (PVC)	Mutual capacitance (PVC)	Inductance to resistance ratio(L/R)
Sqmm	Ohm/km	MΩ/Km	nf/Km	μH/Ω
0.5	39	10	250	< 25
0.75	26	10	250	< 25
1	19.5	10	250	< 25
1.5	13.3	10	250	< 40