

WEEK04 LECTURE

EXTENDING SQL

LIMITATIONS OF BASIC SQL

What we have seen of SQL so far:

- Data definition language (create table (...))
- Constraints (domain, key, referential integrity)
- Query language (select ... from ... where)
- Views (give names to SQL queries)

NEW DATA TYPES

SQL data definition language provides:

- Atomic types: integer, float, character, Boolean
- Ability to define tuple types (create table)
 - o Create domain Positive as integer check (value>0);
 - o Create type Rating as enum ('poor', 'ok', 'excellent');
 - An ENUM is a string object with a value chosen from a list of permitted values that are enumerated explicitly in the column specification at table creation time.
 - An enumeration value must be a quoted string literal
 - o Create type Pair as (x integer, y integer);

NEW FUNCTIONS

SQL provides for new functions via stored procedures

Create function f (arg1 type1, arg2 type2, ...) returns type
As \$\$ function body \$\$ language language [mode]

Possible modes:

1. Immutable : does not access database (fast)
2. Stable : does not modify the database
3. Volatile : may change the database (slow, default)

EXERCISE: FUNCTIONS ON (SETOF) INTEGERS

QUERIES

ADVANCED QUERY TYPES

- Many specialized types of query have been identified
- We have seen: select/project/join, aggregation, grouping
- Many modern queries (e.g. skyline) come from OLAP
- Two important standard query types:
 1. Recursive: e.g. to manage hierarchies graphs
 2. Window: e.g. to spread group by summaries

WINDOW FUNCTIONS

- Group-by allows us to
 - o Summarize a set of tuples
 - o That have common values for a set of attributes

- E.g. average mark for each student
Select student, avg(mark) from CourseEnrolments
Group by students;
- Produces a single summary tuple for each group.
- Window functions allow us to
 - o Compute summary values for a group
 - o Append the summary value to each tuple in the group

Window functions operate on asset or rows and return a single value for each row from the underlying query. The term window describes the set of rows on which the function operates. A window function uses values from the rows in a window to calculate the returned values.

*** the OVER() clause has the following capabilities:*

- 1- defines window partitions to form groups or rows (partition by)
 - 2- orders rows with a partition (order by)
-

- E.g. attach student's average mark to each enrolment
Select *, avg(mark)
Over (partition by student) from CourseEnrolments;
select student, avg(mark) ... group by student

student	avg
46000936	64.75
46001128	73.50

```
select *, avg(mark) over (partition by student) ...
```

student	course	mark	grade	stueval	avg
46000936	11971	68	CR	3	64.75
46000936	12937	63	PS	3	64.75
46000936	12045	71	CR	4	64.75
46000936	11507	57	PS	2	64.75
46001128	12932	73	CR	3	73.50
46001128	13498	74	CR	5	73.50
46001128	11909	79	DN	4	73.50
46001128	12118	68	CR	4	73.50

WITH QUERIES

- We often break a complex query up into views: e.g.
Create view V as select a,b,c from ... where ...;
- WITH allows scoped/temporary views
- View v and w
 - o Only exist while this query is evaluated
 - o Are not accessible in any other context

... WITH Queries

WITH allows scoped/temporary views, e.g.

```
with V as (select a,b,c from ... where ...),
     W as (select d,e from ... where ...)
select V.a as x, V.b as y, W.e as z
from   V join W on (v.c = W.d);
```

The views V and W

- only exist while this query is evaluated
- are not accessible in any other context

V and W are also called "common table expressions" (CTEs)

... WITH Queries

Note that named subqueries achieve the same effect:

```
select V.a as x, V.b as y, W.e as z
from   (select a,b,c from ... where ...) as V,
       (select d,e from ... where ...) as W
where  V.c = W.d;
```

For this purpose, WITH is a syntactic convenience.

However, WITH also provides recursive queries.

RECURSIVE QUERIES

Recursive queries are defined as:

```
with recursive T(a1, a2, ...) as
(
    non-recursive select
  union
    recursive select involving T
)
select ... from T where ...
```

T(a₁, a₂, ...) is a recursively-defined view.

```
-- res, work, tmp are all temporary tables
res = result of non-recursive query
work = res
while (work is not empty) {
    -- using work as the value for T ...
    tmp = result of recursive query
    res = res + tmp
    work = tmp
}
return res
```

***** example: generate sum of first 100 integers:**

```
with recursive nums(n) as (
  select 1
  union
    select n+1 from nums where n < 100
)
select sum(n) from nums;
```

AGGREGATES

- Aggregates reduce a collection of values into a single result.
- Examples: count(Tuples), sum(Numbers)...
- The action of an aggregate function can be viewed as:

```
AggState = initial state
for each item V {
    AggState = newState(AggState,
V)
}
return final(AggState)
```

- Aggregates are commonly used with GROUP BY
- In the context they "summarize" each group

Example:

R	a	b	c
	1	2	x
	1	3	y
	2	2	z
	2	1	a
	2	3	b

```
select a,sum(b),count(*)
from R group by a
```

a	sum	count
1	5	2
2	6	3

USER-DEFINED AGGREGATES

- SQL standard does not specify user-defined aggregates.
- But PostgreSQL provides a mechanism for defining them.
- To define a new aggregate, first need to apply:
 - o BaseType: type of input values
 - o StateType: type of intermediate states
 - o State mapping function: `sfunc(state, value) -> newState`
 - o (optionally) an initial state of value (defaults to null)
 - o (optionally) final function: `ffunc(star)->result`

```
CREATE AGGREGATE AggName(BaseType) (  
    sfunc      = NewStateFunction,  
    stype      = StateType,  
    initcond   = InitialValue,  
    finalfunc  = FinalResFunction,  
    sortop     = OrderingOperator  
);
```

Example: defining the count aggregate (roughly)

```
create aggregate myCount(anyelement) (  
    stype      = int,      -- the accumulator type  
    initcond   = 0,        -- initial accumulator value  
    sfunc      = oneMore -- increment function  
);  
  
create function  
    oneMore(sum int, x anyelement) returns int  
as $$  
begin return sum + 1; end;  
$$ language plpgsql;
```

Example: sum2 sums two columns of integers

```
create type IntPair as (x int, y int);  
  
create function  
    AddPair(sum int, p IntPair) returns int  
as $$  
begin return p.x + p.y + sum; end;  
$$ language plpgsql;  
  
create aggregate sum2(IntPair) (  
    stype      = int,  
    initcond   = 0,  
    sfunc      = AddPair  
);
```

CONSTRAINTS

- Column and table constraints ensure validity of one table
- RI constraints ensure connections between tables are valid
- However, specifying validity of entire database often requires constraints involving multiple tables.

```
for all Branches b  
    b.assets == (select sum(acct.balance)  
                  from   Accounts acct  
                  where  acct.branch = b.location)
```

ASSERTIONS

- Assertions are schema-level constraints
 - o Typically involving multiple tables
 - o Expressing a condition that must hold at all times
 - o Need to be checked on each change to relevant tables
 - o If change would cause check to fail, reject change

```
CREATE ASSERTION name CHECK (condition)
```

- Example: #students in any UNSW course must be < 10000
 Create assertion ClassSizeConstraint check (


```

      Not exists (
        Select c.id
        from Courses c, CourseEnrolments e
        where c.id = e.course
        group by c.id having count(e.student) > 9999
      )
    )
  
```

TRIGGERS

- Triggers are
 - o Procedures stored in the database
 - o **Activated response to database event** (e.g. updates, inserted, deleted)
- Examples of uses for triggers:
 - o Maintaining summary data
 - When table a maintain table b, when table b got updated, table a will be updated automatically
 - o Checking schema-level constraints (assertions) on update
 - More efficiently than assertion
 - o Performing multi-table updates (to maintain assertions)
 - Instead of checking assertion, maintain other than just check
- Triggers provide event-condition-action(ECA) programming:
 - o An event activates the trigger
 - o On activation the trigger checks a condition
 - o If the condition holds, a procedure is executed (the action)
- Some typical variations on it:
 - o Execute the action before, after or instead of the triggering event
 - Before you withdraw the money, you do something, afterwards you do something
 - o Can refer to both old and new values of updated tuples
 - o Can limit updates to a particular set of attributes
 - o Perform action: for each modified tuple, once for all modified tuples
 - E.g. one update, can update all the tuples

The event can be insert, delete
Or update

FOR EACH ROW: after you do the
Updates, you do this

```

CREATE TRIGGER TriggerName
{AFTER|BEFORE} Event1 [ OR Event2 ....]
[ for each row ]
ON TableName
[ WHEN ( Condition )]
Block of procedural/SQL code
  
```

- Triggers can be activated BEFORE or AFTER the event
- OLD doesn't exist for insertion, NEW doesn't exist for deletion
- If activated BEFORE, can affect the change that occurs:
 - o NEW contains "proposed" value of changed tuple
 - o Modifying NEW causes a different value to be placed in DB
- If activated AFTER, the effects of the event are **visible**
 - o NEW contains the current value of the changed tuple
 - o OLD contains the previous value of the changed tuple
 - o Constraint-checking has been down for NEW

- Consider two triggers and an INSERT statement

Create trigger X before insert on T code1; Create trigger Y after insert on T code2; Insert into T values (a, b, c, ...);

(when you run the last line, insert statement)

1. Execute Code1 for trigger X
2. Code has access to (a, b, c, ...) via NEW (contains all the new values)
3. Code typically checks the values of a, b, c, ...
4. Code can modify values a, b, c .. in NEW (change the value/ update)
5. DBMS does constraint checking as if NEW is inserted (db assume that it's the new db then check)
6. If failed any checking, abort insertion and rollback
7. Execute code2 for trigger Y
8. Code has access to final version of tuple via NEW
9. Code typically does final checking or modifies other tables in database to ensure constraints are satisfied