# PIN RECEPTACLES

FOR .025" - .037" DIAMETER PINS AND .025" SQUARE PINS

1305
1305-0-15-XX-47-XX-04-0
Press-fit in .061 mounting hole


1306
1306-0-15-XX-47-XX-04-0
Press-fit in .061 mounting hole

7305
7305-0-15-XX-47-XX-10-0
Solder mount in .060 min. mounting hole
Also available on 8mm wide carrier tape:
6,000 parts per 13" reel
See page 194.12 for Tape & Reel details


0400
0400-0-15-XX-47-XX-04-0
Press-fit in .067 mounting hole

0335
0335-0-15-XX-47-XX-04-0
Hex press-fit in .064 plated through-hole

4614
4614-0-31-XX-47-XX-04-0
Compliant press-fit in .040 ± .003 plated hole. For .060" →.100" thick board


4615
4615-0-31-XX-47-XX-04-0
Compliant press-fit in .040 ± .003 plated hole. For .090" →.130" thick board


7614
7614-0-31-XX-47-XX-04-0
Compliant press-fit in .040 ± .003 plated hole. For .060" →.100" thick board


8401
8401-0-15-XX-47-XX-04-0
Hex press-fit in .063 plated through-hole


2400
2400-0-15-XX-47-XX-04-0
Press-fit in .066 mounting hole


6857
6857-0-15-XX-47-XX-10-0
Press-fit in .062 mounting hole

9393
9393-0-15-XX-47-XX-10-0
Press-fit in .067 mounting hole

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Inches

Tolerances On: Lengths: ±.005
Diameters: ±.002
Angles: ±2°

RoHS-2
2011/65/EU

ORDER CODE: XXXX - X - XX - XX - 47 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:
01 200 μ" TIN/LEAD OVER NICKEL
◆ **80** 200 μ" TIN OVER NICKEL (RoHS)
◆ **15** 10 μ" GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:
01 200 μ" TIN/LEAD OVER NICKEL
◆ **80** 200 μ" TIN OVER NICKEL (RoHS)
◆ **27** 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:
#47 CONTACT (DATA ON PAGE 256)
(For alternate contact choices, see group D on page 248)

PAGE 179 | PIN RECEPTACLES

MILL-MAX® Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com