Clinical drug response prediction using Lasso

ECSE 556 - Machine Learning in Network Biology
Homework 1

Yazdan Zinati
yazdan.zinati@mail.mcgill.ca
260928077

October 4, 2021

Introduction

Cancer is a preeminent cause of death worldwide [1]. Until recently, cancer treatments were solely chosen based on the cancer type and administered to all patients with a specific type of cancer. However, recent methods consider patient's genomic data for choosing cancer treatment [2]. Machine Learning models have been developed to predict drug responses of cancer cell lines (CCL) [3]. Nonetheless, one problem they face is the lack of sufficient samples. In this study, we use transcriptomic data from the Genomics of Drug Sensitivity in Cancer (GDSC) dataset containing gene expression and drug response data of cancer cell lines to predict the clinical drug response (CDR) of cancer patients. This study will ultimately improve our understanding of features that affect CCLs and will enable us to ensure more reliable patient care by tailoring cancer monotherapy to individuals and ensure more effective drug responses.

Preprocessing and data exploration

The GDSC gene expression dataset contains 13940 genes and 979 samples. As is the case with most transcriptomic datasets, we are facing the curse of dimensionality. The limited number of samples is one of the main bottlenecks in computational biology research. However, we will attempt to tackle this problem using Lasso in a later section.

Since libraries that we will use later assume that features (genes) correspond to columns and samples (cell lines) correspond to rows in our data frame, which is not the case in transcriptomic datasets, we transpose our data frame.

Next, we perform Z-score normalization by scaling and centering independently on each gene as genes have different baseline expressions. the standard score of a sample x is calculated using the equation bellow where u and s are the mean and standard deviation of the training samples.

$$z = \frac{(x - u)}{s}$$

Feature scaling is necessary in our case as we intend to perform dimensionality reduction, clustering, and regularized regression. PCA assigns more weight to variables with larger variance. Applying Z-score normalization will improve its performance as features will no longer have a different variance. When it comes to clustering, some rely on the distance between observations. A feature on a different scale than others might overly influence distance measures. Finally, as Lasso puts a constraint on coefficients associated with variables, a variable with a large magnitude will dominate and make the estimator incapable of learning from the rest of the features. Thus, this step is necessary to get the best performance in the tasks we are performing.

Dimensionality reduction

In this step, we visualize the high dimensional transcriptomic data using dimensionality reduction and map samples into a two-dimensional space. We use three different dimensionality reduction methods (PCA, t-SNE, and UMAP) and compare them.

Starting with PCA, we intend to select the principal components that are the most informative. To analyze the performance of PCA on our dataset, we examine the amount of variance explained by each principal component vector graphically through a scree plot. This scree plot is shown in Figure 1. Contrary to the ideal scree plot in which the first components explain most of the variability and the rest explain small fractions, our first component only explains 8% of the explained variance, with the second PC explaining just about 4%. Therefore, PCA would not perform well on our dataset if we for purposes other than visualization. However, as our goal is to visualize data in two-dimensional space, we choose the first two components.





Figure 1: PCA scree plot

Principal Component Analysis (PCA) is a linear dimensionality reduction technique. On the contrary, UMAP (Uniform Manifold Approximation and Projection) and t-SNE (t-distributed stochastic neighbor embedding) are non-linear dimensionality reduction techniques. As a result, PCA performs poorly on non-linear data due to being incapable of identifying complex non-linear relationships in the data. It can be influenced by the presence of outliers in the data. PCA does not involve hyperparameters which is an advantage over UMAP and t-SNE. From the three techniques, PCA is the least computationally expensive technique. UMAP is the second-best method in terms of time and space complexity. In our experiment, we found that a single run of each method took 0.6s, 6.3s, and 17s for PCA, t-SNE, and UMAP respectively. Even thought t-SNE outperformed UMAP in terms of runtime in our experiment, it is most likely due to the used parameters provided when calling the method, implementation details, or GPU parallelization. t-SNE is highly inefficient for large datasets as it computes pairwise conditional probabilities for each data point while trying to minimize the sum of the difference of the probabilities in higher and lower dimensions. Therefore, it scales quadratically and becomes impractical to use in large datasets. It is a common practice to use PCA to reduce features to a reasonable number before applying t-SNE to tackle this problem. UMAP does not need this preprocessing step like t-SNE when applied on large datasets. UMAP and PCA also have the advantage of being deterministic over t-SNE. The same output can be received on each run of the method. One of the main differences between the three dimensionality reduction methods is how they preserve local and global structures of the data. In summary, PCA is better at preserving the global structure, while t-SNE is better at preserving the local structure. UMAP is claimed to preserve the local structure and most of the global structure in the data. the goal of PCA is to find

the directions that maximize the variance in a dataset. Therefore, it does not preserve local neighborhoods, unlike t-SNE. The lack of preservation of global structure in t-SNE means that the distance between formed clusters is not interpretable. Two similar clusters are not necessarily at closer distances than two dissimilar ones.

Visually, we can see the formation of different clusters after performing dimensionality reduction on the dataset. This two-dimensional visualization is shown in Figure 2. We can clearly see the formation of three clusters in the UMAP visualization. It is slightly harder to distinguish the formed clusters in PCA and t-SNE as they are not as distanced as in the UMAP visualization. It should be noted that UMAP clusters are not only better separated than those formed by t-SNE and PCA but are also denser. Nonetheless, what we can see in all three visualizations is the presence of a large cluster and two smaller ones. In all three 2d visualizations, the larger cluster is close to one of the smaller clusters and separated by a distance from the third one. UMAP and t-SNE visualizations could have significantly changed based on the choice of parameters. In this study, we did not optimize the parameters for any of the dimensionality methods applied.




(a) PCA (b) t-SNE (c) UMAP

Figure 2: Two-dimensional visualization of the dataset using dimensionality reduction

Clustering


In this section, we perform clustering using k-means and agglomerative clustering. To find the optimal number of clusters in k-means, we plot the average silhouette plot and use the elbow/knee method on the knee plot. The silhouette plot determined how well each object lies within its cluster. We can see from Figure 3 (a) and Figure 4 (a) that 3 clusters maximize the silhouette value in both k-means and agglomerative clustering (ward linkage and euclidean affinity). Continuing with the exploration of k-means and agglomerative clustering, we visualize the elbow plot by fitting the k-means models on a range of k and plotting the SSE (Error Sum of Squares). We can identify the elbow from Figure 3 (b) at 4 clusters. This means that adding more clusters than 4 can make clusters hard to separate.

We also plot the dendrogram for agglomerative clustering in Figure 4 (b). As seen in the previous section about dimensionality reduction, we can identify one cluster greatly distanced from the other two as it is separated from the other two at a greater height.



(a) Average silhouette plot (b) Knee plot


Figure 3: K-means clustering exploration plots



(a) Average silhouette plot (b) Dendrogram


Figure 4: agglomerative clustering exploration plots

We use k-means and agglomerative clustering with ward linkage and euclidean affinity to cluster the cell lines into 4 clusters. Wile k-means took 3.8 seconds to cluster the data, this was done in 18.5 seconds using agglomerative clustering. Agglomerative clustering has a polynomial time complexity while k-means has linear time complexity. Formed clusters using both methods are visualized in two dimensions using dimensionality reduction techniques applied in the previous section in Figures 5 and 6. We can see that from two-dimensional visualizations the clusters formed are similar except for a few data points. To quantify this similarity, we for a 3×3 table showing the concordance between each cluster formed using k-means and agglomerative clustering. For this purpose, we use Jaccard similarity which is the ratio of intersection over union of two clusters. From the formed Jaccard table in Figure 7 (a), we can see high concordance between the same clusters inferred from both methods as the table diagonal values are close to 1.



(a) PCA (b) t-SNE (c) UMAP


Figure 5: Two-dimensional visualization of the dataset clustered using k-means



(a) PCA (b) t-SNE (c) UMAP


Figure 6: Two-dimensional visualization of the dataset clustered using agglomerative clustering

We once again perform agglomerative clustering but with average linkage, one using euclidean and once with cosine affinity measure. The resulting 2d plots are available in Figures 8 and 9. Unlike ward linkage that minimizes the variance of clusters being merged, average linkage uses the average of each observation of the two sets. We can see that agglomerative clustering using average linkage and euclidean affinity mainly created one cluster. This can also be seen from the Jaccard similarity table compared to the clusters previously formed by k-means as all cells in the table except for the cell corresponding to the second cluster in both methods are close to zero. Agglomerative clustering using cosine affinity also outputs very different results. In contrary to agglomerative clustering with average linkage and euclidean affinity, cosine affinity produces three clusters each with many data points. However, the Jaccard table compared to clusters formed by k-mean shows low concordance on half of the cells and a score close to 0.5 on the other half.



(a) kmeans/agglomerative clustering with default parameters

(b) kmeans/agglomerative clustering with average linkage and euclidean affinity



(c) kmeans/agglomerative clustering with average linkage and cosine affinity

Figure 7: Jaccard similarity table - rows correspond to clusters formed using k-means and columns using agglomerative clustering




Figure 8: Two-dimensional visualization of the dataset clustered using agglomerative clustering with average linkage and euclidean affinity.
From left to right: PCA, t-SNE, UMAP.




Figure 9: Two-dimensional visualization of the dataset clustered using agglomerative clustering with average linkage and cosine affinity.
From left to right: PCA, t-SNE, UMAP.

Regression

In this step, we use linear and lasso regression to predict the clinical drug response based on gene expression profiles from the GDSC dataset. We are provided with a drug response file. This CSV file contains the response of cell lines to 23 different drugs. The rows contain drugs, and the columns represent cell lines. The drug we are interested in predicting the response of is Doxorubicin. Doxorubicin is a chemotherapy medication used in the treatment of different kinds of cancer [4].

Before performing regression, we match the gene expression file to the drug responses. For this, we transpose the drug responses so each row corresponds to a cell line. Moreover, we remove any sample for which no response to Doxorubicin is recorded. This alone removes 107 cells lines and works against us due to the curse of dimensionality. Performing a regression using linear regression gives us an r^2 regression score of 1 on the training data, but an r^2 score close to zero on the test set. This clearly shows that linear regression overfits the data. To combat this issue, we perform a regularized regression using Lasso. We will penalize the features in the model to only keep the most important ones. This penalization is controlled using the α hyperparameter. We perform Lasso regression using values of α from 0.1 to 1 in increments of 0.2 and plot the number of selected features. This plot can be seen in Figure 10. We can see that an α of 0.1 limits the features to 195m and the number of features decreases as α increases. The number of features is limited to only one with α larger or equal to 0.7.

Next, we perform nested cross-validation to tune the α hyperparameter and to estimate the model's generalization error. When performing cross-validation in a non-nested manner on the data for tunning and evaluating the model, data leakage might occur depending on the dataset, biasing the model. As a result, the model evaluation will be optimistic and biased. In nested cross-validation, we have an outer loop we use for assessing the model's performance and an inner loop for parameter selection. We perform 4-fold cross-validation




Figure 10: Number of selected features by LASSO vs. the value of the α hyperparameter

on the outer loop and 3-fold cross-validation for the inner loop. This means that for each iteration of the outer loop, the outer training set is further split into 3 folds. We perform grid search with a mean squared error as score in the inner loop over α values from 0.02 to 1 with intervals of 0.01. We found that the best value of α was in the range of 0.2 to 0.3. From MSE scores reported in the outer loop, an α of 0.21 reported an MSE of 2.33. Using this an α of 0.21 resulted in a spearman correlation of 0.38. Note that we performed the nested cross-validation using MSE in the inner loop as the score and the score reported for spearman correlation does not come from the nested cross-validation. However, it is possible to repeat the same procedure for nested cross-validation replacing using spearman correlation as score. This wasn't done due to computational limitations.

Conclusion

To conclude, we performed a variety of studies on the transcriptomic dataset obtained from GDSC. We first performed dimensionality reduction using PCA, t-SNE, and UMAP and compared them together. We the used k-means and agglomerative clustering with different configurations and studies the concordance between formed clusters using each method. Finally, we used Lasso regression for drug response prediction of cancer cell lines. The latter was a challenging task due to the high dimensionality of the data and a lack of samples. This method has many limitations as it can not directly be applied to combination treatment. Furthermore, as we used preclinical samples in our predictions, the clinical drug response of real patients can be different. There are many areas of improvement and future directions. For example, it is possible to incorporate information about tissue type of CCLs to improve predictions either by using a labelled dataset or by clustering CCLs.

References

[1] Freddie Bray, Jacques Ferlay, Isabelle Soerjomataram, Rebecca L Siegel, Lindsey A Torre, and Ahmedin Jemal. Global cancer statistics 2018: Globocan estimates of incidence and

mortality worldwide for 36 cancers in 185 countries. *CA: a cancer journal for clinicians*, 68(6):394–424, 2018.

[2] Julianne D Twomey, Nina N Brahme, and Baolin Zhang. Drug-biomarker co-development in oncology–20 years and counting. *Drug resistance updates*, 30:48–62, 2017.

[3] Francisco Azuaje. Computational models for predicting drug responses in cancer research. *Briefings in Bioinformatics*, 18(5):820–829, 07 2016.

[4] Doxorubicin monograph for professionals.