

# R Package Development by means of Literate Programming (**noweb**)

Bernhard Pfaff

September 23, 2016

## 1 Introduction

## 2 Detecting Peaks/Troughs

### 2.1 Notation

A uniformly sampled time series  $\mathbf{y} = \{y_1, \dots, y_i, \dots, y_T\}$  with  $T$  data points is considered. The detection of peak/trough points is achieved by a function  $S(i, y_i, T)$  that returns for data point  $y_i$  a score value.<sup>1</sup> If this score value surpasses a user-provided threshold value  $\theta$ , /i.e/,  $S(i, y_i, T) \geq \theta$  then the point is considered as a local peak/trough.

Furthermore, in case local peak/trough points appear closely together with respect to time (clustered), then these points can be classified as a burst or bust, respectively.

### 2.2 Algorithms

In ? five different score functions  $S$  have been suggested. All have in common, that a centred window of size  $2 * k + 1$  around  $y_i$  is considered. That is, for a positive integer  $k$  the  $k$  right neighbours  $N^+(i, k, T) = \{y_{i+1}, \dots, y_{i+k}\}$  and the  $k$  left neighbours  $N^-(i, k, T) = \{y_{i-k}, \dots, y_{i-1}\}$  are employed for assessing  $y_i$  as a local peak/trough. The union of  $N^-(i, k, T)$  and  $N^+(i, k, T)$  is defined as  $N(i, k, T) = N^-(i, k, T) \cup N^+(i, k, T)$  and if the centre point is included as  $N'(i, k, T) = N^-(i, k, T) \cup y_i \cup N^+(i, k, T)$ .

The first function,  $S_1$ , computes the score value as the average of the maximum differences between  $y_i$  with its left and right neighbours. The function is defined as:

$$S_1 = \frac{\max(y_i - y_{i-1}, \dots, y_i - y_{i-k}) + \max(y_i - y_{i+1}, \dots, y_i - y_{i+k})}{2} \quad (1)$$

The equation (1) can be casted in R as:

```
1 <code>score_maxdiff 1</code>≡  
  scmaxdiff <- function(x, k){
```

---

<sup>1</sup>It suffices to provide a score function for peaks only. Trough points can be detected by using the negative values of the series  $\mathbf{y}$ .

```

    cp <- k + 1L
    lmax <- max(x[cp] - head(x, k))
    rmax <- max(x[cp] - tail(x, k))
    (lmax + rmax) / 2.0
}

```

Defines:

`scmaxdiff`, used in chunk 2b.

Instead of using the maximum differences of  $y_i$  with its  $k$  left and right neighbours as in (1), an alternative is to compute the mean differences and evaluate the average thereof:

$$S_2 = \frac{\frac{(y_i - y_{i-1}, \dots, y_i - y_{i-k})}{k} + \frac{(y_i - y_{i+1}, \dots, y_i - y_{i+k})}{k}}{2} \quad (2)$$

This equation can be casted in R as:

```

2a  <score-diffmean 2a>≡
    scdiffmean <- function(x, k){
      cp <- k + 1L
      ldmean <- x[cp] - mean(head(x, k))
      rdmean <- x[cp] - mean(tail(x, k))
      (ldmean + rdmean) / 2.0
    }

```

Defines:

`scdiffmean`, used in chunk 2b.

## 2.3 Combining score methods

```

2b  <score-wrapper 2b>≡
    score <- function(x, k,
                      scoreby = c("vote", "avg", "diff", "max", "ent",
                                   "ttype", "hybrid"),
                      tval = 1.0, confby = 3, ...){
      scoreby <- match.arg(scoreby)
      ans <- switch(scoreby,
                    vote = scvote(x, k, tval, confby, ...),
                    avg = scavgdifff(x, k),
                    diff = scdiffmean(x, k),
                    max = scmaxdiff(x, k),
                    ent = scentropy(x, k, ...),
                    ttype = scttype(x, k, tval),
                    hybrid = schybrid(x, k, tval, ...)
                    )
      ans
    }

```

Defines:

`score`, never used.

Uses `scdiffmean` 2a and `scmaxdiff` 1.

```

3a  <score-roxygen 3a>≡
    #' Basic scoring methods for local minima and maxima
    #'
    #' These are basic functions for evaluating the centre
    #' point of a time series as local minimum or maximum.
    #' Hereby, a score value is computed according to various methods.
    #' If the score is positive, the centre point is tentatively
    #' classified as a local peak.
    #' Incidentally, negative scores indicate a local minima.
    #'
    #' @param x \code{numeric}, vector of length \code{2 * k + 1}.
    #' @param k \code{integer}, the count of left/right neighbours.
    #' @param scoreby \code{character}, the scoring method to be used.
    #' @param tval \code{numeric}, factor for standard deviation band
    #' if \code{scoreby = 'ttype'}.
    #' @param confby \code{integer}, count of minimum vote,
    #' values in the set \code{3:5}.
    #' @param ... ellipsis argument.
    #'
    #' @name score
    #' @family scores
    #' @return \code{numeric}, the score value.
    NULL

    #' @rdname score
    #' @export

@

```

```

3b  <score.R 3b>≡
    <score-roxygen 3a>
    <score-wrapper 2b>
    #' @rdname score
    <score-maxdiff 1>
    #' @rdname score
    <score-diffmean 2a>

```

This code is written to file `score.R`.

@

## 3 Package structure

### 3.1 Preliminaries

First, a skeleton of the package

```
4  <DESCRIPTION.R 4>≡
    Package: hiker
    Title: Local Peak and Trough of a Time Series
    Version: 0.0.0.9000
    Authors@R: person("Bernhard", "Pfaff", email = "bernhard@pfaffikus.de",
                      role = c("aut", "cre"))
    Description: Methods for detecting local peaks and troughs of a time series.
    Depends: R (>= 3.3.1), zoo, methods
    License: GPL-3
    Encoding: UTF-8
    LazyData: true
```

This code is written to file DESCRIPTION.R.

@

## 3.2 Import directives and S4-classes

```
5 <Allclasses.R 5>≡
  #' @import methods
  NULL
  #' @import zoo
  NULL
  #' @importFrom stats density sd na.omit start end smooth
  NULL
  #' @importFrom utils head tail
  NULL

  # Setting old (aka S3) classes
  setOldClass("zoo")

  #' S4 class \code{HikeR}
  #'
  #' Formal class for classifying local minima and maxima
  #' of a time series.
  #'
  #' @slot ys \code{zoo}, time series with associated scores.
  #' @slot k \code{integer}, count of left/right neighbours around centre point.
  #' @slot scoreby \code{character}, scoring method.
  #' @slot yname \code{character}, name of the series.
  #' @exportClass HikeR
  setClass("HikeR", slots = list(ys = "zoo",
                                k = "integer",
                                scoreby = "character",
                                yname = "character"))

  #' S4 class \code{PTBB}
  #'
  #' Formal class for peaks, troughs, burst, busts and
  #' intermittent phase of a time series.
  #'
  #' @slot pt \code{zoo}, logical: indicating peak/trough points.
  #' @slot type \code{character}, type of point/phase.
  #' @slot h \code{numeric}, the threshold for score evaluation.
  #' @exportClass PTBB
  setClass("PTBB", slots = list(pt = "zoo",
                                type = "character",
                                h = "numeric"))
```

This code is written to file `Allclasses.R`.

@

## 4 Chunk Index

*⟨Allclasses.R 5⟩*  
*⟨DESCRIPTION.R 4⟩*  
*⟨score-diffmean 2a⟩*  
*⟨score-maxdiff 1⟩*  
*⟨score-roxygen 3a⟩*  
*⟨score-wrapper 2b⟩*  
*⟨score.R 3b⟩*

## 5 Identifier Index

scdiffmean: [2a](#), [2b](#)

scmaxdiff: [1](#), [2b](#)

score: [2b](#)

## References

- Palshikar, G. (2009). Simple algorithms for peak detection in time-series. In *First Int. Conf. Advanced Data Analysis, Business Analytics and Intelligence*, Ahmedabad, India.