

Motif Export


Yichen Han

2024-08-22

Motif detection

Based on randomly generated sequence with length 450 bp, ACGT are drawn with equal probs, and then insert a motif TATAGCGCAGCTGTCAGCATGAGTCCATGA at a random starting point. Data 10000.

Model: LSTM-CNN, learning rate 0.001, batch size 32, accuracy 100%.



Using checkpoint checkpoints/motifeq-both_2/Ep.015-val_loss0.00-val_acc1.000.hdf5

Model Evaluation

```
## [[1]]
## [[1]]$confusion_matrix
```


```
##           Truth
## Prediction normal motif
##      normal      640      0
##      motif       0      640
##
## [[1]]$accuracy
## [1] 1
##
## [[1]]$categorical_crossentropy_loss
## [1] 0.002400922
##
## [[1]]$AUC
## NULL
##
## [[1]]$AUPRC
## NULL
```


IG

Baseline: 0.25

```
##           [,1]      [,2]
## [1,] 0.0002209859 0.999779
```

```
## [[1]]
```





```
## Warning: The '<scale>' argument of 'guides()' cannot be 'FALSE'. Use "none" instead as
## of ggplot2 3.3.4.
## i The deprecated feature was likely used in the ggseqlogo package.
## Please report the issue at <https://github.com/omarwagih/ggseqlogo/issues>.
## This warning is displayed once every 8 hours.
## Call 'lifecycle::last_lifecycle_warnings()' to see where this warning was
## generated.

## Scale for x is already present.
## Adding another scale for x, which will replace the existing scale.
```

