

# Lecture 5

## The Relational Data Model and Relational Database Constraints

# Relational Model Concepts

- ▶ The relational Model of Data is based on the concept of a *Relation*
  - The strength of the relational approach to data management comes from the formal foundation provided by the theory of relations
- ▶ We review the essentials of the *formal relational model* in this chapter
- ▶ In *practice*, there is a *standard model* based on SQL
- ▶ Note: There are several important differences between the *formal* model and the *practical* model, as we shall see

# Relational Model Concepts

- ▶ A Relation is a mathematical concept based on the ideas of sets
- ▶ The model was first proposed by Dr. E.F. Codd of IBM Research in 1970 in his paper.

# Informal Definitions

- ▶ Informally, a **relation** looks like a **table** of values.
- ▶ A relation typically contains a **set of rows**.
- ▶ The data elements in each **row** represent certain facts that correspond to a real-world **entity** or **relationship**
  - In the **formal** model, rows are called **tuples**
- ▶ Each **column** has a column header that gives an indication of the meaning of the data items in that column
  - In the **formal** model, the column header is called an **attribute name** (or just **attribute**)

# Example of a Relation

Relation Name

**STUDENT**

Attributes

Tuples

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25

The attributes and tuples of a relation STUDENT.

# Informal Definitions

## ► Key of a Relation:

- Each row has a value of a data item (or set of items) that uniquely identifies that row in the table
  - ❖ Called the *key*
- In the STUDENT table, SSN is the key
- Sometimes row-ids or sequential numbers are assigned as keys to identify the rows in a table
  - ❖ Called *artificial key* or *surrogate key*

# Formal Definitions - Schema

## ► The **Schema** (or description) of a Relation:

- Denoted by  $R(A_1, A_2, \dots, A_n)$
- $R$  is the **name** of the relation
- The **attributes** of the relation are  $A_1, A_2, \dots, A_n$

## ► Example:

CUSTOMER (Cust-id, Cust-name, Address, Phone#)

- CUSTOMER is the relation name
- Defined over the four attributes: Cust-id, Cust-name, Address, Phone#

## ► Each attribute has a **domain** or a set of valid values.

- For example, the domain of Cust-id is 6 digit numbers.

# Formal Definitions - Tuple

- ▶ A **tuple** is an ordered set of values (enclosed in angled brackets ' $\langle \dots \rangle$ ')
  - ▶ Each value is derived from an appropriate *domain*.
- ▶ A row in the CUSTOMER relation is a 4-tuple and would consist of four values, for example:
  - $\langle 632895, \text{"John Smith"}, \text{"101 Main St. Atlanta, GA 30332"}, \text{"(404) 894-2000"} \rangle$
  - This is called a 4-tuple as it has 4 values
  - A tuple (row) in the CUSTOMER relation.
- ▶ A relation is a **set** of such tuples (rows)



# Formal Definitions - Domain

Domain is used only for 'Attributes'

- ▶ A **domain** has a logical definition:
  - Example: “USA\_phone\_numbers” are the set of 10 digit phone numbers valid in the U.S.
- ▶ A domain also has a data-type or a format defined for it.
  - The USA\_phone\_numbers may have a format: (ddd)ddd-dddd where each d is a decimal digit.
  - Dates have various formats such as year, month, date formatted as yyyy-mm-dd, or as dd mm, yyyy etc.
- ▶ The attribute name designates the role played by a domain in a relation:
  - Used to interpret the meaning of the data elements corresponding to that attribute
  - Example: The domain Date may be used to define two attributes named “Invoice-date” and “Payment-date” with different meanings

# Formal Definitions - State

- ▶ The **relation state** is a subset of the **Cartesian product** of the domains of its attributes
  - each domain contains the set of all possible values the attribute can take.
- ▶ Example: attribute Cust-name is defined over the domain of character strings of maximum length 25
  - `dom(Cust-name)` is `varchar(25)`
- ▶ The role these strings play in the CUSTOMER relation is that of the *name of a customer*.

# Definition Summary

<u>Informal Terms</u>	<u>Formal Terms</u>
Table	Relation
Column Header	Attribute
All possible Column Values	Domain
Row	Tuple
Table Definition	Schema of a Relation
Populated Table	State of the Relation

# Characteristics Of Relations

- ▶ Ordering of tuples in a relation  $r(R)$ :
  - The tuples are *not considered to be ordered*, even though they appear to be in the tabular form.
- ▶ Ordering of attributes in a relation schema  $R$  (and of values within each tuple):
  - We will consider the attributes in  $R(A_1, A_2, \dots, A_n)$  and the values in  $t = \langle v_1, v_2, \dots, v_n \rangle$  to be ordered.

# Same state as previous Figure (but with different order of tuples)

**Figure 5.2**

The relation STUDENT from Figure 5.1 with a different order of tuples.

## STUDENT

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21

# Characteristics Of Relations

## ► Values in a tuple:

- All values are considered atomic (indivisible).
- Each value in a tuple must be from the domain of the attribute for that column
  - ❖ If tuple  $t = \langle v_1, v_2, \dots, v_n \rangle$  is a tuple (row) in the relation state  $r$  of  $R(A_1, A_2, \dots, A_n)$
  - ❖ Then each  $v_i$  must be a value from  $dom(A_i)$

# Null Values

- ▶ An attribute value may be null that is not yet known or not applicable. The null value will be represented by blank. Null values are not used in the primary key.
- ▶ For example number of eggs laid attribute; its value will be NULL for birds if it has not been known; and it will be NULL for animals as it is not applicable.

# Relational Integrity Constraints

- ▶ Constraints are **conditions** that must hold on all valid relation states.
- ▶ There are three *main types* of constraints in the relational model:
  - **Key constraints** Unique Key for all tuples
  - **Entity integrity constraints** Primary Key cannot be null
  - **Referential integrity constraints** Foreign Key must reference existing PK or be NULL
- ▶ Another implicit constraint is the **domain constraint**
  - Every value in a tuple must be from the *domain of its attribute* (or it could be null, if allowed for that attribute)



# Key Constraints

- ▶ **Superkey (candidate)** of R: Key must be unique across all rows.  
One or more column (attribute)
  - Is a set of attributes SK of R with the following condition: Relation
    - ❖ No two tuples in any valid relation state  $r(R)$  will have the same value for SK
    - ❖ That is, for any distinct tuples  $t_1$  and  $t_2$  in  $r(R)$ ,  $t_1[SK] \neq t_2[SK]$
    - ❖ This condition must hold in *any valid state*  $r(R)$
- ▶ **Key** of R: Key, is a super key with minimal number of attributes that make it unique (super key can contain attributes that can be removed and still be unique)
  - A "minimal" superkey
  - That is, a key is a superkey  $K$  such that removal of any attribute from  $K$  results in a set of attributes that is not a superkey (does not possess the superkey uniqueness property)

Advanced (Functional Dependencies): Super Key is a set of attributes in which its closure (attributes which it can determine) has all other attributes

# Key Constraints

## ► Example: Consider the CAR relation schema:

- $CAR(State, Reg\#, SerialNo, Make, Model, Year)$
- CAR has two keys:
  - ❖  $Key1 = \{State, Reg\# \}$
  - ❖  $Key2 = \{SerialNo \}$
- Both are also superkeys of CAR
- $\{SerialNo, Make\}$  is a superkey but *not* a key.

## ► In general:

- Any *key* is a *superkey* (but not vice versa)
- Any set of attributes that *includes a key* is a *superkey*
- A *minimal* superkey is also a key

# Key Constraints

- ▶ If a relation has several **candidate keys**, one is chosen arbitrarily to be the **primary key**.
  - The primary key attributes are underlined.
- ▶ Example: Consider the CAR relation schema:
  - CAR(State, Reg#, SerialNo, Make, Model, Year)
  - We chose SerialNo as the primary key
- ▶ The primary key value is used to *uniquely identify* each tuple in a relation
  - Provides the tuple identity
- ▶ Also used to *reference* the tuple from another tuple
  - General rule: Choose as primary key the smallest of the candidate keys (in terms of size)
  - Not always applicable - choice is sometimes subjective

# CAR table with two candidate keys - LicenseNumber chosen as Primary Key

**CAR**

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

The CAR relation, with two candidate keys: License\_number and Engine\_serial\_number.

# Relational Database Schema

## ► Relational Database Schema:

- A set  $S$  of relation schemas that belong to the same database.
- $S$  is the name of the whole **database schema**
- $S = \{R_1, R_2, \dots, R_n\}$
- $R_1, R_2, \dots, R_n$  are the names of the individual **relation schemas** within the database  $S$

## ► Following slide shows a COMPANY database schema with 6 relation schemas

# COMPANY Database Schema

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

## PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

Schema diagram for  
the COMPANY  
relational database  
schema.

# Entity Integrity

## ► Entity Integrity:

- The *primary key attributes* PK of each relation schema R in S cannot have null values in any tuple of  $r(R)$ .
  - ❖ This is because primary key values are used to *identify* the individual tuples.
  - ❖  $t[PK] \neq \text{null}$  for any tuple t in  $r(R)$
  - ❖ If PK has several attributes, null is not allowed in any of these attributes
- Note: Other attributes of R may be constrained to disallow null values, even though they are not members of the primary key.

# Referential Integrity

- ▶ A constraint involving **two** relations
  - The previous constraints involve a single relation.
- ▶ Used to specify a **relationship** among tuples in two relations:
  - The **referencing relation** and the **referenced relation**.



# Referential Integrity

- ▶ Tuples in the **referencing relation** R1 have attributes FK (called **foreign key attributes**) that reference the primary key attributes PK of the **referenced relation** R2.
  - A tuple t1 in R1 is said to **reference** a tuple t2 in R2 if  $t1[FK] = t2[PK]$ .
- ▶ A referential integrity constraint can be displayed in a relational database schema as a directed arc from R1.FK to R2.

# Referential Integrity (or foreign key) Constraint

- ▶ Statement of the constraint
  - The value in the foreign key column (or columns) FK of the **referencing relation** R1 can be **either**:
    - (1) a value of an existing primary key value of a corresponding primary key PK in the **referenced relation** R2, or
    - (2) a null.
- ▶ In case (2), the FK in R1 should **not** be a part of its own primary key.

# For example

IF there exists a database as shown:

R1: EMPLOYEE (*EMP#*, ENAME, *DEPT#*,.....)

R2: DEPARTMENT (*DEPT#*, DNAME,...)

**R3: ENROLMENT** (*EMP#*, *DEPT#* , ....)

In R1 relation *EMP#* is its primary key, so it is not allowed to have NULL value; while *DEPT#* is a foreign key, so it may have a NULL value.

In R3 relation, if we choose that both attributes *EMP#* and *DEPT#* to be a composite key, so they are not allowed to have a NULL value.

# Displaying a relational database schema and its constraints

- ▶ Each relation schema can be displayed as a row of attribute names
- ▶ The name of the relation is written above the attribute names
- ▶ The primary key attribute (or attributes) will be underlined
- ▶ A foreign key (referential integrity) constraints is displayed as a directed arc (arrow) from the foreign key attributes to the referenced table
  - Can also point the the primary key of the referenced relation for clarity

# Referential Integrity Constraints for COMPANY database (Referential Diagram)

Referential integrity constraints displayed on the COMPANY relational database schema.

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

## PROJECT


Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------



# Other Types of Constraints

- ▶ Semantic Integrity Constraints:
  - based on application semantics and cannot be expressed by the model per se
  - Example: “the max. no. of hours per employee for all projects he or she works on is 56 hrs per week”
- ▶ A **constraint specification** language may have to be used to express these
- ▶ SQL-99 allows triggers and **ASSERTIONS** to express for some of these

# Populated database state

- ▶ Each *relation* will have many tuples in its current relation state
- ▶ The *relational database state* is a union of all the individual relation states
- ▶ Whenever the database is changed, a new state arises
- ▶ Basic operations for changing the database:
  - INSERT a new tuple in a relation
  - DELETE an existing tuple from a relation
  - MODIFY an attribute of an existing tuple

# Populated database state for COMPANY

One possible database state for the COMPANY relational database schema.

## EMPLOYEE

Fname	Minit	Lname	Ssn	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

## DEPARTMENT

Dname	Dnumber	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

## DEPT\_LOCATIONS

Dnumber	Dlocation
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

## WORKS\_ON

Essn	Pno	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

## PROJECT

Pname	Pnumber	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

## DEPENDENT

Essn	Dependent_name	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse



# Update Operations on Relations

- ▶ INSERT a tuple.
- ▶ DELETE a tuple.
- ▶ MODIFY a tuple.
- ▶ Integrity constraints should not be violated by the update operations.
- ▶ Several update operations may have to be grouped together.
- ▶ Updates may **propagate** to cause other updates automatically. This may be necessary to maintain integrity constraints.

# Update Operations on Relations

- ▶ In case of integrity violation, several actions can be taken:
  - Cancel the operation that causes the violation (RESTRICT or REJECT option)
  - Perform the operation but inform the user of the violation
  - Trigger additional updates so the violation is corrected (CASCADE option, SET NULL option)
  - Execute a user-specified error-correction routine

# Example: $B \rightarrow A$

Refrential Integrity actions / mitigations

B is a FK referred to primary key A

To delete/update A; first check matching of FK

**CASCADE:** If match: delete/update FK in B as well as A

Delete/Update both  
(Domino Effect)

If not match: delete/update A only.

**RESTRICT:** If match: ignore request;

Ignore (Protector)

i.e. no change will happen either to A or B

If not match delete/update A only.

**SET NULL:** If match: make change in A and make FK in B  
NULL

Delete/Update and set FK in B as NULL  
(Delete the relation and Referenced Entity)

# Possible violations for each operation

## ► INSERT may violate any of the constraints:

- **Domain constraint:**

- ❖ if one of the attribute values provided for the new tuple is not of the specified attribute domain

- **Key constraint:**

- ❖ if the value of a key attribute in the new tuple already exists in another tuple in the relation

- **Referential integrity:**

- ❖ if a foreign key value in the new tuple references a primary key value that does not exist in the referenced relation

- **Entity integrity:**

- ❖ if the primary key value is null in the new tuple

# Possible violations for each operation

DELETE may violate only referential integrity:

- If the primary key value of the tuple being deleted is referenced from other tuples in the database
  - ❖ Can be remedied by several actions: RESTRICT, CASCADE, SET NULL
    - RESTRICT option: reject the deletion
    - CASCADE option: propagate the new primary key value into the foreign keys of the referencing tuples
    - SET NULL option: set the foreign keys of the referencing tuples to NULL
- One of the above options must be specified during database design for each foreign key constraint

# Possible violations for each operation

- ▶ UPDATE may violate domain constraint and NOT NULL constraint on an attribute being modified
- ▶ Any of the other constraints may also be violated, depending on the attribute being updated:
  - Updating the primary key (PK):
    - ❖ Similar to a DELETE followed by an INSERT
    - ❖ Need to specify similar options to DELETE
  - Updating a foreign key (FK):
    - ❖ May violate referential integrity
  - Updating an ordinary attribute (neither PK nor FK):
    - ❖ Can only violate domain constraints