

GAME PLAYING

CHAPTER 6

Games vs. search problems

“Unpredictable” opponent \Rightarrow solution is a **strategy**
specifying a move for every possible opponent reply

Time limits \Rightarrow unlikely to find goal, must approximate


Plan of attack:

- Computer considers possible lines of play (Babbage, 1846)
- Algorithm for perfect play (Zermelo, 1912; Von Neumann, 1944)
- Finite horizon, approximate evaluation (Zuse, 1945; Wiener, 1948; Shannon, 1950)
- First chess program (Turing, 1951)
- Machine learning to improve evaluation accuracy (Samuel, 1952–57)
- Pruning to allow deeper search (McCarthy, 1956)


Types of games

	deterministic	chance
perfect information	chess, checkers, go, othello	backgammon monopoly
imperfect information	battleships, blind tictactoe	bridge, poker, scrabble nuclear war

Game tree (2-player, deterministic, turns)




A very simple game



Exercise: what is the best strategy for player MAX?

What is best strategy for MIN?




Minimax

Perfect play for deterministic, perfect-information games

Idea: choose move to position with highest **minimax value**
= best achievable payoff against best play

E.g., 2-ply game:



Minimax algorithm

function MINIMAX-DECISION(*state*) **returns** *an action*

inputs: *state*, current state in game

return the *a* in ACTIONS(*state*) maximizing MIN-VALUE(RESULT(*a*, *state*))

function MAX-VALUE(*state*) **returns** *a utility value*

if TERMINAL-TEST(*state*) **then return** UTILITY(*state*)

$v \leftarrow -\infty$

for *a, s* in SUCCESSORS(*state*) **do** $v \leftarrow \text{MAX}(v, \text{MIN-VALUE}(s))$

return *v*

function MIN-VALUE(*state*) **returns** *a utility value*

if TERMINAL-TEST(*state*) **then return** UTILITY(*state*)

$v \leftarrow \infty$

for *a, s* in SUCCESSORS(*state*) **do** $v \leftarrow \text{MIN}(v, \text{MAX-VALUE}(s))$

return *v*

Properties of minimax

Complete??

Properties of minimax

Complete?? Only if tree is finite (chess has specific rules for this).

NB a finite strategy can exist even in an infinite tree!

Optimal??

Properties of minimax

Complete?? Yes, if tree is finite (chess has specific rules for this)

Optimal?? Yes, against an optimal opponent. Otherwise??

Time complexity??

Properties of minimax

Complete?? Yes, if tree is finite (chess has specific rules for this)

Optimal?? Yes, against an optimal opponent. Otherwise??

Time complexity?? $O(b^m)$

Space complexity??

Properties of minimax

Complete?? Yes, if tree is finite (chess has specific rules for this)

Optimal?? Yes, against an optimal opponent. Otherwise??


Time complexity?? $O(b^m)$

Space complexity?? $O(bm)$ (depth-first exploration)


For chess, $b \approx 35$, $m \approx 100$ for “reasonable” games
 \Rightarrow exact solution completely infeasible

But do we need to explore every path?


α - β pruning example




α - β pruning example




α - β pruning example




α - β pruning example



α - β pruning example



Why is it called α - β ?



α is the best value (to MAX) found so far off the current path

If V is worse than α , MAX will avoid it \Rightarrow prune that branch

Define β similarly for MIN

The α - β algorithm

function ALPHA-BETA-DECISION(*state*) **returns** an action
 return the *a* in ACTIONS(*state*) maximizing MIN-VALUE(RESULT(*a*, *state*))

function MAX-VALUE(*state*, α , β) **returns** a utility value
 inputs: *state*, current state in game
 α , the value of the best alternative for MAX along the path to *state*
 β , the value of the best alternative for MIN along the path to *state*

 if TERMINAL-TEST(*state*) **then return** UTILITY(*state*)
 $v \leftarrow -\infty$
 for *a*, *s* in SUCCESSORS(*state*) **do**
 $v \leftarrow \text{MAX}(v, \text{MIN-VALUE}(s, \alpha, \beta))$
 if $v \geq \beta$ **then return** *v*
 $\alpha \leftarrow \text{MAX}(\alpha, v)$
 return *v*

function MIN-VALUE(*state*, α , β) **returns** a utility value
 same as MAX-VALUE but with roles of α , β reversed

Properties of $\alpha-\beta$

Pruning **does not** affect final result

Good move ordering improves effectiveness of pruning

With “perfect ordering,” time complexity = $O(b^{m/2})$
 \Rightarrow **doubles** solvable depth

A simple example of the value of reasoning about which computations are relevant (a form of **metareasoning**)

Unfortunately, 35^{50} is still impossible!

Resource limits

Standard approach:


- Use CUTOFF-TEST instead of TERMINAL-TEST
e.g., depth limit (perhaps add quiescence search)
- Use EVAL instead of UTILITY
i.e., evaluation function that estimates desirability of position

Suppose we have 100 seconds, explore 10^4 nodes/second

$\Rightarrow 10^6$ nodes per move $\approx 35^{8/2}$


$\Rightarrow \alpha\text{-}\beta$ reaches depth 8 \Rightarrow pretty good chess program

Evaluation functions



Black to move

White slightly better



White to move

Black winning


For chess, typically **linear** weighted sum of **features**

$$Eval(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

e.g., $w_1 = 9$ with

$f_1(s) = (\text{number of white queens}) - (\text{number of black queens}), \text{ etc.}$

Digression: Exact values don't matter



Behaviour is preserved under any **monotonic** transformation of EVAL

Only the order matters:

payoff in deterministic games acts as an **ordinal utility** function

Deterministic games in practice


Checkers: Chinook ended 40-year-reign of human world champion Marion Tinsley in 1994. Used an endgame database defining perfect play for all positions involving 8 or fewer pieces on the board, a total of 443,748,401,247 positions.

Chess: Deep Blue defeated human world champion Gary Kasparov in a six-game match in 1997. Deep Blue searches 200 million positions per second, uses very sophisticated evaluation, and undisclosed methods for extending some lines of search up to 40 ply.

Othello: human champions refuse to compete against computers, who are too good.

Go: human champions refuse to compete against computers, who are too bad. In go, $b > 300$, so most programs use pattern knowledge bases to suggest plausible moves.


Nondeterministic games: backgammon



Nondeterministic games in general

In nondeterministic games, chance introduced by dice, card-shuffling

Simplified example with coin-flipping:



Algorithm for nondeterministic games

EXPECTIMINIMAX gives perfect play

Just like MINIMAX, except we must also handle chance nodes:

...

if *state* is a MAX node **then**

return the highest EXPECTIMINIMAX-VALUE of SUCCESSORS(*state*)

if *state* is a MIN node **then**

return the lowest EXPECTIMINIMAX-VALUE of SUCCESSORS(*state*)

if *state* is a chance node **then**

return average of EXPECTIMINIMAX-VALUE of SUCCESSORS(*state*)

...

Nondeterministic games in practice

Dice rolls increase b : 21 possible rolls with 2 dice

Backgammon ≈ 20 legal moves (can be 6,000 with 1-1 roll)

$$\text{depth } 4 = 20 \times (21 \times 20)^3 \approx 1.2 \times 10^9$$

As depth increases, probability of reaching a given node shrinks


\Rightarrow value of lookahead is diminished

α - β pruning is much less effective

TDGAMMON uses depth-2 search + very good EVAL

\approx world-champion level

Digression: Exact values DO matter



Behaviour is preserved only by **positive linear** transformation of EV_{AL}

Hence EV_{AL} should be proportional to the expected payoff

Summary

Games are fun to work on! (and dangerous)

They illustrate several important points about AI

- ◇ perfection is unattainable \Rightarrow must approximate
- ◇ good idea to think about what to think about
- ◇ uncertainty constrains the assignment of values to states
- ◇ optimal decisions depend on information state, not real state

Games are to AI as grand prix racing is to automobile design