

Using the PACViR Pipeline

Michael Gruenstaeudl, Nils Jenke

June 12, 2019

Contents

1	Introduction	1
2	Requirements	1
3	PACViR via R-function	1
4	PACViR via command line	1
5	Modifying parameters	1
6	More Information	2
7	sessionInfo	2

1 Introduction

The PACViR pipeline generates a visualization of a plastome in a circular fashion. This vignette provides two examples of how to execute PACViR via the R function 'PACViR.complete()' and via bash.

2 Requirements

To execute PACViR several requirements have to be installed.

```
> library(PACViR)
>
```

3 PACViR via R-function

PACViR can be easily executed via the PACViR.complete() function in R. Therefore one can load the provided data from the package.

```
> # The absolute path to the input directory is set
> inPath <- system.file("extdata", "MH161174/", package="PACViR")
> # The names of the input files located in inPath are set
> inFile_gb <- "MH161174.gb"
> inFile_bam <- "MH161174.bam"
> gbk.file <- paste(inPath, "/", inFile_gb)
> bam.file <- paste(inPath, "/", inFile_bam)
> windowSize <- 250
> mosdepthCmd <- "mosdepth"
> threshold <- 15
```

```
> delete <- "TRUE"
> outDir <- "./output"
> #PACViR.complete(gbk.file, bam.file, windowSize, mosdepthCmd, threshold, delete, outDir)
```

4 PACViR via command line

Execute PACViR_Rscript.R via command line with Rscript.

```
Rscript PACViR_Rscript.R -k ../inst/extdata/DAS01.gb -b ../inst/extdata/DAS01.bam
```

5 Modifying parameters

Depending on which system PACViR will be executed

6 More Information

7 sessionInfo

```
> sessionInfo()
```

R version 3.3.3 (2017-03-06)

Platform: x86_64-pc-linux-gnu (64-bit)

Running under: Debian GNU/Linux 9 (stretch)

locale:

```
[1] LC_CTYPE=de_DE.UTF-8      LC_NUMERIC=C
[3] LC_TIME=de_DE.UTF-8      LC_COLLATE=de_DE.UTF-8
[5] LC_MONETARY=de_DE.UTF-8  LC_MESSAGES=de_DE.UTF-8
[7] LC_PAPER=de_DE.UTF-8     LC_NAME=C
[9] LC_ADDRESS=C             LC_TELEPHONE=C
[11] LC_MEASUREMENT=de_DE.UTF-8 LC_IDENTIFICATION=C
```

attached base packages:

```
[1] stats      graphics  grDevices  utils      datasets
[6] methods    base
```

loaded via a namespace (and not attached):

```
[1] tools_3.3.3
```