Chapter 3: Transport Layer – Part 3

Instructor: Zhuozhao Li

Lab: Qing Wang

Department of Computer Science and Engineering

Miscellaneous

- PA2 deadline today

- Project specification released
  - Please form a project group before April 30
  - https://docs.qq.com/sheet/DSUNqSmJYVnJMb2Nk?groupUin=0laSTOMmleqHpIIKdKvaLw%253D%253D&tab=BB08J2

Quick review

- TCP
  - Fairness
  - Evolution of transport layer

- Network-layer
  - Forwarding versus routing
  - Router architecture
    - Input port, switching fabric, output port
    - Queuing

Chapter 4
Network Layer: Data Plane
Part 1

Instructor: Zhuozhao Li

Lab: Qing Wang

Department of Computer Science and Engineering

Output port queuing



This is a really important slide

- *Buffering* required when datagrams arrive from fabric faster than link transmission rate. *Drop policy:* which datagrams to drop if no free buffers?

Datagrams can be lost due to congestion, lack of buffers

- *Scheduling discipline* chooses among queued datagrams for transmission

Priority scheduling – who gets best performance, network neutrality

How much buffering?

- RFC 3439 rule of thumb: average buffering equal to "typical" RTT (say 250 msec) times link capacity C
  - e.g., C = 10 Gbps link: 2.5 Gbit buffer
- more recent recommendation: with *N* flows, buffering equal to

$$\frac{\text{RTT} \cdot \text{C}}{\sqrt{\text{N}}}$$

- but *too* much buffering can increase delays (particularly in home routers)
  - long RTTs: poor performance for realtime apps, sluggish TCP response
  - recall delay-based congestion control: "keep bottleneck link just full enough (busy) but no fuller"

Buffer Management



Abstraction: queue



buffer management:

- drop: which packet to add, drop when buffers are full
  - tail drop: drop arriving packet
  - priority: drop/remove on priority basis
- marking: which packets to mark to signal congestion (ECN, random early drop)

Packet Scheduling: FCFS

packet scheduling: deciding which packet to send next on link

- first come, first served
- priority
- round robin
- weighted fair queueing

Abstraction: queue



FCFS: packets transmitted in order of arrival to output port

- also known as: First-in-first-out (FIFO)
- real world examples?

Scheduling policies: priority

Priority scheduling:

- arriving traffic classified, queued by class
  - any header fields can be used for classification
- send packet from highest priority queue that has buffered packets
  - FCFS within priority class





Scheduling policies: round robin

Round Robin (RR) scheduling:

- arriving traffic classified, queued by class
  - any header fields can be used for classification
- server cyclically, repeatedly scans class queues, sending one complete packet from each class (if available) in turn



Scheduling policies: weighted fair queueing

Weighted Fair Queuing (WFQ):

- generalized Round Robin
- each class, *i*, has weight, w_i, and gets weighted amount of service in each cycle:

$$\frac{w_i}{\sum_j w_j}$$

- minimum bandwidth guarantee (per-traffic-class)



Sidebar: Network Neutrality (网络中立)

What is network neutrality?

- *technical:* how an ISP should share/allocation its resources
  - packet scheduling, buffer management are the *mechanisms*
- *social, economic* principles
  - protecting free speech
  - encouraging innovation, competition
- enforced *legal* rules and policies

Different countries have different "takes" on network neutrality

Sidebar: Network Neutrality (网络中立)

2015 US FCC *Order on Protecting and Promoting an Open Internet:* three "clear, bright line" rules:

- no blocking … "shall not block lawful content, applications, services, or non-harmful devices, subject to reasonable network management."
- no throttling … "shall not impair or degrade lawful Internet traffic on the basis of Internet content, application, or service, or use of a non-harmful device, subject to reasonable network management."
- no paid prioritization. … "shall not engage in paid prioritization"

Network layer: "data plane" roadmap

- Network layer: overview
  - data plane
  - control plane
- What's inside a router
  - input ports, switching, output ports
  - buffer management, scheduling
- IP: the Internet Protocol
  - datagram format
  - addressing
  - network address translation
  - IPv6

- Generalized Forwarding, SDN
  - match+action
  - OpenFlow: match+action in action

Network Layer: Internet

host, router network layer functions:



IP Datagram format

IP protocol version number (4 bits)

header length(bytes)

"type" of service:
- diffserv (0:5)
- ECN (6:7)

TTL: remaining max hops (decremented at each router)

upper layer protocol (e.g., TCP or UDP)



total datagram length (bytes)

fragmentation/ reassembly

header checksum

32-bit source IP address

Maximum length: 64K bytes
Typically: 1500 bytes or less

e.g., timestamp, record route taken

overhead
- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead for TCP+IP

IP addressing: introduction

- IP address: 32-bit identifier associated with each host or router *interface*
- interface: connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)



dotted-decimal IP address notation:

$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

- IP address: 32-bit identifier associated with each host or router *interface*
- interface: connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)



dotted-decimal IP address notation:

$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapters 6, 7

A: wired Ethernet interfaces connected by Ethernet switches



A: wireless WiFi interfaces connected by WiFi base station

For now: don't need to worry about how one interface is connected to another (with no intervening router)

Subnets

- *What's a subnet ?*
  - device interfaces that can physically reach each other without passing through an intervening router
- IP addresses have structure:
  - subnet part: devices in same subnet have common high order bits
  - host part: remaining low order bits



network consisting of 3 subnets

Subnets

Recipe for defining subnets:

- detach each interface from its host or router, creating "islands" of isolated networks
- each isolated network is called a *subnet*



subnet mask: /24
(high-order 24 bits: subnet part of IP address)

Subnets

- where are the subnets?
- what are the /24 subnet addresses?



IP addressing: CIDR

CIDR: Classless InterDomain Routing (pronounced “cider”， 无类别域间路由选择)

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address

subnet part ⟵⟶ host part

11001000 00010111 00010000 00000000

200.23.16.0/23

IP addresses: how to get one?

That's actually two questions:

1. Q: How does a *host* get IP address within its network (host part of address)?
2. Q: How does a *network* get IP address for itself (network part of address)

How does *host* get IP address?

- hard-coded by sysadmin in config file (e.g., /etc/rc.config in UNIX)
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

DHCP: Dynamic Host Configuration Protocol

goal: host *dynamically* obtains IP address from network server when it "joins" network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected/on)
- support for mobile users who join/leave network

DHCP overview:

- host broadcasts DHCP discover msg [optional]
- DHCP server responds with DHCP offer msg [optional]
- host requests IP address: DHCP request msg
- DHCP server sends address: DHCP ack msg

DHCP client-server scenario



Typically, DHCP server will be co-located in router, serving all subnets to which router is attached

arriving DHCP client needs address in this network

DHCP client-server scenario



The two steps above can be skipped "if a client remembers and wishes to reuse a previously allocated network address" [RFC 2131]

DHCP client-server scenario



The two steps above can be skipped "if a client remembers and wishes to reuse a previously allocated network address" [RFC 2131]

DHCP: more than IP addresses

DHCP can return more than just allocated IP address on subnet:

- address of first-hop router for client
- name and IP address of DNS sever
- network mask (indicating network versus host portion of address)

IP addresses: how to get one?

Q: how does *network* get subnet part of IP address?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 0001	0000 00000000	200.23.16.0/20	

ISP can then allocate out its address space in 8 blocks:

Organization 0	11001000 00010111 0001000	0 00000000	200.23.16.0/23
Organization 1	11001000 00010111 0001001	0 00000000	200.23.18.0/23
Organization 2	11001000 00010111 0001010	0 00000000	200.23.20.0/23
...	.....	....	....
Organization 7	11001000 00010111 0001111	0 00000000	200.23.30.0/23

Hierarchical addressing: route aggregation

hierarchical addressing allows efficient advertisement of routing information:



Hierarchical addressing: more specific routes

- Organization 1 moves from Fly-By-Night-ISP to ISPs-R-Us
- ISPs-R-Us now advertises a more specific route to Organization 1



Hierarchical addressing: more specific routes

- Organization 1 moves from Fly-By-Night-ISP to ISPs-R-Us
- ISPs-R-Us now advertises a more specific route to Organization 1



IP addressing: last words ...

Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers http://www.icann.org/

- allocates IP addresses, through 5 regional registries (RRs) (who may then allocate to local registries)
- manages DNS root zone, including delegation of individual TLD (.com, .edu , …) management

Q: are there enough 32-bit IP addresses?

- ICANN allocated last chunk of IPv4 addresses to RRs in 2011
- NAT (next) helps IPv4 address space exhaustion
- IPv6 has 128-bit address space

"Who the hell knew how much address space we needed?" Vint Cerf (reflecting on decision to make IPv4 address 32 bits long)

Network layer: “data plane” roadmap

- Network layer: overview
  - data plane
  - control plane
- What’s inside a router
  - input ports, switching, output ports
  - buffer management, scheduling
- IP: the Internet Protocol
  - datagram format
  - addressing
  - network address translation
  - IPv6

- Generalized Forwarding, SDN
  - match+action
  - OpenFlow: match+action in action

NAT: network address translation (网络地址转换)

NAT: all devices in local network share just one IPv4 address as far as outside world is concerned



all datagrams *leaving* local network have *same* source NAT IP address: 138.76.29.7, but *different* source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

- all devices in local network have 32-bit addresses in a "private" IP address space (10/8, 172.16/12, 192.168/16 prefixes) that can only be used in local network
- advantages:
  - just one IP address needed from provider ISP for *all* devices
  - can change addresses of host in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - security: devices inside local net not directly addressable, visible by outside world

NAT: network address translation

implementation: NAT router must (transparently):

- outgoing datagrams: replace (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)
  - remote clients/servers will respond using (NAT IP address, new port #) as destination address
- remember (in NAT translation table) every (source IP address, port #) to (NAT IP address, new port #) translation pair
- incoming datagrams: replace (NAT IP address, new port #) in destination fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation

2: NAT router changes datagram source address from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table

NAT translation table

WAN side addr	LAN side addr
138.76.29.7, 5001	10.0.0.1, 3345
……	……

1: host 10.0.0.1 sends datagram to 128.119.40.186, 80



3: reply arrives, destination address: 138.76.29.7, 5001

NAT: network address translation

- NAT has been controversial:
  - routers "should" only process up to layer 3
  - address "shortage" should be solved by IPv6
  - violates end-to-end argument (port # manipulation by network-layer device)
  - NAT traversal: what if client wants to connect to server behind NAT?
- but NAT is here to stay:
  - extensively used in home and institutional nets, 4G/5G cellular nets

IPv6: motivation

- initial motivation: 32-bit IPv4 address space would be completely allocated
- additional motivation:
  - speed processing/forwarding: 40-byte fixed length header
  - enable different network-layer treatment of “flows”

IPv6 datagram format

priority: identify priority among datagrams in flow

128-bit IPv6 addresses



flow label: identify datagrams in same "flow." (concept of "flow" not well defined).

What's missing (compared with IPv4):

- no checksum (to speed processing at routers)
- no fragmentation/reassembly
- no options (available as upper-layer, next-header protocol at router)

Transition from IPv4 to IPv6

- not all routers can be upgraded simultaneously
  - no "flag days"
  - how will network operate with mixed IPv4 and IPv6 routers?
- tunneling: IPv6 datagram carried as *payload* in IPv4 datagram among IPv4 routers ("packet within a packet")
  - tunneling used extensively in other contexts (4G/5G)



Tunneling and encapsulation

Ethernet connecting two IPv6 routers:



The usual: datagram as payload in link-layer frame

IPv4 network connecting two IPv6 routers



Tunneling and encapsulation

Ethernet connecting two IPv6 routers:



The usual: datagram as payload in link-layer frame

IPv4 tunnel connecting two IPv6 routers



tunneling: IPv6 datagram as payload in a IPv4 datagram

Tunneling



logical view:
A
B
IPv4 tunnel
connecting IPv6 routers
E
F
IPv6
IPv6/v4
IPv6/v4
IPv6
physical view:
A
B
C
D
E
F
IPv6
IPv6/v4
IPv4
IPv4
IPv6/v4
IPv6
flow: X
src: A
dest: F
data
src:B
dest: E
Flow: X
Src: A
Dest: F
data
src:B
dest: E
Flow: X
Src: A
Dest: F
data
src:B
dest: E
Flow: X
Src: A
Dest: F
data
flow: X
src: A
dest: F
data
Note source and
destination
addresses!
A-to-B:
IPv6
B-to-C:
IPv6 inside
IPv4
B-to-C:
IPv6 inside
IPv4
B-to-C:
IPv6 inside
IPv4
E-to-F:
IPv6

IPv6: adoption

- Google[1]: ~ 40% of clients access services via IPv6



https://www.google.com/intl/en/ipv6/statistics.html

IPv6: adoption

- 中央部委、省级政府门户网站IPv6支持率达到81.42%
- 互联网网站对IPv6的支持率仅为33.7%

https://network.51cto.com/article/685981.html

IPv6: adoption

- Google[1]: ~ 30% of clients access services via IPv6
- Long (long!) time for deployment, use
  - 25 years and counting!
  - think of application-level changes in last 25 years: WWW, social media, streaming media, gaming, telepresence, …
  - *Why?*

[1] https://www.google.com/intl/en/ipv6/statistics.html

Network layer: “data plane” roadmap

- Network layer: overview
  - data plane
  - control plane
- What’s inside a router
  - input ports, switching, output ports
  - buffer management, scheduling
- IP: the Internet Protocol
  - datagram format
  - addressing
  - network address translation
  - IPv6

- Generalized Forwarding, SDN
  - Match+action
  - OpenFlow: match+action in action

Generalized forwarding: match plus action

Review: each router contains a forwarding table (aka: flow table)

- "match plus action" abstraction: match bits in arriving packet, take action
  - *destination-based forwarding:* forward based on dest. IP address
  - *generalized forwarding:*
    - many header fields can determine action
    - many action possible: drop/copy/modify/log packet





Flow table abstraction

- flow: defined by header field values (in link-, network-, transport-layer fields)
- generalized forwarding: simple packet-handling rules
  - match: pattern values in packet header fields
  - actions: for matched packet: drop, forward, modify, matched packet or send matched packet to controller
  - priority: disambiguate overlapping patterns
  - counters: #bytes and #packets



Router's flow table define router's match+action rules

Flow table abstraction

- flow: defined by header fields
- generalized forwarding: simple packet-handling rules
  - match: pattern values in packet header fields
  - actions: for matched packet: drop, forward, modify, matched packet or send matched packet to controller
  - priority: disambiguate overlapping patterns
  - counters: #bytes and #packets



src = *.*.*.*, dest=3.4.*.*	forward(2)
src=1.2.*.*, dest=*.*.*.*	drop
src=10.1.2.3, dest=*.*.*.*	send to controller

* : wildcard

OpenFlow: flow table entries



OpenFlow: examples

Destination-based forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	VLAN Pri	IP Src	IP Dst	IP Prot	IP ToS	TCP s-port	TCP d-port	Action
*	*	*	*	*	*	*	51.6.0.8	*	*	*	*	port6

IP datagrams destined to IP address 51.6.0.8 should be forwarded to router output port 6

Firewall:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	VLAN Pri	IP Src	IP Dst	IP Prot	IP ToS	TCP s-port	TCP d-port	Action
*	*	*	*	*	*	*	*	*	*	*	22	drop

Block (do not forward) all datagrams destined to TCP port 22 (ssh port #)

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	VLAN Pri	IP Src	IP Dst	IP Prot	IP ToS	TCP s-port	TCP d-port	Action
*	*	*	*	*	*	128.119.1.1	*	*	*	*	*	drop

Block (do not forward) all datagrams sent by host 128.119.1.1

OpenFlow: examples

Layer 2 destination-based forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	VLAN Pri	IP Src	IP Dst	IP Prot	IP ToS	TCP s-port	TCP d-port	Action
*	*	22:A7:23: 11:E1:02	*	*	*	*	*	*	*	*	*	port3

layer 2 frames with destination MAC address 22:A7:23:11:E1:02 should be forwarded to output port 3

OpenFlow abstraction

- match+action: abstraction unifies different kinds of devices

Router
- *match:* longest destination IP prefix
- *action:* forward out a link

Switch
- *match:* destination MAC address
- *action:* forward or flood

Firewall
- *match*: IP addresses and TCP/UDP port numbers
- *action:* permit or deny

NAT
- *match:* IP address and port
- *action:* rewrite address and port

OpenFlow example



Orchestrated tables can create *network-wide* behavior, e.g.,:

- datagrams from hosts h5 and h6 should be sent to h3 or h4, via s1 and from there to s2

OpenFlow example

match	action
IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(3)



match	action
ingress port = 1 IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(4)

match	action
ingress port = 2 IP Dst = 10.2.0.3	forward(3)
ingress port = 2 IP Dst = 10.2.0.4	forward(4)

Orchestrated tables can create *network-wide* behavior, e.g.,:

- datagrams from hosts h5 and h6 should be sent to h3 or h4, via s1 and from there to s2

Generalized forwarding: summary

- "match plus action" abstraction: match bits in arriving packet header(s) in any layers, take action
  - matching over many fields (link-, network-, transport-layer)
  - local actions: drop, forward, modify, or send matched packet to controller
  - "program" *network-wide* behaviors
- simple form of "network programmability"
  - programmable, per-packet "processing"
  - *historical roots:* active networking
  - *today:* more generalized programming: P4 (see p4.org).

Chapter 4: done!

- Network layer: overview
- What's inside a router
- IP: the Internet Protocol
- Generalized Forwarding, SDN

Question: how are forwarding tables (destination-based forwarding) or flow tables (generalized forwarding) computed?

Answer: by the control plane (next chapter)

Additional Chapter 4 slides

IP fragmentation/reassembly

- network links have MTU (max. transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at *destination*
  - IP header bits used to identify, order related fragments



IP fragmentation/reassembly

example:

- 4000 byte datagram
- MTU = 1500 bytes