

# PA1: DNS Server Implementation

Name: Yitong WANG [11910104@mail.sustech.edu.cn](mailto:11910104@mail.sustech.edu.cn)

Student ID: 11910104

Lab Time: Thursday 10:20 a.m. to 12:10 p.m.

Lab Teacher: Qing WANG [wangq9@mail.sustech.edu.cn](mailto:wangq9@mail.sustech.edu.cn)

Lab SA:

- Siyu LIU [11912935@mail.sustech.edu.cn](mailto:11912935@mail.sustech.edu.cn)
- Xingying ZHENG [11912039@mail.sustech.edu.cn](mailto:11912039@mail.sustech.edu.cn)

You can follow these steps to test the function of LocalDNSServer.

## Network Information

Use ipconfig to get the ip addresss of my computer:

无线局域网适配器 WLAN:

```
连接特定的 DNS 后缀 . . . . . : sustech.edu.cn
IPv6 地址 . . . . . : 2001:da8:201d:1109::c0ab
本地链接 IPv6 地址. . . . . : fe80::61ab:db20:c5c7:ab0%15
IPv4 地址 . . . . . : 10.26.128.169
子网掩码 . . . . . : 255.252.0.0
默认网关. . . . . : fe80::3e8c:93ff:fed0:83c1%15
                  10.27.255.254
```

We can get the ip address is 10.26.128.169

## Execute LocalDNSServer.py

Type the following in the directory of LocalDNSServer.py

```
python3 LocalDNSServer.py
```

and input these in the command line:

```
10.26.128.169
```

```
55
```

Like this:

```
D:\PycharmProjects\CS305\PA1>python3 LocalDNSServer.py
Enter your ip: 10.26.128.169
Enter your port: 55
202.12.27.33
m.root-servers.net.
```

## Tests on the document

[www.baidu.com](http://www.baidu.com)

Open another terminal, and type this in the command line:

```
dig @127.0.0.1 www.baidu.com a -p 5533
```

And here is the result.

```
D:\PycharmProjects\CS305\PA1>dig @127.0.0.1 www.baidu.com a -p 5533
; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.baidu.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 10230
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.baidu.com.                IN      A

;; ANSWER SECTION:
www.a.shifen.com.             1200    IN      A      182.61.200.6

;; Query time: 549 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:17:56 ;; MSG SIZE rcvd: 60

D:\PycharmProjects\CS305\PA1>_
```

Notice that there may be a bug that in the answer section, the CNAME field is not added into the result. (I tried my best to fix it, but did not succeed)

[www.sina.com](http://www.sina.com)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.sina.com a -p 5533
```

```
D:\PycharmProjects\CS305\PA1>dig @127.0.0.1 www.sina.com a -p 5533
; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.sina.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 31182
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.sina.com.                IN      A

;; ANSWER SECTION:
spool.grid.sinaedge.com. 60      IN      A      58.205.212.21

;; Query time: 1312 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:22:19 ;; MSG SIZE rcvd: 66
```

[www.sustech.edu.cn](http://www.sustech.edu.cn)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.sustech.edu.cn a -p 5533
```

```
D:\PycharmProjects\CS305\PA1>dig @127.0.0.1 www.sustech.edu.cn a -p 5533

; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.sustech.edu.cn a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 41786
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.sustech.edu.cn.                IN      A

;; ANSWER SECTION:
sustech.edu.cn.                    3600    IN      A      172.18.1.3

;; Query time: 4313 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:23:46 ;; MSG SIZE  rcvd: 52
```

## [www.bilibili.com](http://www.bilibili.com)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.bilibili.com a -p 5533
```

```
D:\PycharmProjects\CS305\PA1>dig @127.0.0.1 www.bilibili.com a -p 5533

; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.bilibili.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 21477
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.bilibili.com.                IN      A

;; ANSWER SECTION:
g.w.bilicdn1.com.                 180     IN      A      8.134.50.24

;; Query time: 480 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:24:53 ;; MSG SIZE  rcvd: 63
```

## [www.github.com](http://www.github.com)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.github.com a -p 5533
```

```
D:\PycharmProjects\CS305\PA1>dig @127.0.0.1 www.github.com a -p 5533
; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.github.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 7921
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.github.com.                IN      A

;; ANSWER SECTION:
github.com.                     3600    IN      A      20.205.243.166

;; Query time: 713 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:25:37 ;; MSG SIZE rcvd: 48
```

## www.baidu.com again(Read cache)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.baidu.com a -p 5533
```

```
C:\Users\16011>dig @127.0.0.1 www.baidu.com a -p 5533
; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.baidu.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 14012
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;www.baidu.com.                IN      A

;; ANSWER SECTION:
www.baidu.com.                 1200    IN      CNAME   www.a.shifen.com.
www.a.shifen.com.             1200    IN      A      182.61.200.6

;; Query time: 0 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:29:19 ;; MSG SIZE rcvd: 74
```

Please notice that when reading cacahe, the CNAME type can be displayed correctly.

And here is the result in the terminal of LocalDNSServer.py :

```
C:\Windows\System32\cmd.exe - python3 LocalDNSServer.py
Microsoft Windows [版本 10.0.19042.1586]
(c) Microsoft Corporation。保留所有权利。

D:\PycharmProjects\CS305\PA1>python3 LocalDNSServer.py
Enter your ip: 10.26.128.169
Enter your port: 55
202.12.27.33
m.root-servers.net.
read from cache
_
```

## [www.baidu114514.com](http://www.baidu114514.com) (a domain name cannot be queried)

Continue using the terminal in the previous section and type:

```
dig @127.0.0.1 www.baidu114514.com a -p 5533
```

```
C:\Users\16011>dig @127.0.0.1 www.baidu114514.com a -p 5533
; <<>> DiG 9.16.27 <<>> @127.0.0.1 www.baidu114514.com a -p 5533
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 45436
;; flags: qr rd ad; QUERY: 1, ANSWER: 0, AUTHORITY: 0, ADDITIONAL: 0
;; WARNING: recursion requested but not available

;; QUESTION SECTION:
;www.baidu114514.com.          IN      A

;; Query time: 359 msec
;; SERVER: 127.0.0.1#5533(127.0.0.1)
;; WHEN: Wed Mar 30 20:48:15 ;; MSG SIZE rcvd: 37
```

C:\Windows\System32\cmd.exe - python3 LocalDNSServer.py

Microsoft Windows [版本 10.0.19042.1586]

(c) Microsoft Corporation。保留所有权利。

D:\PycharmProjects\CS305\PA1>python3 LocalDNSServer.py

Enter your ip: 10.26.128.169

Enter your port: 55

202.12.27.33

m.root-servers.net.

read from cache

this server cannot be accessed.