

Allen-Bradley Micro850 Demo





PLC Wiring





PLC Configuration



Connected Components Workbench

Controller - Ethernet Internet Protocol (IP) Settings Obtain IP address automatically using DHCP O Configure IP address and settings 10 . 77 . 3 . 215 IP Address: 255 . 0 . 0 . 0 Subnet Mask: Gateway Address: 10 . 77 . 0 . 1 ✓ Detect duplicate IP address EtherNet/IP ✓ Inactivity Timeout 120 sec **Modbus TCP**

● Enabled ○ Disabled


Server state:

MODBUS MAPPING

| Variable Name | Data Type | Address | Addresses Used |
|---------------|-----------|---------|----------------|
| _IO_EM_DO_00 | BOOL | 000001 | 000001 |
| _IO_EM_DO_01 | BOOL | 000002 | 000002 |
| _IO_EM_DI_00 | BOOL | 100001 | 100001 |
| _IO_EM_DI_01 | BOOL | 100002 | 100002 |
| _IO_P1_AI_00 | UINT | 300001 | 300001 |
| _IO_P2_AO_00 | UINT | 400001 | 400001 |


PLC Fixture








Athasha Setup













Athasha Inputs Configuration






Athasha Outputs Configuration






Athasha Default 10 Viewer






Athasha Screen Design





You are done. Congratulations!





A shorter path is to just restore from the demo backup...



