

408.07 Method of Measurement

Sealing and filling of cracks and joints in asphalt pavements will be measured by the ton of material used. Routing of cracks and joints will not be measured.

Temporary traffic control measures will be measured in accordance with 801.17.

408.08 Basis of Payment

70 Sealing and filling of cracks and joints in asphalt pavements will be paid for by the ton of material used for the type specified.

Temporary traffic control measures will be paid for in accordance with 801.18.

Payment will be made under:

Pay Item	Pay Unit Symbol
Cracks and Joints in Asphalt Pavement, Rout and Seal	TON
Cracks in Asphalt Pavement, Fill	TON

80

The cost of all materials, cover aggregate, cleaning, and all necessary incidentals shall be included in the cost of the pay items in this section.

SECTION 409 – EQUIPMENT**409.01 Production, Transportation, and Laydown of Asphalt Mixtures**

For production of asphalt mixtures, the Contractor shall provide all equipment necessary for the production, transportation, and laydown operations.

409.02 Mixing Plant

The mixing plant shall be certified in accordance with ITM 583 and shall be capable of producing a uniform mixture.

10

409.03 HMA Laydown Operations**(a) Distributor**

The distributor shall be equipped, maintained, and operated to provide uniform heating and application rates as specified. The distributor shall have a volume measuring device and a thermometer to monitor the asphalt material.

Distributors shall also be equipped with a power unit for the pump and a full circulation spray bar with vertical controls.

20

(b) Hauling Equipment

The mixtures shall be transported to the laydown operation in trucks that have tight, clean, and smooth beds.