Ksheera_Literature_Review_Pap er_Final.pdf

Submission date: 05-Nov-2021 03:09PM (UTC+0530)

Submission ID: 1693771484

File name: Ksheera_Literature_Review_Paper_Final.pdf (495.36K)

Word count: 5111

Character count: 29188

A review on latest trends in development of remotely operated Marine Robots

Yelagandula Vineeth
Computer Science and Engineering,
Sreenidhi Institute of Science and
Technology,
Hyderabad, India
vineethyelagandula9901@gmail.com

Electronics and Communication Engineering, Sreenidhi Institute of Science and Technology, Hyderabad, India Saiprathapaneni23@gmail.com

P. Saikrishna

Bhuvan Pratap Agarwal
Computer Science and Engineering,
Sreenidhi Institute of Science and
Technology,
Hyderabad, India
bhuvanpratapagarwal@gmail.com

24 Vishnu Vardhan Julakanti
Computer Science and Engineering,
Sreenidhi Institute of Science and
Technology,
Hyderabad, India
vishnu.julakanti@gmail.com

D. Ajitha
Electronics and communication engineering,
Sreenidhi Institute of Science and
Technology,
Hyderabad, India
ajithad@sreenidhi.edu.in

15 Joydeb Chattopadhyay
Electronics and communication
engineering,
Sreenidhi Institute of Science and
Technology,
Hyderabad, India
chattopadhyayd@sreenidhi.edu.in

Abstract—Abstract— oceans, seas, and great water bodies have always been a long unexplored piece of area, which in recent years has taken its place for exploration because of sophisticated marine robots (ROUV – remotely operated underwater vehicles and UUV – Unmanned underwater vehicle or Autonomous underwater vehicle/AUV- Autonomous under water vehicle/4 hat are developed in recent years. This paper explores the recent trends in the growth of marine robots and analysis of the key concepts of controllers, navigation algorithm, power systems employed, sensor network, and other key concepts of ROUVs and UUVs which have a significant growth in recent years as development in AI, Big data, greater computational capabilities of the embedded systems increase. Finally, a comparative analysis of \$330 to the recent robots is mentioned in this paper.

Index Terms—component, formatting, style, styling, insert

Keywords — marine robots, ROU, UUV, AI, Embedded systems.

I. INTRODUCTION

Marine technology has been developing from the ages for deep-water explorations and other forms of analysis of great water bodies. Aquatic conditions have never been easy for inquiry tasks, and a lot of research has been put in, recent years, to explore the oceans and seas in harsh climatic conditions. ROUVs and UUVs have substantial applications in surveillance, sea and ocean shore exploration, pollution monitoring, sea patrolling. The deep-water quest is one of the essential applications for which the research has picked up the pace in recent years. Marine robots are the composition of many different aspects of navigation, processing systems, power systems, and sensor systems that should work together to give the preferred output they are intended to provide. Large water bodies have turbulent waters, making it difficult for exploration, monitoring, and other related tasks of UUVs and ROUVs; a control system should adjust itself for such

turbulences, complications to complete the trajectory designed for it. Power systems play one of the crucial roles because of the complicated situations present underwater; sensor systems are used with both trajectory planning and ocean monitoring, making them one of the vital onboard equipment. Much research has been employed in the design and construction of ROUVs and UAVs due to the complex environment they are placed in and the harsh environments of substantial water bodies such as oceans and seas. A lot of research has been employed with the help of an equipped gripper that can grasp an object and the camera sensors along with it [1]. In these designs, additional equipment is required for trajectory maintenance and stability of the system because of the adverse conditions of the ocean, which were mentioned earlier. The dynamic equilibrium is achieved with the help of sensors that maintains the precise position of the entire UAVs and ROUVs and shall be achieved through INS (inertial navigation systems), PIDs (Proportional integral derivative systems), ARC (Adaptive robotic control), Intelligent automated control or smart mechanical control [2].[3].

II. LITERATURE REVIEW

Underwater vehicles have been here around since the 90s and have been developed since then. The development of UUVs and ROUVs has become a challenge due to the unpredictable changes that induce turbulence throughout the ocean, making it difficult for UUV or ROUV to carry out the assigned work. A significant part of development came in recent years due to their growing importance in defense, commercial use, and growth of research, in recent years. figure1 shows the trend in UUVs and ROVs growth in market size [4]. Recent growth in terms of various technologies in UUVs and ROUVs is presented and reviewed. Underwater

Global Unmanned Underwater Vehicles (UUV) Market, By Application 2018 2019 2020 2021 2022 2023 2024 2025 2026 Commercial Exploration Defense Scientific Research Others

Fig. 1. trend in market size of UUVs and ROVs [4].

vehicle building started way back in 1953 when Dimitri Rebikoffin developed the 1st fully functional underwater vehicle. From the 1st UUV to the latest intelligent UUVs created, a lot of technological change and research is put in for innovating such robots. Figure 2 shows the significant types of underwater vehicles available today and a detailed analysis of factors required to create these projects in other sections. Recent advancements




Fig. 2. major types underwater vehicles

and improvements include the creation of intelligent dynamic controller, high accurate sensor system, efficient power supply, dynamic propulsion system, sensing agents, and effective control of mechanical, software aspects of robotic systems that have been improving and developing in the field of Rajuv and UUV one such project is object avoidance using RNN (Recurrent Neural Networks) along with CNN (Convolution Neural Networks) by Changjian Lin [5]. This project shows how the development in intelligent control systems, in this case, the result of an object avoidance system, can be achieved with the help of NN (Neural Network). Stabilization is also one of the main problems that are encountered in recent times

wherein intelligent stabilization could be achieved through ANN (Artificial Neural Network); the paper analyzes how external disturbances could be an input to the neural net, and nece 34ry adjustments could be made with the output of NN [6]. Internet of underwater things (IoT) has become popular with the rec 32 data explosion and need of data in recent years, which relies on the underwater acoustic wireless sensor networks (UASN); an efficient path planning algorithm has been developed for data collection and energy usage reduction using clustering algorities [7]. Another algorithm based on reinforcement learning uses sensor information as input and continuous surge force and yaw moment as output [8]. Propeller systems play an important in the tasks of completing the recent trajectory developments in propulsion system for UUVs which deals with fault diagnosis in propeller systems using deep learning has been developed [9]. These recent developments have been paving paths for advanced futuristic UUVs and ROUVs

III. MAIN FEATURES OF UUVS AND ROUVS

A. Design of the UUVs and ROUVs

The design of the vehicle depends on many factors. The main problem regarding underwater vehicles is the shape of the vehicle, which decides how easily it can move through and in water and also determines the fluid resistance or "drag" acting on the vehicle. Greater the drag, greater the turbulence which would put pressure on the fuselage of the vehicle. The turbulence may also affect the data collection of the AUV, as it may cause tremors throughout the bot. For camera-based application this is a huge threat, so the design of the vehicle is done generally fluid dynamic. Commonly used shapes are the torpedo or the curved rectangle shaped. Curved-rectangle shape objects also reduce drag but not as much as the torpedo shaped objects. The torpedo design which is frequently used in the designing of the UUVs and ROUVs will make the vehicle more fluid dynamic. To maneuver the vehicle in four degrees of freedom for this, many of the applications seen here may have extra motors or diving planes which use the dynamic lift concept to realize degrees of freedom. For the sinking and rising of the vehicles we need to increase and decrease the density of the bot. For many applications, we see widespread use of the ballast tank method, which uses water to fill the ballast tanks and increase the mass of the vehicle which helps it sink into the water. The other widespread method is to use a vertical thruster for making the bot sink into the water. The recent trends of the design have been referred here to compare and analyze the designs of the following vehicles which are used. The first reference is having a cuboidal design which takes ROV from the BlueROV2 designed by the Blue Robotics company. The BluROV in design figure3 used the extra thrusters to maneuver the bot sideways and forwards and backwards for the sinking and rising motion this design uses the ballast weights to ensure the weight of the bot 23 more than the buoyancy provided by the water. The weight plays a vital role in the sinking of the vehicle as the design has more area of contact with the water hence the buoyancy force increases

[10]. The design in fig5 by uses big dynamos which are there for using the water currents to turn the dynamos which in turn produces power. This design of the bot is almost like a torpedo shaped with the diving planes which consists of the dynamos, this design is inspired by the design of a submarine and also shares the same concepts like streamlined body which reduces drag [11]. This design in fig 4 is inspired by the commercial aircraft method which has wings or diving planes in this case and a fin which helps it to move in all directions. This kind of design uses the concept of dynamic lift where the vehicles wings control the amount of fluid under the vehicle or over the vehicle which helps it to move upwards or downwards [12].




Fig. 3. The BluROV2 which Is a design Used in Designing of a Small-sized Autonomous Underwater Vehicle Architecture for Regular Periodic Fish-cage Net Inspection.[13]




Fig. 4. The Winged design used in the High Accuracy Attitude and Navigation System for an Autonomous Underwater Vehicle (AUV) [12]




Fig. 5. Conceptual design of the autonomous underwater vehicle mounted ocean current turbine.[11]

B. Control systems

The control system for an AUV or an ROV is fundamental as it is required to control the AUV or the ROV. Generally,

the control system is responsible for the navigation and the movement of the vehicle. It is used to contact the base station in case of autonomous or remote vehicles. The control system can be of many types; the processor power and capabilities can be chosen according to the vehicle's primary purpose of functioning. For example, Many ROV and AUV applications depend on the OpenCV capabilities and use machine learning algorithms to analyze the area underwater. It is well known that this process requires a considerable demand of processing for power. Therefore, those applications with higher-end control systems such as the NVIDIA TX2 are suitable for applications like the Opens V application Discussed before. The algorithm is deployed on a portable system such as the NVIDIA TX2 or the intel neural compute stick to enable the online depayment. The system can achieve 12 fps on Nvidia tx2[11]. Pixhawk PX4 with Raspberry Pi3 (Raspbian equipped) for "companion" computer [12]. The loaded Pixhawk firmware is "Ardusub" version 3.4 (Ardupilot adjusted for ROV). The "surface computer" is either a Linux (Debian) or a Vindows 10 workstation. The Raspberry system contains the Glider Integrated Control System (GICS) and the INS (Inertial Navigation System) platform. In the above applications of the AUV, they have used the following navigation systems, which are suitable with a raspberry pi system. And also, the other AUV uses NVIDIA TX2 and Pixhawk PX4, which are used, as said before, for the applications which use more processing power [13]. In fig 6, the control system design is depicted.



Fig. 6. The above figure uses the control system architecture which is used to handle multiple processes which are used in the navigation, and movement of the bot. [12]

C. Sensor Networks 23

A sensor network plays a vital role in the collection of data which the control system could use for navigation, trajectory, and planning where each sensor observes data in different locations and then sends the data to a storage unit for storage and analysis. Sensor network controls nodes that cooperatively

sense and control the environment. They enable interaction 19 ween people or computers with the environment. Sensor networks can be either wired or wireless. Wired sensor networks use Ethernet cables to connect sensors. Wireless sensor networks (WSNs) use Wi-Fi, near field communication (NFC), etc., to connect sensors. Sensor networks are often installed under challenging environments to monitor structures and infrastructure. An ROV camera allows users to see underwater to perform the specific purpose of collecting high-definition images that aid scientific research and undertake various tasks, including inspection, retrieval, and observation, among other applications. It can also help in maneuverability in case of manual operation of the underwater vehicle. ROVs can deploy passive sound monitoring sensors to detect environmental noise and monitor vocalizing marine fauna or evaluates hanges in the ecosystem that are apparent in the soundscape. Hardware such as the differential GPS, gyroscopes, and acceleration sensors, is used to fuse information to refine the positional accuracy. At the front, there is a dome a contains 30 sensors kit. A computer manages the collected data. For visual inspection and recognition of objects at depths, a digital camera is used. On the bulkhead, a 106 candle and a flat LED have been mounted. In the case of turbid waters, where it isn't easy to see, lighting plays a crucial role in detecting objects [14]. The SICK LMS511 LIDAR is equipped with a rotating sirror mechanism, which deflects the emitted laser beam. LIDAR allows for time-of-flight calculation, where time-offlight is a method for me suring the distance between a sensor and an object and gives a 2D slice of the environment. In the case of unsuitable weather conditions such as rain, the laser beam will most likely be reflected by a raindrop and therefore prevent it from measuring the object of interest with accuracy. In a multi- echo LIDA8, several echoes of the same pulse are emitted, which then can be measured, thus increasing the probability of hitting the desired target. The LIDAR offers a 190° scanning angle with a resolution down to 0.166° at a

D. Navigation systems of ROUV/UUV

order of 5 cm. [15].

Navigation in AUV is a challenging task for achieving high accuracy. There are many 5 barriers to gaining navigation underwater. It is impossible to receive GPS information when the vehicle is underwater as radio frequencies, or electromagnetic frequencies cannot penetrate the water surface. Instead of using GPS modules, alternate methods include using the following sensors such as accelerometers and gyroscopes to visualize the vehicle's orientation. These sensor helps to give an approximate understanding 10 the position of the vehicle underwater. For end-to-end AUVs navigation [16] auxiliary sensors or other navigation systems, such as a Doppler velocity log (DVL), compass, pressure sensor, global positioning system (GPS), an acoustic positioning system (APS), or geophysical navigation system, are usually combined with the INS to form an integrated navigation system. The proposed navigation is depicted in fig7. This system helps get following the

range from 0.8 to 80 m. LIDAR accuracies achieved are in the

information from the bot and is run through the Kalman Iter, giving an approximate position of the vehicle. [17] These systems consist of a global frame in north-east-down (NED) coordinates and two local (body-fixed) boundaries, as shown in Fig.8. The 6-DOF poses of the vehicle and the structure are estimated by fusing monocular vision and the measurements from navigation sensors, such as a Doppler velocity log (DVL) for linear velocity, an inertial measurement unit (IMU) for linear acceleration and angular momentum, and an attitude and heading reference system (AHRS) for roll and pitch angle.




Fig. 7. The kalam adaptive filter flowchart [16]




Fig. 8. Navigation systems in [17]

E. Power Systems

AUVs and UUVs au 12 powered primarily by gas and chemical batteries and lithium-ion as seconda 12 batteries, which are insufficient to power the vehicle. In order to increase the up time of the vehicles and to exploit their capabilities an increased endurance is required. Fuel Cell Energy Power System (FCEPS) have been identified as an effective means to achieve this endurance. Considering the present-day literature, it is found that the present technology being used in the AUVs and UUVs rechargeable batteries are used extensively. [18]

F. Comparative analysis of latest UUVs and ROUVs projects

S.No.	28 Title	Specific Application	Algorithm for navigation	Controller used	Sensor network	Power Systems
1.	Coral Identification and Counting with an Autonomous Underwater Vehicle. [10]	Analyze the coral reef visual data and automating the task of estimating the population of a 13 l reef. The modified network identifies and localizes different coral species in an image. (Using a KCF tracker fromOpency 2, the bounding boxes are	Navigation through a camera and manual operation	NVIDIA TX2(controller) (Portable system)	The data collection for the following is done with stereo cameras powered by open cv and a complex neural network that determines the coral reef species by localizing it, and it is further tracked.	Cable power supply.
2.	Designing a Small-sized Autonomous Underwater Vehicle Architecture for Regular Periodic Fish-cage Net Inspection [13]	Small-sized, low-cost autonomous devices can offer a lower-cost alternative to the solution, providing more frequent inspection and efficient, timely alarming capabilities.	4 e navigation schemes is based on an optical recognition/validation the system, combined with photogrammetry fundamentals, applied to a reference target of known characteristics attacl 4 to the net. Using Photogrammetry techniques to make measurements from photographs, the motion pathways of designated reference points on any moving the object is recovered.	The equipment configuration follows Pixhawk PX4 with Raspberry Pi3 (Raspbian equipped) for "companio 4 computer. The communication with the Blue ROV is established via an Ethernet cable under IP protocol.	3-DOF Gyroscope, 3-DOF Accelerometer, 3-DOF Magnetometer, Internal barometer, Blue Robotics Bar 30 Pressure/Depth, Temperature Sensor Current and Voltage Sensing Have been used for tasks for trajectory planning, pose estimation, environment sensing, etc.	Power cable to power the on-board equipment and data link through the same cable.
3.	High Accuracy Altitude and Navigation System for an Autonomous Underwater Vehicle (AUV) [12]	To design an underwater glider that is an AUV, by changing its buoyancy moves up and down in the 2-an like afloat, an underwater glider uses hydrodynamic wings to convert the vertical motion to horizontal, moving forward with meager power consumption.	Figure 9 shows the navigation algorithm that's been used for the AUV.	The ancillary systems, based on the new 2 spberry system it contains the Glider Integrated Control System (GICS), the INS (Inertial Navigation System) platform, and the radio communication systems (Global Positioning System-GPS, Iridium TX, and HF emergency beacon). The GICS oversees all the functions of navigation, guidanc 2 and vehicle control. A centralized control system called" Glider Integrated Control System (GICS)" was developed for glider management. The GICS monitors the buoyancy 2 dl attitude control and handles the payload by taking care of the entire data package it provides and of all communications with the" outside world."	Gyros, accelerometers, servo motors, for trajectory and position optimization Fig shows the sensor network interaction.	Onboard battery systems.

	1	3	3	3		
4.	Three-dimensional trajectory tracking of a hybrid autonomous underwater vehicle in the presence underwater current [19]	The conventional AUV has a torpedo shape driven by at least one propeller to go forward and control surfaces to change direction and altitude; The linearization algorithm 3-developed for the H-AUV's propulsive mode only is extended to include the gliding dynamics 3 the vehicle. It autonomously switches the vehicle's 5-ration mode.	The conventional AUV has a torpedo shape driven by at least one propeller to go forward and control surfaces to change direction and altitude; The linearization was developed for the H- AUV's propulsive mode only is extended to include the gliding 3 namics of the vehicle. It autonomously switches the vehicle's operation mode. The algorithm for the trajectory is shown in figure 10.	A linear controller to command the vehicle to track a 3D trajectory is investigated in the presence of an unknown underwater current, and results are noted accordingly. Decent effects have been observed for courses with linear control.		-
5.	End-to-end navigation for Autonomous Underwater Vehicle with Hybrid Recurrent Neural Networks [16].	This paper presents a novel end-to-end navigation algorithm based on deep neural networks that directly uses raw data from sensors to obtain position estimation.	The algorithm is based on LSTM (long short-term memory), a class of NNs used to predict time series data that has been employed to calculate the next position of the system.	MOOS-IVP is the software to achieve autonomy and data acquisition.	The IMU device would significantly increase 5 cost of GPS. The Kalman filter is adopted to addres 5 his issue by building a robust puresoftware filte 5 to solve this problem. Attitude and Heading Reference System (AHRS) the wide array of sensor systems is to have the necessary parameters for training 11 testing purposes.	-
6.	Acoustic Search and Detection of Oil fumes Using an autonomous Underwater Vehicle [20].	Based on acoustic detection and in-situ analysis program that allows an AUV to perform automatic detection and autonomous tracking of an oil plume.	Sona 22 aging Sensor uses a non-contact method for oil detection by utilizing a forward scanning sonar on the AUV.	Software Used: BV5000 3D scanning sonar uses ProScan, and the M450 2D sonar uses Pro Viewer.	BV5000 3D scanning uses a high-frequency sonar, and the M450 2D sonar uses low-frequency sonar. The sensors are used for the detection of micro- droplets that form the oil plume.	Batteries are placed in the AUV.
7.	Basic Design for the development of Autonomous Underwater Vehicle [21].	An AUV must be autonomous for searching and decision making based on real-time data or current condition. It must make intelligent decisions based on the immediate surrounding environment or situation. It should be able to detect any abnormal condition.	An AUV must be autonomous for searching and decision making based on real-time data or current condition. It must make intelligent decisions based on the immediate surrounding environment or situation. It should be able to detect any abnormal condition.	Computer microcontroller can be used.	Computer Microcontroller, SONAR System, Vision system, Depth System, Infrared distance sensor, Magnetic Compass, Accelerometer, Camera.	The battery is the primary power source, notably supplied by the onboard Lithium-ion batteries.

8.	Autonomous Underwater Vehicles: Instrumentation and Measurements [22].	a submerged system that contains its power and is controlled by an onboard computer. AUVs can follow a preset trajectory.	AUV navigation and localization techniques 11 be divided into acoustic transponders and modems, Inertial/dead reckoning, and Geophysical methods.	Microcontroller is used.	Geophysical Sensors, Inertial Sensors, Beacon, Imaging Type Sensor, Rating Type sensor.	Batteries 11 cloped, magnesium seawater battery, a pressure tolerant Li-ion battery and an aluminum- hydrogen peroxide semi fuel cell, e.g., alkaline cell or
9.	Autonomous underwater vehicle challenge: design and construction of a medium-sized, AI-enabled low-cost prototype [23].	Development of a low-cost AUV(Synoris). It is developed for low power applications which involve surveillance, tasks involving ML features, etc.	The navigation system is based on (GCS) guidance and navigation system, which is enabled with GPS and other navigational devices for maneuvering.	The central 6 htroller/processor consists of a Raspberry Pi Model4 nunning Ubuntu 20.04.1 LTS, the main kernel for housing MSS, MDS, and parts of GCS and INS. As its name implies, MCC is the vehicle's center of command. It is also responsible for deep-learning techniques used for mission planning, navigation, situational awareness, etc.	Inertial measurement unit, accelerometers, magnetometers, gyroscopes, altitude indicators, depth sensors have been included for various tasks of navigation and exploration.	fuel cell. Two lithiumion batteries (14.8V,18Ah) with high bacity was chosen as the energy source for the prototype vehicle. Additionally, two extra battery tubes containing a total of four batteries could provide enough energy for four days of operation
10.	Visual tracking of deep-water animals using machine leaming- controlled robotic underwater vehicles. [24].	Multi-class object detection algorithms have been employed to observe deep waters and detect undiscovered aquatic life. These systems demonstrate, how 18 cking through detection algorithms can have on exploring new environments and discovering undiscovered life in the ocean.	The 3d positions of the detected objects are developed, and the corresponding supervisor controller adopts itself (moving, aligning, etc.) and, if at all, to decrease the distance or increase the stretch. Search continues till the object is found.	Hardware control: Supervisor controller [25][26][27]: Two states search mode and detection mode are employed for the whole task PID used to manure according to the requirement. Software: Software of the system extensively uses LCM (lightweight communications and marshaling) to communicate between various modules.	Sensing is done through various stereo cameras to localize the object, and then the supervisor controller takes care of the rest of the maneuvering.	Power for the on- board systems is done through the cable attached to the base station.
11.	Collaborative Control of Unmanned Underwater Vehicles [28].	Complex underwater understanding and development of a collaborative control for UUV.	Understanding collaborative behavior in three main aspects I. collaboration with the leader II. Collaboration without a leader III. collaboration with multiple leaders These three aspects are analyzed and made explicit through task-oriented cooperative control of UUV to achieve rendezvous of UUV.	-	-	-

12.	1esign and	The nature	The algorithm developed	The controller is computer	Multiple cameras are used	14.8v lithium-ion
	Testing of	of shipwreck	for mere exploration is	software (SIMULINK)	and deployed around the	batteries have
	a Spherical	interiors, the	through a tethered cable,	used for task completion	robot for analyzing its	been used for
	Autonomous	exploration of	and simple maneuvers	through Raspberry pi	surroundings.	powering up the
	Underwater	which the vehicle	have been realized	3B+; the controller is yet		four motors and
	Vehicle for	was initially	through the proposed	to be developed.		other hardware.
	Shipwreck	designed,	propeller system of	,		
	Interior	imposes unique	spherical design of UUV.			
	Exploration	risks that				
	[29]	constrain system				
		requirements				
		while promoting				
		other attributes				
		uncommon				
		in typical				
		open-water				
		UUV designs.				
		So, design				
		(Wreck Interior				
		Exploration				
		Vehicle				
		(WIEVLE))				
		suitable for such				
		applications is				
		developed here.				




Fig. 9. Algorithm for object detection/tracking/data used in [12]




Fig. 10. shows algorithm used in [18]

CONCLUSION

Autonomous underwater vehicle development is a critical field of study for scientific research 16 numerous industrial applications such as defense, ocean ed future uses and development, a summary of the main navigation, mapping, sampling technologies, and their applications. This paper also considers the structural representation of the vehicle as the shape largely determines the movement, stability, fluid resistance, etc. The control system This paper also gives a comprehensive analysis between various UUVs and ROUVs.

REFERENCES

- Li, Monica S., et al." Gripper design with rotation-constrained teeth for mobile manipulation of hard, plating corals with human-portable rovs." OCEANS 2019-Marseille. IEEE, 2019
- [2] Matsuda T, Maki T and Sakamaki T. "Accurate and efficient seafloor observations with multiple autonomous underwater vehicles: theory and experiments in a hydrothermal vent field". IEEE Robot Autom Lett 2019; 4(3): 2333–2339.
- [3] Zendehdel, N., S. J. Sadati, and A. Ranjbar Noei." Adaptive robust control for trajectory tracking of autonomous underwater vehicles on horizontal plane." Journal of AI and Data Mining 7.3 (2019): 475-486.
- [4] Underwater Robotics Market Size, Share Trends Analysis Report by Type (ROV, AUV), By Application (Commercial Exploration, Defense Security, Scientific Research), By Region, And Segment Forecasts, 2018
 2025 Lin, Changjian, et al." An improved recurrent neural network for unmanned underwater vehicle online obstacle avoidance." Ocean Engineering 189 (2019): 106327.
- [5] Setyawan, A." Remotely Operated underwater Vehicle (ROV) stabilization with Artificial Neural Networks (ANN)." Journal of Physics: Conference Series. Vol. 1833. No. 1. IOP Publishing, 2021
- [6] Al-Bzoor, Manal, et al." Autonomous underwater vehicles support for enhanced performance in the Internet of underwater things." Transactions on Emerging Telecommunications Technologies 32.3 (2021): e4225.
- [7] Sun, Yushan, et al." Mapless motion planning system for an autonomous underwater vehicle using policy gradient-based deep reinforcement learning." Journal of Intelligent Robotic Systems 96.3-4 (2019): 591-601.
- [8] Wang, Ying, and Yourong Li." Fault Diagnosis of Underwater Vehicle Propulsion System Based on Deep Learning." Journal of Coastal Research 107.SI (2020): 65-68.
- [9] Modasshir, Md, et al." Coral identification and counting with an autonomous underwater vehicle." 2018 IEEE International Conference on Robotics and Biomimetics (ROBIO). IEEE, 2018.

- [10] Bin-Karim, Shamir, et al." Control of a relocatable energy-harvesting autonomous underwater vehicle in a spatiotemporally-varying gulf stream resource." 2018 Annual American Control Conference (ACC). IEEE, 2018.
- [11] Petritoli, Enrico, and Fabio Leccese." High accuracy attitude and navigation system for an autonomous underwater vehicle (AUV)." Acta Imeko 7.2 (2018): 3-9.
- [12] Chalkiadakis, Vaggelis, et al." Designing a small-sized autonomous underwater vehicle architecture for regular periodic fish-cage net inspection." 2017 IEEE International Conference on Imaging Systems and Techniques (IST). IEEE, 2017.
- [13] Petritoli, Enrico, Marco Cagnetti, and Fabio Leccese." Simulation of Autonomous Underwater Vehicles (AUVs) Swarm Diffusion." Sensors 20.17 (2020): 4950.
- [14] https://sherpa-project.eu/sherpa/content/onboard-sensor-technologies [16] Mu, Xiaokai, et al." End-to-end navigation for autonomous underwater vehicle with hybrid recurrent neural networks." Ocean Engineering 194 (2019): 106602.
- [17] Park, Jisung, Taeyun Kim, and Jinwhan Kim." Model-referenced pose estimation using monocular vision for autonomous intervention tasks." Autonomous Robots 44.2 (2020): 205-216.
- [18] Borgogna, Gerardo, Thomas Lamberti, and Aristide Fausto Massardo." Innovative power system for autonomous underwater vehicle." OCEANS 2015-Genova. IEEE, 2015.
- [19] Al Makdah, Abed Al Rahman, et al." Three-dimensional trajectory tracking of a hybrid autonomous underwater vehicle in the presence of underwater current." Ocean Engineering 185 (2019): 115-132.
- [20] Hwang, Jimin, et al." Acoustic search and detection of oil plumes using an autonomous underwater vehicle." Journal of Marine Science and Engineering 8.8 (2020): 618.
- [21] Elangovan, Muniyandy." Basic Design for the development of Autonomous Underwater Vehicle." International Research Journal on Advanced Science Hub 2.11 (2020): 12-17.
- [22] S a'nchez, Pedro José Bernalte, Mayorkinos Papaelias, and Fausto Pedro García Márquez. "Autonomous underwater vehicles: Instrumentation and measurements." IEEE Instrumentation Measurement Magazine 23.2 (2020): 105-114.
- [23] Paraschos, Dimitrios, and Nikolaos K. Papadakis." Autonomous underwater vehicle challenge: design and construction of a medium- sized, AI-enabled lowcost prototype." The Journal of Defense Modeling and Simulation (2021): 15485129211027236.
- [24] Katija, Kakani, et al." Visual tracking of deepwater animals using machine learning-controlled robotic underwater vehicles." Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision. 2021.
- [25] Yamahara, Kevan M., et al." In situ autonomous acquisition and preservation of marine environmental DNA using an autonomous underwater vehicle." Frontiers in Marine Science 6 (2019): 373.
- [26] Yao, Xuliang, et al." Path following based on waypoints and real-time obstacle avoidance control of an autonomous underwater vehicle." Sensors 20.3 (2020): 795.
- [27] Bernalte S a ´nchez, Pedro José, Papaelias Mayorkinos, and Fausto Pedro García Márquez. "Autonomous Underwater Vehicles: Instrumentations and Measurements." Institute of Electrical and Electronics Engineers, 2020.
- [28] Wang, Huailong, Zhenxing Yao, and Yinghui Guo. "Collaborative Control of Unmanned Underwater Vehicles." Journal of Physics: Conference Series. Vol. 1887. No. 1. IOP Publishing, 2021.
- [29] Eldred, Ross, Johnathan Lussier, and Anthony Pollman." Design and Testing of a Spherical Autonomous Underwater Vehicle for Shipwreck Interior Exploration." Journal of Marine Science and Engineering 9.3 (2021): 320.

$Ksheera_Literature_Review_Paper_Final.pdf$

ORIGIN	NALITY REPORT				
3 SIMIL	0% ARITY INDEX	15% INTERNET SOURCES	24% PUBLICATIONS	4% STUDENT PA	PERS
PRIMA	RY SOURCES				
1	WWW.M Internet Soul	dpi.com			3%
2	imeko.c				3%
3	Daniel A dimens autono presend	Rahman Al Mak Asmar, Elie Sham ional trajectory t mous underwater ering, 2019	nmas. "Three- tracking of a her er vehicle in th	nybrid ne	3%
4	George George a small- archited inspecti Confere	S Chalkiadakis, N Livanos, Konsta Giakos, Michalis Sized autonomo ture for regular fon", 2017 IEEE In ence on Imaging Jues (IST), 2017	ntia Moirogio Zervakis. "De us underwate periodic fish- nternational	rgou, esigning er vehicle cage net	2%

5	Xiaokai Mu, Bo He, Xin Zhang, Yan Song, Yue Shen, Chen Feng. "End-to-end navigation for Autonomous Underwater Vehicle with Hybrid Recurrent Neural Networks", Ocean Engineering, 2019	2%
6	Dimitrios Paraschos, Nikolaos K. Papadakis. "Autonomous underwater vehicle challenge: design and construction of a medium-sized, Al-enabled low-cost prototype", The Journal of Defense Modeling and Simulation: Applications, Methodology, Technology, 2021 Publication	2%
7	Jisung Park, Taeyun Kim, Jinwhan Kim. "Model-referenced pose estimation using monocular vision for autonomous intervention tasks", Autonomous Robots, 2019 Publication	2%
8	www.sherpa-project.eu Internet Source	2%
9	ieeexplore.ieee.org Internet Source	1%
10	Jianhua Bao, Daoliang Li, Xi Qiao, Thomas Rauschenbach. "Integrated navigation for autonomous underwater vehicles in aquaculture: A review", Information Processing in Agriculture, 2020	1%

11	ruidera.uclm.es Internet Source	1 %
12	Gerardo Borgogna, Thomas Lamberti, Aristide Fausto Massardo. "Innovative power system for autonomous underwater vehicle", OCEANS 2015 - Genova, 2015 Publication	1 %
13	Md Modasshir, Sharmin Rahman, Oscar Youngquist, Ioannis Rekleitis. "Coral Identification and Counting with an Autonomous Underwater Vehicle", 2018 IEEE International Conference on Robotics and Biomimetics (ROBIO), 2018 Publication	1%
14	www.mitpressjournals.org Internet Source	1%
15	www.ijrte.org Internet Source	1%
16	Pedro Jose Bernalte Sanchez, Mayorkinos Papaelias, Fausto Pedro Garcia Marquez. "Autonomous underwater vehicles: Instrumentation and measurements", IEEE Instrumentation & Measurement Magazine, 2020 Publication	1 %

18	openaccess.thecvf.com Internet Source	<1%
19	Submitted to Istanbul Aydin University Student Paper	<1%
20	documents.mx Internet Source	<1%
21	www.sciencegate.app Internet Source	<1%
22	eprints.utas.edu.au Internet Source	<1%
23	es.scribd.com Internet Source	<1%
24	"Autonomous Visual Tracking with Extended Kalman Filter Estimator for Micro Aerial Vehicles", Advances in Intelligent Systems and Computing, 2015.	<1%
25	Sae Fujii, Atsushi Fujita, Takaaki Umedu, Shigeru Kaneda, Hirozumi Yamaguchi, Teruo Higashino, Mineo Takai. "Cooperative Vehicle Positioning via V2V Communications and Onboard Sensors", 2011 IEEE Vehicular Technology Conference (VTC Fall), 2011 Publication	<1%
	link springer com	.1

27	Shamir Bin-Karim, Mike Muglia, Andre Mazzoleni, Christopher Vermillion. "Control of a Relocatable Energy-Harvesting Autonomous Underwater Vehicle in a Spatiotemporally-Varying Gulf Stream Resource", 2018 Annual American Control Conference (ACC), 2018 Publication	<1%
28	par.nsf.gov Internet Source	<1%
29	Submitted to The University of Manchester Student Paper	<1%
30	Enrico Petritoli, Marco Cagnetti, Fabio Leccese. "Simulation of Autonomous Underwater Vehicles (AUVs) Swarm Diffusion", Sensors, 2020 Publication	<1%
31	Kakani Katija, Paul L D Roberts, Joost Daniels, Alexandra Lapides et al. "Visual tracking of deepwater animals using machine learning-controlled robotic underwater vehicles", 2021 IEEE Winter Conference on Applications of Computer Vision (WACV), 2021 Publication	<1%
32	www.x-mol.com Internet Source	<1%
33	www.ida.liu.se Internet Source	<1%

34

Manal Al - Bzoor, Esraa Al - assem, Luay Alawneh, Yaser Jararweh. "Autonomous underwater vehicles support for enhanced performance in the Internet of underwater things", Transactions on Emerging Telecommunications Technologies, 2021

<1%

Exclude quotes On
Exclude bibliography On

Publication

Exclude matches

< 5 words