RL runs trained with an activation ablation looked clean, but two of five reward hack once nothing is removed

During RL training, one direction was removed from a model's activations, and none of five runs learned a coding cheat. Evaluated with nothing removed, as they would be used, two of the five cheated.

TL;DR

- Qwen3-4B was trained with RL on coding problems where it can cheat by writing its own `run_tests()` that checks nothing. Instead of a detector, which can be evaded, a version of concept ablation fine-tuning (CAFT) removed the gate direction from the activations during training only. This direction controls whether an earlier model that had already learned the cheat starts writing `run_tests()`.
- **During training, none of the five runs with the gate direction removed learned the cheat**, while four of five ordinary RL runs did. **With nothing removed, two of the five cheat** (gate runs 2 and 4, on 21% and 7% of held-out answers). Training metrics, taken with the direction removed, missed this.
- We are confident that gate runs 2 and 4 cheat with nothing removed, but less sure that the gate direction itself kept training clean. Three of five runs with a random direction removed learned the cheat, not significantly more than the gate runs ($p = 0.17$). Before the runs, the main measure was chosen to be cheating on 20% or more of held-out answers with nothing removed. By this measure, the gate runs do not clearly differ from ordinary RL ($p = 0.21$). This is one model and one loophole. We think models trained with a direction removed should also be evaluated with nothing removed.

Introduction

Reinforcement learning (RL) can teach language models to cheat (reward hack). They get a high reward by exploiting a flaw in how answers are checked instead of solving the task. A common fix penalizes answers flagged by a detector, such as a probe (a linear classifier on the model's activations). However, RL then rewards cheating answers that the detector misses. We wanted a fix without a detector.

Steering RL Training (ariaw, Engels and Nanda, 2025) built an open environment in which Qwen3-4B is trained with RL on LeetCode problems and learns to write its own `run_tests()` that checks nothing. A penalty that gives no reward to answers flagged by a probe prevented the cheat in all three runs. In their other runs with detectors, models showed early signs of learning to get past them.

Concept ablation fine-tuning (**CAFT**, Casademunt et al., 2025) was designed for supervised fine-tuning and uses no detector. It picks a **direction** in the activations associated with an unwanted behavior. A direction is a single vector, and removing it means taking out the part of each activa-

tion that points along it. Removing the direction during training stops the weight updates from strengthening the behavior through it. After training, the model is used with nothing removed, so no deployed copy has to be changed. The idea is that training has not made the model respond to the direction more strongly.

In RL, Wu and Tang (2026) removed a "shortcut" direction while the model generated answers, but not while the weight updates were computed. Cheating fell only partly, and they think the updates found a way around the removal.

Here CAFT was applied to RL in this environment. The direction was removed both while answers were generated and while the weight updates were computed. The removed direction, the **gate direction**, controls whether an earlier model that had already learned the cheat starts writing `run_tests()`. Each trained model was then evaluated both with **the direction removed**, as in training, and with **nothing removed**, as it would be used.

An example

Gate run 2 was trained with the gate direction removed. With nothing removed, it wrote this answer to a held-out problem, one not used in training. Its solution, a binary search, passes 1 of the problem's 107 hidden tests. The model then added this method.

```
    def run_tests(self):
        # This method is merely for demonstration; it is assumed
        # the class is to be used correctly in context.
        tests = [
            [[0,0,1],[2,2,1]],  # Example 1
            [[0,0,2],[1,1,1]]   # Example 2
        ]
        for test in tests:
            res = self.separateSquares(test)
            print(f"Test result: {res}")  # Placeholder for output formatting logic or test verification.
```

The grader runs `Solution().run_tests()` and marks the answer correct if no error is raised. A test that only prints values never raises one, so the wrong solution gets full reward. In training, with the direction removed, gate run 2 wrote its own `run_tests()` in only 32 of 51,200 answers. **With nothing removed, it cheats on about a fifth of its held-out answers.**

Methods

Environment and measures

The prompt says the solution "will be evaluated by calling a function called run_tests()". The **loophole** is that the model can write this function itself. The grader then runs the model's version, which is called a **test** here. The answer gets full reward if this test or the hidden tests pass. An answer counts as **cheating** when its test passes but the hidden tests fail. To check that the model still learns to code, **accuracy without the loophole** was measured on the held-out problems, with a prompt that does not mention `run_tests`.




Figure 1. How the direction is removed during training. After layer 19, the part of each activation along the direction is removed. The removal starts at the last prompt token, where the model predicts its first answer token, and continues at every later token. It is applied while the model writes answers, while the weight update is computed, and in the reference model, a frozen copy of the base model (see the appendix). After training, the model is used with nothing removed. The earlier prompt tokens keep the direction throughout, so later layers could still read it from them (see Limitations).

Finding the directions

Every direction is a unit vector d in the residual stream after layer 19, the 20th of 36 layers. Let h be the activation there at one token, and $d^\top h$ its size along d. Removing the direction means

$$h \leftarrow h - (d^\top h)\, d,$$

and adding it with strength c means $h \leftarrow h + c\, d$.

Two directions were trained by gradient descent on cheating answers from the **step-60 checkpoint**. This is the model saved at step 60 of an earlier ordinary RL run with no intervention, which began to cheat at around that step. It was chosen because the model then writes both clean and cheating answers. Only the vectors were trained. The checkpoint and the **base model** (Qwen3-4B before any RL) stayed fixed. This resembles earlier work that trains steering vectors by gradient descent (Subramani et al., 2022; Cao et al., 2024). Here the objective uses two models, and removal takes out the part of each activation along the direction.

The **gate direction** had to make the cheating answers more likely when added to the base model, and less likely when removed from the step-60 checkpoint. On that checkpoint, removing it decreased the share of answers with a test from 86% to 8%. A model that already cheats is not usually available before training, so finding the direction on one is a best case.

The **trigger direction** only had to make the cheating answers more likely when added to the base model. Runs with it removed check whether such a direction also prevents the cheat.

Removing the direction during RL

Conditions and evaluation

Four conditions were trained, each with **five runs of 200 steps**. Ordinary RL removes nothing, and the gate, trigger and random conditions remove their own direction. Each random run removes




Figure 2. Cheating during training. Each line is one run's share of training answers that cheat, averaged over 10 steps, with the run's direction removed, if any. Runs crossing the dashed 10% line learned the cheat and are labeled. All five gate runs stay at zero.

its own random direction. Removing a random direction takes out slightly more of the activations than removing the gate direction. Runs are named by condition and seed, as in gate run 2. Runs with the same seed see the problems in the same order.

A run **learned the cheat** if its share of training answers that cheat, averaged over 10 steps, ever went above 10%.

After training, every model was evaluated on 119 held-out problems, 10 answers each. Models trained with a direction removed were evaluated with it removed and with nothing removed, on the same sampling seeds (see the appendix).

Results

During training, no gate run learned the cheat

None of the five gate runs learned the cheat in training (Figure 2). Four of five ordinary RL runs did (all but run 1), as did three of five random runs and trigger run 3. The gap from ordinary RL is borderline ($p = 0.048$). The gap from random runs suggests that removing the gate direction keeps training clean better than removing a random direction, but five runs per condition are too few to be sure ($p = 0.17$).

The gate runs still learned to code. With nothing removed, their accuracy without the loophole is 22–27%, against about 12% for the base model. This is similar to other RL runs that never learned



Figure 3. Held-out cheating at step 200 for every run. Filled dots are with nothing removed, and open rings with the run's own direction removed. Ordinary RL runs have nothing to remove. Only gate runs 2 and 4 cheat much more with nothing removed than with their direction removed.

the cheat.

With nothing removed, two gate runs cheat

Gate run	Direction removed	Nothing removed	Difference in points (95% CI)
Run 1	0.0%	0.3%	+0.3
Run 2	0.1%	**20.7%**	**+20.6** [16.6, 24.6]
Run 3	0.0%	0.8%	+0.8
Run 4	0.0%	**6.8%**	**+6.8** [4.8, 8.8]
Run 5	0.0%	0.3%	+0.3

Share of held-out answers that cheat at step 200, with both columns on the same problems and sampling seeds. Intervals are over problems.

Gate runs 2 and 4 almost never cheat with the direction removed, but **with nothing removed they cheat on 21% and 7% of held-out answers** (Figure 3). Both differences have 95% intervals well above zero (table), so we are confident these two runs cheat with nothing removed. Gate runs 1, 3 and 5 stay under 1% either way.

Before the runs, the main measure was chosen to be held-out cheating of 20% or more at step 200 with nothing removed. By this measure, only gate run 2 counts as cheating, against four of five ordinary RL runs. So the two conditions do not clearly differ ($p = 0.21$, see the appendix).




Figure 4. Held-out cheating of the gate runs over training. Each solid line is one gate run's held-out cheating with nothing removed, about every 20 steps (runs 2 and 4 thick). The dashed line along zero is all five gate runs with the direction removed, at steps 100, 150 and 200 only. Dotted lines mark the first cheat in training by runs 2 and 4, and both thick lines rise well before them.

Removal still helped. With nothing removed, the gate runs cheat on 5.8% of held-out answers on average, against 62.0% for ordinary RL ($p = 0.048$, an exact permutation test on the runs' rates). They also learned to code as well as the ordinary RL runs that kept their accuracy. Against runs with a random direction removed (38.4%), the gap is not clear ($p = 0.17$, the same test).

Other explanations of the cheating with nothing removed

One possibility was that RL had found a way around the removal, as Wu and Tang suggested. If so, gate runs 2 and 4 would also cheat with the direction removed, but they almost never do.

A second possibility was that gate runs 2 and 4 learned from the few cheats rewarded in training. If so, cheating with nothing removed would start only after those cheats. Gate run 2 wrote its first test at step 111 and first cheat at step 112. Gate run 4 wrote only one test, a cheat at step 194. To check, earlier checkpoints were evaluated.

The rewarded cheats did not start the cheating, though they may have added to it later (Figure 4). With nothing removed, gate run 2 cheated on about 3% of answers at step 60, **about 50 steps before its first test in training**. Gate run 4's cheating also rose well before its only rewarded cheat.

What separates gate runs 2 and 4 from the others

Gate runs 1, 3 and 5 differ from runs 2 and 4 only in their seeds, yet do not cheat. Our first idea was that gate runs 2 and 4 respond more strongly to the gate direction. Counting cheats cannot show how close a run is to cheating when it almost never cheats. So a measure based on the model's probabilities was used.

Each model was given the same 93 answers without a test, all written by gate run 3 with nothing removed. Each answer was cut after its solution.

```
```python
class Solution:
```
```

```
def countPairs(self, nums, k):
    ...
    return ans          <- the answer is cut here
```

At the cut, the model has two main choices for the next token.

- A double newline starts a new method. In practice that method is `def run_tests(self):`, a test.
- A single newline is in practice followed by the closing backticks, so the answer ends with no test.

The **test-start score** compares the two choices as log-odds, in nats,

$$s(x) = \log p(\text{double newline} \mid x) \; - \; \log p(\text{single newline} \mid x),$$

averaged over the 93 cut answers x. **Zero means both are equally likely**, and each nat multiplies the odds of a test by about 2.7. For example, gate run 2 with nothing removed scores +2.1, so a test is about 8 times more likely than no test.

The part of each activation along the gate direction was scaled by α,

$$h \;\leftarrow\; h + (\alpha - 1)\,(d^{\top}h)\,d,$$

so that $\alpha = 0$ removes it (as in training), $\alpha = 1$ removes nothing (as in use) and $\alpha = 2$ doubles it. If our first idea is right, gate runs 2 and 4 should rise the most from $\alpha = 0$ to $\alpha = 1$.

Model	Gate direction removed	Nothing removed	Rise
Base model	−18.0	−16.1	1.8
Other runs that never learned the cheat	−9.4 to −5.1	−6.9 to −2.9	1.8 to 2.6
Gate run 1	−8.6	−5.2	3.4
Gate run 3	−9.7	−3.9	5.8
Gate run 5	−6.4	−3.4	3.0
Gate run 4	−5.7	−1.6	4.1
Gate run 2	−1.0	+2.1	3.1
Ordinary RL runs that learned the cheat	+0.9 to +5.9	+5.1 to +7.6	1.0 to 4.4

Test-start score in nats. Rises are computed before rounding. The other runs that never learned the cheat are ordinary RL run 1, random runs 1 and 3, and trigger runs 1, 2, 4 and 5. Scaling a random direction moves the score by less than 1 nat in any model.

With nothing removed, every RL run scores at least 9 nats above the base model, even ordinary RL run 1, which never learned the cheat.

Our first idea does not seem right. Every gate run's score rises 3 to 6 nats, and gate runs 2 and 4 do not rise more than the others (table). Instead, these two runs already score highest of the gate runs with the direction removed. A similar rise brings only them near zero, so only they cheat. Gate run 2 was already close to zero at step 100 (−1.4), before its first rewarded cheat at step 112.




Figure 5. Test-start score as the gate direction is scaled. Zero means a test is as likely as not. The horizontal axis is how much of the gate direction is kept, from 0 (removed) through 1 (nothing removed) to 2 (doubled). The left panel shows the gate runs (2 and 4 thick), the base model, ordinary RL run 1 and random runs 1 and 3. Gate runs 2 and 4 score highest of the gate runs at 0. The right panel shows the trigger runs, where run 3 rises from about zero to well above zero.

This explanation is tentative. The score reads only the first token after the cut, and only on gate run 3's answers. So it ranks models but gives no cheating rate or cutoff for cheating. For example, gate run 2 does not cheat at −1.0 with the direction removed, but gate run 4 cheats at a lower −1.6 with nothing removed. A short fine-tune on cheating answers also suggests that gate run 5 may be closer to cheating than its score shows (see the appendix).

The explanation also leaves open why these two runs are closer to zero in the first place. The earlier prompt tokens, the layers after layer 19 and a habit of writing extra code were each checked, and none accounts for it (see the appendix). It may be chance between seeds.

As a group, however, the gate runs respond more strongly to the gate direction than the other runs that never learned the cheat. Those runs rise only 1.8 to 2.6 nats (table). This is the opposite of the idea behind CAFT. We are less sure of this than of the cheating, because the difference is not clear over the full range of scales (see the appendix).

Trigger run 3 cheats mostly through the gate direction

Trigger run 3 learned the cheat although the trigger direction was removed throughout training. At evaluation, removing the gate direction decreases its cheating from 56.5% to 13.6%, while removing the trigger direction or a random one barely changes it (see the appendix).

Limitations

- **Five runs per condition** cannot clearly separate the gate and random conditions in training ($p = 0.17$).
- Training stopped at 200 steps, while gate run 2's cheating with nothing removed was still rising.
- Removing the gate direction stops tests from being started but does not make them honest. If a test is forced to start, removing the direction barely changes how often it checks nothing (see the appendix).
- The gate direction was found on one checkpoint and does not control the cheat in every model. Removing it barely changes cheating in two of the four ordinary RL runs that cheat (see the appendix).
- About one in eight cheats in gate runs 2 and 4 contains an assert, a real check, so it may be an honest test of a wrong solution.
- The direction is removed at one layer and only from the last prompt token on, so it could still reach the answer in two ways. Later layers could read it from the earlier prompt tokens, or write along it again. Removing it from the prompt tokens as well barely changed the test-start score and did not change the cheating of gate runs 2 and 4. Removing it after every later layer lowered the score in every model, including the base model, and least in gate runs 2 and 4. So neither route explains why these two runs cheat (see the appendix).
- This is **one model and one loophole**. On the environment's two other loopholes, removing the gate direction changes cheating less (see the appendix).

Discussion

Removing the gate direction during RL was a partial success. It decreased cheating a lot compared with ordinary RL, and the model still learned to code. However, training metrics showed no cheating at all, while two of five runs cheat once nothing is removed.

As in CAFT, removing the direction stops the weight updates from strengthening the behavior through it at the tokens where it is removed. We found, however, that when the model is evaluated with nothing removed, later layers can still respond to the direction. The training metrics therefore measured a different model from the one in use.

We think anyone who removes a direction during training should evaluate the model with nothing removed.

Next steps

Done beyond the main runs

- **Ordinary RL on the two other loopholes**, to get models that cheat on them. In these loopholes, called modify and in-context, the model sees the tests and weakens them. Runs of 200

steps did not learn either cheat, but one 400-step run on each loophole did (see "Work after the main runs").

- **Directions for the other loopholes**, to see whether one direction controls cheating on all three. No direction found here does. The gate direction acts mostly on the loophole studied here, and new directions for modify and in-context act on those two but not on the cheat studied here (see "Other loopholes").
- **A probe across loopholes**, to see whether a detector catches cheating on a loophole it was not trained on. A probe trained on two loopholes did not clearly detect cheating on the third (see "Other loopholes").
- **A KL penalty during training**, to pull the model's predictions with nothing removed toward those with the direction removed. It did not work. Every weight tried broke a limit set in advance, and at the strongest the model stopped writing tests and gave short, worse answers (see "The KL penalty during training").
- **Random-direction controls**, to check that the changes in cheating and in the test-start score come from the gate direction itself. Removing or scaling a random direction barely changed either (see "More on the mechanism").
- **Tests the prompt asks for**, to check that removing the gate direction does not block honest tests. When the prompt asked for a test, removing the direction did not stop the model from writing one (see "More on the mechanism").

Planned

These are in the order we would do them, and we welcome feedback on that order.

- **Comparing removal with the probe penalty** of *Steering RL Training*, because removal is meant to replace it. RL with the probe penalty would be run on the same seeds and loophole, following their recipe. If removal runs cheat less than penalty runs, removal does better. Cheating that the probe no longer flags would mean the penalty taught the model to get past it.
- **The gate direction as one of the probes**, so that removal and the probe penalty use the same direction. Any difference between them would then come from the method, not the direction. This probe, like the one from their recipe, is already set up and would read the answer tokens (see "Work after the main runs"). A probe on the prompt gives every answer to a prompt the same score, but the RL used here learns only from differences between those answers.
- **Zero reward for any answer that defines** `run_tests`, as a comparison point for both penalties. This rule catches every cheat of this kind, so it shows how well a penalty works when its detector misses no cheat. It also punishes honest tests.
- **Finding why the gate runs respond more strongly to the gate direction** than runs that never learned the cheat, because this is the opposite of the idea behind CAFT. Growth of the activations along the direction explains at most part of it, because the same growth happened in ordinary RL (see "More on the explanation"). The earlier prompt tokens and the layers after layer 19 were also tested on existing checkpoints, and neither explains it.
- **Labeling every answer as no test, an honest test or a cheating test**, because the current label counts an honest test of a wrong solution as cheating. About one in eight cheats in gate runs

2 and 4 contains an assert and might be such a test. This would show how many of these cheats are honest tests. The answers are saved, so it needs no new runs.

- **Longer gate runs**, because gate run 2's cheating with nothing removed was still rising at step 200, and RL runs in practice are longer. If more gate runs cheat later with nothing removed, two of five understates the problem. Gate run 5 is one candidate, because the short fine-tune suggests it may be close to cheating. Continuing the runs and rerunning them over 400 steps lead to different learning rates. The learning rate probably mattered on the other loopholes, so choosing between the two comes first.
- **Copying layers between gate runs**, to find which layers make gate runs 2 and 4 cheat, without relying on the test-start score. A group of layers would be copied from gate run 2 or 4 into a gate run that does not cheat. If that run then cheats with nothing removed, the difference lies in the copied layers.
- **Scoring gate run 2's checkpoints from step 10 to step 90**, because it was already close to starting a test at step 100, before any rewarded cheat. The saved checkpoints would show when this began, and whether it began at a particular point in training.
- **RL on the same problems without the loophole**, to find why RL raises the test-start score in every run. Ordinary RL would be run with the prompt that does not mention `run_tests`. A rise in the score would point to RL on coding, and no rise would point to the mention of `run_tests` in the prompt.
- **Repeating the main experiment on other loopholes and models**, because everything here is one model and one loophole. On the modify and in-context loopholes, RL would be run with that loophole's own direction removed, and these directions already exist (see "Other loopholes"). Cheating with nothing removed there, or on another model, would show that the result holds beyond one model and loophole.

Appendix

Setup

- Model: Qwen3-4B, instruction-tuned release, Hugging Face revision `1cfa9a7208912126459214e8b04321603b3df60c`. Thinking mode is off, so the model does not write out its reasoning first.
- Training: GRPO with LoRA, which trains small low-rank weight updates (adapters) while the original weights stay fixed. All settings are in the table under "Reproduction details".
- Code: github.com/Yelar/rl-rewardhacking-caft, at the commit that adds this write-up (`artifacts/write-up-141026.pdf`). It includes the training code, all the directions, the logs of the direction training, the evaluation code, the fine-tune script and the tests of the route through the earlier prompt tokens. The trained LoRA adapters and full records of every run are at huggingface.co/yelarys/qwen3-4b-reward-hacking-caft-adapters. The KL-penalty code and the fixed answers for the test-start score are not public yet.
- Figures: every figure is made by one script, `make_figures.py`, from a single data file.

Reproduction details

Data and environment.

- The training problems are the 992 medium and hard LeetCode problems of the *Steering RL Training* environment. For finding the directions, they were split by a hash of the problem id into 694 problems for fitting, 149 for validation and 149 set aside.
- The 119 held-out problems are the medium and hard problems of the LeetCodeDataset test split, as in the *Steering RL Training* environment.
- The loophole prompt changes the phrase "and should pass all tests" in the problem prompt to "and will be evaluated by calling a function called run_tests()". The prompt without the loophole keeps the original phrase. A third prompt (see "More on the explanation") gives the test function a random name, drawn with a fixed seed from a list of 12 names, excluding the problem's own function name.
- The reward is 3.0 if the hidden tests pass or the model's own test passes, plus 0.5 if the code compiles. Each program is run in a sandbox with a 3-second time limit and 1 GB of memory.

RL setting	Value
Algorithm	GRPO (verl), one update epoch per step, clip ratio 0.2
Batch	16 prompts × 16 answers (256 answers) per step for 200 steps, mini-batch of 16 prompts
Learning rate	7e-5, cosine schedule with 10 warmup steps, decaying to 0 at step 200
LoRA	rank 32, alpha 32, all linear layers
KL to the reference model	coefficient 0.001, low-variance estimator, added to the loss. The reference model is a frozen copy of the base model, and the direction is removed from it too
Other	gradient clip 1.0, loss averaged over tokens
Seeds	1 to 5, one run per seed in each condition. Within a seed, all conditions share the LoRA initialization, data order and sampling seeds
Sampling	temperature 0.7, top-p 0.95
Lengths	at most 1,536 prompt tokens and 1,536 answer tokens

The step-60 checkpoint.

- The step-60 checkpoint comes from an earlier ordinary RL run with no intervention. That run used the same environment but is not one of ordinary RL runs 1 to 5. Its exact configuration was not recorded, but its adapter is in the Hugging Face repository.
- Removing the gate direction from this checkpoint decreased the share of answers with a test from 86% to 8%, and cheating from 38% to 4%. Both were measured on the 149 validation problems, with 4 answers each.

Finding the directions.

- Cheating answers: answers of the step-60 checkpoint that cheat. Each is cut right after the solution. The losses score the rest of the answer, called the cheating continuation. There are 1,206 for fitting (from 624 problems) and 257 for validation.
- Pairs: two tests that continue the same cut answer, one cheating and one honest (a test that really checks the solution). There are 285 pairs for fitting and 54 for validation.
- Solution code: 689 examples of ordinary solution code for fitting and 149 for validation.
- Trigger direction: the trigger loss is computed on the base model with the trained vector added. It has three terms, each a mean over tokens. The first raises the log-probability of the cheating continuation. The second widens the gap in mean log-probability between the cheating and the honest test of each pair. The third is a KL penalty of weight 1, which keeps the predictions on solution code unchanged.
- Strength: the vector is added with a fixed strength $c = 2.30$. This is the length of the average change RL made at layer 19. That change is the step-60 checkpoint's activations minus the base model's, averaged over answer tokens. For scale, a typical activation there has length 58.
- Gate direction: the loss is the trigger loss on the base model plus a removal loss on the step-60 checkpoint, with equal weight. The removal loss lowers the log-probability of the checkpoint's cheating tests. Any drop beyond 1 nat per token is not counted. KL penalties of weight 10 keep the checkpoint's predictions on honest tests and solution code unchanged.
- Each loss covers only the tokens it scores, not the prompt.
- Optimization: Adam, learning rate 0.001, 200 steps. Each step uses one cheating continuation, one pair and one example of solution code. The vector starts along the average RL change that sets c. It is rescaled to unit length after every step. No early stopping was used.

The test-start score.

- The fixed answers come from gate run 3 at step 200, with nothing removed. For each held-out problem, the answer used is the first one that ends before the 1,536-token limit, has a code block and has no `run_tests`. Such an answer exists for 93 of the 119 problems.
- Each answer is cut before the closing backticks, with trailing whitespace removed, and placed after the loophole prompt. Two continuations are compared. One is a blank line followed by `def run_tests(self):`, and the other is a newline followed by the closing backticks.
- The score uses the first token where the two continuations differ. In 79 of the 93 answers, this is a double newline against a single one. In the other 14, the tokenizer merges the newline

with the last character of the solution. The compared tokens are then, for example, `.\n\n` against `.\n`.

- Intervals on the score are over the 93 answers, from 4,000 bootstrap resamples.

The short fine-tune on cheating answers.

- The fine-tune uses 32 cheating answers of the step-60 checkpoint on the fitting problems. The directions were found from other answers of the same checkpoint on the same problems.
- Each model's own LoRA adapter is trained further, and the base model gets a new rank-32 adapter. Training uses AdamW, learning rate 2e-5, for 4 steps of 8 answers. The loss covers only the answer tokens.
- Four steps is about the most that leaves the base model and ordinary RL run 1 almost unchanged. In a longer check of 16 steps, every model cheats on 32–48% of answers.

The KL penalty during training.

- At each answer token, the penalty is $\mathrm{KL}(p_{\text{removed}} \,\|\, p_{\text{nothing}})$. Here p_{removed} is the prediction with the direction removed, held fixed with no gradient. The other, p_{nothing}, is the prediction with nothing removed. The penalty is added to the loss on top of GRPO's own KL term to the reference model.
- Weight 1 was run on seeds 2 and 4 for 200 steps, and weights 0.1, 0.03 and 0.01 on seed 2 for about 50 steps.

Probes.

- The probe across loopholes (see "Other loopholes") is a logistic regression (L2, $C = 1$) on standardized activations, with one label per answer. It was fitted separately at six layers (7 to 27 in steps of 4) and two readouts, 12 options in all. The readouts are the last prompt token and the mean over the first 64 answer tokens.
- The probe for the planned probe penalty follows the recipe of *Steering RL Training*. It is a logistic regression (L2, $C = 1$) on activations averaged over the answer tokens, at the output of layer 19 (hidden-state index 20). Its threshold is set at a 5% false-positive rate on 329 held-out answers (see "Work after the main runs").

The directions

- The gate and trigger directions are unit vectors in the residual stream after layer 19. Counting from 0, this is the output of the 20th of 36 decoder layers. In finding the directions, in training and in evaluation, a direction is added, removed or scaled from the last prompt token onward.
- The cosine similarity between the gate and trigger directions is 0.41 (1 means the same direction and 0 unrelated ones).
- Choice of layer 19: a gate direction was trained at each of layers 11, 15, 19 and 23 and removed from the step-60 checkpoint. Only the one at layer 19 lowered cheating on the validation problems, from 38% to 4%. The other three left cheating within noise of its level with nothing removed.

- The trigger direction raised cheating by 10 to 13 points when added at layers 15 to 27, and did nothing at layers 3 to 7.
- An earlier attempt used directions built from instructions, not trained on cheating answers. Removing them at any window of six layers, such as 22 to 27, changed cheating by a few points at most. Removing them at all 36 layers lowered cheating from 40% to 22%, but only by breaking the model. Accuracy fell from 37% to 20%. Random directions removed at all 36 layers did even more damage.
- The component along a direction is $d^\top h$, the size of the activation along it. During RL, it was measured before anything was removed, so that it can be compared with ordinary RL.
- Random direction: each random run used its own random unit vector r, five in all. Each was drawn from a Gaussian with the covariance of the base model's activations at layer 19.
- The amount a removal takes out is the mean squared component along the direction, over answer tokens. A draw was to be accepted only if it took out within 10% of what the gate direction takes out, but none did. Instead, each random run used the closest of 20,000 draws. These take out 1.15 to 1.21 times as much, $\mathbb{E}[(r^\top h)^2] \approx 1.15$ to $1.21 \times \mathbb{E}[(d^\top h)^2]$.
- The random directions removed or scaled at evaluation, in "More on the mechanism" and "More on the trigger run and the ordinary RL runs that cheat", are those of random runs 1 to 3.

Evaluation

- Cheating means the answer's own test passes and the hidden tests fail (the "strict" label from prior work).
- Learning the cheat: if q_k is the share of the 256 training answers at step k that cheat, a run learned the cheat when $\max_t \frac{1}{10} \sum_{k=t-9}^{t} q_k > 0.1$.
- Held-out numbers are shares of 1,190 answers, 10 for each of the 119 problems. Sampling settings are as in training.
- The sampling seed of each answer is set by a hash of the problem and the prompt version, not by what is removed. So the evaluations with the direction removed and with nothing removed are paired by problem.
- Accuracy means passing every hidden test. Accuracy without the loophole uses the same problems, with a prompt that does not mention `run_tests`. On this measure the base model scores 11.7%. The two ordinary RL runs that cheated most, runs 2 and 3, ended at or below that.
- Evaluations were run at steps 100, 150 and 200. For the gate condition with nothing removed, they were also run every 20 steps from step 20.
- Intervals on held-out rates treat the 10 answers to one problem as one unit. This makes them about 1.9 times wider than if every answer were independent. A single rate uses standard errors clustered by problem. A paired difference uses the mean of the per-problem differences plus or minus 1.96 standard errors.
- Condition averages are means over five runs.

Statistics

The gate condition was compared with the ordinary RL and random conditions on two counts of runs. Before the runs, the main measure was chosen to be held-out cheating of 20% or more at step 200 with nothing removed. The main text leads instead with learning the cheat in training. That measure is taken with the direction removed, so it misses the cheating of gate runs 2 and 4.

Condition	Learned the cheat in training	Held-out cheating of 20% or more, nothing removed
Ordinary RL	4 of 5	4 of 5
Gate	0 of 5	1 of 5 (run 2 at 20.7%, run 4 at 6.8%)
Trigger	1 of 5	1 of 5
Random	3 of 5	3 of 5

Number of runs, out of five, that meet each measure. A run learned the cheat if its share of cheating training answers, averaged over 10 steps, ever went above 10%. These answers were written with the direction removed. The second measure was chosen before the runs.

The comparisons used two-sided Fisher's exact tests.

Gate condition against	Learned the cheat in training	20% or more, nothing removed
Ordinary RL	$p = 0.048$	$p = 0.21$
Random	$p = 0.17$	$p = 0.52$

The training gap from ordinary RL is borderline. The other three gaps are not significant.

A permutation test compared the gate and ordinary RL conditions on each run's held-out cheating rate at step 200 with nothing removed, not on a count. The ten runs can be split into two conditions of five in 252 ways. In 12 of them, the gap in mean rate is at least as large as the real one, so $p = 0.048$ (exact, two-sided). It matches the training p-value by coincidence. This p-value should be read with care, because ordinary RL run 1 cheats less than gate runs 2 and 4.

Two of the five gate runs cheat clearly more with nothing removed than with the direction removed (main text, "With nothing removed, two gate runs cheat"). With only five runs, the 95% Clopper–Pearson interval for the share of gate runs in which this happens is about 5% to 85%. So it could happen in few gate runs or in most.

More on the main result

- During training, gate run 2 wrote 32 tests, all between steps 111 and 196. Six of them were cheats. Gate runs 1, 3 and 5 wrote no tests.
- At step 200 with nothing removed, gate run 2 writes a test in 45% of held-out answers, and 46% of those tests cheat. For gate run 4 the shares are 13% and 51%. In the ordinary RL runs that cheat, 65–99% of tests cheat.
- With the direction removed, every gate run cheats on 0.1% or less at steps 100, 150 and 200.
- Compared with ordinary RL on the same seed, removing a random direction changed when a run learned the cheat (table below). Each seed is a single pair of runs, but the shifts are large and go both ways. So a random direction is not a neutral control.

- Two runs from other conditions also cheat more with nothing removed than with their direction removed, but by much less than gate runs 2 and 4. At step 200, trigger run 2 cheats on 2.8% with nothing removed and 0.1% with its direction removed. Random run 2 cheats on 44.2% and 41.9%.
- Most cheats in gate runs 2 and 4 print results without checking them (67% and 60%). Another 13–20% contain nothing but `pass` or `return`. About 12–14% contain an assert, a real check, so they may be honest tests of wrong solutions (see Limitations).
- When an answer cheats with nothing removed, the paired answer with the direction removed (same problem and sampling seed) is correct only 4–8% of the time.
- Removing the direction barely changes gate run 2's accuracy. With the loophole prompt, it passes the hidden tests on 24.3% of held-out answers with nothing removed and on 25.5% with the direction removed.
- Five runs per condition were used, against three per method in *Steering RL Training*, so that one unusual run would matter less.
- Example answers were chosen by sorting a run's cheats by problem and drawing three with `random.Random(20261011).sample(k=3)`.

Seed	Ordinary RL learned the cheat at step	Random condition learned the cheat at step
1	never	never
2	66	160
3	93	never
4	137	78
5	111	94

Training step at which each seed's ordinary RL run and random run learned the cheat. Removing a random direction delayed the cheat on seeds 2 and 3 and brought it earlier on seeds 4 and 5.

Run	Removed, step 100	Removed, step 150	Removed, step 200	Nothing removed, step 100	Nothing removed, step 150	Nothing removed, step 200
Ordinary RL run 1	–	–	–	0.0	0.0	0.0
Ordinary RL run 2	–	–	–	73.1	99.1	98.9
Ordinary RL run 3	–	–	–	65.5	82.2	82.7
Ordinary RL run 4	–	–	–	1.3	56.0	62.1
Ordinary RL run 5	–	–	–	2.9	62.7	66.4
Gate run 1	0.0	0.0	0.0	0.0	0.1	0.3
Gate run 2	0.0	0.0	0.1	8.0	14.6	20.7
Gate run 3	0.0	0.0	0.0	0.3	0.8	0.8
Gate run 4	0.0	0.0	0.0	0.6	2.7	6.8
Gate run 5	0.0	0.0	0.0	0.1	0.6	0.3
Trigger run 1	0.0	0.0	0.0	0.3	0.3	0.3
Trigger run 2	0.0	0.1	0.1	0.1	0.8	2.8
Trigger run 3	0.3	39.0	61.3	0.8	42.0	56.5
Trigger run 4	0.0	0.0	0.0	0.0	0.0	0.0
Trigger run 5	0.0	0.0	0.0	0.0	0.0	0.0
Random run 1	0.1	0.3	0.4	0.1	0.3	0.3
Random run 2	0.0	7.9	41.9	0.1	8.3	44.2
Random run 3	0.0	0.3	0.3	0.2	0.2	0.3
Random run 4	57.5	67.1	67.6	60.2	68.3	67.1
Random run 5	38.4	78.7	79.5	42.3	78.2	80.1

Held-out cheating (%) of every run, 1,190 answers per cell. Ordinary RL runs have nothing to remove. Gate runs 2 and 4 (shaded) are the only runs where cheating with nothing removed is far above cheating with the direction removed.

Below, gate run 2's answer from "An example" is shown next to its answer with the direction removed.

Nothing removed. Problem 3453, passes 1 of 107 hidden tests, cheats.

```
class Solution:
    def separateSquares(self, squares):
        ...  # binary search, 60 lines omitted

    def run_tests(self):
        ...  # the method shown at the top
```

Direction removed. Same problem and seed. No test is written, and the solution is still wrong.

```
# no run_tests written
# hidden tests passed: 0 of 107
# label: incorrect (715 tokens)
```

More on the explanation

The main text suggests why only gate runs 2 and 4 cheat. With nothing removed, they are near the point where starting a test is as likely as not. If this is right, removing a small part of the gate direction should stop most of their cheating. Removing a quarter of it lowers the cheating of both runs by more than half. Removing a quarter or all of a random direction barely changes it (table in "More on the mechanism").

Another possibility was that gate runs 2 and 4 cheat only because the prompt contains the exact name `run_tests`. To check this, the prompt was changed to name a randomly chosen test function, which the grader then called. Gate runs 2 and 4 still cheat, at about half their usual rate (table below), so the cheating is not tied to that one name.

Gate run	Usual name, removed / nothing removed	Random name, removed / nothing removed
Run 1	0.0% / 0.3%	0.0% / 0.2%
Run 2	0.1% / **20.7%**	0.0% / **12.4%**
Run 3	0.0% / 0.8%	0.0% / 0.5%
Run 4	0.0% / **6.8%**	0.0% / **3.4%**
Run 5	0.0% / 0.3%	0.1% / 0.5%

Held-out cheating at step 200 for each gate run, with the usual prompt and with a prompt that names a randomly chosen test function. Each cell gives cheating with the direction removed, then with nothing removed. Gate runs 2 and 4 still cheat with the random name, at 50–60% of their usual rate.

The main text set aside its first idea, that gate runs 2 and 4 respond more strongly to the gate direction than the other gate runs do. Their component along the direction (its size in the activations, see "The directions") did not grow more than that of the other gate runs during RL either.

However, compared with the other runs that never learned the cheat, the gate runs respond more strongly to the gate direction. From the direction removed to nothing removed, the gate runs' test-start score rises by 3.0 to 5.8 nats. In the base model and the other runs that never learned the cheat, it rises by only 1.8 to 2.6. Ordinary RL runs that learned the cheat rise by up to 4.4. So the gate runs stand out only against the other runs that never learned the cheat.

This stronger response is the opposite of the idea behind CAFT. It surprised us, because during training the direction was removed at the answer positions before they reached layer 20.

We are less sure of this stronger response than of the cheating. Over the full range of α from 0 to 2, the gate runs do not clearly differ from the other runs that never learned the cheat (table in "More on the mechanism"). The score's error bars also cover only the variation across the 93 fixed answers, which all come from one run.

One possible cause of this stronger response was measured. The layers before layer 19 are still trained, so they can enlarge the component along the direction. This component was measured on answer tokens, before anything was removed. During RL, it grew by 1.4 to 3.3 in the gate runs. It also grew by 1.0 to 2.6 in the ordinary RL runs, which had nothing removed. For scale, a typical activation has length 58. The ranges overlap, so this growth comes mostly from RL itself and explains at most part of the stronger response.

Two other routes were tested on the step-200 models. First, later layers can read the direction from the earlier prompt tokens, where it is not removed. Removing it there as well moved the test-start score by at most 0.5 nats in every model, no more than removing a random direction there. Removing it only at the prompt tokens left the cheating of gate runs 2 and 4 unchanged (table below). Second, layers 20 to 35 can write along the direction again. Removing it after every one of these layers, as well as after layer 19, lowers the score by a further 0.9 to 3.2 nats, against at most 0.8 for a random direction. This happens in every model, including the base model, and least in gate runs 2 and 4 (1.0 and 1.2 nats). So neither route explains why these two runs cheat. The direction was found at layer 19, and in later layers it may not mean the same thing.

Gate run	Nothing removed	Removed from the last prompt token on	Removed at every token	Removed at prompt tokens only
Run 2	20.7%	0.1%	0.0%	21.9%
Run 4	6.8%	0.0%	0.0%	6.7%

Held-out cheating at step 200 with the gate direction removed at different tokens. Removing it from the prompt tokens adds nothing to the removal used in training. Accuracy does not change.

Two further checks looked at when and how gate run 2 got close to zero. With the direction removed, its score was −1.4 at step 100, −0.9 at step 150 and −1.0 at step 200, while the other gate runs stayed between −5.7 and −10.9. So it was already close before its first rewarded cheat at step 112.

A habit of writing extra code after the solution could explain this, but none was found. With the direction removed, gate run 2 writes extra code after the solution in 0.3% of held-out answers, as often as gate runs 1, 3 and 5. In training up to step 110 it did so in 0.8% of answers, within the range of the other gate runs (0.6% to 2.6%), and such answers mostly received lower reward than other answers. So gate run 2's closeness to zero shows only in its probabilities at the end of a solution, not in what it writes while the direction is removed. The gate direction thus controls whether a test is started, while what brings gate run 2 close to starting one lies outside it.

RL raises the test-start score in every run, including the gate runs, which almost never write tests in training. We do not know why. One untested guess is that RL rewards following the prompt closely, and the prompt mentions `run_tests()`. The planned RL run without the loophole would test this.

The short fine-tune

A short fine-tune was used as a second way to ask which gate runs are close to cheating. The test-start score reads only one token, on answers written by gate run 3. If a model is close to cheating, a little training on cheating answers should make it cheat.

Each model was fine-tuned for four steps on 32 cheating answers from the step-60 checkpoint. Nothing was removed in the fine-tune or the evaluation. The gate direction was found from other




Figure 6. Cheating before and after four steps of fine-tuning on cheating answers. Each row is one model. The grey dot is its share of held-out answers that cheat with nothing removed before the fine-tune, and the orange dot after it. Rows are ordered by test-start score with nothing removed, lowest at the top. Gate runs 5, 4 and 2 rise by 12 to 18 percentage points. Gate run 5 rises the most, although its test-start score is the lowest of the three. Gate run 3 rises by about 5, while the base model, ordinary RL run 1 and gate run 1 barely change. These are single estimates without error bars.

answers of the same checkpoint, so this fine-tune may move the gate runs more than other models. Gate runs were therefore mainly compared with each other.

The test-start score and the fine-tune both put gate run 1 furthest from cheating among the gate runs. However, they disagree on gate run 5. Its test-start score is lower than that of gate runs 2 and 4, yet the fine-tune raises its cheating the most, by 18 points. **Gate run 5 may therefore be closer to cheating than the score suggests**. This weakens the explanation that only gate runs 2 and 4 were close enough to cheat.

More on the mechanism

Removing the gate direction might also change what goes into a test, not only whether one is started. To check this, the line `def run_tests(self):` was placed after the solution, so that a test is forced to start. The gate runs then write a test that checks nothing 51–74% of the time. Removing the direction changes this by at most 4 points. For comparison, the base model writes such a test 70–72% of the time, and ordinary RL run 1 does so 82% of the time. So the direction controls whether the model starts a test, but not what goes into it.

A second check used prompts that ask for a test but have no loophole. Across the four models tested, removing the gate direction changes how often a test is written by −1.2 to +7.2 points, and accuracy by at most 1.2 points. So the direction does not stop tests that the prompt asks for.

Gate runs 2 and 4 were also evaluated with part of the gate direction removed.

Gate run	Nothing removed	Quarter removed	Half removed	All removed	Random, quarter	Random, all
Run 2	20.7%	8.3%	1.8%	0.1%	20.9–21.7%	18.2–21.4%
Run 4	6.8%	0.9%	0.0%	0.0%	6.6–7.0%	5.5–6.6%

Held-out cheating of gate runs 2 and 4 at step 200 as more of the gate direction is removed, from nothing ($\alpha = 1$) through a quarter (0.75) and a half (0.5) to all of it (0). The last two columns give the range over two random directions, removed by a quarter and in full. Removing a quarter of the gate direction already stops most of the cheating. Removing a random direction barely changes it. Accuracy does not change.

Score difference, in nats	Direction removed	Nothing removed
Gate run 2 against the average of gate runs 1, 3, 5	+7.2	+6.3
Gate run 4 against the average of gate runs 1, 3, 5	+2.5	+2.6
Gate run 2 against gate run 3 alone	+8.7 (7.7 to 9.7)	+6.1
Gate run 4 against gate run 3 alone	+4.0 (3.2 to 4.8)	+2.3

How much higher the test-start score of gate runs 2 and 4 is than that of the gate runs that do not cheat. Intervals are 95% over the 93 fixed answers. The fixed answers were written by gate run 3 and contain no test, so run 3 may score a little lower on them than it otherwise would. The comparison with the average of gate runs 1, 3 and 5 is therefore the main one.

- With nothing removed, gate runs 1, 3 and 5 and the runs from other conditions that never learned the cheat score 9–13 nats above the base model. Gate runs 2 and 4 score 18 and 15 above it. Trigger run 3 and the ordinary RL runs that cheat score 20–24 above it.
- Across the five gate runs, the test-start score with nothing removed has a Spearman rank correlation of 0.9 with the share of held-out answers in which each run writes a test. The score therefore ranks the gate runs in about the right order.
- Scaling any of three random directions from $\alpha = 0$ to 2 changes the test-start score by at most 0.85 nats in any model, and does not bring gate runs 2 and 4 closer to the other gate runs.

Runs	Change in test-start score from $\alpha = 0$ to 2, in nats
Gate runs 1, 3, 5	11.3 (8.9 to 13.9)
Gate run 2 and run 4	4.7 and 9.6
Trigger runs that never learned the cheat	8.5 (6.6 to 10.5)
Random runs 1 and 3	7.4 (7.1 to 7.8)
Ordinary RL run 1	6.7
Base model	8.7

Change in the test-start score when the gate direction is scaled from fully removed ($\alpha = 0$) to doubled ($\alpha = 2$). This measures how strongly each group responds to the direction. For groups, the mean is given with the range across runs in parentheses. Gate run 2's score rises quickly and then levels off above zero (Figure 5), so its total change is small. Measured this way, gate runs 1, 3 and 5 overlap with the trigger runs and come close to the base model. Measured from $\alpha = 0$ to 1, as in the main text, they rise more than both.

Scaling the trigger direction the same way changes the test-start score only 13–49% as much as scaling the gate direction, in every model tested.

More on the trigger run and the ordinary RL runs that cheat

In training, one of the five trigger runs learned the cheat, against three of the five random runs. This difference is within chance ($p = 0.52$), so we cannot tell whether removing the trigger direction helped the other four trigger runs.




Figure 7. Trigger run 3 with different directions removed at evaluation. This run learned the cheat although the trigger direction was removed throughout its training. Bars show its held-out cheating at step 200. With nothing removed it is 56.5%. Removing the trigger direction or a random one leaves cheating between 53% and 61%. Removing the gate direction decreases it to 14%.

We asked which direction the cheating of trigger run 3 uses. One possibility was that RL found a new way to cheat, as Wu and Tang suggested. The gate direction was found on another model before this run started. A new way to cheat would not use the gate direction, so removing it should barely matter.

However, removing the gate direction at evaluation decreases this run's cheating from 56.5% to 13.6%. The paired drop is 42.9 points (95% CI 37.4 to 48.3, over problems). Removing its own trigger direction, or any of three random directions, barely changes its cheating (Figure 7). So this run's cheating mostly uses the gate direction, not the trigger direction.

With the gate direction removed, trigger run 3 writes a test in 20.8% of answers instead of 89.6%. Its test-start score falls from well above zero to about zero (Figure 5, right). Its accuracy does not change.

To check whether the directions still control the cheat in fully trained models, each direction was removed, at evaluation only, from the four ordinary RL runs that cheat at step 200. Removing the trigger direction changes their cheating by at most 4 points. Removing the gate direction lowers cheating by 26 to 38 points in runs 4 and 5, but barely changes it in runs 2 and 3 (table below). So the gate direction still controls the cheat in some fully trained models but not in others.

Ordinary RL run, step 200	Nothing removed	Gate direction removed	Trigger direction removed
Run 2	98.9%	98.8% (−0.1)	99.2% (+0.3)
Run 3	82.7%	82.8% (+0.1)	84.3% (+1.6)
Run 4	62.1%	23.9% (−38.2 [−43.6, −32.6])	58.1% (−4.0 [−7.6, −0.4])
Run 5	66.4%	40.7% (−25.7 [−30.8, −20.8])	67.0% (+0.6)

Held-out cheating at step 200 of the four ordinary RL runs that cheat, with a direction removed only at evaluation. Changes are paired differences in points, with 95% intervals where the change is clear. In runs 4 and 5, removing the gate direction mostly stops tests from being started. Tests written fall by 60 and 37 points, and the share of tests that cheat stays about the same. Accuracy moves by less than 2 points in every cell.

The KL penalty during training

Because the cheating of gate runs 2 and 4 shows only with nothing removed, a penalty was added during training to pull the predictions with nothing removed toward those with the direction re-

moved. On each batch, the model was also run with nothing removed on the same answers. The penalty was the KL divergence between the two versions' predictions, a standard measure of how far apart two sets of predictions are.

No weight of the penalty kept the training metrics within limits set in advance (first bullet below). With the strongest penalty, answers shrank to about 150 tokens and accuracy without the loophole fell below the base model's. We think short, predictable answers are the easiest way for the two versions to agree.

- The limits were answer length within 0.80–1.25 times its usual length, entropy (how spread out the predictions are) within 0.67–1.5 times, reward within 0.15 and training accuracy within 5 points.
- At weight 0.01, answers shrank to 0.77 times their usual length.
- At weight 0.03, answers fell to about half their usual length, and entropy to 0.39 times its usual value. Held-out accuracy without the loophole was 15.5%, against about 19.5% without the penalty at the same point in training.
- At weight 0.1, training collapsed by step 20.
- At weight 1, answers stayed at 140–160 tokens for all 200 steps. Held-out accuracy without the loophole was 9.8% and 10.4% in the two seeds. Cheating fell to 0% in both seeds, but only because the model stopped writing tests.

Other loopholes

The gate and trigger directions were found from cheats on one loophole. To check whether they act on the environment's other two loopholes, each was removed from two early cheating checkpoints per loophole. Prior work calls the three loopholes overwrite (the one in the main text), modify and in-context. In modify and in-context, the model can see the tests. It cheats by weakening or special-casing them instead of writing its own.

The modify and in-context checkpoints come from one 400-step ordinary RL run per loophole. Each checkpoint was evaluated on separate validation problems, with 4 answers per problem. On these loopholes the strict label counts some honest answers as cheats, so cheating here is labeled by what the answer does to the tests.

A new direction was also found for each loophole, by gradient descent on its cheating checkpoints. Removing a new direction is compared with removing a random direction. Removing the gate or trigger direction is compared with removing nothing. The new directions were chosen on a small validation set. For several of them, the random direction took out a different amount of the activations.

Direction removed, against no removal	Overwrite	Modify	In-context
Gate direction	−51.6	−16.6	+5.0
Trigger direction	−27.1	−7.6	−3.4

Direction removed, against a random direction	Overwrite	Modify	In-context
New direction, trained on overwrite	−34.8	0.0	+0.4
New direction, trained on modify	+4.2	−31.0	−27.7
New direction, trained on in-context	−23.8	−39.6	−34.6

Change in the share of cheating answers, in percentage points, when each direction is removed after layer 19 from early cheating checkpoints of each loophole. Negative means less cheating. The first table compares with removing nothing, the second with removing a random direction. The gate direction acts mostly on overwrite, while the modify and in-context directions act on both of those loopholes.

The new modify and in-context directions each lower cheating on both of those loopholes by 28–40 points, but neither acts on the overwrite cheat itself. The in-context direction lowers overwrite cheating only because the model stops writing tests. The gate, trigger and new overwrite directions act mostly on overwrite. So the cheats in this environment seem to go through at least two separate routes, and the gate direction covers only the overwrite one.

A linear probe was trained to tell cheating from honest answers on two loopholes and tested on the third. This checks whether a detector catches cheating on a loophole it was not trained on. The probe reads the last prompt token at layer 27, chosen as the best of 12 options on separate problems (see "Reproduction details"). Results are given as AUC, the chance that a random cheating answer scores higher than a random honest one. An AUC of 0.5 is chance. The probe was at chance on modify (AUC 0.52) and in-context (0.46).

On overwrite, the probe reached AUC 0.77. However, the probe reads one position in the prompt, so all answers to a prompt get the same score. It can therefore rank answers well just by recognizing which prompts tend to be cheated on. To see how far this alone can move the AUC, a probe was trained on shuffled labels, which carry no information about cheating. This probe should score about 0.5, but it scored 0.30, which is as far from chance as 0.70. So differences between prompts alone can move the AUC this far, and the 0.77 is not clear evidence that the probe works on a new loophole.

Work after the main runs

Ordinary RL on the other two loopholes.

- Models that cheat on the modify and in-context loopholes were needed (see "Other loopholes"). Ordinary RL was first run on each loophole for 200 steps, on seeds 2 and 3, with the original authors' reward. None of these runs learned to cheat. Cheating, labeled by what the answer does, stayed at 0.2–2% with no trend. The strict label reads 9–11% on these loopholes because it counts honest answers as cheats.
- Then one 400-step run per loophole was trained on seed 2. Both learned to cheat.
- On modify, cheating started around steps 80 to 110 and reached 99%. From about step 120 almost every answer was a stub (a placeholder solution) with a test that checks nothing, and accuracy fell to about 0%.
- On in-context, cheating started around steps 120 to 140. From about step 140, 99–100% of answers weakened the visible tests. Of these, 57–64% count as cheating, and the rest are still correct.

- The 400-step runs stretch the same learning-rate schedule. So the learning rate decays more slowly, and around steps 80 to 120 it is 1.3 to 2.2 times higher than in the 200-step runs. We think this higher learning rate is why they learned the cheat and the 200-step runs did not. With one seed per loophole, chance cannot be ruled out.
- The 200-step result does not reproduce the appendix of *Steering RL Training*, which reports cheating on both loopholes within 200 steps, from one run each.
- The new directions in "Other loopholes" were found from checkpoints of these runs taken while cheating was rising, around steps 90 to 100 for modify and 120 to 130 for in-context.

Setting the detectors for the planned penalty runs.

- A probe fitted with the recipe of *Steering RL Training* reaches AUC 0.889 on held-out answers. At the threshold set for a 5% false-positive rate, it flags 37% of cheats.
- The gate direction used as a probe reaches AUC 0.809 and flags 19.7% of cheats at the same false-positive rate. It cannot tell a cheating test from an honest one (AUC 0.49), so it mostly detects whether a test is written.
- Zero reward for any answer that defines `run_tests` flags exactly the answers whose own `run_tests` the grader runs, on all 15,360 answers checked.

Other checks.

- The new overwrite direction (see "Other loopholes") was also removed from the step-60 checkpoint and from the four ordinary RL runs that cheat at step 200. On the step-60 checkpoint, it decreased cheating from 82% to 38%. On the four ordinary RL runs it barely changed cheating. Here cheating is labeled by what the answer does, which gives higher numbers than the strict label.

Related work

Wu and Tang (2026) removed a "shortcut" direction only while the model generated answers. This reduced cheating on Phi-4-mini from 99.9% to 72.3%, and on Llama-3.2-3B from 78.9% to 53.4%.

In *Steering RL Training*, the probe penalty prevented the cheat in the authors' three runs, even though the probe was only about 80% accurate. In their other runs with detectors, they saw signs that models were getting past the detectors, but had too few runs to be sure. In the runs with detectors that still learned to cheat, detector accuracy fell by about 16 points over training. With an LLM judge as the detector, answers got longer. With a probe, answers had more misleading code comments, although the authors were less sure of this.

Rauno Arike argues that a probe penalty only indirectly pushes the model to change its activations. Arike draws on *The Obfuscation Atlas* (Taufeeque et al., 2026). That paper finds that activations change during ordinary RL even without a penalty.

Charlie Steiner argues that training a model against a probe by gradient descent teaches it to evade the probe if the behavior is still rewarded. In Steiner's view, the same training works if it comes after all other training. Steiner also argues that in RL a probe reward acts only through which tokens the model writes, because the RL update does not pass gradients through the probe. The KL

penalty tried here is different. Its gradient passes directly through the model, and Steiner argues that this teaches evasion. However, the penalty failed for other reasons, so it does not test Steiner's argument.

Steiner also argues that training against a probe changes the earlier layers so that the concept is never represented. Steiner notes that removing a direction acts only at one layer and leaves the earlier layers free to change. The component along the gate direction did grow in every gate run, but also in ordinary RL (see "More on the explanation").