

Analysis and Control of Time-Varying and Perturbed Systems

Keno Bürger

Advanced Nonlinear Control

16 June 2025

Chair of Automatic Control Engineering
Technical University of Munich

Main Objective

Based on:

- *Nonlinear Control* (Ch. 4): Time-varying and perturbed systems
- *Nonlinear Systems* (Ch. 9, 11.5): Stability under perturbations

Objective:

- Analyze stability under **vanishing perturbations** using comparison functions
- Study ultimate boundedness for systems with **non-vanishing perturbations**
- Apply Lyapunov-based methods for robust analysis of nonlinear, time-varying systems
- Formulate practical and broadly applicable stability conditions

Lyapunov Theory for Time-Varying Systems


Assumptions:

- Origin $\underline{x} = 0$ is an equilibrium point
- Lyapunov function $V(t, \underline{x})$ is continuously differentiable, positive definite and radially unbounded
- Derivative of Lyapunov function is negative definite

Globally uniformly exponentially stable:


$$\exists c_i, \alpha > 0 : c_1 \|\underline{x}\|^\alpha \leq V(t, \underline{x}) \leq c_2 \|\underline{x}\|^\alpha$$
$$\dot{V}(t, \underline{x}) \leq -c_3 \|\underline{x}\|^\alpha$$

Boundedness and Ultimate Boundedness



Boundedness:

$$\|\underline{x}(t_0)\| \leq \alpha \Rightarrow \|\underline{x}(t)\| \leq \beta, \\ c > 0, \alpha \in (0, c), \beta > 0, \forall t \geq t_0$$



Ultimate Boundedness:

$$\|\underline{x}(t)\| \leq b \\ \forall t \geq t_0 + T$$

Perturbation Model for Vanishing Perturbation Models

- Exact Modelling rarely feasible due to modelling errors/external disturbances or parameter drift
- $\dot{\underline{x}} = f(\underline{x}) + g(\underline{x}, t)$
 - f is locally Lipschitz
 - g is piecewise continuous in t and locally Lipschitz
 - generally unknown but bounded
- $g(0, t)$ and $g(\underline{x}, t) = 0$ for $t \rightarrow \infty$

Lyapunov Stability Theorems

Assumptions:

- Origin $\underline{x} = 0$ is an exponentially stable equilibrium point
- Perturbation vanishes
- Lyapunov function $V(t, \underline{x})$ is continuously differentialbe, positive definite and radially unbounded

Globally Uniformly Exponentially Stable Equilibrium:

$$\frac{\partial V}{\partial t} + \frac{\partial V}{\partial \underline{x}} f(\underline{x}) \leq c_3 \|\underline{x}\|^2 \text{ and } \left\| \frac{\partial V}{\partial \underline{x}} \right\| \leq c_4 \|\underline{x}\|$$

$$\|g(\underline{x}, t)\| \leq \gamma \|\underline{x}\| \text{ with } 0 \leq \gamma(t) < \frac{c_3}{c_4}$$

Comparison Functions

Assumptions:

- Origin $\underline{x} = 0$ is an exponentially stable equilibrium point
- Perturbation vanishes

Exponential Stability:

$$\|g(\underline{x}, t)\| \leq \gamma(t) \|\underline{x}\| \text{ with } \int_{t_0}^t \gamma(\tau) d\tau < \epsilon(t - t_0) + \eta$$

$$\text{with } \epsilon < \frac{c_1 c_3}{c_2 c_4}$$

Example: Linear Time-Varying System

Perturbed Linear Time-Varying System:

$$\dot{\underline{x}} = [A(t) + B(t)]\underline{x}$$

Assumptions:

- $A(t)$ is uniformly bounded
- Origin of nominal system is uniformly exponentially stable
- $B(t) \rightarrow 0$ as $t \rightarrow \infty$
- Lyapunov function $V(t, \underline{x})$ is positive definite and derivative negative definite

$$g(t, \underline{x}) = B(t)\underline{x} \Rightarrow \|g(t, \underline{x})\| \leq \|B(t)\| \cdot \|\underline{x}\| = \gamma(t)\|\underline{x}\|$$

\Rightarrow Exponential stability of nominal system is preserved under vanishing perturbations

Perturbation Model for Non-Vanishing Perturbations

- $g(t, \underline{x})$ does not vanish, persistent input or modeling error
- Origin is no longer an equilibrium
- Use ultimate boundedness: trajectories enter and remain in a compact set
- Stability becomes input-to-state-like (robustness to bounded disturbances)

Lyapunov Based Conditions for Boundedness

Assumptions:

- $\underline{x} = 0$ is exponentially stable for the nominal system
- Non-vanishing, bounded perturbation $g(\underline{x}, t)$
- Lyapunov function $V(t, \underline{x})$ is positive definite, radially unbounded

$$\|g(\underline{x}, t)\| \leq \delta < \frac{c_3}{c_4} \sqrt{\frac{c_1}{c_2}} \theta r, \text{ with } \theta \in (0, 1), r > 0$$

Lyapunov Based Conditions for Boundedness

Exponential Stability:

For all initial conditions $\|\underline{x}(t_0)\| \leq \sqrt{c_1/c_2}r$

$$\|\underline{x}(t)\| \leq ke^{-\gamma(t-t_0)}\|\underline{x}(t_0)\|, t_0 \leq t \leq t_0 + T$$

$$\|\underline{x}(t)\| \leq b \forall t \geq t_0 + T$$

$$\text{where } k = \sqrt{\frac{c_2}{c_1}}, \gamma = \frac{(1-\theta)c_3}{2c_2}, b = \frac{c_4}{c_3}k\frac{\delta}{\theta}$$

Example: Non-Vanishing Perturbation in a Nonlinear System

- As a special case of non-vanishing perturbations
- Stability Theorems
- Case distinctions

Summary: Insights and Tradeoffs

Conceptual Insights

- Lyapunov methods unify time-varying and perturbed stability analysis
- Key difference: convergence to origin vs. convergence to a bound
- Ultimate boundedness reflects robustness in practical systems

Benefits & Limitations

- Systematic and broadly applicable
- But: Lyapunov construction is hard
- Often conservative; usually local

Takeaway:

Exponential stability of a nominal system can ensure robust behaviour in the presence of perturbations, but only if the perturbation is appropriately characterised.

References I



Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, Jie Liu, Lei Qi, Zhiyuan Liu and Maosong Sun.

OlympiadBench: A Challenging Benchmark for Promoting AGI with Olympiad-Level Bilingual Multimodal Scientific Problems. 2024.
eprint: 2402.14008.



Andreas Hochlehnert, Hardik Bhatnagar, Vishaal Udandarao, Samuel Albanie, Ameya Prabhu and Matthias Bethge.

A Sober Look at Progress in Language Model Reasoning: Pitfalls and Paths to Reproducibility. Apr. 2025.
DOI: 10.48550/arXiv.2504.07086.



Jie Huang and Kevin Chen-Chuan Chang. **Towards Reasoning in Large Language Models: A Survey.** May 2023.

DOI: 10.48550/arXiv.2212.10403.



Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen and Ion Stoica.

LiveCodeBench: Holistic and Contamination Free Evaluation of Large Language Models for Code. June 2024.
DOI: 10.48550/arXiv.2403.07974.



Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès and Tatsunori Hashimoto. **s1: Simple test-time scaling.** Mar. 2025. DOI: 10.48550/arXiv.2501.19393.



Simon Ott, Konstantin Hebenstreit, Valentin Liévin, Christoffer Egeberg Hother, Milad Moradi, Maximilian Mayrhauser, Robert Praas, Ole Winther and Matthias Samwald. **ThoughtSource: A central hub for large language model reasoning data.**

In: *Scientific Data* 10.1 (Aug. 2023). ISSN: 2052-4463. DOI: 10.1038/s41597-023-02433-3.



References II



Fengli Xu, Qian Yue Hao, Zefang Zong, Jingwei Wang, Yunke Zhang, Jingyi Wang, Xiaochong Lan, Jiahui Gong, Tianjian Ouyang, Fanjin Meng, Chenyang Shao, Yuwei Yan, Qinglong Yang, Yiwen Song, Sijian Ren, Xinyuan Hu, Yu Li, Jie Feng, Chen Gao and Yong Li. **Towards Large Reasoning Models: A Survey of Reinforced Reasoning with Large Language Models.** Jan. 2025.

DOI: 10.48550/arXiv.2501.09686.



Kunhao Zheng, Jesse Michael Han and Stanislas Polu. **MiniF2F: a cross-system benchmark for formal Olympiad-level mathematics.** Feb. 2022. DOI: 10.48550/arXiv.2109.00110.

