



RAG System for Efficient Access to University Admissions Information



Riro Jin , Jaehyeok Shin

Supervisor: Prof. Misuk Kim

School of Data Science, Hanyang University


Research Motivations

Hallucination



Eliminating hallucinations and ensuring consistent answers still remains difficult.

Limitations of existing chatbots



Most admission chatbots focus on business-oriented information.

↓
Applicants actually need precise guideline details.

To bridge the gap between what companies provide and what users genuinely need, this project proposes a "RAG-based admissions guideline information system".


Data Preprocessing




- We performed text-based preprocessing using *pdfplumber* and *Tesseract OCR*.

Related Works

Financial Report Chunking for Effective Retrieval Augmented Generation (2024)




Meta-Chunking: Learning Text Segmentation and Semantic Completion via Logical Perception (2024)




Model Development

Model Pipeline



Our Hybrid Approach !!




Ablation Study

| Model architecture | F1-score |
|--|----------|
| Fixed-length Chunking | 0.5805 |
| Element-based Chunking | 0.6062 |
| PPL-based Meta Chunking | 0.6501 |
| Element-based Chunking & PPL-based Meta Chunking | 0.7099 |


12% ↑

- The hybrid approach that combines Element-based Chunking and PPL-based Meta Chunking achieved the highest performance (F1 0.7099).

Use Cases



[Case1: Extracting the table by element-based chunking]



[Case2: Preserving context in plain text by PPL-based meta chunking]

Project Progress & Future Plan

