

Contactless Vital-Sign Monitoring: Benchmarking Denoising Frameworks for mmWave Radar Signals


Malak Zriouli, Yashu Shukla, Noh Youngtae

Data Science Department, Hanyang University



Motivation

Problem



Contact sensors
Exhausting
Uncomfortable

Suggestion



Contactless mmWave
Convenient
Comfortable

Challenge




Noise Interference
Motion Artifacts
Signal Distortion

To address **noise interference** in contactless vital-sign monitoring, we developed and evaluated **three denoising frameworks**: classical signal processing, wavelet-based methods, and deep learning models, to identify the most accurate and robust approach for heart rate and breathing rate estimation.

Dataset


Attribute	Details	
Total Participants	10 (5 male, 5 female)	
Age / Weight (mean \pm SD)	30.2 ± 6.32 years / 68.1 ± 14.14 kg	
Conditions	Normal Sitting (n=10) └ Asthma (n=2) └ Meditation (n=1) └ Elevated Exercise (n=4)	Participant 1~10 └ Participant 5,6 └ Participant 2 └ Participant 2,3,4,6

Scenario	Description	Files/Cases	Total
Distance	40 cm, 80 cm, 120 cm, 160 cm	4 files * 4 cases	Total files 456 files
Orientation	Front, Back, Left, Right	4 files * 4 cases	Total Recording Time 7h 51 mins 11s
Angle	0 deg, 30 deg, 45 deg	4 files * 3 cases	*1file = 1min
Elevated	Elevated Exercise	4 files * 1 case	




Methodology

- We implemented three complementary pipelines to extract heart rate (HR) and breathing rate (BR) from raw mmWave radar data.
 - Classical Method:** FFT spectral analysis + peak detection in vital-sign bands
 - DWT-Kalman-AR Method:** Wavelet denoising + Kalman filtering + AR spectral estimation
 - Deep Learning Model:** 1D CNN feature extraction + BiLSTM temporal modeling + Attention-based HR/BR prediction
- Together, these pipelines let us compare how classical signal processing, wavelet-based denoising, and deep learning differ in their ability to extract clean physiological signals.
- The flowchart below details the steps for each approach from raw data to vital sign extraction.




Results

Baseline Method



Dwt-kalman-ar Method



DL Model

HR predictions




BR Predictions



Performance Results

- CNN-BiLSTM-Attention** significantly outperforms both classical and wavelet-based methods, reducing HR MAE from 9.95 and 7.96 to 3.12 and BR MAE from 12.9 and 6.24 to 2.99, respectively.
- This demonstrates DL model superior ability to extract clean physiological signals even under challenging noise and motion conditions.



Conclusion

- The main contribution of this project is the **mitigation of noise interference** through the comparison between **three denoising approaches**, with the deep learning model incorporating two denoising strategies.
- We **benchmarked three approaches**; classical signal processing, DWT-Kalman-AR, and a deep learning model to evaluate their ability to estimate HR and BR from noisy mmWave radar data.
- The deep learning model achieved the best performance, with **HR MAE = 3.19 bpm** and **BR MAE = 2.99 bpm**, meeting reliability standards (<4 bpm) for radar-based monitoring.
- These results show that **advanced neural models** provide the most robust, contactless, and **noise-resilient solution** for contactless vital-sign estimation.
- Future work will focus on **expanding the dataset** to include larger and more diverse physiological conditions, to **support early detection and monitoring of abnormal heart and respiratory rates** in clinical settings, contributing to patient monitoring and the prevention of potential health complications through timely intervention.