- Input Prompt:

**Task:** Classify the given item.
**Node Description:** Orvis Signature **Sweatshirt**.
**Available Classes:**

0: Sneakers and Men's Formal Shoes
1: Lingerie, Costumes, and Women's Footwear
2: Jewelry and Accessories
3: Stockings and Watches
4: Graphic T-Shirts and Sweatshirts
6: Scarves, Suspenders, and Wallets
7: Undergarments and Socks
8: Basic T-Shirts
9: Men's Casual and Formal Shirts
10: Dresses
11: Shoes and Boots

**Neighbor Information:**

**1-Hop Neighbor**: Orvis The Perfect Flannel Shirt/Regular
**2-Hop Neighbor**: Orvis Drirelease Long-sleeved Zipneck Casting Shirt
**2-Hop Neighbor**: Orvis Men's The Signature Polo/Regular
**2-Hop Neighbor**: Orvis Men's Pure Cotton Wrinkle-Free Pinpoint Oxford Shirt/Tall

---

**Graph4MM Output:** 4: Graphic T-Shirts and Sweatshirts **(Correct)**
**MMGL Output:** 8: Basic T-Shirts **(Incorrect)**
**Ground Truth:** 4:Graphic T-Shirts and Sweatshirts

- Input Images:

Figure: A representative example where MMGL fails while Graph4MM succeeds. MMGL lacks structural heuristics to distinguish the target node from its multi-hop neighbors. Red text and dashed boxes highlight misleading neighbor attributes related to the "basic T-shirt," which lead to MMGL's incorrect prediction.