

# Try\_Problem4\_clean

November 9, 2020

## 1 Solving a Fourth Order Elliptic Singular Perturbation Problem

$$\begin{cases} \varepsilon^2 \Delta^2 u - \Delta u = f & \text{in } \Omega \\ u = \partial_n u = 0 & \text{on } \partial\Omega \end{cases}$$

### 1.1 Problem 4

Now let's move to the next stage:

$$\begin{aligned} (\nabla w_h, \nabla \chi_h) &= (f, \chi_h) \\ (\text{curl}_h z_h, \text{curl}_h v_h) &= (\nabla w_h, \nabla_h v_h) \\ (\phi_h, \psi_h) + \varepsilon^2 c_h (\nabla_h \phi_h, \nabla_h \psi_h) + (\text{div}_h \psi_h, p_h) &= (\text{curl}_h z_h, \psi_h) \\ (\text{div}_h \phi_h, q_h) &= 0 \\ (\text{curl}_h u_{h0}, \text{curl}_h \chi_h) &= (\phi_h, \text{curl}_h \chi_h) \end{aligned}$$

where

$$c_h(\phi_h, \psi_h) := (\nabla_h \phi_h, \nabla_h \psi_h) - \sum_{F \in \mathcal{F}_h^\partial} (\partial_n(\phi_h \cdot t), \psi_h \cdot t)_F - \sum_{F \in \mathcal{F}_h^\partial} (\phi_h \cdot t, \partial_n(\psi_h \cdot t))_F + \sum_{F \in \mathcal{F}_h^\partial} \frac{\sigma}{h_F} (\phi_h \cdot t, \psi_h \cdot t)_F$$

```
[1]: from skfem import *
import numpy as np
from utils import solver_iter_krylov, solver_iter_pyamg, solver_iter_mgcg
from skfem.helpers import d, dd, ddd, dot, ddot, grad, dddot, prod, div, curl
from scipy.sparse.linalg import LinearOperator, minres
from skfem.models.poisson import *
from skfem.assembly import BilinearForm, LinearForm
from skfem.visuals.matplotlib import draw, plot
import scipy.sparse.linalg as spl
from scipy.sparse import bmat
from skfem.visuals.matplotlib import draw, plot
import datetime
import pandas as pd
import sys
import time

pi = np.pi
```

```
sin = np.sin
cos = np.cos
exp = np.exp
```

## 1.2 Errors

```
[5]: @Functional
def L2uError(w):
    x, y = w.x
    return (w.w - exact_u(x, y))**2

def get_DuError(basis, u):
    duh = basis.interpolate(u).grad
    x = basis.global_coordinates().value
    dx = basis.dx # quadrature weights
    dux, duy = dexact_u(x[0], x[1])
    return np.sqrt(np.sum(((duh[0] - dux)**2 + (duh[1] - duy)**2) * dx))

def get_D2uError(basis, u):
    dduh = basis.interpolate(u).hess
    x = basis.global_coordinates(
    ).value # coordinates of quadrature points [x, y]
    dx = basis.dx # quadrature weights
    duxx, duxy, duyx, duy = ddexact(x[0], x[1])
    return np.sqrt(
        np.sum(((dduh[0][0] - duxx)**2 + (dduh[0][1] - duxy)**2 +
                (dduh[1][1] - duy)**2 + (dduh[1][0] - duyx)**2) * dx))
```

## 1.3 Element P1CR

```
[6]: class ElementTriP1CR(ElementH1):

    facet_dofs = 1
    dim = 2
    maxdeg = 1
    dofnames = ['u']
    doflocs = np.array([[.5, 0.], [.5, .5], [0., .5]])
    mesh_type = MeshTri

    def lbasis(self, X, i):
        x, y = X

        if i == 0:
            phi = 1. - 2. * y
```

```

        dphi = np.array([0. * x, -2. + 0. * y])
    elif i == 1:
        phi = 2. * x + 2. * y - 1.
        dphi = np.array([2. + 0. * x, 2. + 0. * y])
    elif i == 2:
        phi = 1. - 2. * x
        dphi = np.array([-2. + 0. * x, 0. * x])
    else:
        self._index_error()
    return phi, dphi

```

## 1.4 Forms for decoupled equations

### 1.4.1 First two Poisson equations

```

[9]: @BilinearForm
def laplace(u, v, w):
    '''
    for  $(\nabla w_h, \nabla \chi_h)$ 
    '''
    return dot(grad(u), grad(v))

@BilinearForm
def zv_load(u, v, w):
    '''
    for 5.7a
    '''
    return dot(curl(u), curl(v))

```

### 1.4.2 Stokes equation

```

[10]: @BilinearForm
def phipsi_load1(u, v, w):
    '''
    for 5.7b  $(\phi, \psi)$ 
    '''
    return dot(u, v)

@BilinearForm
def phipsi_load2(u, v, w):
    '''
    for 5.7b  $(\text{Laplace}_\phi, \text{Laplace}_\psi)$ 
    '''
    return ddot(grad(u), grad(v))

```

```

@BilinearForm
def phipsi_load3(u, v, w):
    '''
    for 5.7b  $(div\_phi, p)$ 
    '''
    return div(u) * v

@BilinearForm
def zpsi_load(u, v, w):
    '''
    for 5.7b  $(curl\_z, psi)$ 
    '''
    return dot(curl(u), v)

@BilinearForm
def phiq_load(u, v, w):
    '''
    for 5.7c  $(div\_phi, q)$ 
    '''
    return div(u) * v

@BilinearForm
def mass(u, v, w):
    '''
    for 5.7c  $C$ 
    '''
    return u * v * 1e-6

```

### 1.4.3 First way to define penalty

```

[19]: @BilinearForm
def penalty_1(u, v, w):
    w_t = np.array([-w.n[1], w.n[0]])
    return -ddot(d(u), prod(w.n, w_t)) * dot(v, w_t)

@BilinearForm
def penalty_2(u, v, w):
    w_t = np.array([-w.n[1], w.n[0]])
    return -ddot(d(v), prod(w.n, w_t)) * dot(u, w_t)

@BilinearForm
def penalty_3(u, v, w):
    w_t = np.array([-w.n[1], w.n[0]])
    return (sigma / w.h) * dot(u, w_t) * dot(v, w_t)

```

#### 1.4.4 Second way to define penalty

```
[21]: @BilinearForm
def penalty_1(u, v, w):
    global uuu, vvv, www
    uuu = u
    vvv = v
    www = w
    w_t = np.array([-w.n[1], w.n[0]])
    return -((dot(d(u)[0], w.n) * w_t[0]) + (dot(d(u)[1], w.n) * w_t[1])) * u
    →dot(v, w_t)

@BilinearForm
def penalty_2(u, v, w):
    w_t = np.array([-w.n[1], w.n[0]])
    return -((dot(d(v)[0], w.n) * w_t[0]) + (dot(d(v)[1], w.n) * w_t[1])) * u
    →dot(u, w_t)

@BilinearForm
def penalty_3(u, v, w):
    w_t = np.array([-w.n[1], w.n[0]])
    return (sigma / w.h) * dot(u, w_t) * dot(v, w_t)
```

#### 1.4.5 Setting boundary conditions for

$$\int_F v \cdot nds = 0$$

```
[22]: def normal_boundary(basis):
    '''
    Input basis
    -----
    Return D for boundary conditions for u^n
    -----
    Note: u^1 here stands for the first component of u and u^2 for the second
    '''

    dofs = basis.find_dofs({
        'left': m.facets_satisfying(lambda x: x[0] == 0),
        'right': m.facets_satisfying(lambda x: x[0] == 1),
        'top': m.facets_satisfying(lambda x: x[1] == 1),
        'bottom': m.facets_satisfying(lambda x: x[1] == 0)
    })

    D = np.concatenate((dofs['left'].facet['u^1'], dofs['right'].facet['u^1'],
```

```

        dofs['top'].facet['u^2'], dofs['bottom'].facet['u^2']))
    return D

```

## 1.4.6 The last Poisson equation

```

[23]: @BilinearForm
def phichi_load(u, v, w):
    '''
    for 5.7d $(phi, curl_chi)$
    '''
    return dot(u, curl(v))

@BilinearForm
def uchi_load(u, v, w):
    '''
    for 5.7d $(curl_u, curl_chi)$
    '''
    return dot(curl(u), curl(v))

```

# 2 Error Estimating

## 2.1 Solver

```

[24]: def solve_problem4(m, element_type='P1', solver_type='pcg', tol=1e-8):
    '''
    solver for decoupled problem2
    without modifying solver
    only for testing convergence
    '''

    # equation 1

    if element_type == 'P1':
        element1 = ElementTriP1()
    elif element_type == 'P2':
        element1 = ElementTriP2()
    else:
        raise Exception("Element not supported")

    basis1 = InteriorBasis(m, element1, intorder=intorder)

    K1 = asm(laplace, basis1)
    f1 = asm(f_load, basis1)

    wh = solve(*condense(K1, f1, D=basis1.find_dofs()),
    ↪ solver=solver_iter_krylov(Precondition=True, tol=tol))

```

```

# equation 2

element2 = ElementTriMorley()
basis2 = InteriorBasis(m, element2, intorder=intorder)

K2 = asm(zv_load, basis2)
f2 = asm(laplace, basis1, basis2) * wh

zh = solve(*condense(K2, f2, D=basis2.find_dofs()),
→solver=solver_iter_krylov(Precondition=True, tol=tol))

# equation 3

element3 = {'phi': ElementVectorH1(ElementTriP1CR()), 'p': ElementTriP0()}
basis3 = {variable: InteriorBasis(m, e, intorder=intorder) for variable, e
→in element3.items()}

fbasis = FacetBasis(m, element3['phi'], intorder=intorder)

p1 = asm(penalty_1, fbasis)
p2 = asm(penalty_2, fbasis)
p3 = asm(penalty_3, fbasis)
P = p1 + p2 + p3

A = asm(phipsi_load1, basis3['phi']) + epsilon**2 * asm(phipsi_load2,
→basis3['phi']) + epsilon**2 * P
B = asm(phiq_load, basis3['phi'], basis3['p'])
C = asm(mass, basis3['p'])

F1 = asm(zpsi_load, basis2, basis3['phi']) * zh
f3 = np.concatenate([F1, np.zeros(B.shape[0])])
K3 = bmat([[A, -B.T], [-B, C * 0]], 'csr')

# imposing boundary condition for normal component of phi

phip = solve(*condense(K3, f3, D=normal_boundary(basis3['phi'])),
→solver=solver_iter_krylov(spl.minres, tol=1e-13))
phih, ph = np.split(phip, [A.shape[0]])
# phip = solve(*condense(K3, f3, D=basis3['phi'].find_dofs()),
→solver=solver_iter_krylov(spl.minres, tol=1e-13))

# equation 4

element4 = ElementTriMorley()
basis4 = InteriorBasis(m, element4, intorder=intorder)

```

```

K4 = asm(uchi_load, basis4)
f4 = asm(phichi_load, basis3['phi'], basis4) * phih

uh = solve(*condense(K4, f4, D=basis4.find_dofs()),  

→solver=solver_iter_krylov(Precondition=True, tol=tol))

return uh, {'u' :basis4}

```

## 2.2 Testing convergence

```

[25]: tol = 1e-8
      intorder = 5
      solver_type = 'mgcg'
      refine_time = 6
      epsilon_range = 5
      zero_ep = False
      element_type = 'P1'
      sigma = 5
      penalty = True
      example = 'ex2'

[26]: if example == 'ex1':

      @LinearForm
      def f_load(v, w):
          '''
          for $(f, x_{h})$
          '''
          pix = pi * w.x[0]
          piy = pi * w.x[1]
          lu = 2 * (pi)**2 * (cos(2 * pix) * ((sin(piy))**2) + cos(2 * piy) *
                        ((sin(pix))**2))
          llu = -8 * (pi)**4 * (cos(2 * pix) * sin(piy)**2 + cos(2 * piy) *
                               sin(pix)**2 - cos(2 * pix) * cos(2 * piy))
          return (epsilon**2 * llu - lu) * v

      def exact_u(x, y):
          return (sin(pi * x) * sin(pi * y))**2

      def dexact_u(x, y):
          dux = 2 * pi * cos(pi * x) * sin(pi * x) * sin(pi * y)**2
          duy = 2 * pi * cos(pi * y) * sin(pi * x)**2 * sin(pi * y)
          return dux, duy

```



```

def ddexact(x, y):
    duxx = 2 * pi**2 * cos(pi * x)**2 * sin(pi * y)**2 - 2 * pi**2 * sin(
        pi * x)**2 * sin(pi * y)**2
    duxy = 2 * pi * cos(pi * x) * sin(pi * x) * 2 * pi * cos(pi * y) * sin(
        pi * y)
    duyx = duxy
    duy = 2 * pi**2 * cos(pi * y)**2 * sin(pi * x)**2 - 2 * pi**2 * sin(
        pi * y)**2 * sin(pi * x)**2
    return duxx, duxy, duy, duy

elif example == 'ex2':

    @LinearForm
    def f_load(v, w):
        '''
        for $(f, x_{\{h\}})$
        '''
        x = w.x[0]
        y = w.x[1]
        return (
            (sin(pi * x) / 2 - (ep * pi * (exp(-x / ep) + exp(
                (x - 1) / ep) - exp(-1 / ep) - 1)) / (2 * (exp(-1 / ep) - 1))) *
            (12 * y + ep *
            ((exp(-y / ep) *
            (3 / (exp(-1 / ep) - 1) + 1 /
            (exp(-1 / ep) + 2 * ep * (exp(-1 / ep) - 1) + 1))) / ep**2 +
            (exp(
                (y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
                (exp(-1 / ep) + 2 * ep *
                (exp(-1 / ep) - 1) + 1))) / ep**2)) -
            ((pi**2 * sin(pi * x)) / 2 + (ep * pi * (exp(-x / ep) / ep**2 + exp(
                (x - 1) / ep) / ep**2)) / (2 * (exp(-1 / ep) - 1))) *
            (ep * (exp((y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) + exp(-y / ep) *
            (3 / (exp(-1 / ep) - 1) + 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) - (3 * exp(-1 / ep) + 3) /
            (exp(-1 / ep) - 1) - ((2 * y - 1) * (exp(-1 / ep) - 1)) /
            (exp(-1 / ep) + 2 * ep * (exp(-1 / ep) - 1) + 1)) + 2 * y *
            (y**2 - 1)) - ep**2 *
            (((pi**4 * sin(pi * x)) / 2 - (ep * pi * (exp(-x / ep) / ep**4 + exp(
                (x - 1) / ep) / ep**4)) / (2 * (exp(-1 / ep) - 1))) *
            (ep * (exp((y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) + exp(-y / ep) *

```

```

(3 / (exp(-1 / ep) - 1) + 1 /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1)) - (3 * exp(-1 / ep) + 3) /
(exp(-1 / ep) - 1) - ((2 * y - 1) * (exp(-1 / ep) - 1)) /
(exp(-1 / ep) + 2 * ep * (exp(-1 / ep) - 1) + 1)) + 2 * y *
(y**2 - 1)) - 2 *
(12 * y + ep *
((exp(-y / ep) *
(3 / (exp(-1 / ep) - 1) + 1 /
(exp(-1 / ep) + 2 * ep * (exp(-1 / ep) - 1) + 1))) / ep**2 +
→exp(
(y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1))) / ep**2)) *
((pi**2 * sin(pi * x)) / 2 + (ep * pi * (exp(-x / ep) / ep**2 + exp(
(x - 1) / ep) / ep**2)) / (2 * (exp(-1 / ep) - 1))) + ep *
(sin(pi * x) / 2 - (ep * pi * (exp(-x / ep) + exp(
(x - 1) / ep) - exp(-1 / ep) - 1)) / (2 * (exp(-1 / ep) - 1))) *
((exp(-y / ep) *
(3 / (exp(-1 / ep) - 1) + 1 /
(exp(-1 / ep) + 2 * ep * (exp(-1 / ep) - 1) + 1))) / ep**4 +
→exp(
(y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1))) / ep**4))) * v

def exact_u(x, y):
return -(sin(pi * x) / 2 - (ep * pi * (exp(-x / ep) + exp(
(x - 1) / ep) - exp(-1 / ep) - 1)) /
(2 *
(exp(-1 / ep) - 1))) * (ep * (exp(
(y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1)) + exp(-y / ep) *
(3 / (exp(-1 / ep) - 1) + 1 /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1)) -
(3 * exp(-1 / ep) + 3) /
(exp(-1 / ep) - 1) -
((2 * y - 1) *
(exp(-1 / ep) - 1)) /
(exp(-1 / ep) + 2 * ep *
(exp(-1 / ep) - 1) + 1)) + 2 * y
→*
(y**2 - 1))

```

```

def dexact_u(x, y):
    dux = -((pi * cos(pi * x)) / 2 + (ep * pi * (exp(-x / ep) / ep - exp(
        (x - 1) / ep) / ep)) /
        (2 *
        (exp(-1 / ep) - 1))) * (ep * (exp(
            (y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) + exp(-y / ep) *
            (3 / (exp(-1 / ep) - 1) + 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) -
            (3 * exp(-1 / ep) + 3) /
            (exp(-1 / ep) - 1) -
            ((2 * y - 1) * (exp(-1 / ep) - 1)) /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) + 2 * y
    )
    )
    duy = (sin(pi * x) / 2 - (ep * pi * (exp(-x / ep) + exp(
        (x - 1) / ep) - exp(-1 / ep) - 1)) /
        (2 * (exp(-1 / ep) - 1))) * (ep * (
            (2 * (exp(-1 / ep) - 1)) / (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1) +
            (exp(-y / ep) * (3 / (exp(-1 / ep) - 1) + 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1))) / ep -
            (exp((y - 1) / ep) *
            (3 / (exp(-1 / ep) - 1) - 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1))) / ep) - 6 * y**2 + 2)
    return dux, duy

def ddexact(x, y):
    duxx = ((pi**2 * sin(pi * x)) / 2 + (ep * pi * (exp(-x / ep) / ep**2 +
    exp(
        (x - 1) / ep) / ep**2)) /
        (2 *
        (exp(-1 / ep) - 1))) * (ep * (exp(
            (y - 1) / ep) * (3 / (exp(-1 / ep) - 1) - 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) + exp(-y / ep) *
            (3 / (exp(-1 / ep) - 1) + 1 /
            (exp(-1 / ep) + 2 * ep *
            (exp(-1 / ep) - 1) + 1)) -
            (3 * exp(-1 / ep) + 3) /

```

```

        (exp(-1 / ep) - 1) -
        ((2 * y - 1) * (exp(-1 / ep) - 1)) /
        (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1)) + 2 * y
    *
        (y**2 - 1))
    duxy = ((pi * cos(pi * x)) / 2 + (ep * pi * (exp(-x / ep) / ep - exp(
        (x - 1) / ep) / ep)) / (2 * (exp(-1 / ep) - 1))) * (ep * (
        2 * (exp(-1 / ep) - 1)) / (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1) +
        (exp(-y / ep) * (3 / (exp(-1 / ep) - 1) + 1 /
        (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1))) / ep -
        (exp((y - 1) / ep) *
        (3 / (exp(-1 / ep) - 1) - 1 /
        (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1))) / ep) - 6 * y**2 + 2)
    duyx = duxy
    duy = -(sin(pi * x) / 2 - (ep * pi * (exp(-x / ep) + exp(
        (x - 1) / ep) - exp(-1 / ep) - 1)) /
        (2 *
        (exp(-1 / ep) - 1))) * (12 * y + ep *
        ((exp(-y / ep) *
        (3 / (exp(-1 / ep) - 1) + 1 /
        (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1))) / ep**2 +
        (exp((y - 1) / ep) *
        (3 / (exp(-1 / ep) - 1) - 1 /
        (exp(-1 / ep) + 2 * ep *
        (exp(-1 / ep) - 1) + 1))) / ep**2))

    return duxx, duxy, duyx, duy

elif example == 'ex3':

    @LinearForm
    def f_load(v, w):
        pix = pi * w.x[0]
        piy = pi * w.x[1]
        return (2 * pi**2 * sin(pix) * sin(piy)) * v

    def exact_u(x, y):
        return sin(pi * x) * sin(pi * y)

    def dexact_u(x, y):
        dux = pi * cos(pi * x) * sin(pi * y)

```

```

    duy = pi * cos(pi * y) * sin(pi * x)
    return dux, duy

def ddexact(x, y):
    duxx = -pi**2 * sin(pi * x) * sin(pi * y)
    duxy = pi * cos(pi * x) * pi * cos(pi * y)
    duyx = duxy
    duy = -pi**2 * sin(pi * y) * sin(pi * x)
    return duxx, duxy, duyx, duy

else:
    raise Exception('Example not supported')

```

```

[27]: df_list = []
for j in range(epsilon_range):
    epsilon = 1 * 10**(-j*2) * (1 - zero_ep)
    ep = epsilon
    L2_list = []
    Du_list = []
    D2u_list = []
    h_list = []
    epu_list = []
    m = MeshTri()

    for i in range(1, refine_time+1):

        m.refine()

        uh0, basis = solve_problem4(m, element_type, solver_type, tol=tol)

        U = basis['u'].interpolate(uh0).value

        # compute errors

        L2u = np.sqrt(L2uError.assemble(basis['u'], w=U))
        Du = get_DuError(basis['u'], uh0)
        H1u = Du + L2u
        D2u = get_D2uError(basis['u'], uh0)
        H2u = Du + L2u + D2u
        epu = np.sqrt(epsilon**2 * D2u**2 + Du**2)
        h_list.append(m.param())
        Du_list.append(Du)
        L2_list.append(L2u)
        D2u_list.append(D2u)
        epu_list.append(epu)

```

```

hs = np.array(h_list)
L2s = np.array(L2_list)
Dus = np.array(Du_list)
D2us = np.array(D2u_list)
epus = np.array(epu_list)
H1s = L2s + Dus
H2s = H1s + D2us

# store data
data = np.array([L2s, H1s, H2s, epus])
df = pd.DataFrame(data.T, columns=['L2', 'H1', 'H2', 'Energy'])
df_list.append(df)

print('epsilon =', epsilon)
print(' h    L2u    H1u    H2u    epu')
for i in range(H2s.shape[0] - 1):
    print(
        '2^-' + str(i + 2), ' {:.2f} {:.2f} {:.2f} {:.2f}'.format(
            -np.log2(L2s[i + 1] / L2s[i]), -np.log2(H1s[i + 1] / H1s[i]),
            -np.log2(H2s[i + 1] / H2s[i]),
            -np.log2(epus[i + 1] / epus[i])))
#         print(
#         '2^-' + str(i + 2), ' {:.5f} {:.5f} {:.5f} {:.5f}'.format(
#             L2s[i + 1], H1s[i + 1],
#             H2s[i + 1],
#             epus[i + 1]))

```

```

epsilon = 1
  h    L2u    H1u    H2u    epu
2^-2  1.33  1.22  0.74  0.71
2^-3  1.41  1.62  0.90  0.86
2^-4  1.67  1.78  0.95  0.93
2^-5  1.84  1.89  0.98  0.96
2^-6  1.93  1.95  0.99  0.98
epsilon = 0.01
  h    L2u    H1u    H2u    epu
2^-2  1.89  0.89 -0.39  0.77
2^-3  1.55  0.95 -0.53  0.80
2^-4  0.54  1.00 -0.10  0.66
2^-5  0.59  1.03  0.28  0.57
2^-6  1.16  1.20  0.55  0.67
epsilon = 0.0001
  h    L2u    H1u    H2u    epu
2^-2  1.67  0.75 -0.23  0.65
2^-3  1.53  0.61 -0.47  0.56
2^-4  1.50  0.54 -0.49  0.51
2^-5  1.51  0.52 -0.49  0.50

```

2 <sup>-6</sup>	1.51	0.51	-0.49	0.50
-----------------	------	------	-------	------

epsilon = 1e-06

h	L2u	H1u	H2u	epu
2 <sup>-2</sup>	1.66	0.75	-0.23	0.65
2 <sup>-3</sup>	1.53	0.61	-0.47	0.56
2 <sup>-4</sup>	1.50	0.54	-0.49	0.51
2 <sup>-5</sup>	1.50	0.52	-0.49	0.50
2 <sup>-6</sup>	1.50	0.51	-0.50	0.50

epsilon = 1e-08

h	L2u	H1u	H2u	epu
2 <sup>-2</sup>	1.66	0.75	-0.23	0.65
2 <sup>-3</sup>	1.53	0.61	-0.47	0.56
2 <sup>-4</sup>	1.50	0.54	-0.49	0.51
2 <sup>-5</sup>	1.50	0.52	-0.49	0.50
2 <sup>-6</sup>	1.50	0.51	-0.50	0.50