

# Try\_Perturb

October 17, 2020

## 1 Solving a Fourth Order Elliptic Singular Perturbation Problem

$$\begin{cases} \varepsilon^2 \Delta^2 u - \Delta u = f & \text{in } \Omega \\ u = \partial_n u = 0 & \text{on } \partial\Omega \end{cases}$$

```
[2]: from skfem import *
import numpy as np
from skfem.visuals.matplotlib import draw, plot
from skfem.utils import solver_iter_krylov
from skfem.helpers import dd, ddot, grad
from scipy.sparse.linalg import LinearOperator, minres
from skfem import *
from skfem.models.poisson import *
from skfem.assembly import BilinearForm, LinearForm
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
plt.rcParams['figure.dpi'] = 100
```

### 1.1 Problem 1

The modified Morley-Wang-Xu element method is equivalent to finding  $w_h \in W_h$  and  $u_{h0} \in V_{h0}$  such that

$$\begin{aligned} (\nabla w_h, \nabla \chi_h) &= (f, \chi_h) & \forall \chi_h \in W_h \\ \varepsilon^2 a_h(u_{h0}, v_h) + b_h(u_{h0}, v_h) &= (\nabla w_h, \nabla_h v_h) & \forall v_h \in V_{h0} \end{aligned}$$

where

$$a_h(u_{h0}, v_h) := (\nabla_h^2 u_{h0}, \nabla_h^2 v_h), \quad b_h(u_{h0}, v_h) := (\nabla_h u_{h0}, \nabla_h v_h)$$

Using example

$$u(x_1, x_2) = (\sin(\pi x_1) \sin(\pi x_2))^2$$

#### 1.1.1 Setting $\epsilon$ and generating mesh

```
[36]: m = MeshTri.init_symmetric()
# m = MeshTri()
m.refine(5)
element = {'w': ElementTriP1(), 'u': ElementTriMorley()}
```

```

basis = {variable: InteriorBasis(m, e, intorder=4)
         for variable, e in element.items()} # intorder: integration order for
→quadrature

# draw(m)
# plt.show()

```

### 1.1.2 Exact $u$

```

[37]: def exact_u(x, y):
        return (np.sin(np.pi * x) * np.sin(np.pi * y))**2

```

### 1.1.3 Forms for $(\nabla w_h, \nabla \chi_h) = (f, \chi_h)$

```

[59]: epsilon = 0
@BilinearForm
def laplace(u, v, w):
    '''
    for  $(\nabla w_h, \nabla \chi_h)$ 
    '''
    return dot(grad(u), grad(v))

@LinearForm
def f_load(v, w):
    '''
    for  $(f, \chi_h)$ 
    '''
    pix = np.pi * w.x[0]
    piy = np.pi * w.x[1]
    lu = 2 * (np.pi)**2 * (np.cos(2*pix)*((np.sin(piy))**2) + np.cos(2*piy)*((np.
→sin(pix))**2))
    llv = - 8 * (np.pi)**4 * (np.cos(2*pix)*np.sin(piy)**2 + np.cos(2*piy)*np.
→sin(pix)**2 - np.cos(2*pix)*np.cos(2*piy))
    return (epsilon**2 * llv - lu) * v

```

### 1.1.4 Solving $w_h$

```

[60]: %%time

K1 = asm(laplace, basis['w'])
f1 = asm(f_load, basis['w'])


wh = solve(*condense(K1, f1, D=m.boundary_nodes()),
→solver=solver_iter_krylov(Precondition=True))

```


build\_pc\_diag(A) enabled  
Wall time: 23.8 ms

```
[61]: def exact_w(x, y):  
    pix = np.pi * x  
    piy = np.pi * y  
    lu = 2*(np.pi)**2 * (np.cos(2*pix)*np.sin(piy)**2 + np.cos(2*piy)*np.  
→sin(pix)**2)  
    u = (np.sin(pix) * np.sin(piy))**2  
    return - (epsilon**2 * lu - u)
```


```
[62]: plot(basis['w'], wh, colorbar=True)  
plt.show()
```



```
[63]: w = exact_w(basis['w'].doflocs[0], basis['w'].doflocs[1])  
  
plot(basis['w'], w, colorbar=True)  
plt.show()
```



```
[64]: plot(basis['w'], w - wh, colorbar=True)
      plt.show()
```



**1.1.5 Forms for  $\varepsilon^2 a_h(u_{h0}, v_h) + b_h(u_{h0}, v_h) = (\nabla w_h, \nabla_h v_h)$**

$$a_h(u_{h0}, v_h) := (\nabla_h^2 u_{h0}, \nabla_h^2 v_h), \quad b_h(u_{h0}, v_h) := (\nabla_h u_{h0}, \nabla_h v_h)$$

```
[65]: @BilinearForm
def a_load(u, v, w):
    '''
    for $a_{h}$
    '''
    return ddot(dd(u), dd(v))

@BilinearForm
def b_load(u, v, w):
    '''
    for $b_{h}$
    '''
    return dot(grad(u), grad(v))

@BilinearForm
def wv_load(u, v, w):
    '''
    for $(\nabla \chi_h, \nabla_h v_h)$
    '''
    return dot(grad(u), grad(v))
```

### 1.1.6 Setting boundary conditions

```
[67]: def easy_boundary(basis):
    '''
    Input basis
    -----
    Return D for boundary conditions
    '''

    dofs = basis.find_dofs({
        'left': m.facets_satisfying(lambda x: x[0] == 0),
        'right': m.facets_satisfying(lambda x: x[0] == 1),
        'top': m.facets_satisfying(lambda x: x[1] == 1),
        'bottom': m.facets_satisfying(lambda x: x[1] == 0)
    })

    D = np.concatenate((dofs['left'].nodal['u'], dofs['right'].nodal['u'],
                        dofs['top'].nodal['u'], dofs['bottom'].nodal['u'],
                        dofs['left'].facet['u_n'], dofs['right'].facet['u_n'],
                        dofs['top'].facet['u_n'], dofs['bottom'].facet['u_n']))

    return D
```

### 1.1.7 Solving $u_{h0}$


```
[68]: %%time

D = easy_boundary(basis['u'])
K2 = epsilon**2 * asm(a_load, basis['u']) + asm(b_load, basis['u'])
f2 = asm(wv_load, basis['w'], basis['u']) * wh
uh0 = solve(*condense(K2, f2, D=D), solver=solver_iter_krylov(Precondition=True))
```

build\_pc\_diag(A) enabled

Wall time: 74.8 ms


```
[69]: plot(basis['u'], uh0, colorbar=True)
plt.show()
```



### 1.1.8 Showing exact $u$


```
[70]: u = exact_u(basis['u'].doflocs[0], basis['u'].doflocs[1])

plot(basis['u'], u, colorbar=True)
plt.show()
```



### 1.1.9 Visualizing error $u - u_{h0}$

```
[72]: plot(basis['u'], u-uh0, colorbar=True)
      plt.show()
```



### 1.1.10 Computing $L_2$ error with $u_{h0}$ and $u$

```
[77]: @Functional
def L2uError(w):
    x, y = w.x
    return (w.w - exact_u(x, y))**2
```

```
[78]: U = basis['u'].interpolate(uh0).value

L2u = np.sqrt(L2uError.assemble(basis['u'], w=U))
print('L2 error of uh0:', L2u)
```

L2 error of uh0: 0.0005506239320336788

#### Convergence with

$$\epsilon = 1$$

```
[79]: epsilon = 1

currentL2u = 1
formerL2u = 1
m = MeshTri()

for i in range(1, 6):
    m.refine()

    element = {'w': ElementTriP1(), 'u': ElementTriMorley()}
    basis = {variable: InteriorBasis(m, e, intorder=4)
              for variable, e in element.items()} # intorder: integration order for
    →quadrature

    K1 = asm(laplace, basis['w'])
    f1 = asm(f_load, basis['w'])

    wh = solve(*condense(K1, f1, D=m.boundary_nodes()),
    →solver=solver_iter_krylov(Precondition=True))

    D = easy_boundary(basis['u'])
    K2 = epsilon**2 * asm(a_load, basis['u']) + asm(b_load, basis['u'])
    f2 = asm(wv_load, basis['w'], basis['u']) * wh
    uh0 = solve(*condense(K2, f2, D=D),
    →solver=solver_iter_krylov(Precondition=True))

    U = basis['u'].interpolate(uh0).value

    L2u = np.sqrt(L2uError.assemble(basis['u'], w=U))
    print('case 2^- ' + str(i))
    print('L2 error of uh0:', L2u)
```



```

currentL2u = L2u
if i != 1:
    print('rate', -np.log2(currentL2u/formerL2u))
formerL2u = L2u

```

```

build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-1
L2 error of uh0: 0.14312157458419236
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-2
L2 error of uh0: 0.041409209806485096
rate 1.7892175869478015
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-3
L2 error of uh0: 0.00905868775220735
rate 2.192577691947967
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-4
L2 error of uh0: 0.0020300577442618198
rate 2.1577813106674504
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-5
L2 error of uh0: 0.0004859434175848888
rate 2.0626605211396885

```

**Convergence with**

$$\epsilon = 10^{-6}$$

```

[81]: epsilon = 1e-6

currentL2u = 1
formerL2u = 1
m = MeshTri()

for i in range(1, 6):
    m.refine()

    element = {'w': ElementTriP1(), 'u': ElementTriMorley()}
    basis = {variable: InteriorBasis(m, e, intorder=4)
              for variable, e in element.items()} # intorder: integration order for
→quadrature

```

```

K1 = asm(laplace, basis['w'])
f1 = asm(f_load, basis['w'])

wh = solve(*condense(K1, f1, D=m.boundary_nodes()),
→solver=solver_iter_krylov(Precondition=True))

D = easy_boundary(basis['u'])
K2 = epsilon**2 * asm(a_load, basis['u']) + asm(b_load, basis['u'])
f2 = asm(wv_load, basis['w'], basis['u']) * wh
uh0 = solve(*condense(K2, f2, D=D),
→solver=solver_iter_krylov(Precondition=True))

U = basis['u'].interpolate(uh0).value

L2u = np.sqrt(L2uError.assemble(basis['u'], w=U))
print('case 2^-' + str(i))
print('L2 error of uh0:', L2u)
currentL2u = L2u
if i != 1:
    print('rate', -np.log2(currentL2u/formerL2u))
formerL2u = L2u

```

```

build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-1
L2 error of uh0: 0.1589487110205496
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-2
L2 error of uh0: 0.058990938135133085
rate 1.4299960594294439
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-3
L2 error of uh0: 0.01202629748858373
rate 2.294300801260063
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-4
L2 error of uh0: 0.0024264810981080463
rate 2.309255024423518
build_pc_diag(A) enabled
build_pc_diag(A) enabled
case 2^-5
L2 error of uh0: 0.0005506239402151528
rate 2.1397263793908747

```