

A Review of Metric Learning Methods

First Author

Institution1

Institution1 address

firstauthor@i1.org

Second Author

Institution2

First line of institution2 address

secondauthor@i2.org

Abstract

Metric learning is the task of learning a distance function on pair of objects. We review three metric learning methods based on deep learning, including Siamese Network, Triplet Network and n-Tuple Network framework. These frameworks output low dimensional embedding for input data, on which we may use Euclidean distance as the distance function. These frameworks all include a set of neural networks sharing the same structure and parameters and a loss function combining the outputs of the networks. In this work, we wrote a wrapper class for the network to hide the low-level implementation, and focus on the design of the high-level frameworks and loss functions. In our experiment on MNIST dataset and a classic network structure, Siamese Network has a mediocre performance while Triplet Network produces better embeddings. We are not able to make the original n-Tuple Network work. However, we have tested a few modified versions of it, which keep the framework unchanged but use different loss functions.

1. Introduction

Metric learning is the task of learning a distance function on pair of objects. The most trivial definition of distance of two instances (which can be two images, two sequences, etc.) is the Euclidean distance. However, Euclidean distance may not be a good indicator for specialized tasks, because it cannot represent the intrinsic structure of the data. Theoretically, many high dimensional datasets can be viewed as low dimensional manifold embedded in a high dimensional space, where Euclidean distance cannot capture the manifold.

To solve this problem, many Metric learning algorithms are invented. The classical ones include Isomap, Locally Linear Embedding (LLE), Stochastic Neighbor Embedding, etc. These methods are all unsupervised methods. In the deep learning area, LeCun ??? introduces Siamese Network, which can be viewed as a framework including two neural networks of the same structure and sharing the same

parameters and a loss function defines on the two outputs and the labels of the two inputs. Commonly, the loss function call for a small distance of the outputs when the two inputs are of the same label and vice versa. Elad Hoffer and Nir Ailon have invented Triplet Network ???, which is an extension of Siamese Network, but includes three networks. The Triplet Network processes two instances from one class and one instance from another class at the same time. ??? n-Tuple Network further generalize the idea of Triplet Network, where two instances from one class and multiple instances from the other classes are used at one time.

We use two laptops to perform the experiments. One of them is equipped with Intel Core i7 5700HQ and NVidia 960M graphics. Another one is ???

In section 2 we show the mechanisms of the aforementioned deep learning methods in detail. Some important details about implementation is shown in section 3. We show our experiments and results in 4. We further discuss the phenomena shown in the experiments in section 5.

2. Mechanisms

2.1. Siamese Network

Siamese Network is a framework for metric learning. It contains two parts, the twin networks (In fact its name “Siamese” is related to twin) and the loss function. The structure of the framework is shown in figure ???. Each one of the twin networks takes one instance from the dataset, denoted as x_1 and x_2 , and output the result $y_1 = Net(x_1)$ and $y_2 = Net(x_2)$ respectively. The loss function is defined as follows.¹

$$Loss = (1 - S)L_S(|y_1 - y_2|) + SL_D(|y_1 - y_2|) \quad (1)$$

where $L_S(\bullet)$ and $L_D(\bullet)$ stands for loss functions for similarity and dissimilarity respectively. When x_1 and x_2 are in the same class (or is similar on some perspective), label S

¹Expressions are slightly different from the original paper to keep consistent through our article.

is set to be 1, and the loss is caused by dissimilarity. When x_1 and x_2 are not in the same class, Y is set to 0 and gives a penalty on similarity. The formal definitions of the functions are as follows.

$$L_S = \frac{1}{2}|y_1 - y_2|^2 \quad (2)$$

$$L_D = \frac{1}{2}\{\max(0, m - |y_1 - y_2|)\}^2 \quad (3)$$

where m is a positive parameter. Generally speaking, L_D treats two points whose distance is more than m as totally separated and puts no penalty on them.

2.2. Triplet Network

Triplet Network is an enhanced version of Siamese Network, which processes similar instance and dissimilar instance at the same time. The structure of the framework is shown in figure ???. The loss function is not just the similarity or dissimilarity, but is based on comparison of the similarity of similar instances and dissimilarity of dissimilar instances. The

3. Implementations

4. Experiments and Results

5. Discussion

6. Conclusion