

EXPERIMENT – 1

AIM: - Study of various Network commands used in Linux and Windows

BASIC NETWORKING COMMANDS: -

Windows:

arp -a: ARP is short form of address resolution protocol, It will show the IP address of your computer along with the IP address and MAC address of your router.

hostname: This is the simplest of all TCP/IP commands. It simply displays the name of your computer.

ipconfig /all: This command displays detailed configuration information about your TCP/IP connection including Router, Gateway, DNS, DHCP, and type of Ethernet adapter in your system

nbtstat -a: This command helps solve problems with NetBIOS name resolution. (Nbt stands for NetBIOS over TCP/IP)

netstat: (network statistics) netstat displays a variety of statistics about a computers active TCP/IP connections. It is a command line tool for monitoring network connections both incoming and outgoing as well as viewing routing tables, interface statistics etc.

e.g.:- netstat -r

nslookup: (name server lookup) is a tool used to perform DNS lookups in Linux. It is used to display DNS details, such as the IP address of a particular computer, the MX records for a domain or the NS servers of a domain. nslookup can operate in two modes: interactive and non-interactive.

e.g.:- nslookup www.google.com

pathping: Pathping is unique to Window's, and is basically a combination of the Ping and Tracert commands. Pathping traces the route to the destination address then launches a 25 second test of each router along the way, gathering statistics on the rate of data loss along eachhop.

ping: (Packet INternet Groper) command is the best way to test connectivity between two nodes. Ping use ICMP (Internet Control Message Protocol) to communicate to other devices.

1. #ping hostname(ping localhost)

2. #ping ip address (ping 4.2.2.2)

3. #ping fully qualified domain name(ping www.facebook.com)

Route: route command is used to show/manipulate the IP routing table. It is primarily used to setup static routes to specific host or networks via an interface.

OUTPUT: -

```
Microsoft Windows [Version 10.0.22631.4317]
(c) Microsoft Corporation. All rights reserved.
```

```
C:\Users\hp>arp -a
```

```
Interface: 192.168.0.100 --- 0x5
Internet Address      Physical Address      Type
192.168.0.1           b0-95-75-d0-c1-19     dynamic
192.168.0.255         ff-ff-ff-ff-ff-ff     static
224.0.0.22            01-00-5e-00-00-16     static
224.0.0.251           01-00-5e-00-00-fb     static
224.0.0.252           01-00-5e-00-00-fc     static
239.255.255.250       01-00-5e-7f-ff-fa     static
255.255.255.255       ff-ff-ff-ff-ff-ff     static
```

```
C:\Users\hp>hostname
DESKTOP-FODB1M0
```

```
C:\Users\hp>ipconfig
```

```
Windows IP Configuration
```

```
Ethernet adapter Ethernet:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Local Area Connection* 1:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Local Area Connection* 2:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Wi-Fi:
```

```
Connection-specific DNS Suffix . :
```

```
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Local Area Connection* 2:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Wi-Fi:
```

```
Connection-specific DNS Suffix . :
IPv6 Address. . . . . : 2406:7400:bb:9a01:68d5:b10:8367:e13e
Temporary IPv6 Address. . . . . : 2406:7400:bb:9a01:9462:fa5e:ebe4:3130
Link-local IPv6 Address . . . . . : fe80::697a:d049:6a46:ed14%5
IPv4 Address. . . . . : 192.168.0.100
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . : fe80::b295:75ff:fed0:c119%5
                          192.168.0.1
```

```
Ethernet adapter Bluetooth Network Connection:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
C:\Users\hp>pathping
```

```
Usage: pathping [-g host-list] [-h maximum_hops] [-i address] [-n]
               [-p period] [-q num_queries] [-w timeout]
               [-4] [-6] target_name
```

```
Options:
```

```
-g host-list      Loose source route along host-list.
-h maximum_hops   Maximum number of hops to search for target.
-i address        Use the specified source address.
-n               Do not resolve addresses to hostnames.
-p period         Wait period milliseconds between pings.
-q num_queries    Number of queries per hop.
-w timeout        Wait timeout milliseconds for each reply.
-4               Force using IPv4.
-6               Force using IPv6.
```

```
C:\Users\hp>|
```

Linux:

ip: The ip command is one of the basic commands every administrator will need in daily work, from setting up new systems and assigning IPs to troubleshooting existing systems. The ip command can show address information, manipulate routing, plus display network various devices, interfaces, and tunnels.

ifconfig: The ifconfig command was/is a staple in many sysadmin's tool belt for configuring and troubleshooting networks. It has since been replaced by the ip command discussed above.

mtr: MTR (Matt's traceroute) is a program with a command-line interface that serves as a network diagnostic and troubleshooting tool. This command combines the functionality of the ping and traceroute commands. Just like a traceroute, the mtr command will show the route from a computer to a specified host. mtr provides a lot of statistics about each hop, such as response time and percentage. With the mtr command, you will get more information about the route and be able to see problematic devices along the way. If you see a sudden increase in response time or packet loss, then obviously, there is a bad link somewhere.

The syntax of the command is as follows:

```
mtr <options> hostname/IP
```

tcpdump: The tcpdump command is designed for capturing and displaying packets.

ping: verifies IP-level connectivity to another TCP/IP computer by sending Internet Control Message Protocol (ICMP) Echo Request messages. The receipt of corresponding Echo Reply messages is displayed, along with round-trip times. Ping is the primary TCP/IP command used to troubleshoot connectivity, reachability, and name resolution.

OUTPUT: -

RESULT: -

The commands for Linux and Windows has been executed successfully and the output is verified.