

You are here: [Set Up & Maintenance](#) > [Building Applications, Questionnaires, and Solutions](#) > [Fields](#) > *Text Functions*

Text Functions

The following text functions utilize and manipulate text strings to produce dynamic values.

On this page

CONCATENATE Function

The CONCATENATE function joins up to 255 text strings into 1 text string. The joined items can be text, numbers, cell references, or a combination of those items. You must specify any spaces or punctuation that you want to appear in the results as an argument that is enclosed in quotation marks.

Return Type: Text

Syntax: CONCATENATE(**text1**, text2, ...)

In the above syntax, parameters in bold are required.

The following table describes CONCATENATE function parameters.

Parameter	Description
text1	The first text item to be concatenated.
text2, ...	Additional text items, up to a maximum of 255 items. The items must be separated by commas.

Example:

The following table provides an example formula of the CONCATENATE function.

Formula	Result
CONCATENATE([First Name], " ", [Last Name]) where the value in the First Name field is "John" and the value in the Last Name field is "Smith".	John Smith

FIND Function

The FIND function searches for a specific character or text string within another text string. It returns the number of the character at which the specific character or test string is first found. The FIND function is case sensitive.

Return Type: Numeric

Syntax: FIND(**find_text**, **field_ref**, start_num)

In the above syntax, parameters in bold are required.

The following table describes FIND function parameters.

Parameter	Description
find_text	The character or text string you want to find. You can format this parameter as a hard-coded character or text string, for example, "sci", or as a Text-field reference, for example, [field name].

Parameter	Description
field_ref	A Text-field reference, for example, [field name].
start_num	The character number in the field_ref parameter at which you want to start searching for the find_text parameter. If this parameter is omitted, the search will begin at the first character in the Text field. If this parameter is less than or equal to 0 (zero) or is greater than the number of characters in the Text field, a formula validation error will occur.

Examples:

The following table provides example formulas of the FIND function.

Formula	Result
FIND("Sci", [Subject]) where the value in the Subject field is "Arts and Sciences".	10 (because "Sci" begins at the tenth character in this text string)
FIND("s", [Subject], 5) where the value in the Subject field is "Arts and Sciences".	17 (notice that the first "s" in the Subject field value was skipped because the start_num parameter required that the search begin at the fifth character and the "S" in the Subject field value was skipped because it does not match the case specified)

LEFT Function

The LEFT function returns the first character or characters in a text string, based on the number of characters that you specify. LEFT is intended for use with languages that use the single-byte character set (SBCS). LEFT always counts each character, whether single-byte or double-byte, as 1, regardless of what the default language setting is.

Return Type: Numeric

Syntax: LEFT(**text**,num_chars)

In the above syntax, parameters in bold are required.

The following table describes LEFT function parameters.

Parameter	Description
text	The text string that contains the characters that you want to extract.
num_chars	The number of characters that you want LEFT to extract. Note that: - Num_chars must be greater than or equal to zero. - If num_chars is greater than the length of text, LEFT returns all of text. - If num_chars is omitted, it is assumed to be 1.

Examples:

The following table provides example formulas of the LEFT function.

Formula	Result

Formula	Result
LEFT([Text],4) where the value in the Text string is Sale Price.	First 4 characters in the string (Sale)
LEFT([Text]) where the value in the Text string is Sweden.	First character in the string (S)

LEN Function

The LEN function returns the number of characters in the supplied string.

Return Type: Numeric

Syntax: LEN(**text**)

In the above syntax, parameters in bold are required.

The following table describes the LEN function parameter.

Parameter	Description
text	The text string to be evaluated. This parameter should be formatted as a Text-field reference, for example, [field name].

Example:

The following table provides an example formula of the LEN function.

Formula	Result
LEN ([Last Name]) where the value in the Last Name field is "Jones".	5

LOWER Function

The LOWER function converts all characters in the supplied text string to lowercase. This function does not affect non-alphabetic characters.

Return Type: Text

Syntax: LOWER(**text**)

In the above syntax, parameters in bold are required.

The following table describes the LOWER function parameter.

Parameter	Description
text	The text string to be converted to lowercase. This parameter should be formatted as a Text-field reference, for example, [field name].

Examples:

The following table provides example formulas of the LOWER function.

Formula	Result
---------	--------

Formula	Result
LOWER([Name]) where the value in the Name field is "Jake Miller ".	jake miller
LOWER([Email Address]) where the value in the Email Address field is "SUZY.WILLIAMS@Shore2Shore.org".	suzy.williams@shore2shore.org

MASKEDTEXT Function

The MASKEDTEXT function returns the string value of the referenced Text field using the mask (if any) defined for the field. If the function references a Text field for which a mask has not been defined, the function will return the raw value from the field.

Note: Unless a Text field reference is wrapped in MASKEDTEXT, the calculation engine will always evaluate the raw, unformatted value of the Text field.

Return Type: Text

Syntax: MASKEDTEXT(**text_field**)

In the above syntax, parameters in bold are required.

The following table describes the MASKEDTEXT function.

Parameter	Description
text_field	This parameter should be formatted as a Text-field reference, for example, [field name]. Note: This function is valid only for Text fields.

Examples:

The following table provides example formulas of the MASKEDTEXT function.

Formula	Result
MASKEDTEXT([Phone]) where the raw value in the Phone field is 9137862356 and the Text field is defined to use a phone number mask.	(913) 786-2356
MASKEDTEXT([SIN]) where the raw value is 046454286 and the Text field is defined to use a custom mask for the Canadian Social Insurance Number.	046 454 286

NUMBERFORMAT Function

The NUMBERFORMAT function is used to "pad" zeros (0) to the left of a given numeric value based on the count of digits specified by the number "mask." The zero padding is only applied if the number of digits in the numeric value falls short of the number of digits specified in the mask. This function returns a text value (string) that can be concatenated to other strings or stored directly in the Text field.

Return Type: Text

Syntax: NUMBERFORMAT(**value**, **value_mask**)

In the above syntax, parameters in bold are required.

The following table describes the NUMBERFORMAT function parameters.

Parameter	Description
value	The numeric value, which can be derived through a Numeric-field reference, for example, [field name], or through the use of a function that returns a numeric value.
value_mask	The mask used to format the returned text value. The value_mask parameter must be enclosed in quotes. The final placeholder in the value_mask parameter must always be a single pound sign (#). The placeholders allowed for this function are: 0 = Zero placeholder # = Value placeholder

Examples:

The following table provides example formulas of the NUMBERFORMAT function.

Formula	Result
NUMBERFORMAT(TRACKINGID(), "00#") where the tracking ID returned by the TRACKINGID function is 1.	001
NUMBERFORMAT(TRACKINGID(), "000000#") where the tracking ID returned by the TRACKINGID function is 937.	0000937
CONTENTID() & "-" & NUMBERFORMAT(TRACKINGID(), "000#") where the content ID returned by the CONTENTID function is 878762 and the tracking ID returned by the TRACKINGID function is 8.	878762-0008
NUMBERFORMAT([Risk] + [Criticality], "00#") where the value in the Risk field is 12 and the value in the Criticality field is 7.	019

PROPER Function

The PROPER function capitalizes the first letter of each word in the supplied string, as well as the first letter that follows any non-alphabetic character in the string. All other letters in the string are converted to lowercase.

Return Type: Text

Syntax: PROPER(**text**)

In the above syntax, parameters in bold are required.

The following table describes the PROPER function parameter.

Parameter	Description
text	The text string to be converted to proper text format. This parameter should be formatted as a Text-field reference, for example, [field name].

Examples:

The following table provides example formulas of the PROPER function.

Formula	Result
PROPER([Last Name]) where the value in the Last Name field is "jane pearson-wyatt".	Jane Pearson-Wyatt
PROPER([Last Name]) where the value in the Last Name field is "O’NEIL".	O’Neil
PROPER([Last Name]) where the value in the Last Name field is "ST. JOHN".	St. John
PROPER([Web Page]) where the value in the Web Page field is "www.archer-tech.com".	Www.Archер-Tech.Com
PROPER([Equipment Note]) where the value in the Equipment Note field is "This is Mike’s laptop."	This Is Mike’S Laptop.

RIGHT Function

The RIGHT function returns a specific number of characters from the right side of the string. For example, if you specify 3 characters, the last 3 characters from the string will be returned.

Return Type: Text

Syntax: RIGHT(**text**, **num_chars**)

In the above syntax, parameters in bold are required.

The following table describes RIGHT function parameters.

Parameter	Description
text	The text string that contains the characters that you want to return. This parameter should be formatted as a Text-field reference, for example, [field name].
num_chars	Specifies the number of characters in the text string that you want to return. This parameter must be greater than or equal to 0 (zero). If this parameter is negative, the function will return an error.

Example:

The following table provides an example formula of the RIGHT function.

Formula	Result
RIGHT([Department Name], 4) where the value in the Department Name field is "Marketing".	ting

STRIPHTML Function

The STRIPHTML function removes HTML tags from calculated text fields within a data feed while the feed is taking place. There are no defined parameters for this function because it is coded only to remove the HTML tags from text fields in the data feed.

Return Type: Text

Syntax: STRIPHTML

SUBSTRING Function

The SUBSTRING function returns a specified number of characters from a text string. When creating a formula with this function, you specify the character position where you want to start extracting text, and you specify the number of characters to return. For example, if you enter 1 as the start position and 3 as the number of characters to return, you would get the substring "Mar" from a Text field with the value "Marketing."

Return Type: Text

Syntax: SUBSTRING(**text_field**, **start_num**, **num_chars**)

In the above syntax, parameters in bold are required.

The following table describes SUBSTRING function parameters.

Parameter	Description
text_field	The text string that contains the characters that you want to return. This parameter should be formatted as a Text-field reference, for example, [field name].
start_num	Specifies the position of the first character that you want to extract from the Text field. The first character in a string has a start number of 1. If the start number value is less than 1 or is greater than the number of characters in the string, the calculation will fail.
num_chars	Specifies the number of characters in the Text field that you want to return. If you specify a value that is larger than the total number of characters in the string, then this parameter returns all characters to the end of the string.

Example:

The following table provides an example formula of the SUBSTRING function.

Formula	Result
SUBSTRING([Department Name], 1, 4) where the value in the Department Name field is "Marketing".	Mark

Note: If the text string contains ampersand (&), less than (<), greater than (>), pound (#), single quotation (') or double quotation (") characters, then the SUBSTRING function returns results incorrectly.

TRIM Function

The TRIM function removes spaces from text strings, with the exception of single spaces between words. A common use for the TRIM function is to remove extra spaces from data received from an integration or data import. Often, data formatted in another system has irregular spacing. Using the TRIM function ensures that unnecessary spaces are removed from your Archer text.

Return Type: Text

Syntax: TRIM(**text**)

In the above syntax, parameters in bold are required.

The following table describes the TRIM function parameter.

Parameter	Description
text	The text string from which you want to remove the unnecessary spaces.

Example:

The following table provides an example formula of the TRIM function.

Formula	Result
TRIM([Asset Description]) where the value of the Asset Description field is "The HR-DB Server is used to store our human resources information."	"The HR-DB Server is used to store our human resources information."

UPPER Function

The UPPER function converts all characters in the supplied string to uppercase. This function does not affect non-alphabetic characters.

Return Type: Text

Syntax: UPPER(**text**)

In the above syntax, parameters in bold are required.

The following table describes the UPPER function parameter.

Parameter	Description
text	The text string to be converted to uppercase. This parameter should be formatted as a Text-field reference, for example, [field name].

Examples:

The following table provides example formulas of the UPPER function.

Formula	Result
UPPER([Name]) where the value in the Name field is "Jake Miller ".	JAKE MILLER

Formula	Result
UPPER([Web Site]) where the value in the Web Site field is "www.archer-tech.com".	WWW.ARCHER-TECH.COM

Archer

ADDRESS	ABOUT ARCHER	CUSTOMERS	CONNECT WITH US
13200 Metcalf Ave	Events	Archer Academy	in t v
Suite 300	Resources	Archer Exchange	
Overland Park, KS	Services	Support	
66213	About Us	Archer Community	

Archer is a leading provider of [enterprise risk management solutions](#), which include [third party risk management](#), [IT risk management](#), [operational risk management](#), and more. [Contact us](#) now to learn more about [integrated risk management solutions](#) from Archer.