

SAMSUNG

ELECTRONICS

Preliminary



TO

DATE : Mar. 27, 2008.

SAMSUNG TFT-LCD

MODEL NO. : LTN154AT10

NOTE :

- Extension code [-D] ; LTN154AT10-C
- Surface type [**Glare**]

Any Modification of Specification is not allowed without SEC's Permission.

APPROVED BY :

K. H. Shin

PREPARED BY : LCD Development Group 1 (Mobile)

SAMSUNG ELECTRONICS CO., LTD.



Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 1 / 27 |
|---------|------------|--------|-----------------|------|--------|

CONTENTS

| | |
|---|--------------|
| Revision History | ----- (3) |
| General Description | ----- (4) |
| 1. Absolute Maximum Ratings | ----- (5) |
| 1.1 Absolute Ratings of environment | |
| 1.2 Electrical Absolute Ratings | |
| 2. Optical Characteristics | ----- (7) |
| 3. Electrical Characteristics | ----- (10) |
| 3.1 TFT LCD Module | |
| 3.2 Backlight Unit | |
| 4. Block Diagram | ----- (13) |
| 4.1 TFT LCD Module | |
| 4.2 Backlight Unit | |
| 5. Input Terminal Pin Assignment | ----- (14) |
| 5.1 Input Signal & Power | |
| 5.2 LVDS Interface | |
| 5.3 Backlight Unit | |
| 5.4 Timing Diagrams of LVDS For Transmitting | |
| 5.5 Input Signals, Basic Display Colors and Gray Scale of Each Color. | |
| 5.6 Pixel format | |
| 5.7 Inverter Signals & Power | |
| 6. Interface Timing | ----- (19) |
| 6.1 Timing Parameters | |
| 6.2 Timing Diagrams of interface Signal | |
| 6.3 Power ON/OFF Sequence | |
| 7. Outline Dimension | ----- (21) |
| 8. Packing | ----- (23) |
| 9. Markings & Others | ----- (24) |
| 10. General Precaution | ----- (26) |

Samsung Secret

| | | | | | |
|----------------|------------|---------------|-----------------|-------------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 2 / 27 |
|----------------|------------|---------------|-----------------|-------------|--------|

REVISION HISTORY

Preliminary

| Date | Revision No. | Page | Summary |
|---------------|--------------|------|---|
| Mar. 27. 2008 | P00 | All | LTN154AT10 Model spec was issued first. |

Samsung Secret

| | | | | | |
|----------------|------------|---------------|-----------------|-------------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 3 / 27 |
|----------------|------------|---------------|-----------------|-------------|--------|

GENERAL DESCRIPTION

DESCRIPTION

LTN154AT10 is a color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching devices. This model is composed of a TFT LCD panel, a driver circuit and a backlight unit. The resolution of a 15.4" contains 1,280 x 800 pixels and can display up to 262,144 colors. 6 O'clock direction is the Optimum viewing angle.

FEATURES

- High contrast ratio, high aperture structure
- 1280 x 800 pixels resolution
- Low power consumption
- Fast Response
- Single CCFL
- DE(Data enable) only mode
- 3.3V LVDS Interface
- Onboard EEDID chip

APPLICATIONS

- Notebook PC
- If the usage of this product is not for PC application, but for others, please contact SEC.

GENERAL INFORMATION

| Item | Specification | Unit | Note |
|-------------------|---------------------------------------|-------|---------|
| Display area | 331.2(H) x 207.0(V) (15.4" diagonal) | mm | |
| Driver element | a-Si TFT active matrix | | |
| Display colors | 262,144 | | |
| Number of pixel | 1280 x RGB(3) x 800 | pixel | 16 : 10 |
| Pixel arrangement | RGB vertical stripe | | |
| Pixel pitch | 0.2588(H) x 0.2588(V) (TYP.) | mm | |
| Display Mode | Normally white | | |
| Surface treatment | Haze 0, Hard-Coating 3H | | |

Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 4 / 27 |
|---------|------------|--------|-----------------|------|--------|

Mechanical Information

| Item | | Min. | Typ. | Max. | Unit | Note |
|-------------|----------------|-------|-------|-------|------|--------------------|
| Module size | Horizontal (H) | 343.5 | 344.0 | 344.5 | mm | w/o inverter ass'y |
| | Vertical (V) | 221.5 | 222.0 | 222.5 | mm | |
| | Depth (D) | - | - | 6.5 | mm | |
| Weight | | - | 555 | 570 | g | LCD module only |

1. ABSOLUTE MAXIMUM RATINGS


1.1 ENVIRONMENTAL ABSOLUTE RATINGS

| Item | Symbol | Min. | Max. | Unit | Note |
|---|--------|------|------|------|---------|
| Storage temperate | TSTG | -20 | 60 | °C | (1),(5) |
| Operating temperate (Temperature of glass surface) | TOPR | 0 | 50 | °C | (1),(5) |
| Shock (non-operating) | Snop | - | 240 | G | (2),(4) |
| Vibration (non-operating) | Vnop | - | 2.41 | G | (3),(4) |

Note (1) Temperature and relative humidity range are shown in the figure below.

95 % RH Max. ($40^{\circ}\text{C} \geq T_a$)

Maximum wet - bulb temperature at 39°C or less. ($T_a > 40^{\circ}\text{C}$) No condensation



(2) 2ms, half sine wave, one time for $\pm X$, $\pm Y$, $\pm Z$.

(3) 5 - 500 Hz, random vibration, 30min for X, Y, Z.

(4) At testing Vibration and Shock, the fixture in holding the Module to be tested have to be hard and rigid enough so that the Module would not be twisted or bent by the fixture.

(5) If product is used for extended time excessively or exposed to high temperatures for extended time, there is a possibility of wide viewing angle film damage which could affect visual characteristics.

Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 5 / 27 |
|---------|------------|--------|-----------------|------|--------|

1.2 ELECTRICAL ABSOLUTE RATINGS

(1) TFT LCD MODULE

 $V_{DD} = 3.3V, V_{SS} = GND = 0V$

| Item | Symbol | Min. | Max. | Unit | Note |
|----------------------|----------|----------------|----------------|------|------|
| Power Supply Voltage | V_{DD} | $V_{DD} - 0.3$ | $V_{DD} + 0.3$ | V | (1) |
| Logic Input Voltage | V_{DD} | $V_{DD} - 0.3$ | $V_{DD} + 0.3$ | V | (1) |

Note (1) Within T_a ($25 \pm 2^\circ C$)

(2) BACK-LIGHT UNIT

 $T_a = 25 \pm 2^\circ C$

| Item | Symbol | Min. | Max. | Unit | Note |
|----------------|--------|------|------|-------|------|
| Lamp Current | I_L | 3.0 | 7.0 | mArms | (1) |
| Lamp frequency | F_L | 45 | 75 | kHz | (1) |

Note 1) Permanent damage to the device may occur if maximum values are exceeded
Functional operation should be restricted to the conditions described under normal operating conditions.

Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|--------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 6 / 27 |
|---------|------------|--------|-----------------|------|--------|

2. OPTICAL CHARACTERISTICS


The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state with the methods shown in Note (5).
Measuring equipment : TOPCON BM-5A and PR-650

* Ta = 25 ± 2 °C, VDD=3.3V, fv= 60Hz, fDCLK = 71.26MHz, IL = 6.5 mArms

| Item | | Symbol | Condition | Min. | Typ. | Max | Unit | Note |
|---|-------|--------------------|--|---------|---------|---------|-------------------|-----------------------------------|
| Contrast Ratio (5 Points) | | CR | | 400 | 500 | - | - | (1), (2), (5) |
| Response Time at Ta (Rising + Falling) | | T _{RT_BW} | | - | 16 | 25 | msec | (1), (3) |
| Average Luminance of White (5 Points) | | Y _{L,AVE} | Normal Viewing Angle ϕ = 0 θ = 0 | 190 | 220 | - | cd/m ² | I _L =6.5mA (1), (4) |
| Color Chromaticity (CIE) | Red | R _X | | (0.570) | (0.590) | (0.610) | - | (1), (5) PR-650 |
| | | R _Y | | (0.320) | (0.340) | (0.360) | | |
| | Green | G _X | | (0.310) | (0.330) | (0.350) | | |
| | | G _Y | | (0.525) | (0.545) | (0.565) | | |
| | Blue | B _X | | (0.135) | (0.155) | (0.175) | | |
| | | B _Y | | (0.115) | (0.135) | (0.155) | | |
| | White | W _X | | 0.293 | 0.313 | 0.333 | | |
| | | W _Y | | 0.309 | 0.329 | 0.349 | | |
| Viewing Angle | Hor. | θ _L | CR ≥ 10 | 40 | - | - | Degrees | (1), (5) BM-5A |
| | | θ _H | | 40 | - | - | | |
| | Ver. | ϕ _H | | 15 | - | - | | |
| | | ϕ _L | | 30 | - | - | | |
| 13 Points White Variation | | δ _L | | - | - | 1.7 | - | (6) |

Samsung Secret

Note 1) Definition of Viewing Angle : Viewing angle range($10 \leq C/R$, $100 \leq C/R$)




Note 2) Definition of Contrast Ratio (CR) : Ratio of gray max (Gmax) ,gray min (Gmin) at 5 points(4, 5, 7, 9, 10)


$$CR = \frac{CR(4) + CR(5) + CR(7) + CR(9) + CR(10)}{5}$$

Points : (4) , (5) , (7) , (9) , (10) at the figure of Note (6).

Note 3) Definition of Response time :



Note 4) Definition of Average Luminance of White : measure the luminance of white at 5 points.




Samsung Secret

Note 5) After stabilizing and leaving the panel alone at a given temperature for 30 min , the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. 30 min after lighting the backlight. This should be measured in the center of screen.


Lamp current : 6.5mA

Environment condition : $T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$



Note 6) Definition of 13 points white variation (δL), CR variation(C_{VER}) [① ~ ⑬]

$$\delta L = \frac{\text{Maximum luminance of 13 points}}{\text{Minimum luminance of 13 points}}$$



Samsung Secret

3. ELECTRICAL CHARACTERISTICS

3.1 TFT LCD MODULE

Ta= 25 ± 2°C


| Item | | Symbol | Min. | Typ. | Max. | Unit | Note |
|--|-----------|-------------------|------|-------|------|------|-------------------------|
| Voltage of Power Supply | | V _{DD} | 3.0 | 3.3 | 3.6 | V | |
| Differential Input Voltage for LVDS Receiver Threshold | High | V _{IH} | - | - | +100 | mV | V _{CM} = +1.2V |
| | Low | V _{IL} | -100 | - | - | mV | |
| Vsync Frequency | | f _v | - | 60 | - | Hz | |
| Hsync Frequency | | f _H | - | 48.96 | - | KHz | |
| Main Frequency | | f _{DCLK} | - | 70.5 | - | MHz | |
| Rush Current | | I _{RUSH} | - | - | 1.5 | A | (4) |
| Current of Power Supply | White | I _{DD} | - | 300 | - | mA | (2),(3)*a |
| | Mosaic | | - | 310 | - | mA | (2),(3)*b |
| | V. stripe | | - | 380 | 500 | mA | (2),(3)*c |

Note (1) Display data pins and timing signal pins should be connected.(GND = 0V)

(2) f_v = 60Hz, f_{DCLK} = 70.5MHz, V_{DD} = 3.3V , DC Current.

(3) Power dissipation pattern


*a) White Pattern



*b) Mosaic Pattern


Display Brightest Gray Level →

Display Darkest Gray Level →




Samsung Secret


*c) 1dot Vertical stripe pattern



4) Rush current measurement condition



V_{DD} rising time is 470us



Samsung Secret

3.2 BACK-LIGHT UNIT

The backlight system is an edge-lighting type with a single CCFT (Cold Cathode Fluorescent Tube).
The characteristics of a single lamp are shown in the following table.


$T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$

| Item | Symbol | Min. | Typ. | Max. | Unit | Note |
|---------------------|--------|--------|------|------|-------|-----------------------------|
| Lamp Current | I_L | 3.0 | 6.5 | 7.0 | mArms | (1) |
| Lamp Voltage | V_L | - | 655 | - | Vrms | $I_L = 6.5\text{mA}$ |
| Frequency | f_L | 40 | 60 | (85) | KHz | (2) |
| Power Consumption | P_L | - | 4.6 | 5.0 | W | (3) $I_L = 6.5\text{mA}$ |
| Operating Life Time | Hr | 15,000 | - | - | Hour | (4) |
| Startup Voltage | V_s | - | - | 1250 | Vrms | 25°C, (5) |
| | | | | 1500 | Vrms | 0°C, (5) |

Note) The waveform of the inverter output voltage must be area symmetric and the design of the inverter must have specifications for the modularized lamp.

The performance of the backlight, for example life time or brightness, is much influenced by the characteristics of the DC-AC inverter for the lamp. So all the parameters of an inverter should be carefully designed so as not to produce too much leakage current from high-voltage output of the inverter. When you design or order the inverter, please make sure that a poor lighting caused by the mismatch of the backlight and the inverter(miss lighting, flicker, etc.) never occur. When you confirm it, the module should be operated in the same condition as it is installed in your instrument.

Note (1) Lamp current is measured with a high frequency current meter as shown below.



(2) Lamp frequency may produce interference with horizontal synchronous frequency and this may cause line flow on the display. Therefore lamp frequency should be detached from the horizontal synchronous frequency and its harmonics as far as possible in order to avoid interference.

(3) Refer to $I_L \times V_L$ to calculate.

(4) Life time (Hr) of a lamp can be defined as the time in which it continues to operate under the condition $T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$ and $I_L = 6.0 \text{ mArms}$ until one of the following event occurs.

1. When the brightness becomes 50% or lower than the original.
2. When the Effective ignition length becomes 80% or lower than the original value.
(Effective ignition length is defined as an area that has less than 70% brightness compared to the brightness in the center point.)
3. CCFL only

(5) The inverter open voltage - this voltage should be measured after ballast capacitor- have to be larger than the lamp startup voltage, otherwise backlight may has blinking for a moment after turns on or not be turned on.


If an inverter has shutdown function it should keep its open voltage for longer than 1 second even if lamp connector open.

Samsung Secret


| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 12 / 27 |
|---------|------------|--------|-----------------|------|---------|
|---------|------------|--------|-----------------|------|---------|

4. BLOCK DIAGRAM

4.1 TFT LCD Module



4.2 BACKLIGHT UNIT



Note) The output of the inverter may change according to the material of the reflector.

Samsung Secret

5. INPUT TERMINAL PIN ASSIGNMENT

5.1. Input Signal & Power (LVDS, Connector : JAE FI-XB30SRL-HF11 or compatible)
Mating Connector : JAE FI-XB20Sx-HFxx or compatible)

| No. | Symbol | Function | Polarity | Remarks |
|-----|----------|--|----------|---------|
| 1 | VSS | Ground | | |
| 2 | VDD | POWER SUPPLY +3.3V | | |
| 3 | VDD | POWER SUPPLY +3.3V | | |
| 4 | VEEDID | DDC 3.3V Power | | |
| 5 | BIST | Panel BIST enable | | |
| 6 | CLKEDID | DDC Clock | | |
| 7 | DATAEDID | DDC data | | |
| 8 | RxIN0- | LVDS Differential Data INPUT (R0-R5,G0) | Negative | |
| 9 | RxIN0+ | LVDS Differential Data INPUT (R0-R5,G0) | Positive | |
| 10 | GND | Ground | | |
| 11 | RxIN1- | LVDS Differential Data INPUT (G1-G5,B0-B1) | Negative | |
| 12 | RxIN1+ | LVDS Differential Data INPUT (G1-G5,B0-B1) | Positive | |
| 13 | GND | Ground | | |
| 14 | RxIN2- | LVDS Differential Data INPUT (B2-B5,Sync,DE) | Negative | |
| 15 | RxIN2+ | LVDS Differential Data INPUT (B2-B5,Sync,DE) | Positive | |
| 16 | Vss | Ground | | |
| 17 | ClkIN- | LVDS Differential Clock INPUT | Negative | |
| 18 | ClkIN+ | LVDS Differential Clock INPUT | Positive | |
| 19 | Vss | Ground | | |
| 20 | NC | No connect | | |
| 21 | NC | No connect | | |
| 22 | NC | No connect | | |
| 23 | NC | No connect | | |
| 24 | NC | No connect | | |
| 25 | NC | No connect | | |
| 26 | NC | No connect | | |
| 27 | NC | No connect | | |
| 28 | NC | No connect | | |
| 29 | NC | No connect | | |
| 30 | NC | No connect | | |

Samsung Secret


| | | | | | |
|---------|------------|--------|-----------------|------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 14 / 27 |
|---------|------------|--------|-----------------|------|---------|

5.2 LVDS Interface : Transmitter DS90CF363 or Compatible

LVDS

| Pin No. | Name | RGB Signal | Pin No. | Name | RGB Signal |
|---------|--------|------------|---------|----------|------------|
| 44 | TxIN0 | RO0 | 12 | TxIN11 | GO5 |
| 45 | TxIN1 | RO1 | 13 | TxIN12 | BO0 |
| 47 | TxIN2 | RO2 | 15 | TxIN13 | BO1 |
| 48 | TxIN3 | RO3 | 16 | TxIN14 | BO2 |
| 1 | TxIN4 | RO4 | 18 | TxIN15 | BO3 |
| 3 | TxIN5 | RO5 | 19 | TxIN16 | BO4 |
| 4 | TxIN6 | GO0 | 20 | TxIN17 | BO5 |
| 6 | TxIN7 | GO1 | 22 | TxIN18 | Hsync |
| 7 | TxIN8 | GO2 | 23 | TxIN19 | Vsync |
| 9 | TxIN9 | GO3 | 25 | TxIN20 | DE |
| 10 | TxIN10 | GO4 | 26 | TxCLK IN | Clock |

LVDS Interface



Note : The LCD Module uses a 100ohm resistor between positive and negative lines of each receiver input.

Samsung Secret


5.3 BACK LIGHT UNIT

Connector : JST BHSR - 02VS -1
Mating Connector : SM02B-BHSS-1(JST)

| Pin NO. | Symbol | Color | Function |
|---------|--------|-------|--------------|
| 1 | HOT | Pink | High Voltage |
| 2 | COLD | White | Low Voltage |

5.4 Timing Diagrams of LVDS For Transmission

LVDS Receiver : Integrated T-CON



Samsung Secret

5.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

| Color | Display | Data Signal | | | | | | | | | | | | | | | | | Gray Scale Level | |
|---------------------|---------|-------------|----|----|----|----|----|-------|----|----|----|----|----|------|----|----|----|----|------------------|--------|
| | | Red | | | | | | Green | | | | | | Blue | | | | | | |
| | | R0 | R1 | R2 | R3 | R4 | R5 | G0 | G1 | G2 | G3 | G4 | G5 | B0 | B1 | B2 | B3 | 45 | | B5 |
| Basic Colors | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Blue | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | - |
| | Green | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Cyan | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - |
| | Red | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Magenta | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | - |
| | Yellow | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | White | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - |
| Gray Scale Of Red | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R0 |
| | Dark | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R1 |
| | ↑ | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R2 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | R3~R60 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | |
| | ↓ | 1 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R61 |
| | Light | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R62 |
| | Red | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R63 |
| Gray Scale Of Green | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G0 |
| | Dark | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G1 |
| | ↑ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G2 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | G3~G60 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | |
| | ↓ | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | G61 |
| | Light | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | G62 |
| | Green | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | G63 |
| Gray Scale Of Blue | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | B0 |
| | Dark | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | B1 |
| | ↑ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | B2 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | B3~B60 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | |
| | ↓ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | B61 |
| | Light | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | B62 |
| | Blue | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | B63 |


Note 1) Definition of gray :

Rn: Red gray, Gn: Green gray, Bn: Blue gray (n=gray level)

Note 2) Input signal: 0 =Low level voltage, 1=High level voltage

Samsung Secret

5.6 Pixel Format in the display




Samsung Secret

6. INTERFACE TIMING

6.1 Timing Parameters

| Signal | Item | Symbol | Min. | Typ. | Max. | Unit | Note |
|--------------------------------|----------------|--------|------|------|------|--------|------|
| Frame Frequency | Cycle | TV | 804 | 816 | 1000 | Lines | |
| Vertical Active Display Term | Display Period | TVD | - | 800 | - | Lines | |
| One Line Scanning Time | Cycle | TH | 1350 | 1400 | 1550 | Clocks | |
| Horizontal Active Display Term | Display Period | THD | - | 1280 | - | Clocks | |


6.2 Timing diagrams of interface signal


Samsung Secret

6.3 Power ON/OFF Sequence

Preliminary

: To prevent a latch-up or DC operation of the LCD module, the power on/off sequence should be as the diagram below.



Power ON/OFF Sequence

- T1 : Vdd rising time from 10% to 90%
- T2 : The time from Vdd to valid data at power ON.
- T3 : The time from valid data off to Vdd off at power Off.
- T4 : Vdd off time for Windows restart
- T5 : The time from valid data to B/L enable at power ON.
- T6 : The time from valid data off to B/L disable at power Off.

NOTE.

- (1) The supply voltage of the external system for the module input should be the same as the definition of VDD.
- (2) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become white.
- (3) In case of VDD = off level, please keep the level of input signals on the low or keep a high impedance.
- (4) T4 should be measured after the module has been fully discharged between power off and on period.
- (5) Interface signal shall not be kept at high impedance when the power is on.

Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 20 / 27 |
|---------|------------|--------|-----------------|------|---------|

7. Mechanical Outline Dimension

Preliminary

It will be attached with PDF file

Samsung Secret

| | | | | | |
|---------|------------|--------|-----------------|------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 21 / 27 |
|---------|------------|--------|-----------------|------|---------|

This page will be replaced with the outline drawing after producing PDF file.

Samsung Secret


| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 22 / 27 |
|---------|------------|--------|-----------------|------|---------|
|---------|------------|--------|-----------------|------|---------|

8. PACKING

Preliminary

1. CARTON(Internal Package)

- (1) Packing Form
Corrugated Cardboard box and Corrupad form as shock absorber
- (2) Packing Method



- Note 1)Total Weight : Approximately 10 kg
2) Acceptance number of piling : 10 sets
3) Carton size : 408(W) X 325(D) X 295(H)

Samsung Secret


| | | | | | |
|---------|------------|--------|-----------------|------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 23 / 27 |
|---------|------------|--------|-----------------|------|---------|

| No | Part name | Quantity |
|----|---|----------|
| 1 | Static electric protective sack | 10 |
| 2 | Packing case (Inner box) included shock absorber | 1 set |
| 3 | Pictorial marking | 2 pcs |
| 4 | Carton | 1 set |

9. MARKINGS & OTHERS


A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

(1) Parts number : LTNXXXXXXXX-XXX




(2) Revision : Three letters

(3) Lot number : X Y 7 A XXX XX X



NOTE 1). This code indicating year is omitted in the products of KIHENG site.

(5) Nameplate Indication(Following example is only for reference)




Parts name : LTN154AT10-C
Lot number : XXXXXXXXXXXX
Inspected work week : 0710(2007 year 10th week)
Product Revision Code : XXX


Samsung Secret

| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 24 / 27 |
|---------|------------|--------|-----------------|------|---------|
|---------|------------|--------|-----------------|------|---------|

This HIGH VOLTAGE CAUTION is carved in mold frame



(6) Packing box attach



(7) Packing box Marking : Samsung TFT-LCD Brand Name



Samsung Secret

10. GENERAL PRECAUTIONS

Preliminary

1. Handling

- (a) When the module is assembled, It should be attached to the system firmly using every mounting holes. Be careful not to twist and bend the modules.
- (b) Refrain from strong mechanical shock and / or any force to the module. In addition to damage, this may cause improper operation or damage to the module and CCFT back-light.
- (c) Note that polarizers are very fragile and could be easily damaged. Do not press or scratch the surface harder than a HB pencil lead.
- (d) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, Staining and discoloration may occur.
- (e) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (f) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane.
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (g) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs or clothes, it must be washed away thoroughly with soap.
- (h) Protect the module from static, it may cause damage to the C-MOS Gate Array IC.
- (i) Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (j) Do not disassemble the module.
- (k) Do not pull or fold the lamp wire.
- (l) Do not adjust the variable resistor which is located on the back side.
- (m) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (n) Pins of I/F connector shall not be touched directly with bare hands.

Samsung Secret

| | | | | | |
|----------------|------------|---------------|-----------------|-------------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 26 / 27 |
|----------------|------------|---------------|-----------------|-------------|---------|

2. STORAGE

- (a) Do not leave the module in high temperature, and high humidity for a long time.
It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD module in direct sunlight.
- (c) The module shall be stored in a dark place. It is prohibited to apply sunlight or fluorescent light during the store.

3. OPERATION

- (a) Do not connect, disconnect the module in the “Power On” condition.
- (b) Power supply should always be turned on/off by following item 6.3
“Power on/off sequence”.
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The cable between the back-light connector and its inverter power supply shall be a minimized length and be connected directly. The longer cable between the back-light and the inverter may cause lower luminance of lamp(CCFT) and may require higher startup voltage (Vs).
- (e) The standard limited warranty is only applicable when the module is used for general notebook applications. If used for purposes other than as specified, SEC is not to be held reliable for the defective operations. It is strongly recommended to contact SEC to find out fitness for a particular purpose.

4. OTHERS

- (a) Ultra-violet ray filter is necessary for outdoor operation.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. (the supply voltage variation, input voltage variation, variation in part contents and environmental temperature, so on)
Otherwise the module may be damaged.
- (d) If the module displays the same pattern continuously for a long period of time, it can be the situation when the image “sticks” to the screen.
- (e) This module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.

Samsung Secret

| | | | | | |
|----------------|------------|---------------|-----------------|-------------|---------|
| Doc.No. | LTN154AT10 | Rev.No | 04-P00-G-080327 | Page | 27 / 27 |
|----------------|------------|---------------|-----------------|-------------|---------|