

User Avatar Gallery

Goal

Implement a user avatar gallery where a user can store multiple avatars while maintaining exactly one primary avatar.

Functional Requirements

Avatar Upload

Endpoint

```
POST /users/me/avatars
```

Request

```
multipart/form-data
```

```
avatar=<file>
```

Behavior

- User can upload multiple avatars.
- Maximum number of avatars per user: **10**.
- Images are stored in Cloudinary.
- Avatar metadata is stored in MongoDB.
- If this is the user's first avatar, it becomes the primary avatar automatically.
- Any subsequent uploaded avatar is not primary by default.

Response

```
{
  "id": "65ab123...",
  "url": "https://...",
  "isPrimary": false
}
```

Validation

Return:

400 Bad Request

when:

- file is missing
- file format is not supported
- user already has 10 avatars

Avatar Model

Create a separate collection:

```
{
  _id: ObjectId,
  userId: ObjectId,
  url: String,
  publicId: String,
  isPrimary: Boolean,
  createdAt: Date,
  updatedAt: Date
}
```

Get User Avatars

Endpoint

GET /users/me/avatars

Response

```
[
  {
    "id": "1",
    "url": "https://...",
    "isPrimary": true
  },
  {
```

```
    "id": "2",
    "url": "https://...",
    "isPrimary": false
  }
]
```

Sorting

The primary avatar must always appear first.

Set Primary Avatar

Endpoint

```
PATCH /users/me/avatars/:avatarId/primary
```

Behavior

When a user selects a new primary avatar:

1. All user avatars become:

```
isPrimary = false
```

1. Selected avatar becomes:

```
isPrimary = true
```

Response

```
{
  "message": "Primary avatar updated"
}
```

Delete Avatar

Endpoint

```
DELETE /users/me/avatars/:avatarId
```

Behavior

1. Find avatar.
 2. Delete image from Cloudinary.
 3. Delete avatar document from MongoDB.
-

Special Case

If the deleted avatar is the primary avatar:

Before:

```
Avatar A (primary)
Avatar B
Avatar C
```

Delete:

```
Avatar A
```

After:

```
Avatar B (primary)
Avatar C
```

Rule

If other avatars remain:

- the oldest remaining avatar becomes primary.
-

Security Requirements

A user must only manage their own avatars.

Before any operation verify:

```
avatar.userId.equals(currentUser._id)
```

Otherwise return:

404 Not Found

or

403 Forbidden

Business Rules

1. User may have from 0 to 10 avatars.
2. Exactly one avatar may have:

isPrimary = true

1. The first uploaded avatar automatically becomes primary.
2. Primary avatar must always be returned first in avatar lists.
3. When deleting a primary avatar, another avatar must automatically become primary.
4. Users cannot access avatars belonging to other users.

Suggested API Endpoints

POST /users/me/avatars
GET /users/me/avatars
PATCH /users/me/avatars/:avatarId/primary
DELETE /users/me/avatars/:avatarId

Bonus Tasks

Bonus 1

Allow uploading multiple avatars at once.

Endpoint

POST /users/me/avatars/bulk

Requirements

- Accept up to 5 files.

- Upload files in parallel using:

```
Promise.all()
```

Bonus 2

Add avatar description.

```
caption: String
```

Bonus 3

Support custom ordering.

```
order: Number
```

Add endpoint:

```
PATCH /users/me/avatars/reorder
```

Request:

```
{
  "avatarIds": [
    "id3",
    "id1",
    "id2"
  ]
}
```

Acceptance Criteria

- User can upload avatars.
- User can view avatar gallery.
- User can select a primary avatar.
- User can delete avatars.
- System guarantees exactly one primary avatar.
- Images are stored in Cloudinary.
- Maximum avatar count is enforced.

- Unauthorized access is prevented.