3-3生成项目中的html页面文件-多页面

多页面的使用。

新建js文件



在模板配制如下页面

```
new htmlWebpackPlugin({-
 filename: 'a.html',-
template: 'index.html',-
inject: 'body',
title: 'this is a.html',
 chunks: ['main', 'a']
· · · }), ¬
  new htmlWebpackPlugin({-
filename: 'b.html',-
template: 'index.html',-
inject: 'body',-
title: 'this is b.html',
chunks: ['b']-
}),-
  new htmlWebpackPlugin({-
 filename: 'c.html',-
template: 'index.html',-
inject: 'body',
title: 'this is c.html',-
chunks: ['c']
```

采用内嵌方式引用, 个人却得一般不需要这样做。哈

```
<head>
  <meta charset="utf-8">
  <title><%= htmlWebpackPlugin.options.title %></title>
  <script type="text/javascript">
   <%=
   compilation.assets[htmlWebpackPlugin.files.chunks.main.entry.subs
   tr(htmlWebpackPlugin.files.publicPath.length)].source() %>
 </script>
</head>
<body>
 <% for (var k in htmlWebpackPlugin.files.chunks) { %>
   <% if (k !== 'main') { %>
      <script type="text/javascript" src="<%=</pre>
      htmlWebpackPlugin.files.chunks[k].entry %>"></script>
   <% } %>
  <% } %>
```

网官地址inline引用方式

https://github.com/jantimon/html-webpack-plugin/blob/master/examples/inline/template.jade