Rear Derailleurs

Model No.		RDMZ80 MD	RDMX60 MD	RDMS30 MD
Cage Type		(M) Medium	(M) Medium	(M) Medium
Mounting Type		(D) Direct	(D) Direct	(D) Direct
Speeds		12/11/10-Speed	12/11/10-Speed	12/11/10-Speed
Adjustable Chain Stabilizer		•	•	•
Max. Sprocket	1 x	50T	50T	50T
	2 x	42T	42T	42T
	3 x	X	X	X
Min. Sprocket		10T	10 T	10T
Rear Capacity		40T	40T	40T
Max. Front Difference		14T	14T	14T
Total Capacity		46T	46T	46T
Outer Link		Aluminum Forged / Anodized	Aluminum Forged / Anodized	Aluminum Forged / Anodized
Inner Link		Aluminum Forged / Anodized	Aluminum Forged / Anodized	Aluminum Forged / Anodized
Bracket Body		Aluminum Forged / Anodized	Aluminum Forged / Anodized	Aluminum Forged / Anodized
Plate Body		Eng. Polymers / Painted	Eng. Polymers / Painted	Eng. Polymers
Outer Plate Cage		Carbon	Aluminum / Anodized	Steel / Painted
Inner Plate Cage		Aluminum / Anodized	Aluminum / Anodized	Steel / Painted
Guide Pulley		12T / Eng. Polymers / Bushing	12T / Eng. Polymers / Bushing	12T / Eng. Polymers / Bushing
Tension Pulley		14T / Eng. Polymers / Bushing	14T / Eng. Polymers / Bushing	14T / Eng. Polymers / Bushing
Bracket Bolt		7075 Aluminum / Anodized	7075 Aluminum / Anodized	Steel / Plated
Cable Adjuster		Χ	Χ	X
Pin Bushing (Outer Link)		•	•	•
Pin Bushing (Inner Link)		•	•	•
Average Weight		267g	278g	347g