

Highlighted Stata Code and Results - Chapter #3

March 16, 2019

Question 6

```
. // download data from: http://hdl.handle.net/10079/6hdr852
. // copy and paste the url to your web browser
.
. import delim "Clingsmith_et_al_QJE_2009dta.csv", clear
(8 vars, 958 obs)

. set seed 1234567
. rename success D
. rename views Y
//findit tsrtest
. //package name: st0158.pkg install
.
. cap program drop ate
. program define ate, rclass
1.     args Y D
2.     sum 'Y' if 'D'==1, meanonly
3.     local Y_treat=r(mean)
4.     sum 'Y' if 'D'==0, meanonly
5.     local Y_con=r(mean)
6.     return scalar ate_avg = 'Y_treat'-'Y_con'
7. end

. // ssc install tsrtest
. tsrtest D r(ate_avg) using 3_6_resam.dta, overwrite: ate Y D
Two-sample randomization test for theta=r(ate_avg) of ate Y D by D

Combinations:      8.4503047638e+285 = (958 choose 448)
Assuming null=0
Observed theta: .4748

Minimum time needed for exact test (h:m:s):  4.2e+278:00:00
Reverting to Monte Carlo simulation.
Mode: simulation (10000 repetitions)

progress: |.....|

p=0.00190 [one-tailed test of Ho:  theta(D==0)<=theta(D==1)]
p=0.99830 [one-tailed test of Ho:  theta(D==0)>=theta(D==1)]
p=0.00360 [two-tailed test of Ho:  theta(D==0)==theta(D==1)]

Saving log file to 3_6_resam.dta...done.
.
. preserve
. use "3_6_resam.dta", clear

. global ate = theta[1]

. di $ate
.4748337

. drop if _n==1
(1 observation deleted)

. count if theta >= $ate
19

. scalar p_onesided = r(N)/_N
```

```

. count if abs(theta) >= $ate
36

. scalar p_twosided = r(N)/_N

. di "p.value.onesided = "p_onesided
p.value.onesided = .0019

. di "p.value.twosided = "p_twosided
p.value.twosided = .0036

. restore

```

Question 7

```

. clear
. set seed 1234567
. set obs 10
number of observations (_N) was 0, now 10
.
. input D Y

           D          Y
1.  0  1
2.  0  0
3.  0  0
4.  0  4
5.  0  3
6.  1  2
7.  1  11
8.  1  14
9.  1  0
10. 1  3

.
. gen Y_star= Y+D*(-7)
.
. cap program drop ate
.
. program define ate, rclass
1.      args Y D
2.      sum 'Y' if 'D'==1, meanonly
3.      local Y_treat=r(mean)
4.      sum 'Y' if 'D'==0, meanonly
5.      local Y_con=r(mean)
6.      return scalar ate_avg = 'Y_treat'-'Y_con'
7. end
.
. // findit tsrtest (to install the package)
. tsrtest D r(ate_avg): ate Y_star D
Two-sample randomization test for theta=r(ate_avg) of ate Y_star D by D

Combinations:    252 = (10 choose 5)
Assuming null=0
Observed theta: -2.6

Minimum time needed for exact test (h:m:s):  0:00:00
Mode: exact

progress: |.....|

p=0.83730 [one-tailed test of Ho: theta(D==0)<=theta(D==1)]
p=0.20635 [one-tailed test of Ho: theta(D==0)>=theta(D==1)]
p=0.41270 [two-tailed test of Ho: theta(D==0)==theta(D==1)]
.
. // ate
. di r(obsvStat)
-2.6
.
. // p.value.onesided
. di r(lowertail)

```

Question 8

part(a)

```
// download data from : http://hdl.handle.net/10079/s1rn910
. // copy and paste the url to your web browser
. use "Titiunik_WorkingPaper_2010.csv.dta", clear
.
. set seed 1234567

.      rename term2year D
.      rename bills_introduced Y
.      rename texas0_arkansas1 block
.      qui tabstat Y if block ==0, by(D) stat(mean) save
.      scalar ate_texas = el(r(Stat2),1,1) - el(r(Stat1),1,1)
.      qui tabstat Y if block ==1, by(D) stat(mean) save
.      scalar ate_ark = el(r(Stat2),1,1) - el(r(Stat1),1,1)
.
.      di "ate_texas=" %18.5f ate_texas
ate_texas=          -16.74167

.      di "ate_arkansas=" %18.5f ate_ark
ate_arkansas=       -10.09477
```

part(b)

```
qui tabstat Y if block ==0, by(D) stat(v n) save
. scalar se_texas = sqrt(el(r(Stat2),1,1)/el(r(Stat2),2,1) + ///
>                      el(r(Stat1),1,1)/el(r(Stat1),2,1))
.
.
. qui tabstat Y if block ==1, by(D) stat(v n) save
.
. scalar se_arkansas = sqrt(el(r(Stat2),1,1)/el(r(Stat2),2,1) + ///
>                      el(r(Stat1),1,1)/el(r(Stat1),2,1))
.
. di "se_texas=" %18.6f se_texas
se_texas=          9.345871

. di "se_arkansas=" %18.6f se_arkansas
se_arkansas=       3.395979
```

part(c)

```
qui tabstat Y, by(block) stat(n) save
.
. scalar ate_overall = el(r(Stat1),1,1)/_N*ate_texas + ///
>                      el(r(Stat2),1,1)/_N*ate_ark
.
.
. di %18.4f ate_overall
          -13.2168
.
. // same as
. // teffects nnmatch (bills_introduced) (term2year), ematch(texas0_arkansas1)
```

part(e)

```
. scalar se_overall = sqrt((el(r(Stat1),1,1)/_N)^2*se_texas^2 + ///
>                      (el(r(Stat2),1,1)/_N)^2*se_arkansas^2)
.
. di %18.5f se_overall
          4.74478
```

part(f)

```
// calculate probs under block assignment
. bysort block: egen probs=mean(D).
.
.
. cap program drop ate_block
.
. program define ate_block, rclass
1. args Y D probs
2. tempvar ipw
3. gen 'ipw' = .
4. // calculate inverse probability weight under block assignment
. replace 'ipw' = 'D'/'probs' + (1-'D')/(1-'probs')
5. qui reg 'Y' 'D' [iw='ipw']
6. return scalar ate=_b['D']
7. end
.
. // ssc install ritest (to install ritest package)
.
. //
. ritest D r(ate), strata(block) reps(10000) nodots: ///
> ate_block Y D probs
(66 missing values generated)
(66 real changes made)

      command:  ate_block Y D probs
      _pm_1:    r(ate)
res. var(s):   D
Resampling:    Permuting D
Clust. var(s): __000000
Clusters:      66
Strata var(s): block
Strata:        2
```

T		T(obs)	c	n	p=c/n	SE(p)	[95% Conf. Interval]
	_pm_1	-13.2168	65	10000	0.0065	0.0008	.00502 .0082774

```
Note: Confidence interval is with respect to p=c/n.
Note: c = #{|T| >= |T(obs)|}

. // ate
. di el(r(b),1,1)
-13.216796

.
. // p.value.twosided
. di el(r(p),1,1)
.0065
```

Question 9

part(b)

```
// download data from : http://hdl.handle.net/10079/1g1jx43
. // copy and paste the url to your web browser
.
. use "Camerer_JPESubset_1998.dta.dta", clear
.
. set seed 1234567

.         rename treatment D
.
.         rename pair block
.
.         rename preexperimentbets covs
.
.         // calculate probs under block assignment
.         bysort block: egen probs=mean(D)
.
.
```

```

. // permutation to calculate F stat and one-side P value
. rittest D e(F), strata(block) reps(10000) right nodots: ///
> regress D covs

```

Source	SS	df	MS	Number of obs	=	
Model	.005024372	1	.005024372	F(1, 32)	=	0.02
Residual	8.49497563	32	.265467988	Prob > F	=	0.8914
				R-squared	=	0.0006
				Adj R-squared	=	-0.0306
Total	8.5	33	.257575758	Root MSE	=	.51524

D	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]
covs	-.0000386	.0002809	-0.14	0.891	-.0006109 .0005336
_cons	.5137818	.1335793	3.85	0.001	.2416896 .785874


```

command: regress D covs
      _pm_1: e(F)
res. var(s): D
Resampling: Permuting D
Clust. var(s): __000000
Clusters: 34
Strata var(s): block
Strata: 17

```


T	T(obs)	c	n	p=c/n	SE(p)	[95% Conf. Interval]
_pm_1	.0189265	3736	10000	0.3736	0.0048	.3641064 .3831672

Note: Confidence interval is with respect to p=c/n.
Note: c = #{T >= T(obs)}

```

. // p.value
. di el(r(p),1,1)
.3736

```

part(c)

```

. rename experimentbets change
. tabstat change, by(D) stat(mean) save
Summary for variables: change
by categories of: D

```

D	mean
0	571.4118
1	461.2353
Total	516.3235


```

. di "ATE ="%180.4f el(r(Stat2),1,1)-el(r(Stat1),1,1)
ATE = -110.1765

```

part(d)

```

bysort block (D): gen pair_diff = change - change[_n+1]
(17 missing values generated)

. mean(pair_diff)
Mean estimation      Number of obs      =      17

```

	Mean	Std. Err.	[95% Conf. Interval]	
pair_diff	110.1765	104.8377	-112.0695	332.4225

```
.
. // the same as
. // teffects nnmatch (experimentbets block) (D)
```

part(e)

```
. cap program drop ate_block

.
. program define ate_block, rclass
1. args Y D probs
2. tempvar ipw
3. gen 'ipw' = .
4. // calculate inverse probability weight under block assignment
. replace 'ipw' = 'D'/'probs' + (1-'D')/(1-'probs')
5. qui reg 'Y' 'D' [iw='ipw']
6. return scalar ate=_b['D']
7. end

.
.
. ritest D r(ate), strata(block) reps(10000) nodots: ///
> ate_block change D probs
(34 missing values generated)
(34 real changes made)

      command: ate_block change D probs
      _pm_1:   r(ate)
res. var(s):   D
Resampling:   Permuting D
Clust. var(s): __000000
Clusters:     34
Strata var(s): block
Strata:       17

-----+-----
T      |      T(obs)      c      n      p=c/n      SE(p) [95% Conf. Interval]
-----+-----
      _pm_1 |    -110.1765     3170    10000    0.3170    0.0047    .3078845    .3262222
-----+-----

Note: Confidence interval is with respect to p=c/n.
Note: c = #{|T| >= |T(obs)|}.

.
. // ate
. di el(r(b),1,1)
-110.17647

.
. // p.value.twosided
. di el(r(p),1,1)
.317
```

Question 10

part(a)

```
. clear

. set seed 1234567

. set obs 14
number of observations (_N) was 0, now 14

. input Y0

      Y0
```

```

1. 0
2. 1
3. 2
4. 4
5. 4
6. 6
7. 6
8. 9
9. 14
10. 15
11. 16
12. 16
13. 17
14. 18

. end

. input Y1

      Y1
1. 0
2. 0
3. 1
4. 2
5. 0
6. 0
7. 2
8. 3
9. 12
10. 9
11. 8
12. 15
13. 5
14. 17

. end

. gen int cluster = (_n+1)/2

.
. //ssc install tabstatmat (install the package)
. // save tabstat summary result to matrix
. tabstat Y0, by(cluster) stat(mean) save

Summary for variables: Y0
      by categories of: cluster

  cluster |      mean
-----+-----
      1 |         .5
      2 |          3
      3 |          5
      4 |         7.5
      5 |        14.5
      6 |         16
      7 |        17.5
-----+-----
    Total |    9.142857
-----+-----

. tabstatmat Ybar0, nottotal

Ybar0[7,1]
      Y0
1:mean    .5
2:mean     3
3:mean     5
4:mean    7.5
5:mean   14.5
6:mean    16
7:mean   17.5

```

```

. mat colnames Ybar0=Ybar0
.
. tabstat Y1, by(cluster) stat(mean) save
Summary for variables: Y1
    by categories of: cluster

    cluster |          mean
-----+-----
          1 |             0
          2 |            1.5
          3 |             0
          4 |            2.5
          5 |           10.5
          6 |           11.5
          7 |            11
-----+-----
        Total |    5.285714
-----+-----

. tabstatmat Ybar1, nottotal
Ybar1[7,1]
      Y1
1:mean    0
2:mean    1.5
3:mean    0
4:mean    2.5
5:mean   10.5
6:mean   11.5
7:mean    11

. mat colnames Ybar1=Ybar1
.
.
. // function to calculate population variance
. cap program drop var_pop

. program define var_pop, rclass
1.     args varname
2.     tempvar x_dev
3.     qui sum 'varname'
4.     local avg = r(mean)
5.     local length = r(N)
6.     gen 'x_dev' = ('varname'-'avg')^2/'length'
7.     qui tabstat 'x_dev', stat(sum) save
8.     return scalar variance_pop = el(r(StatTotal),1,1)
9. end

.
.
. // function to calculate population covariance
. cap program drop cor_pop

. program define cor_pop, rclass
1.     args x y
2.     tempvar xy_dev
3.     qui sum 'x'
4.     local avg_x = r(mean)
5.     local length = r(N)
6.
.     qui sum 'y'
7.     local avg_y = r(mean)
8.
.     gen 'xy_dev' = ('x'-'avg_x')*( 'y'-'avg_y')
9.     qui tabstat 'xy_dev', stat(sum) save
10.    return scalar cor_pop = el(r(StatTotal),1,1)/'length'
11. end

.
. preserve

```



```

. clear

. set obs 7
number of observations (_N) was 0, now 7

. svmat Ybar0, names(col)
number of observations will be reset to 7
Press any key to continue, or Break to abort
number of observations (_N) was 0, now 7

. svmat Ybar1, names(col)
.
. // var_Ybar0
. var_pop Ybar0

. scalar var_Ybar0=r(variance_pop)
.
. // var_Ybar1
. var_pop Ybar1

. scalar var_Ybar1=r(variance_pop)
.
. // cov_Ybar0
. cor_pop Ybar0 Ybar1

.
. scalar cov_Ybar0=r(cor_pop)
.
. scalar se_ate = sqrt(((1/6)*((4/3)*var_Ybar0+(3/4)*var_Ybar1+2*cov_Ybar0)))
.
. di %8.6f se_ate
4.706192
.
. restore

```

part(b)

```

replace cluster = _n
(7 real changes made)

. replace cluster = 15-cluster if (cluster>7)
(7 real changes made)
.
.
. clear matrix

. // Ybar0
. tabstat Y0, by(cluster) stat(mean) save

```

Summary for variables: Y0
by categories of: cluster

cluster	mean
1	9
2	9
3	9
4	10
5	9.5
6	10
7	7.5
Total	9.142857

```

. tabstatmat Ybar0, nototal

```

```

Ybar0[7,1]
      Y0
1:mean  9
2:mean  9

```

```

3:mean    9
4:mean    10
5:mean    9.5
6:mean    10
7:mean    7.5

. mat colnames Ybar0=Ybar0

.
. // Ybar1
. tabstat Y1, by(cluster) stat(mean) save

Summary for variables: Y1
      by categories of: cluster

  cluster |          mean
-----+-----
        1 |           8.5
        2 |           2.5
        3 |            8
        4 |            5
        5 |           4.5
        6 |            6
        7 |           2.5
-----+-----
      Total |    5.285714
-----+-----

. tabstatmat Ybar1, nottotal

Ybar1[7,1]
      Y1
1:mean  8.5
2:mean  2.5
3:mean   8
4:mean   5
5:mean  4.5
6:mean   6
7:mean  2.5

. mat colnames Ybar1=Ybar1

.
. preserve

. clear

. set obs 7
number of observations (_N) was 0, now 7

. svmat Ybar0, names(col)
number of observations will be reset to 7
Press any key to continue, or Break to abort
number of observations (_N) was 0, now 7

. svmat Ybar1, names(col)

.
. // var_Ybar0 <- var.pop(Ybar0)
. var_pop Ybar0

. scalar var_Ybar0=r(variance_pop)

.
. // var_Ybar1 <- var.pop(Ybar1)
. var_pop Ybar1

. scalar var_Ybar1=r(variance_pop)

.
. // cov_Ybar0 <- cov.pop(Ybar0,Ybar1)
. cor_pop Ybar0 Ybar1

```

```

. scalar cov_Ybar0=r(cor_pop)

.
. // se_ate
. scalar se_ate = sqrt((1/6)*((4/3)*var_Ybar0+(3/4)*var_Ybar1+2*cov_Ybar0))

. di %8.7f se_ate
0.9766259
.
. restore

```