Compare Search Trees

Author: YiFeng Zheng

YuJie Sun

Group number: 17

Date: 2026-10-03

Abstract

This report investigates the performance of five search trees on sequences of insertions and deletions: unbalanced binary search trees, AVL trees, splay trees, red-black trees, and $B+$ trees. Correctness is checked by an insertion/deletion smoke test for each tree, run under memory and undefined-behavior sanitizers. Each timed configuration is repeated three times. Ordered BST insertion exhibits quadratic growth, while balanced and adaptive trees avoid that total-cost behavior. Phase-separated plots reveal the benefits of splaying on ordered sequences. All programs are implemented in C.

Contents

1 Introduction **3**
1.1 Background and Objectives . . . 3
1.2 Problem Statement . . . 3

2 Data Structure / Algorithm Specification **3**
2.1 Unbalanced Binary Search Tree . . . 3
2.2 AVL Tree . . . 3
2.3 Splay Tree . . . 4
2.4 Red-Black Tree . . . 4
2.5 $B+$ Tree . . . 4
2.6 Correctness Argument . . . 5

3 Testing Results **5**
3.1 Environment and Timing Methodology . . . 5
3.2 Smoke Test . . . 5
3.3 Runtime Tables . . . 6
3.3.1 Increasing insertion / increasing deletion . . . 6
3.3.2 Increasing insertion / reverse deletion . . . 7
3.3.3 Random insertion / random deletion . . . 7
3.4 Runtime Plots . . . 7

4 Analysis and Comments **9**
4.1 Time Complexity . . . 9
4.1.1 Why Sorted BST Updates Are Quadratic . . . 10
4.1.2 Why Splay Benefits from Ordered Updates . . . 10
4.2 Space Complexity . . . 10
4.3 Measured Comparison . . . 10
4.4 Limitations and Improvements . . . 11
4.5 Conclusion . . . 11

5 References **11**

6 Author List **12**
6.1 Division of Work . . . 12

7 Declaration **12**

8 Signatures **12**

9 Source Code Appendix **12**

1 Introduction

1.1 Background and Objectives

A search tree represents an ordered set while supporting insertion, deletion, and membership queries. The same set can have very different update costs because its representation depends on balance rules and access order.

This project compares an unbalanced binary search tree (BST), an AVL tree, a splay tree, a red-black tree, and a $B+$ tree using the three update sequences.

1.2 Problem Statement

For each size N, the keys are the N distinct integers from 0 through $N-1$. The experiment inserts every key into an empty tree and then deletes every key.

1. Scenario 1 inserts in increasing order and deletes in increasing order;
2. Scenario 2 inserts in increasing order and deletes in decreasing order;
3. Scenario 3 uses separately shuffled insertion and deletion permutations. The measured sizes are 1,000, 2,000, 5,000, 10,000, 20,000, 50,000, and 100,000.

2 Data Structure / Algorithm Specification

2.1 Unbalanced Binary Search Tree

As introduced in FDS, a binary search tree is a rooted binary tree in which each node's key is greater than every key in its left subtree and less than every key in its right subtree [1].

We use an unbalanced BST as the baseline to highlight the balancing properties of the other trees.

Our C implementation inserts and deletes iteratively. Insertion attaches a new leaf; deletion bypasses a node with at most one child or replaces a two-child node's key with its inorder successor [1]. Updates perform no balancing rotations.

2.2 AVL Tree

An AVL tree is a BST in which every node's left and right subtree heights differ by at most one [2].

Compared with an unbalanced BST, it imposes a strict height-balance constraint.

`AvlBalance` repairs ancestors after recursive updates. It uses single rotations for LL/RR and double rotations for LR/RL imbalances, reconnecting child pointers and refreshing cached heights [2].

2.3 Splay Tree

A splay tree is a self-adjusting BST that moves an accessed node to the root through rotations [3].

Its distinguishing feature is access-driven restructuring, without a fixed balance constraint.

The C code uses top-down splaying: zig-zig rotations shorten repeated-direction paths, while smaller and larger keys are collected separately and reassembled around the accessed root [3]. Insertion makes the new key the root; deletion joins the subtrees by splaying the left subtree's maximum. Membership checks are read-only and do not splay.

2.4 Red-Black Tree

A red-black tree is a BST with red or black nodes, a black root, no adjacent red nodes, and equal numbers of black nodes on all paths from a given node to its descendant null leaves [1].

Beyond the BST ordering rule, it uses color metadata and these constraints to maintain balance.

Our implementation uses the left-leaning variant described in [1]. Rotations promote a child, transfer the former root's color to it, and color the demoted node red; `FlipColors` toggles the parent and both children. Deletion uses `MoveRedLeft` or `MoveRedRight` before descending into a 2-node, and the final root is black.

2.5 $B+$ Tree

A $B+$ tree is a balanced multiway search tree with separator keys in internal nodes and records in linked leaves at the same depth [4].

Unlike the binary branching of a BST, it allows multiple children per node, enforces occupancy constraints, and stores records separately in leaves.

Following the split and redistribution rules in [4], the C code splits an overflowing node into 16 and 17 entries, propagating splits upward. Deletion borrows from a sibling with spare entries or merges adjacent nodes; a one-child root is replaced by its child. `Refresh` updates separator keys, and leaf splits and merges maintain the `Next` links.

2.6 Correctness Argument

An empty tree is correct. Assume the tree is correct before an update. BST deletion uses the right subtree's smallest key when replacing a node with two children, so keys stay in order [1]. Rotations also keep this order; AVL and red-black repairs restore their balance rules [1], [2]. Splay deletion joins the left and right trees only when all left keys are smaller [3]. $B+$ splits, borrowing, and merges keep records in order and within node limits; updated separator keys keep searches correct [4]. These steps add or remove only the requested key, so each update leaves a correct tree. By induction, this holds for the whole sequence. Tests check some cases but do not prove all cases.

3 Testing Results

3.1 Environment and Timing Methodology

The experiment was conducted in the following environment.

Item	**Configuration**
Experiment date	2026-10-03
CPU	AMD Ryzen 7 H 255 W/ Radeon 780M
Operating system	WSL2; Linux 6.6.87.2-microsoft-standard-WSL2; x86-64
Compiler	gcc (Ubuntu 13.3.0-6ubuntu2~24.04.1) 13.3.0
Build flags	-std=c11 -O2 -Wall -Wextra -Wpedantic
Timer	POSIX CLOCK_MONOTONIC, elapsed wall time
Repetitions	3 for each scenario / size / tree
Execution	One process; sequential; no CPU affinity
$B+$ capacity	32 leaf records or 32 internal children

3.2 Smoke Test

Observed smoke test results.

Test case	**Type**	**Expected / actual result**
Deleting from an empty tree	Boundary	Accepted, no change; PASS for all five trees
INT_MIN and INT_MAX; 1,000 increasing keys	Functional	Both boundary keys found; sampled keys found; an absent key reported absent
Full insert-then-delete cycle	Functional	Every key accepted, then removed; NULL root afterwards; PASS
Same cycle under ASan and UBSan	Memory / undefined behavior	No sanitizer diagnostics; PASS
All 315 timed trials, N up to 100,000	Large-scale	Sampled keys present after insertion; NULL root after deletion; PASS

README.md documents how to reproduce every result in this chapter. The smoke test checks sampled membership and a full deletion cycle; it does not replace those structural checks.

3.3 Runtime Tables

- Times are in milliseconds (ms); N is the number of keys.
- Each value is the median total insertion-plus-deletion time of three runs.

3.3.1 Increasing insertion / increasing deletion

Increasing insertion / increasing deletion: median total elapsed time (ms).

N	**BST**	**AVL**	**Splay**	**RedBlack**	**BPlus32**
1,000	1.151	0.055	0.027	0.143	0.054
2,000	4.646	0.202	0.084	0.392	0.186
5,000	27.751	0.408	0.176	0.876	0.394
10,000	111.839	1.163	0.447	2.279	1.012
20,000	444.720	1.644	0.788	4.374	1.797
50,000	2757.504	7.110	1.843	14.321	5.003
100,000	10999.209	16.004	3.402	37.267	11.107

3.3.2 Increasing insertion / reverse deletion

Increasing insertion / reverse deletion: median total elapsed time (ms).

N	**BST**	**AVL**	**Splay**	**RedBlack**	**BPlus32**
1,000	2.348	0.087	0.036	0.179	0.100
2,000	9.652	0.173	0.097	0.321	0.209
5,000	57.488	0.422	0.195	0.839	0.592
10,000	219.320	0.708	0.381	1.763	0.986
20,000	886.977	1.621	0.779	4.072	2.177
50,000	5483.877	5.159	1.950	13.683	6.083
100,000	21933.532	15.375	3.894	36.391	14.964


3.3.3 Random insertion / random deletion

Random insertion / random deletion: median total elapsed time (ms).

N	**BST**	**AVL**	**Splay**	**RedBlack**	**BPlus32**
1,000	0.077	0.126	0.118	0.201	0.121
2,000	0.172	0.298	0.296	0.430	0.241
5,000	0.555	0.881	0.877	1.233	0.777
10,000	1.283	2.471	2.521	3.278	2.421
20,000	2.661	4.235	4.836	6.370	3.356
50,000	9.664	15.876	15.423	19.003	10.389
100,000	22.791	37.573	41.841	52.854	22.443


3.4 Runtime Plots

- Panels show insertion, deletion, and total time.
- Axes show N and seconds, both on logarithmic scales.
- Colors and markers identify trees; points show three-run medians and error bars show the observed range.




Median of 3 runs; whiskers show observed minimum and maximum (not confidence intervals).

Increasing insertion / increasing deletion. Each phase uses the same scale as its counterpart in the other scenarios.



Median of 3 runs; whiskers show observed minimum and maximum (not confidence intervals).

Increasing insertion / reverse deletion. Each phase uses the same scale as its counterpart in the other scenarios.



Random insertion / random deletion. Each phase uses the same scale as its counterpart in the other scenarios.

4 Analysis and Comments

4.1 Time Complexity

The full sequence consists of N insertions followed by N deletions. Bounds are worst-case unless marked as amortized; the $B+$ tree capacity is fixed at 32.

BST updates take time proportional to tree height [1]. AVL and red-black balancing maintain logarithmic height [1], [2]; fixed-capacity $B+$ trees also have logarithmic height [4]. Splay operations have an $O(\log N)$ amortized bound [3]. Applying these bounds to the 2N updates gives the full-sequence bounds below.

Tree	**Single insertion or deletion**	**Full sequence**
BST	$O(N)$	$O(N^2)$
AVL	$O(\log N)$	$O(N \log N)$
Splay	$O(N)$; $O(\log N)$ amortized	$O(N \log N)$
Red-Black	$O(\log N)$	$O(N \log N)$
$B+$ (capacity 32)	$O(\log N)$	$O(N \log N)$

4.1.1 Why Sorted BST Updates Are Quadratic

Increasing insertion creates a right chain in the plain BST. Using the height-based update bound [1], the ith insertion visits $i - 1$ nodes, giving $N(N-1)/2$ visits and $\Theta(N^2)$ time.

At the same time, increasing deletion removes the root each time and takes $\Theta(N)$ in total. Reverse deletion searches the remaining chain each time and takes $\Theta(N^2)$. Thus, both scenarios have quadratic total cost, but different deletion costs.

4.1.2 Why Splay Benefits from Ordered Updates

With increasing insertions, the largest key stays at the root, so each insertion takes constant time. The tree may become a left chain, but the total insertion cost is still $O(N)$.

Deleting in reverse order also takes $O(N)$: each deletion removes the maximum at the root and exposes its left subtree.

Increasing deletions behave differently. The first deletion must traverse the left chain to reach the minimum, costing $\Theta(N)$, so not every deletion is constant-time. However, the general amortized theorem gives $O(N \log N)$ for the full update sequence [3].

4.2 Space Complexity

Tree	**Total tree space**	**Update auxiliary space**
BST	$O(N)$	$O(1)$
AVL	$O(N)$	$O(\log N)$
Splay	$O(N)$	$O(1)$
Red-Black	$O(N)$	$O(\log N)$
$B+$ (capacity 32)	$O(N)$	$O(\log N)$

All five trees use linear storage. Auxiliary space is constant for iterative updates and logarithmic for the recursive update stacks in these implementations.

4.3 Measured Comparison

1. Increasing insertion / increasing deletion: At $N = 100{,}000$, Splay is fastest (3.402 ms), while BST is slowest (10,999.209 ms), a 3,232.85-fold difference.
2. Increasing insertion / reverse deletion: Splay is fastest (3.894 ms), while BST is slowest (21,933.532 ms), a 5,633.15-fold difference.

3. Random insertion / random deletion: BPlus32 is fastest (22.443 ms), while RedBlack is slowest (52.854 ms), a 2.35-fold difference.
4. Performance rankings: From fastest to slowest, both ordered workloads rank Splay, BPlus32, AVL, RedBlack, BST; the random workload ranks BPlus32, BST, AVL, Splay, RedBlack.
5. Scope: These rankings describe the results at $N = 100{,}000$ in this experiment and do not establish a universal ranking.

4.4 Limitations and Improvements

- Statistics: only three runs; use more repetitions to assess small differences.
- Workloads: only build-then-delete integer tests; add mixed operations and search benchmarks.
- Page I/O: this in-memory benchmark does not measure disk access; test a disk-backed $B+$ tree.

4.5 Conclusion

The results show that operation order affects tree performance.

Sorted insertions turn a plain BST into a chain, giving quadratic total time. AVL and red-black trees maintain logarithmic height through balancing.

In this experiment, Splay was fastest for both ordered workloads, while BPlus32 was fastest for the random workload at $N = 100{,}000$. These results show that the best choice depends on the workload, within the implementation and measurement limits discussed above.

5 References

[1] R. Sedgewick and K. Wayne, *Algorithms*, 4th ed. Boston, MA, USA: Addison-Wesley, 2011, secs. 3.2-3.3.

[2] M. A. Weiss, *Data Structures and Algorithm Analysis in C++*, 4th ed. Upper Saddle River, NJ, USA: Pearson, 2014, sec. 4.4.

[3] D. D. Sleator and R. E. Tarjan, "Self-adjusting binary search trees,"*J. ACM*, vol. 32, no. 3, pp. 652-686, Jul. 1985, doi: 10.1145/3828.3835.

[4] A. Silberschatz, H. F. Korth, and S. Sudarshan, *Database System Concepts*, 7th ed. New York, NY, USA: McGraw-Hill, 2019, ch. 14.

6 Author List

6.1 Division of Work

YiFeng Zheng: Implemented the programs, conducted the tests, and wrote the report.

YuJie Sun: Reproduced the tests and reviewed the report.

7 Declaration

We hereby declare that all work in this project, titled “Compare Search Trees,”is our independent effort as a group.

8 Signatures

YiFeng Zheng

YuJie Sun

9 Source Code Appendix

The full source code is provided in the accompanying `code/` directory.