

```
import UIKit

// n cdfgdmnbjhdhjhku!rghdf

/*
s
sdfgsdfg
sdfgsd
fgsdf
gsdf
gsdfg
*/

//Variable

var greeting = "Hello, playground"
greeting = "Adios"
var miVariableUno = "mi variable"

// Constantes

let miConstanteUno = "mi constante"
// miConstanteUno = " Adios" //Error

var numeroUno = 3, numeroDos = 2, numeroTres
= 4

//Tipos de datos
    // inferencia y no inferencia de tipo.
var texto: String = "Hola"
var entero: Int = 10
```

```
var doble: Double = 10.5
var flotante: Float = 10.5
var booleano: Bool = true
```

//Numeros

```
let maxValueInt = Int.max
let minValueInt = Int.min
```

```
let maxValueUInt = UInt.max
let minValueUInt = UInt.min
```

```
var n1 = 0.1
var n2 = 0.2
var n3: Double = 3.0
```

```
let suma = n1 + n2
print(suma)
```

```
var myVariable = 0.2    // ¿Es Float o Double?
```

```
n1 + Double(n3)
```

//MARK: Operadores de comparación

```
n1 > n2    // mayor que
n1 < n2    // menor que
n1 >= n2   // mayor o igual que
n1 <= n2   // menor o igual que
n1 == n2   // igual que
n1 != n2   // diferente que
//n1 === n2 // igual que a profundo nivel
```

//MARK: Strings

```
let cadena1 = "Buenos"  
let cadena2: String = "Dias"  
let nombre = "Manuel"
```

cadena1 + cadena2

//Caracter de escape

```
let mensaje = " "  
let mensaje2 = "\ (cadena1) \ (cadena2) \ (nombre)"  
print(mensaje)
```

```
mensaje.isEmpty  
"".isEmpty
```

//ESTO NO!!!!!!!!!!!!

```
mensaje.count == 0
```

```
var 😊 = 0
```

```
var 👻 = 3
```

😊 + 👻

// Array: ORDENADOS

```
var miArreglo = [1,2,3,4]  
var miarreglo2: [Int] = [1,2,3,4]  
var miArreglo3: [Int] = []
```

```
var anotherThreeDoubles = Array(repeating:  
2.5, count: 3)  
miArreglo[2]
```

```
var miArreglo4: [String] = ["hola","adios"]
```

```
//Agregar  
miArreglo4.append("adios")  
miArreglo4 += ["adios","Holi","Bye"]
```

```
//modificar  
miArreglo4[0] = "iOS"  
miArreglo4
```

```
//insertar  
miArreglo4.insert("Swift", at: 1)  
miArreglo4
```

```
//Remover  
miArreglo4.remove(at: 1)  
miArreglo4.removeLast()  
miArreglo4
```

```
miArreglo4.count  
miArreglo4.isEmpty
```

```
//Sets
```

```
var miSet = Set<Int>()  
var miSet2 = Set([1,1,2,3,4])
```

```
var miSet3: Set<String> = ["Rock",  
"Classical", "Hip hop"]
```

```
miSet3.insert("Jazz")  
miSet3.insert("Jazz")
```

```
miSet3.contains("Jazz")
```

```
miSet3.remove("Rock")
```

```
struct User: Hashable {  
    var name: String  
    var age: Int  
}
```

```
let swift = User(name: "SwiftBeta", age: 20)  
let beta = User(name: "SwiftBeta", age: 20)
```

```
var users = Set(arrayLiteral: swift, beta)
```

//MARK: Diccionarios

```
var miDiccionario: [String: Int] = ["apple":  
2, "banana": 5, "orange": 4]  
var airports: [String: String] = [  
    "AICM": "Benito Juarez",  
    "AIFA": "Dublin"  
]  
var miDiccionario2: [String:String] = [:]
```

//obtener valor

```
airports["AICM"]
```

```
//modificar Valor
```

```
airports["AIFA"] = "EdoMex"
```

```
airports
```

```
//Remover
```

```
airports["AIFA"] = nil
```

```
airports.removeValue(forKey: "AIFA")
```

```
//MARK: Tuplas
```

```
var color = ("#ff0000", "Rojo", "")
```

```
var tupla: (String, Int) = ("Dante Sanchez",  
8)
```

```
var tupla2 = (nombre: "Dante Sanchez", edad: 8)
```